



## Technical Specifications



# EUROLIVE B1520DSP

Digital Processor-Controlled 600-Watt 15" PA Speaker System  
with Integrated Mixer

# EUROLIVE B1520DSP

## Digital Processor-Controlled 600-Watt 15" PA Speaker System with Integrated Mixer

- High-power 600-Watt 2-way PA sound reinforcement speaker system with integrated mixer for live and playback applications
- State-of-the-art 24-bit digital signal processor for ultimate system control
- Digital crossover, phase and time correction for perfect driver alignment plus dual compressor/limiter for total system protection
- Digital noise gate, low-cut filter, 2-band EQ, dynamic Contour filter for ultimate sound reproduction
- 2 ULN Mic/Line inputs with individual volume controls and peak LEDs
- Extremely powerful 15" long-excursion driver provides incredibly deep bass and acoustic power
- State-of-the-art 1.75" titanium-diaphragm compression driver for exceptional high-frequency reproduction
- Additional Line output enables linking of additional speaker systems
- Versatile trapezoidal enclosure design allows different positioning:
- Cluster and stacking mode
- Stand mounting with 35-mm pole socket
- Rugged steel grill for optimal speaker protection
- Ergonomically shaped handles for easy carrying and setup
- High-quality components and exceptionally rugged construction ensure long life
- Conceived and designed by BEHRINGER Germany

# Specifications

## Audio Inputs

MIC/LINE (2)	XLR (balanced)
Input impedance	27 kOhm
Sensitivity	-40 to +10 dBu

## Audio Outputs

LINE OUT	XLR (balanced)
Output impedance	120 Ohm

## Processing

DSP	24-bit Motorola
AD/DA converter	24-bit / 48 kHz
Limiter	dual protection for woofer and driver
Dynamic EQ	dual parametric EQ's
NOISE GATE	variable (off to -30 dB)
TIMED TURNOFF	switchable (3 min < -45 dB)
CONTOUR	switchable speech / music contour
EQ HIGH	+/- 15 dB (12 kHz)
EQ LOW	+/- 15 dB (100 Hz)
LOW CUT	40 - 160 Hz (24 dB/Oct.)

## Loudspeaker System Data

Frequency range	40 Hz to 20 kHz
Crossover	Butterworth, 1.5 kHz, 24 dB/Oct.
Max. sound pressure level	128 dB @ 1 m
Dispersion angle	90° x 45°

## Output Power

### Low-Frequency Range

RMS @ 1% THD	320 W @ 8 Ohm
Peak Power	460 W @ 8 Ohm

### High-Frequency Range

RMS @ 1% THD	80 W @ 8 Ohm
Peak Power	140 W @ 8 Ohm

## Power Supply

### Mains Voltage/Fuses

100 V~, 50/60 Hz	T 6,3 A H 250 V
120 V~, 60 Hz	T 6,3 A H 250 V
220 V~, 50 Hz	T 4,0 A H 250 V
230 V~, 50 Hz	T 4,0 A H 250 V
Power consumption	max. 650 W
Mains connector	Standard IEC receptacle

## Dimensions/Weight

Dimensions (W x H x D)	approx. 18 3/10" x 27 3/5" x 19" approx. 465 x 700 x 482 mm
Weight	approx. 80.3 lbs. approx. 36.5 kg

BEHRINGER is constantly striving to maintain the highest professional standards. As a result of these efforts, modifications may be made from time to time to existing products without prior notice. Specifications and appearance may differ from those listed or illustrated.

TECHNICAL SPECIFICATIONS AND APPEARANCES ARE SUBJECT TO CHANGE WITHOUT NOTICE AND ACCURACY IS NOT GUARANTEED. BEHRINGER IS PART OF THE MUSIC GROUP (MUSIC-GROUP.COM). ALL TRADEMARKS ARE THE PROPERTY OF THEIR RESPECTIVE OWNERS. MUSIC GROUP ACCEPTS NO LIABILITY FOR ANY LOSS WHICH MAY BE SUFFERED BY ANY PERSON WHO RELIES EITHER WHOLLY OR IN PART UPON ANY DESCRIPTION, PHOTOGRAPH OR STATEMENT CONTAINED HEREIN. COLORS AND SPECIFICATIONS MAY VARY FROM ACTUAL PRODUCT. MUSIC GROUP PRODUCTS ARE SOLD THROUGH AUTHORIZED FULLFILLERS AND RESELLERS ONLY. FULLFILLERS AND RESELLERS ARE NOT AGENTS OF MUSIC GROUP AND HAVE ABSOLUTELY NO AUTHORITY TO BIND MUSIC GROUP BY ANY EXPRESS OR IMPLIED UNDERTAKING OR REPRESENTATION. THIS MANUAL IS COPYRIGHTED. NO PART OF THIS MANUAL MAY BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS, ELECTRONIC OR MECHANICAL, INCLUDING PHOTOCOPYING AND RECORDING OF ANY KIND, FOR ANY PURPOSE, WITHOUT THE EXPRESS WRITTEN PERMISSION OF MUSIC GROUP IP LTD. ALL RIGHTS RESERVED. © 2012 MUSIC GROUP IP LTD. TRIDENT CHAMBERS, WICKHAMS CAY, P.O. BOX 146, ROAD TOWN, TORTOLA, BRITISH VIRGIN ISLANDS