THANK YOU FOR CHOOSING A MORLEY PEDAL. YOU NOW OWN THE BEST PEDAL MADE!

Please take a few minutes to familiarize yourself with the features of your new pedal. We hope you enjoy using it as much as we enjoyed building it.

ABOUT OUR M2 SLIDE POT:

The M2VC Voltage Control / Expression Pedal is designed to use a slide pot to control parameters of the device it's hooked up to. A durable Monofilament cable is used to move the internal slide pot when the foot treadle is moved. We have developed a special lubricant to extend the slide pot life and prevent static and scratchiness of typical rotary pots.

ABOUT THE CONNECTIONS:

TRS TO DEVICE: Plug from device controller / pedal jack using 1/4" Stereo cable. Stereo cables are also known as TRS (Tip/Ring/Sleeve) cables.

USING AN AC ADAPTER:

The M2VC is a passive device (no power is required)

USING A BATTERY:

The M2VC is a passive device (no power is required).

ONE YEAR WARRANTY

All Morley® pedals are warranted for one year from date of purchase with a copy of dated purchase receipt. To obtain warranty service, contact dealer where pedal was purchased.

M2 VOLTAGE CONTROL (MODEL M2VC) FEATURES:

• Slide Pot: Internal slide pot and durable monofilament control Expression function.

M2VC SPECIFICATIONS:

Power: None Required

Dimensions: 9.13" L x 5.88" W x 2.75" H

Current Draw: N/A

Slide Pot: 10K Linear Taper Weight: 3.7 lb./ 1.68 kg

www.morleyproducts.com

