Roland®





Owner's Manual

Thank you, and congratulations on your choice of the Roland RS-5/9 64 Voice Synthesizer

Before using this unit, carefully read the sections entitled: "USING THE UNIT SAFELY" and "IMPORTANT NOTES" (p. 2; p. 3). These sections provide important information concerning the proper operation of the unit. Additionally, in order to feel assured that you have gained a good grasp of every feature provided by your new unit, Owner's manual should be read in its entirety. The manual should be saved and kept on hand as a convenient reference.

How to read this manual

The RS-5/9 Owner's Manual consists of two volumes, "Quick Start" and "Advanced Use."


"Quick Start" explains the basic functionality of the RS-5/9. By reading the Quick Start, you will gain an overall understanding of the RS-5/9's functions and features. And, for every item explained, you will find a convenient reference to the relevant page numbers in "Advanced Use," which you can turn to for additional information.

Read the material in "Advanced Use" when making detailed settings, when saving settings, and when using the RS-5/9 together with external devices.

This manual is arranged into sections, according to objective. Whenever you are curious about a certain item that can be set, and want to learn more about the function, refer to the Parameter List. The relevant reference pages are provided.

Convention Used in This Manual

- Words enclosed in square brackets [] indicate panel buttons.
 Example: [SPLIT] indicates the SPLIT button.
- (p. **) indicates a reference page



Copyright © 2000 ROLAND CORPORATION

All rights reserved. No part of this publication may be reproduced in any form without the written permission of ROLAND CORPORATION.

IMPORTANT: THE WIRES IN THIS MAINS LEAD ARE COLOURED IN ACCORDANCE WITH THE FOLLOWING CODE.

BLUE: NEUTRAL BROWN: LIVE

As the colours of the wires in the mains lead of this apparatus may not correspond with the coloured markings identifying the terminals in your plug, proceed as follows:

The wire which is coloured BLUE must be connected to the terminal which is marked with the letter N or coloured BLACK. The wire which is coloured BROWN must be connected to the terminal which is marked with the letter L or coloured RED. Under no circumstances must either of the above wires be connected to the earth terminal of a three pin plug.


USING THE UNIT SAFELY

INSTRUCTIONS FOR THE PREVENTION OF FIRE, ELECTRIC SHOCK, OR INJURY TO PERSONS

About AWARNING and ACAUTION Notices

| ≜WARNING | Used for instructions intended to alert the user to the risk of death or severe injury should the unit be used improperly. |
|------------------|---|
| | Used for instructions intended to alert the user to the risk of injury or material damage should the unit be used improperly. |
| ⚠ CAUTION | * Material damage refers to damage or other adverse effects caused with respect to the home and all its furnishings, as well to domestic animals or pets. |

About the Symbols



The symbol alerts the user to things that must be carried out. The specific thing that must be done is indicated by the design contained within the circle. In the case of the symbol at left, it means that the power-cord plug must be unplugged from the outlet.

----- ALWAYS OBSERVE THE FOLLOWING

∴ WARNING

 Before using this unit, make sure to read the instructions below, and the Owner's Manual.



 Do not open (or modify in any way) the unit or its AC adaptor.



 Do not attempt to repair the unit, or replace parts within it (except when this manual provides specific instructions directing you to do so). Refer all servicing to your retailer, the nearest Roland Service Center, or an authorized Roland distributor, as listed on the "Information" page.



- Never use or store the unit in places that are:
 - Subject to temperature extremes (e.g., direct sunlight in an enclosed vehicle, near a heating duct, on top of heat-generating equipment); or are
 - Damp (e.g., baths, washrooms, on wet floors); or are
 - · Humid; or are
 - Exposed to rain; or are
 - Dusty; or are
 - Subject to high levels of vibration.

MARNING

 Make sure you always have the unit placed so it is level and sure to remain stable. Never place it on stands that could wobble, or on inclined surfaces.



 Be sure to use only the AC adaptor supplied with the unit. Also, make sure the line voltage at the installation matches the input voltage specified on the AC adaptor's body. Other AC adaptors may use a different polarity, or be designed for a different voltage, so their use could result in damage, malfunction, or electric shock.



 Do not excessively twist or bend the power cord, nor place heavy objects on it. Doing so can damage the cord, producing severed elements and short circuits. Damaged cords are fire and shock hazards!



This unit, either alone or in combination with an amplifier and headphones or speakers, may be capable of producing sound levels that could cause permanent hearing loss. Do not operate for a long period of time at a high volume level, or at a level that is uncomfortable. If you experience any hearing loss or ringing in the ears, you should immediately stop using the unit, and consult an audiologist.



WARNING

 Do not allow any objects (e.g., flammable material, coins, pins); or liquids of any kind (water, soft drinks, etc.) to penetrate the unit.



- Immediately turn the power off, remove the AC adaptor from the outlet, and request servicing by your retailer, the nearest Roland Service Center, or an authorized Roland distributor, as listed on the "Information" page when:



- The AC adaptor, the power-supply cord, or the plug has been damaged; or
- Objects have fallen into, or liquid has been spilled onto the unit; or
- The unit has been exposed to rain (or otherwise has become wet); or
- The unit does not appear to operate normally or exhibits a marked change in performance.
- In households with small children, an adult should provide supervision until the child is capable of following all the rules essential for the safe operation of the unit.



 Protect the unit from strong impact. (Do not drop it!)

.....



 Do not force the unit's power-supply cord to share an outlet with an unreasonable number of other devices. Be especially careful when using extension cords—the total power used by all devices you have connected to the extension cord's outlet must never exceed the power rating (watts/amperes) for the extension cord. Excessive loads can cause the insulation on the cord to heat up and eventually melt through.



 Before using the unit in a foreign country, consult with your retailer, the nearest Roland Service Center, or an authorized Roland distributor, as listed on the "Information" page.



A CAUTION

 The unit and the AC adaptor should be located so their location or position does not interfere with their proper ventilation.



 Always grasp only the plug or the body of the AC adaptor when plugging into, or unplugging from, an outlet or this unit.



 Whenever the unit is to remain unused for an extended period of time, disconnect the AC adaptor.



 Try to prevent cords and cables from becoming entangled. Also, all cords and cables should be placed so they are out of the reach of children.



 Never climb on top of, nor place heavy objects on the unit.



 Never handle the AC adaptor body, or its plugs, with wet hands when plugging into, or unplugging from, an outlet or this unit.



 Before moving the unit, disconnect the AC adaptor and all cords coming from external devices.



 Before cleaning the unit, turn off the power and unplug the AC adaptor from the outlet.



 Whenever you suspect the possibility of lightning in your area, disconnect the AC adaptor from the outlet.



 Should you remove the screws used for attaching the music stand, make sure to put them in a safe place out of children's reach, so there is no chance of them being swallowed accidentally.

.....



- * GS (🝑) is a registered trademark of Roland Corporation.
- * Apple is a registered trademark of Apple Computer, Inc.
- * Macintosh is a registered trademark of Apple Computer, Inc.
- * IBM is a registered trademark of International Business Machines Corporation.
- * IBM PC is a registered trademark of International Business Machines Corporation.
- * All product names mentioned in this document are trademarks or registered trademarks of their respective owners.

IMPORTANT NOTES

In addition to the items listed under "USING THE UNIT SAFELY" on page 2-3, please read and observe the following:

Power Supply

- Do not use this unit on the same power circuit with any device that will generate line noise (such as an electric motor or variable lighting system).
- The AC adaptor will begin to generate heat after long hours of consecutive use. This is normal, and is not a cause for concern.
- Before connecting this unit to other devices, turn off the power to all units. This will help prevent malfunctions and/or damage to speakers or other devices.

Placement

- Using the unit near power amplifiers (or other equipment containing large power transformers) may induce hum.
 To alleviate the problem, change the orientation of this unit; or move it farther away from the source of interference.
- This device may interfere with radio and television reception. Do not use this device in the vicinity of such receivers.
- Do not expose the unit to direct sunlight, place it near devices that radiate heat, leave it inside an enclosed vehicle, or otherwise subject it to temperature extremes. Excessive heat can deform or discolor the unit.
- To avoid possible breakdown, do not use the unit in a wet area, such as an area exposed to rain or other moisture.
- Do not allow objects to remain on top of the keyboard.
 This can be the cause of malfunction, such as keys ceasing to produce sound.

Maintenance

- For everyday cleaning wipe the unit with a soft, dry cloth or one that has been slightly dampened with water. To remove stubborn dirt, use a cloth impregnated with a mild, non-abrasive detergent. Afterwards, be sure to wipe the unit thoroughly with a soft, dry cloth.
- Never use benzine, thinners, alcohol or solvents of any kind, to avoid the possibility of discoloration and/or deformation.

Additional Precautions

- Please be aware that the contents of memory can be irretrievably lost as a result of a malfunction, or the improper operation of the unit. To protect yourself against the risk of loosing important data, we recommend that you periodically save a backup copy of important data you have stored in the unit's memory in another MIDI device (e.g., a sequencer).
- Unfortunately, it may be impossible to restore the contents of data that was stored in another MIDI device (e.g., a sequencer) once it has been lost. Roland Corporation assumes no liability concerning such loss of data.
- Use a reasonable amount of care when using the unit's buttons, sliders, or other controls; and when using its jacks and connectors. Rough handling can lead to malfunctions.
- · Never strike or apply strong pressure to the display.
- When connecting / disconnecting all cables, grasp the connector itself—never pull on the cable. This way you will avoid causing shorts, or damage to the cable's internal elements.
- To avoid disturbing your neighbors, try to keep the unit's volume at reasonable levels. You may prefer to use headphones, so you do not need to be concerned about those around you (especially when it is late at night).
- When you need to transport the unit, package it in the box (including padding) that it came in, if possible. Otherwise, you will need to use equivalent packaging materials.
- Use only the specified expression pedal (EV-5; sold separately). By connecting any other expression pedals, you risk causing malfunction and/or damage to the unit.

What can I do with the RS-5/9? (Main features)

High-Quality Tones at a Low Price

The onboard Tones were composed using Tone resources from previous XP and JV Series models. Despite the low cost of this instrument, it features 640 high-quality internal Tones (Preset: 512, including GM and GM2 Tones; User: 128), plenty for just about any live performance.

Includes Piano Button (RS-9 Only)

Regardless of the mode, pressing this button provides you with the optimum settings for piano performances (p. 60).

16-Part, 64-Voice GM2 Sound Generator

Maximum polyphony is 64 notes, and up to 16 parts can be handled simultaneously. When working with music data that conforms to General MIDI and/or General MIDI 2 (GM scores), you can combine the RS-5/9 with a computer or sequencer, and use the RS-5/9 to play back the data (p. 128).

Includes Favorite Performance Bank Buttons

You can register the Performances you like to these eight buttons and easily call them up whenever you wish (p. 58).

Knob Controls for Adjusting the Sound in Real Time

These six convenient knobs let you can change the properties of the sound while you perform (p. 74).

Powerful Onboard Effects

Advanced DSP (Digital Signal Processor) technology provides a wide array of studio quality effects. In addition to the multiple effects section that features 42 different types of effects, the RS-5/9 also features an independent chorus unit and reverb unit (p. 79).

Arpeggiator Included

The RS-5/9's arpeggiator function allows you to produce arpeggios (broken chords) simply by playing a chord in the keyboard. You can also use these knobs for changing Patterns in real time. Additionally, you can use them to synchronize arpeggio tempos with a connected sequencer or other device (p. 75).

Tone Search and Phrase Preview Functions Included

The Tone Search function (p. 23) lets you rapidly find the tone you want simply by specifying a tone category. By pressing [PHRASE PREVIEW] button, you can then hear the selected tone play a phrase suitable for that type of tone. (Phrase Preview function, p. 33)

Stylish Aluminum Panel

The RS-5/9 features a titanium-toned aluminum panel for a great look onstage. The light weight adds to the RS-5/9's portability; and what's more, it's extremely durable.

GM/General MIDI



General MIDI is a set of recommendations which seeks to provide a way to go beyond the limitations of proprietary designs, and standardize the MIDI capabilities of sound generating devices. Sound generating devices and music files that meet the General MIDI standard bear the General MIDI logo (Music files bearing the General MIDI logo can be played back using any General MIDI sound generating unit to produce essentially the same musical performance.

GM 2/General MIDI 2



GS Format



The GS Format () is Roland's set of specifications for standardizing the performance of sound generating devices. In addition to including support for everything defined by the General MIDI, the highly compatible GS Format additionally offers an expanded number of sounds, provides for the editing of sounds, and spells out many details for a wide range of extra features, including effects such as reverb and chorus. Designed with the future in mind, the GS Format can readily include new sounds and support new hardware features when they arrive.

Contents

| USING THE UNIT SAFELY | 2 |
|---|--|
| IMPORTANT NOTES | 4 |
| What can I do with the RS-5/9? (Main features) | |
| What can I do with the h3-5/9: (want leatures) | 10 |
| Front and Rear Panel | 10 |
| Quick Start | 13 |
| Getting Ready | 14 |
| Connecting the RS-5/9 to external equipment | 14 |
| Turning On the Power | 15 |
| Turning the power off | 10 |
| Adjusting the display contrast (LCD CONTRAST) | 16 |
| Adjusting the pitch to other instruments (Master Tuning) | 18 |
| Listening to the Demo (DEMO) | 19 |
| Demo Songs List | 20 |
| Playing the Sounds | 21 |
| Restoring the Factory Settings (Factory Reset) | 21 |
| Selecting Tones By Category (TONE CATEGORY) | 23 |
| Selecting Tones by Specifying the Group and Number | 26 |
| Fasy Tone Selection (Switching Parts) | 28 |
| Playing Percussion Instruments (Drum Sets) | 29 |
| Changing a Drum Set | 29 |
| Selecting Drum Sets by Specifying the Group and Number | 30 |
| Playing a Drum Set in a Part Other Than Part 10 | 31 |
| Notes when selecting a Drum Set | 32 |
| Trying out tones (PHRASE PREVIEW) | 33 |
| | |
| Playing Two Tones on the Keyboard | 34 |
| Playing Two Tones on the Keyboard Dividing the Keyboard into Separate Ranges and Playing Different Tones in Each (SPLIT) | 34 34 |
| Playing Two Tones on the Keyboard | 34 34 36 |
| Playing Two Tones on the Keyboard Dividing the Keyboard into Separate Ranges and Playing Different Tones in Each (SPLIT) Playing two Tones from the keyboard (DUAL) | 34 36 37 |
| Playing Two Tones on the Keyboard Dividing the Keyboard into Separate Ranges and Playing Different Tones in Each (SPLIT) Playing two Tones from the keyboard (DUAL) Selecting Tones and Drum Sets Selecting Tones By Category (TONE CATEGORY) | 34 36 37 |
| Playing Two Tones on the Keyboard Dividing the Keyboard into Separate Ranges and Playing Different Tones in Each (SPLIT) Playing two Tones from the keyboard (DUAL) Selecting Tones and Drum Sets Selecting Tones By Category (TONE CATEGORY) Selecting Tones by Specifying the Group and Number | 34 36 37 37 |
| Playing Two Tones on the Keyboard Dividing the Keyboard into Separate Ranges and Playing Different Tones in Each (SPLIT) Playing two Tones from the keyboard (DUAL) Selecting Tones and Drum Sets Selecting Tones By Category (TONE CATEGORY) Selecting Tones by Specifying the Group and Number Changing the Two Parts Being Used | 34 36 37 37 38 39 |
| Playing Two Tones on the Keyboard Dividing the Keyboard into Separate Ranges and Playing Different Tones in Each (SPLIT) Playing two Tones from the keyboard (DUAL) Selecting Tones and Drum Sets Selecting Tones By Category (TONE CATEGORY) Selecting Tones by Specifying the Group and Number Changing the Two Parts Being Used Changing the Split Point | 34 36 37 37 38 39 |
| Playing Two Tones on the Keyboard Dividing the Keyboard into Separate Ranges and Playing Different Tones in Each (SPLIT) Playing two Tones from the keyboard (DUAL) Selecting Tones and Drum Sets Selecting Tones By Category (TONE CATEGORY) Selecting Tones by Specifying the Group and Number Changing the Two Parts Being Used Changing the Split Point | 34 36 37 37 38 39 40 |
| Playing Two Tones on the Keyboard Dividing the Keyboard into Separate Ranges and Playing Different Tones in Each (SPLIT) Playing two Tones from the keyboard (DUAL) | 34 36 37 38 39 40 42 |
| Playing Two Tones on the Keyboard Dividing the Keyboard into Separate Ranges and Playing Different Tones in Each (SPLIT) Playing two Tones from the keyboard (DUAL) Selecting Tones and Drum Sets Selecting Tones By Category (TONE CATEGORY) Selecting Tones by Specifying the Group and Number Changing the Two Parts Being Used Changing the Split Point Using the Convenient Functions in Performances Creating Arpeggios from the Chords You Play (ARPEGGIO ON/OFF) Using Multi-effects, Chorus, and Reverb | 34 36 37 37 38 40 42 42 |
| Playing Two Tones on the Keyboard Dividing the Keyboard into Separate Ranges and Playing Different Tones in Each (SPLIT) Playing two Tones from the keyboard (DUAL) Selecting Tones and Drum Sets Selecting Tones By Category (TONE CATEGORY) Selecting Tones by Specifying the Group and Number Changing the Two Parts Being Used Changing the Split Point Using the Convenient Functions in Performances Creating Arpeggios from the Chords You Play (ARPEGGIO ON/OFF) Using Multi-effects, Chorus, and Reverb Turning the Effects On and Off (EFFECTS ON/OFF) | 3436373839404244 |
| Playing Two Tones on the Keyboard Dividing the Keyboard into Separate Ranges and Playing Different Tones in Each (SPLIT) Playing two Tones from the keyboard (DUAL) Selecting Tones and Drum Sets Selecting Tones By Category (TONE CATEGORY) Selecting Tones by Specifying the Group and Number Changing the Two Parts Being Used Changing the Split Point Using the Convenient Functions in Performances Creating Arpeggios from the Chords You Play (ARPEGGIO ON/OFF) Using Multi-effects, Chorus, and Reverb Turning the Effects On and Off (EFFECTS ON/OFF) Setting the Amount of Chorus and Reverb | 343637383940424244 |
| Playing Two Tones on the Keyboard Dividing the Keyboard into Separate Ranges and Playing Different Tones in Each (SPLIT) Playing two Tones from the keyboard (DUAL) Selecting Tones and Drum Sets Selecting Tones By Category (TONE CATEGORY) Selecting Tones by Specifying the Group and Number Changing the Two Parts Being Used Changing the Split Point Using the Convenient Functions in Performances Creating Arpeggios from the Chords You Play (ARPEGGIO ON/OFF) Using Multi-effects, Chorus, and Reverb Turning the Effects On and Off (EFFECTS ON/OFF) Setting the Amount of Chorus and Reverb Changing the Multi-effect Type | 343637383940424444 |
| Playing Two Tones on the Keyboard Dividing the Keyboard into Separate Ranges and Playing Different Tones in Each (SPLIT) Playing two Tones from the keyboard (DUAL) Selecting Tones and Drum Sets Selecting Tones By Category (TONE CATEGORY) Selecting Tones by Specifying the Group and Number Changing the Two Parts Being Used Changing the Split Point Using the Convenient Functions in Performances Creating Arpeggios from the Chords You Play (ARPEGGIO ON/OFF) Using Multi-effects, Chorus, and Reverb Turning the Effects On and Off (EFFECTS ON/OFF) Setting the Amount of Chorus and Reverb Changing the Multi-effect Type Transposing All the Parts (TRANSPOSE ON/OFF) | 3436373839404244444647 |
| Playing Two Tones on the Keyboard Dividing the Keyboard into Separate Ranges and Playing Different Tones in Each (SPLIT) Playing two Tones from the keyboard (DUAL) Selecting Tones and Drum Sets Selecting Tones By Category (TONE CATEGORY) Selecting Tones by Specifying the Group and Number Changing the Two Parts Being Used Changing the Split Point Using the Convenient Functions in Performances Creating Arpeggios from the Chords You Play (ARPEGGIO ON/OFF) Using Multi-effects, Chorus, and Reverb Turning the Effects On and Off (EFFECTS ON/OFF) Setting the Amount of Chorus and Reverb Changing the Multi-effect Type Transposing All the Parts (TRANSPOSE ON/OFF) | 3436373839404244444647 |
| Playing Two Tones on the Keyboard Dividing the Keyboard into Separate Ranges and Playing Different Tones in Each (SPLIT) Playing two Tones from the keyboard (DUAL) Selecting Tones and Drum Sets Selecting Tones By Category (TONE CATEGORY) Selecting Tones by Specifying the Group and Number Changing the Two Parts Being Used Changing the Split Point Using the Convenient Functions in Performances. Creating Arpeggios from the Chords You Play (ARPEGGIO ON/OFF) Using Multi-effects, Chorus, and Reverb Turning the Effects On and Off (EFFECTS ON/OFF) Setting the Amount of Chorus and Reverb Changing the Multi-effect Type Transposing All the Parts (TRANSPOSE ON/OFF) Setting the Amount of Transposition Changing the Sound's Pitch in Real Time (Pitch Bend Lever) | 34 36 37 38 39 40 42 44 44 46 48 48 |
| Playing Two Tones on the Keyboard Dividing the Keyboard into Separate Ranges and Playing Different Tones in Each (SPLIT) Playing two Tones from the keyboard (DUAL) | 34363738394042444446474850 |
| Playing Two Tones on the Keyboard Dividing the Keyboard into Separate Ranges and Playing Different Tones in Each (SPLIT) Playing two Tones from the keyboard (DUAL) | 3436373839404244444647485051 |
| Playing Two Tones on the Keyboard Dividing the Keyboard into Separate Ranges and Playing Different Tones in Each (SPLIT) Playing two Tones from the keyboard (DUAL) Selecting Tones and Drum Sets Selecting Tones By Category (TONE CATEGORY) Selecting Tones by Specifying the Group and Number Changing the Two Parts Being Used Changing the Split Point Using the Convenient Functions in Performances Creating Arpeggios from the Chords You Play (ARPEGGIO ON/OFF) Using Multi-effects, Chorus, and Reverb Turning the Effects On and Off (EFFECTS ON/OFF) Setting the Amount of Chorus and Reverb Changing the Multi-effect Type Transposing All the Parts (TRANSPOSE ON/OFF) Setting the Amount of Transposition Changing the Sound's Pitch in Real Time (Pitch Bend Lever) Adding a Vibrato Effect to the Sound (Modulation Lever) Changing the Tone with the Knobs Vibrato and Wah Effects (LFO) | 3436373839404244444647485051 |
| Playing Two Tones on the Keyboard Dividing the Keyboard into Separate Ranges and Playing Different Tones in Each (SPLIT) Playing two Tones from the keyboard (DUAL) | 34343637383940424444464750515252 |
| Playing Two Tones on the Keyboard Dividing the Keyboard into Separate Ranges and Playing Different Tones in Each (SPLIT) Playing two Tones from the keyboard (DUAL) Selecting Tones and Drum Sets Selecting Tones By Category (TONE CATEGORY) Selecting Tones by Specifying the Group and Number Changing the Two Parts Being Used Changing the Split Point Using the Convenient Functions in Performances Creating Arpeggios from the Chords You Play (ARPEGGIO ON/OFF) Using Multi-effects, Chorus, and Reverb Turning the Effects On and Off (EFFECTS ON/OFF) Setting the Amount of Chorus and Reverb Changing the Multi-effect Type Transposing All the Parts (TRANSPOSE ON/OFF) Setting the Amount of Transposition Changing the Sound's Pitch in Real Time (Pitch Bend Lever) Adding a Vibrato Effect to the Sound (Modulation Lever) Changing the Tone with the Knobs Vibrato and Wah Effects (LFO) Changing the Sound's Volume (ENVELOPE) Changing the Brightness of the Sound and Adding Special Qualities (FILTER) Changing the RS-5/9's Settings All At Once (Selecting Performances) | 343637383940424444464550515252 |
| Playing Two Tones on the Keyboard Dividing the Keyboard into Separate Ranges and Playing Different Tones in Each (SPLIT) Playing two Tones from the keyboard (DUAL) Selecting Tones and Drum Sets Selecting Tones By Category (TONE CATEGORY) Selecting Tones by Specifying the Group and Number Changing the Two Parts Being Used Changing the Split Point Using the Convenient Functions in Performances Creating Arpeggios from the Chords You Play (ARPEGGIO ON/OFF) Using Multi-effects, Chorus, and Reverb Turning the Effects On and Off (EFFECTS ON/OFF) Setting the Amount of Chorus and Reverb Changing the Multi-effect Type Transposing All the Parts (TRANSPOSE ON/OFF) Setting the Amount of Transposition Changing the Sound's Pitch in Real Time (Pitch Bend Lever) Adding a Vibrato Effect to the Sound (Modulation Lever) Changing the Tone with the Knobs Vibrato and Wah Effects (LFO) Changing the Brightness of the Sound and Adding Special Qualities (FILTER) Changing the RS-5/9's Settings All At Once (Selecting Performances) Easily Selecting the Performances You Like (FAVORITE PERFORM BANK) | 3434363738394042444444465051525255 |
| Playing Two Tones on the Keyboard Dividing the Keyboard into Separate Ranges and Playing Different Tones in Each (SPLIT) Playing two Tones from the keyboard (DUAL) Selecting Tones and Drum Sets Selecting Tones By Category (TONE CATEGORY) Selecting Tones by Specifying the Group and Number Changing the Two Parts Being Used Changing the Split Point Using the Convenient Functions in Performances Creating Arpeggios from the Chords You Play (ARPEGGIO ON/OFF) Using Multi-effects, Chorus, and Reverb Turning the Effects On and Off (EFFECTS ON/OFF) Setting the Amount of Chorus and Reverb Changing the Multi-effect Type Transposing All the Parts (TRANSPOSE ON/OFF) Setting the Amount of Transposition Changing the Sound's Pitch in Real Time (Pitch Bend Lever) Adding a Vibrato Effect to the Sound (Modulation Lever) Changing the Tone with the Knobs Vibrato and Wah Effects (LFO) Changing the Sound's volume (ENVELOPE) Changing the Brightness of the Sound and Adding Special Qualities (FILTER) Changing the RS-5/9's Settings All At Once (Selecting Performances) Easily Selecting the Performances | 34363738394042444446455051525255 |
| Playing Two Tones on the Keyboard Dividing the Keyboard into Separate Ranges and Playing Different Tones in Each (SPLIT) Playing two Tones from the keyboard (DUAL) Selecting Tones and Drum Sets Selecting Tones By Category (TONE CATEGORY) Selecting Tones by Specifying the Group and Number Changing the Two Parts Being Used Changing the Split Point Using the Convenient Functions in Performances Creating Arpeggios from the Chords You Play (ARPEGGIO ON/OFF) Using Multi-effects, Chorus, and Reverb Turning the Effects On and Off (EFFECTS ON/OFF) Setting the Amount of Chorus and Reverb Changing the Multi-effect Type Transposing All the Parts (TRANSPOSE ON/OFF) Setting the Amount of Transposition Changing the Sound's Pitch in Real Time (Pitch Bend Lever) Adding a Vibrato Effect to the Sound (Modulation Lever) Changing the Tone with the Knobs Vibrato and Wah Effects (LFO) Changing the Sound's Seltings All At Once (Selecting Performances) | 3436373839404244444647485051525255 |


| Advanced Use | 61 |
|--|-----|
| Chapter 1. An overview of the RS-5/9 | 62 |
| Basic Organization of the RS-5/9 | 62 |
| Classification of RS-5/9 Sound Types | 62 |
| Tone | 62 |
| Drum Set | 62 |
| Performance | 62 |
| About Memory | 63 |
| Maximum Polyphony | 64 |
| Preventing notes of an important Part from being cut off (Voice Reserve) | 64 |
| Modifying the Value of a Setting | 64 |
| Convenient shortcuts | 65 |
| If "Stuck" Notes Occur (PANIC) | 65 |
| When Sounds From the RS-5/9 Do Not Stop Playing | 65 |
| What to Do When an External Sound Generator Fails to Stop Sounding | 65 |
| Chapter 2. Part Volume and Pan Settings | |
| | |
| Chapter 3. Mastering Use of the Performance Features | 67 |
| Playing single-note lines (Solo) | 67 |
| Smoothly Changing the Pitch of the Sound (Portamento) | 67 |
| Determining the Volume from the Force Used To Play the Keys (Velocity Sense) | 68 |
| Transposing Performances | 69 |
| Transposing All Parts (TRANSPOSE ON/OFF) | 69 |
| Transposing a Specified Part (Key Shift) | 69 |
| Adding Breadth to the Sound by Layering Tones with Different Pitches (Fine Tune) | 69 |
| Changing to Pure Temperament or an Arabic scale (Scale Tune) | 70 |
| What are Equal Temperament, Pure Temperament, and Arabic scales? | 70 |
| Making Scale Tune settings | 70 |
| Chapter 4. Changing Tones in Real Time | 71 |
| Changing the Pitch in Realtime (Pitch Bend Lever) | 71 |
| Using the Modulation Lever to modify the sound | 71 |
| Using a pedal to modify the sound | 73 |
| Switching the Pedal's Polarity (Pedal Polarity) | 73 |
| Using a knob to modify the sound | 74 |
| Switching to the Value at the Current Knob Positions (MANUAL) | 74 |
| Chapter 5. Using the arpeggiator | |
| Turning the Arpeggio Function On and Off (ARPEGGIO ON/OFF) | / 5 |
| Tip for Creating Arpeggio Patterns | 75 |
| Arpeggiator parameters you can set | 75 |
| Creating a pattern | |
| Using the Knobs to Change Patterns in Real Time | // |
| _ | |
| Chapter 6. Effect Settings | 79 |
| Turning the Effect Function On and Off (EFFECTS ON/OFF) | |
| The Effect Signal Path | 80 |
| Making Multi-Effects Settings | 80 |
| Setting the Multi-Effects Source | 80 |
| Select the Type and Set Each Parameter | |
| 00: THROUGH | 82 |
| 01: STEREO EQ (Stereo Equalizer) | 82 |
| 02: OVERDRIVE | 83 |
| 03: DISTORTION | 83 |
| 04: PHASER | |
| 05: SPECTRUM | |
| 06: ENHANCER | 85 |
| 07: AUTO WAH | 85 |
| 08: ROTARY | 86 |

Contents

| 09: COMPRESSOR | |
|---|-----|
| 10: LIMITER | |
| 11: HEXA-CHORUS | 88 |
| 12: TREMOLO CHORUS | |
| 13: SPACE-D | 89 |
| 14: STEREO CHORUS | 89 |
| 15: STEREO FLANGER | 90 |
| 16: STEP FLANGER | 91 |
| 17: STEREO DELAY | 92 |
| 18: MODULATION DELAY | 93 |
| 19: TRIPLE TAP DELAY | 94 |
| 20: QUADRUPLE TAP DELAY | 95 |
| 21: TIME CONTROL DELAY | |
| 22: 2VOICE PITCH SHIFTER | |
| 23: FBK PITCH SHIFTER (Feedback Pitch Shifter) | 97 |
| 24: REVERB | |
| 25: GATED REVERB | |
| 26: OVERDRIVE→CHORUS | |
| 27: OVERDRIVE→FLANGER | 100 |
| 28: OVERDRIVE→DELAY | |
| 29: DISTORTION—CHORUS | |
| 30: DISTORTION—FLANGER | |
| 31: DISTORTION→DELAY | |
| 32: ENHANCER→CHORUS | |
| 33: ENHANCER→FLANGER | |
| 34: ENHANCER→DELAY | |
| 35: CHORUS→DELAY | |
| 36: FLANGER→DELAY | |
| 37: CHORUS→FLANGER | |
| 38: CHORUS/DELAY | 105 |
| 39: FLANGER/DELAY | 105 |
| 40: CHORUS/FLANGER | |
| 40: CHOROS/TEANGER | |
| 42: SLICER | |
| Setting Multi-Effects as On/Off for Individual Parts | |
| Making Chorus Settings | 107 |
| Select the Type and Set Each Parameter | 107 |
| Setting the Chorus Depth for Each Part | 108 |
| Making Reverb Settings | 108 |
| Selecting the Type and Setting Each Parameter | 108 |
| Setting the Type and Setting Each Parameter Setting the Reverb Depth of Each Individual Part | 100 |
| | |
| Chapter 7. Creating your original Tone or Drum Set | 110 |
| Creating a Tone | |
| Tone Parameters That Can Be Set | |
| Creating a Tone | |
| Creating a Drum Set | |
| Drum Set Parameters That Can Be Set | |
| Creating a Drum Set | 112 |
| Chapter 8. Saving Your Settings | 113 |
| Saving Tone / Drum Set / Performance | 113 |
| Assigning a name | 113 |
| How to Save | |
| Saving settings on an external sequencer (Bulk Dump) | |
| Setting the Device ID Number | |
| Bulk dump procedure | |
| Setting the System Exclusive Receive Switch | |
| Restoring saved settings to the RS-5/9 | |
| | |

| Chapter 9. Restoring the Original Settings | 117 |
|---|------------|
| Restoring the Factory Settings (Factory Reset) | 117 |
| Restoring GM/GM2 Basic Settings (GM/GM2 SYSTEM ON) | |
| Chapter 10. Performing With An External MIDI Device | 118 |
| About MIDI | |
| MIDI connectors | |
| MIDI Channels and Multi-timbral Sound Generators | |
| MIDI messages used by the RS-5/9 | 120 |
| Playing Sounds from an External MIDI Sound Generator With the RS-5/9 Connecting to External MIDI Sound Generators | 120 |
| Set the Keyboard Transmit Channel | |
| Selecting sounds on another device using the RS-5/9 | 121 |
| Playing the RS-5/9's Sound Generator from an External MIDI Device | 122 |
| Connecting External MIDI Device | 122 |
| Setting the Receive Channel and Tone Change Receive Switch | 122 |
| Selecting RS-5/9 Sounds from an External MIDI Device | 123 |
| Using an External MIDI Controller to Change the RS-5/9's Tones | 123 |
| Chapter 11. Recording Performances on the RS-5/9 to an External Device | 124 |
| Recording to an External Sequencer | 124 |
| Connecting to an External Sequencer | |
| Making Settings Before Recording | 124 |
| Recording | 125 |
| Listening to the Recorded Performance | 126 |
| Playing Together with the Playback of a Recorded Performance Transposing Playback of Performances (Master Key Shift) | 126 |
| Enjoying Computer Music | |
| Connecting a Computer | |
| Making Settings Prior to Recording, Recording, and Listening to the Recorded Performance. | 128 |
| Using the RS-5/9 as a GM/GM2 System-Compatible Sound Module | 128 |
| Playing Back GM/GM2 Music Data | 128 |
| Creating Songs for GM and GM2 System Sound Generators | 129 |
| | 101 |
| Appendices | 3 1 |
| Troubleshooting | 132 |
| Error Messages/Message List | |
| Error Message List | 135 |
| Message List | 135 |
| Parameter List | |
| Performance | |
| Performance Part | |
| Tone | |
| Drum Set | |
| System | |
| Multi-Effect | 142 |
| Performance List | 147 |
| Tone List | |
| Drum Set List | |
| | |
| Arpeggio Style List | |
| MIDI Implementation | |
| Specifications | |
| Index | |
| Information | 178 |

Front and Rear Panel



PIANO Button (RS-9 Only)

You can get the perfect settings for piano performances with the press of a single button (p. 60).

A

VOLUME Knob

Adjusts the overall volume that is output from the OUTPUT jacks, and the PHONES jack (p. 16).

LFO

RATE Knob

Changes the LFO Rate value (p. 52).

DEPTH Knob

Changes the LFO Depth value (p. 52).

ENVELOPE

ATTACK Knob

Changes the Envelope Attack Time value (p. 54).

RELEASE Knob

Changes the Envelope Release Time value (p. 54).

MANUAL Button

Sets the parameters assigned to the six knobs (LFO, ENVELOPE, FILTER) to the values at the current knob positions (p. 74).

ARPEGGIO/CONTROL Button

Allows control of other parameters with the four LFO and ENVELOPE knobs (p. 74, 78).

FILTER

LFO ON/OFF Button

This determines whether the LFO changes the filter cutoff frequency (ON), or the pitch (OFF) (p. 52).

CUTOFF Knob

Changes the Tone's Cutoff Frequency value (p. 55).

RESONANCE Knob

Changes the Tone's Resonance value (p. 55).

B

LED Display


Displays the Tone number, Drum Set number, or Performance number.

Display

This displays information regarding the operation you are performing.

FAVORITE PERFORM BANK Buttons 1-8

These allow you to register and immediately call up your favorite Performances (p. 58).



C

PHRASE PREVIEW Button

Press this button to check the sound of a Tone or Drum Set before selecting (p. 33).

UTILITY Button

Used when saving data (p. 113), transmitting GM or GM2 Setup messages (p. 129), and restoring previous settings (p. 117).

PART **◄**/► Button

Switches the Parts (p. 28).

VALUE -/+ Button

This is used to modify values. When one of these buttons is first held down and the other is pressed, the value then changes rapidly while [SHIFT] is held down (p. 64).

D

KEY MODE

SPLIT Button

Sets Key Mode to Split. When pressed, the keyboard is split into two separate ranges, with a different Tone played in each (p. 34).

DUAL Button

Sets Key Mode to Dual. When pressed, two different Tones are layered together (p. 36).

ARPEGGIO ON/OFF Button

This button turns the arpeggio on or off (p. 75).

EFFECTS ON/OFF Button

Switches the multi-effects, reverb, and chorus effects on and off (p. 79).

TRANSPOSE ON/OFF Button

Transposes all Parts (p. 48).

SHIFT Button

This button is used in conjunction with other buttons (p. 64, 65).

E

TONE CATEGOTY Button

Selects Tones when the Tone Search function is used (p. 23).

PERFORM/TONE Button

This button switches between the Tone Select display and the Performance Select display (p. 23, 29, 57).

USER/PRESET Button

This button switches between User Tones (or Drum Sets or Performances) and Preset Tones (or Drum Sets or Performances) (p. 26, 30, 57).

F

Numeric Keys 1-0


Used for inputting numbers when selecting and saving Tones and Performances (p. 27, 30, 57). When selecting Tones by category, these specify the category (p. 23). When the EDIT button is pressed, the functions printed beneath the buttons can be selected.

EDIT Button

Press this button when you wish to adjust various settings.

ENTER Button

Use this button to finalize a value or execute an operation.



G

MIDI Connectors

External MIDI devices can be connected here (p. 120, 122, 124, 127). Use MIDI cables (sold separately) to make connections.

IN:

MIDI messages from an external device are received at this connector.

OUT:

MIDI messages are transmitted from this connector to an external device.

THRU:

MIDI messages received at MIDI IN are re-transmitted without change from this connector to an external MIDI device.

Н

PEDAL Jack

CONTROL:

Accepts connection of an external pedal, such as an expression pedal (the optional EV-5), pedal switch (the optional DP-2/6), or foot switch (the optional BOSS FS-5U) (p. 14).

HOLD:

Allows you to use a connected pedal switch (the optional DP-2/6) or foot switch (the optional BOSS FS-5U) as a hold pedal (p. 14).

I

OUTPUT Jacks

Connect your amp or mixer to these jacks (p. 14). These jacks output the audio signal in stereo. For mono output, use the L jack.

J


PHONES Jack

Accepts connection of headphones (p. 14).

K

Cord Hook

To prevent the inadvertent disruption of power to your unit (should the plug be pulled out accidentally), and to avoid applying undue stress to the AC adaptor jack, anchor the power cord using the cord hook, as shown in the illustration.



L

AC Adaptor Jack

Connect the included AC adaptor here (p. 14).

M

POWER Switch

Turns the power on/off (p. 15).


Quick Start

Getting Ready

Connecting the RS-5/9 to external equipment

The RS-5/9 does not contain an amp or speaker. You'll need to listen to it through powered monitors, a mixer and connected monitors, a stereo system, or through headphones.

Connect as follows when using the RS-5/9 as a stand-alone device.



Before starting the connection procedure, make sure that the power to all devices has been turned off.

NOTE

- To prevent the inadvertent disruption of power to your unit (should the plug be pulled out accidentally), and to avoid applying undue stress to the AC adaptor jack, anchor the power cord using the cord hook, as shown in the illustration.
- Audio cables, MIDI cables, and stereo headphones are not included. You will need to purchase these items from your dealer.
- Use only the specified expression pedal (EV-5; sold separately). By connecting any other expression pedals, you risk causing malfunction and/or damage to the unit.

NOT

To prevent malfunction and/or damage to speakers or other devices, always turn down the volume, and turn off the power on all devices before making any connections.

1

- **2** Connect the supplied AC adaptor to the RS-5/9, and then plug its other end into a power outlet.
- Connect the RS-5/9 and the external device as shown in the figure.

Use audio cables to connect audio equipment, such as an amp or speakers. If you are using headphones, plug them into the PHONES jack. Connect pedal switches or expression pedals as necessary.

When you want to how to make the connections for use with another external device

- "Playing Sounds from an External MIDI Sound Generator With the RS-5/9" (p. 120)
- "Playing the RS-5/9's Sound Generator from an External MIDI Device" (p. 122)
- "Recording to an External Sequencer" (p. 124)
- "Enjoying Computer Music" (p. 126)

MEMO

- CONTROL PEDAL jack can also accommodate pedal switches.
- In order to take full advantage of the RS-5/9's performance, we recommend using a stereo amp/speaker system, If you are using a mono system, make you connections to the OUTPUT jack L (MONO).

Turning On the Power

- Before turning on the RS-5/9's power, make sure that:
 - Are all devices connected properly?
 - Are the volume controls of the RS-5/9 and the other connected equipment turned to the minimum position?
 - Is the AC adapter correctly connected to the RS-5/9?
- **2** Press the RS-5/9's power switch on the rear panel to turn on the power.





Once the connections have been completed (p. 14), turn on power to your various devices in the order specified. By turning on devices in the wrong order, you risk causing malfunction and/or damage to speakers and other devices.



This unit is equipped with a protection circuit. A brief interval (a few seconds) after power up is required before the unit will operate normally.

3 Turn on the power of the connected audio devices.

Getting Ready

4

Play the RS-5/9's keyboard and gradually raise the volume controls of the RS-5/9, or the connected audio equipment to an appropriate volume level.





Turn up the RS-5/9's volume level carefully. Excessive volume can damage connected audio devices, your hearing, or annoy your neighbors.

Turning the power off


- Before you turn off the power, make sure of the following points.
 - Are the volume controls of the RS-5/9 and the other connected equipment turned to the minimum position?
 - Have you saved the sounds or other data you've created? (p. 113)
- **2** Turn off the power for all connected audio devices.
- **3** Turn off the RS-5/9 power switch.

Adjusting the display contrast (LCD CONTRAST)


The characters in the display may be difficult to view immediately after turning on the power or after extended use; this may also be because of where and how the display is situated. Follow the steps below to adjust the display's contrast.



The LCD CONTRAST setting affects the RS-5/9 as a whole (i.e., is a system setting). This setting remains stored in memory even while the power is off.



- **1** Press [EDIT], getting the indicator to light.
- **2**Use VALUE [-]/[+] to select "System Setup."
- **3** Press [ENTER].
- 4 Press [5] a number of times to select "LCD Contrast."



HINT


If you hold down [SHIFT] and press [5], you will return to the previous item.

- **5** Press VALUE [-]/[+] to set the value (1–8).
- Press [EDIT].

 The [EDIT] indicator goes out, and you are returned to the previous screen.


Easily Setting the LCD Contrast

If you hold down [SHIFT] while you press [PHRASE PREVIEW], you can select the "LCD Contrast" screen directly. Make settings as explained in steps 5–6 of the above procedure.



Adjusting the pitch to other instruments (Master Tuning)

When playing the RS-5/9 together with other instruments, the pitch of all instruments must be adjusted to match—otherwise you will be out of tune! In general, the tuning of an instrument is indicated by the pitch in Hertz (Hz) of the middle "A" note.



- **7** Press [EDIT], getting the indicator to light.
- **2** Use VALUE [-]/[+] to select "System Setup."
- **3** Press [ENTER].
- Press [4] a number of times to select "Master Tune."

| SYSTEM | | TUNE |
|--------|-------|---------|
| Master | Tune: | 440.0Hz |

- Press VALUE [-]/[+] to set the value (415.3–440.0–466.2).

 Match the pitch of the middle "A" note on the RS-5/9 to the other instruments.
- Press [EDIT].

 The [EDIT] indicator goes out, and you are returned to the previous screen.

MEMO

The Master Tune setting is a system setting that is applied to the entire RS-5/9 (i.e., is a system setting). This setting remains stored in memory even while the power is off.

HINT

If you hold down [SHIFT] and press [4], you will return to the previous item.



The process of putting the standard pitches in tune is called "**Tuning**."


Listening to the Demo (DEMO)

The RS-5/9 contains Demo songs.

Here's how to hear the demo songs and experience the superb sounds and effects of the RS-5/9.



All rights reserved. Unauthorized use of this material for purposes other than private, personal enjoyment is a violation of applicable laws.



Press [SHIFT] and [TRANSPOSE ON/OFF] at the same time.
The following display will appear.

DEMO Press CENTERI All Songs

- Press VALUE [-]/[+] to select the song that you wish to hear.

 If you want to listen to all of the songs played in order, select "All Songs."
- Press [ENTER] to start demo song playback.

 The selected song is played back repeatedly.

 When "All Songs" is selected, the entire selection of songs is played back
- **4** Press [EXIT] to stop playback.

repeatedly.

To return the keyboard to performance mode, press [EXIT] once more.

NOTE

- While the demo songs are playing back, playing the keyboard will not produce sound.
- No data for the music that is played will be output from MIDI OUT.

HINT

- In Step 4, the performance stops even when [ENTER] is pressed instead of [EXIT].
- In Step 5, the keyboard is returned to performance mode even when [ENTER] is pressed instead of simultaneously pressing [SHIFT] and [TRANSPOSE ON/OFF].

Listening to the Demo (DEMO)

Demo Songs List

The RS-5/9 comes with 3 demos.

1. The Groove's Up

Copyright © 2000, Roland Corporation

2. RS Fanfare

Copyright © 2000, Roland Corporation

3. Journey To RS

Copyright © 2000, Roland Corporation

Playing the Sounds

Playing the Sounds

Restoring the Factory Settings (Factory Reset)

When learning how to use the RS-5/9, it's a good idea to reset it to its factory settings to ensure that its operation matches the behavior described in its manuals.

NOTE


When this operation is executed, the settings stored in the User Area (where the User Tones and other Tones you have created are stored) as well as the System setup settings are lost. If you want to keep this data, save it to an external sequencer or computer using "Bulk Dump" (p. 115).

Notes



When data is being written to the User Memory, the message "KEEP POWER ON!" appears in the display; be sure not to turn off the power while this message is displayed.

If the power is turned off or interrupted while data is being written to memory, the internal data may become corrupted, and you may not be able to turn the power back on. If you have confirmed that internal data has been lost, or if a similar problem exists, consult your Roland dealer or Roland Service. Note, however, that Roland assumes no liability, including compensation, for consequences arising from loss of data.




- **1** Press [UTILITY], getting the indicator to light.
- **2** Use VALUE [-]/[+] to select "Factory Reset."

UTILITY [ENTER] Factory Reset

3 Press [ENTER].

Playing the Sounds



4 Use VALUE [-]/[+] to select "All."

| FACTORY | CENTERI |
|---------|---------|
| A11 | |

5 Press [ENTER].

The confirmation message appears.

Press [ENTER] once again to start the Factory Reset operation.

After the Factory Reset operation is finished, the display will indicate "Completed."

The [UTILITY] indicator goes out, and you are returned to the previous screen.

When you want to return a portion of the User memory to factory settings

• "Restoring the Factory Settings (Factory Reset)" (p. 117)

MEMO


- To cancel the Factory Reset, press [EXIT].
- Even if the Factory Reset operation is executed, the display may be difficult to read, depending on the angle at which the RS-5/9 is placed. When this occur, adjust depth of the display (p. 16).

Selecting Tones By Category (TONE CATEGORY)


The RS-5/9 features a **Tone Search function** that allows you to rapidly select and call up Tones by specifying the type of tone (Category). The 35 categories are organized into 10 groups.

MEMO

When shipped from the factory, [TONE CATEGORY] is set to "ON."



- Press [PERFORM/TONE] to call up the Tone Search screen.
- Make sure that the [TONE CATEGORY] indicator is lit.
 If the [TONE CATEGORY] indicator is not lit, press [TONE CATEGORY] once more.



- Press the numeric keys ([1]–[0]) a number of times until you can select the Category you want.
- Press VALUE [-]/[+] to select a Tone in the currently selected Category.

HINT

Should "PERFORM" be displayed, simply press [PERFORM/TONE] once more, and the Tone selection screen is

Playing the Sounds

Selecting Categories from the Full List

In Step 3, if you hold down [TONE CATEGORY] and press a numerical key ([1]–[0]), the Category selection screen is displayed.

The indicator will begin blinking, instead of lighting steadily.

Press the numeric keys ([1]–[0]) a number of times, or press VALUE [-]/[+], to select the Category.

Pressing [TONE CATEGORY] or [EXIT] returns you to the original screen (the screen displayed in Step 2).

The indicator changes from blinking to lit.

When a Drum Set is Selected

"DRM" appears in the display if a Drum Set is selected when [TONE CATEGORY] is on (p. 29).

Note that, in this case, the numerical keys ([1]–[10]) are disabled.

DRUM1: RS Pop Kit 1 Part 10 User:(DRM) The following categories can be selected.

| Category Group | Catego | ory | Contents |
|-------------------|--------|--------------|---|
| Piano | PNO | AC.PIANO | Acoustic Piano |
| | EP | EL.PIANO | Electric Piano |
| Keys&Organ | KEY | KEYBOARDS | Other Keyboards (Clav, Harpsichord etc.) |
| | BEL | BELL | Bell, Bell Pad |
| | MLT | MALLET | Mallet |
| | ORG | ORGAN | Electric and Church Organ |
| | ACD | ACCORDION | Accordion |
| | HRM | HARMONICA | Harmonica, Blues Harp |
| Guitar | AGT | AC.GUITAR | Acoustic Guitar |
| | EGT | EL.GUITAR | Electric Guitar |
| | DGT | DIST.GUITAR | Distortion Guitar |
| Bass | BS | BASS | Acoustic & Electric Bass |
| | SBS | SYNTH BASS | Synth Bass |
| Orchestral | STR | STRINGS | Strings |
| | ORC | ORCHESTRA | Orchestra Ensemble |
| | HIT | HIT&STAB | Orchestra Hit, Hit |
| | WND | WIND | Winds (Oboe, Clarinet etc.) |
| | FLT | FLUTE | Flute, Piccolo |
| Brass | BRS | AC.BRASS | Acoustic Brass |
| | SBR | SYNTH BRASS | Synth Brass |
| | SAX | SAX | Sax |
| Synth | HLD | HARD LEAD | Hard Synth Lead |
| • | SLD | SOFT LEAD | Soft Synth Lead |
| | TEK | TECHNO SYNTH | Techno Synth |
| | PLS | PULSATING | Pulsating Synth |
| | FX | SYNTH FX | Synth FX (Noise etc.) |
| | SYN | OTHER SYNTH | Poly Synth |
| Vocal&Pad | VOX | VOX | Vox, Choir |
| | BPD | BRIGHT PAD | Bright Pad Synth |
| | SPD | SOFT PAD | Soft Pad Synth |
| Ethnic | PLK | PLUCKED | Plucked (Harp etc.) |
| | ETH | ETHNIC | Other Ethnic |
| | FRT | FRETTED | Fretted Inst (Mandolin etc.) |
| Rhythm&SFX | PRC | PERCUSSION | Percussion |
| | SFX | SOUND FX | Sound FX |
| | | | |

Selecting Tones by Specifying the Group and Number

Tones are separated into the following two groups. You can select Tones by specifying the group and number.

User


128 Tones can be stored here. You can overwrite the Tones already stored here, replacing them with Tones you create (p. 113).

Preset


This area holds 512 Tones; these cannot be overwritten or replaced. However you may modify the settings of the currently selected tone, and then store the modified tone in User memory.

1–256 are the RS-5/9's original Tones.

Tones 257–512 provide compliance with GM2.



- **7** Press [PERFORM/TONE] to display the Tone selection screen.
- **2** Press [TONE CATEGORY] to make the indicator goes out. The following screen appears.



3 Press [USER/PRESET] to select the group (User or Preset).

HINT

Should "PERFORM" be displayed, simply press [PERFORM/TONE] once more, and the Tone selection screen is Press the numeric keys ([1]–[0]) to specify the Tone number (User: 1–128, Preset: 1–512).

If you make a mistake, press [EXIT] and specify the number once more.

5 Press [ENTER] to finalize the entry.

HINT

MEMO

Instead of using Steps 4 and 5, you can also switch Tones by pressing VALUE [-]/[+].

Changing values by large amounts

When changing values on the RS-5/9, press VALUE [-]/[+]. You can change values by large amounts using the methods described below.

To increase the value, hold down VALUE [+] and press VALUE [-].

To decrease the value, hold down VALUE [-] and press VALUE [+].

To increase the value in units of ten, hold down [SHIFT] and press VALUE [+].

To decrease the value in units of ten, hold down [SHIFT] and press VALUE [-].

When you want to know the name and number of the Tone

• "Tone List" (p. 148)

When you want to know how to switch Tones with Key Mode set to Split or Dual

• "Selecting Tones and Drum Sets" (p. 37)

To create Tones by yourself

• "Creating a Tone" (p. 110)

When you want to store a Tone you have created to User memory

• "Saving Tone / Drum Set / Performance" (p. 113)

When you want to switch Tones from an external MIDI device

• "Selecting RS-5/9 Sounds from an External MIDI Device" (p. 123)

Easy Tone Selection (Switching Parts)


By switching Parts, you can select Tones easily.

The RS-5/9 has 16 Parts. Parts are the equivalent of performers playing instruments, and you can assign a different Tone to each individual Part.

- Selecting Tones By Category (TONE CATEGORY)
- Selecting Tones by Specifying the Group and Number


The two methods of selecting Tones shown above are used to change Tones while a single Part is selected.

Here, let's select a Tone easily by switching Parts.



1

Press PART [\blacktriangleleft]/[\blacktriangleright] and select one of the Parts 1–16.



HINT

By selecting a Tone (p. 23, 26) or Drum Set (p. 29, 30) after selecting a Part, you can then switch the Tone or Drum Set for that Part.

When you want to perform in ensemble using multiple parts

- "Recording to an External Sequencer" (p. 124)
- "Enjoying Computer Music" (p. 126)

When you want to know how to switch Parts with Key Mode set to Split or Dual

• "Changing the Two Parts Being Used" (p. 39)

Playing the Sound


Playing Percussion Instruments (Drum Sets)

The RS-5/9 contains Drum Sets that allow you to play different percussion instruments or sound effects from each key of the keyboard.


Changing a Drum Set

Factory settings have a Drum Set assigned to Part 10, so you can immediately use the keyboard to play percussion instrument sounds by pressing PART [\blacktriangleleft]/[\blacktriangleright] to select Part 10.

Here, let's select Part 10 and learn how to switch Drum Sets.



- Press [PERFORM/TONE] to call up the Tone/Drum Set selection screen.
- **2** Press PART [**◄**]/[**▶**] to select Part 10.



3 Press VALUE [-]/[+] to switch the Drum Set.

HINT

Should "PERFORM" be displayed, simply press [PERFORM/TONE] once more, and the Tone/Drum Set selection screen is displayed.

Selecting Drum Sets by Specifying the Group and Number

Just as are Tones, Drum Sets are separated into two groups. You can also select Drum Sets by specifying the group and number.

User


Two Drum Sets can be stored here. You can overwrite these, replacing them with Drum Sets you create (p. 113).

Preset


This area holds twenty Drum Sets; these cannot be overwritten or replaced. However, you can change the settings of a currently selected Drum Set, and then store those settings in User memory.

1–11 are the RS-5/9's original Drum Sets.

Drum Sets 12–20 provide compliance with GM2.



- Press [PERFORM/TONE] to call up the Tone/Drum Set selection screen.
- Press [TONE CATEGORY] to make the indicator goes out.
 The following screen appears.



- **3** Press [USER/PRESET] to select the group (User or Preset).
- Press the numeric keys ([1]–[0]) to specify the Drum Set number (USER: 1, 2, Preset: 1–20).

HINT

Should "PERFORM" be displayed, simply press [PERFORM/TONE] once more, and the Tone/Drum Set selection screen is displayed.



If you make a mistake, press [EXIT] and specify the number once again.


5 Press [ENTER] to finalize the entry.

Playing a Drum Set in a Part Other Than Part 10

You can also Play Drum Sets in Parts other than Part 10.

HINT

Instead of using Steps 4 and 5, you can also switch Drum Sets by pressing VALUE [-]/[+].



- **1** Press [EDIT], getting the indicator to light.
- **2**Use VALUE [-]/[+] to select "Performance Part."
- **3** Press [ENTER].
- **5** Press [5] a number of times to select "Tone Type."

| PART | 1 | CONTROL |
|------|-------|---------|
| Tone | Type: | DRUM1 |

- **6** Press VALUE [-]/[+] to select "DRUM1" or "DRUM2."
- Press [EDIT].

 The [EDIT] indicator goes out, and you are returned to the previous screen.

MEMO

Separate Tone Type settings can be made for each individual Part in a Performance (p. 56).

NOTE

When Key Mode (p. 34) is set to Split or Dual, you can select only the Upper Part and the Lower Part.

HINT

If you hold down [SHIFT] and press [5], you will return to the previous item.

MEMO

- If you wish to make settings for other Parts, repeat steps 4–6.
- If you want to go from Drum Sets back to regular Tones, press "TONE" in Step 6.


Notes when selecting a Drum Set

Whether a Tone or a Drum Set is played in any Part is determined with the selection of TONE, DRUM1, or DRUM2 in the Tone Type setting as described in Step 6 of "Playing a Drum Set in a Part Other Than Part 10" (p. 31).

Up to 2 Drum Sets can be assigned to the Parts. The same Drum Set will be selected for each Part whose Tone Type is set to DRUM1. The same is true for a setting of DRUM2.

Example:

DRUM1 has been specified for Parts 1 and 2, and the STANDARD Drum Set is selected. In this situation if you change Part 1 from STANDARD to ELECTRONIC, Part 2 will automatically be set to ELECTRONIC.



When you want to play a percussion instrument assigned to a key outside the key range

• "Transposing All the Parts (TRANSPOSE ON/OFF)" (p. 48)

When you want to know a Drum Set's name and number

• "Drum Set List" (p. 151)

To create your own Drum Sets

• "Creating a Drum Set" (p. 112)

When you want to store a Drum Set you have created to User memory


• "Saving Tone / Drum Set / Performance" (p. 113)

When you want to switch Drum Sets from an external MIDI device

• "Selecting RS-5/9 Sounds from an External MIDI Device" (p. 123)

Trying out tones (PHRASE PREVIEW)

You can check out Tones using specially prepared phrases in each Tone Category.



- **1** Select a Tone or Drum Set (p. 23, 26, 29, 30).
- **2** Press and hold [PHRASE PREVIEW].
- **3** Release your finger from [PHRASE PREVIEW], and the phrase will stop playing.

MEMO

The selected Tone or Drum Set plays when Key Mode (p. 34) is set to Split or Dual.



Tone and Drum Set categories are set; they cannot be modified.

Playing Two Tones on the Keyboard

The setting that determines whether one or two Tones are played by a key is referred to as "**Key Mode**." There are three Key modes.

Single: The same Tone is played by all keys on the keyboard. This is the normal playing mode.

Split: One key acts as the division point (the "split point") separating the keyboard into left- and right-hand sides, with a different Tone


played in each.

Dual: Two Tones can be layered together.



Different Key Mode settings can be made for each individual Performance.


Dividing the Keyboard into Separate Ranges and Playing Different Tones in Each (SPLIT)



1

Press [SPLIT], getting the indicator to light.

Try fingering the keyboard.



In Split, two Parts are used. These are referred to as the "**Upper Part**" and the "**Lower Part**." The tone data for the currently selected parts appears in the display.

The above figure shows an example where Part 1 is used for the Upper Part, and Part 16 is used for the Lower Part.


The split point is set to C4 at the factory. The upper range of the keyboard, including C4, plays the tone in the Upper Part, and the Lower Part Tone is played in the range below C4.

HINT

In some Preset
Performances, Key Mode is
set to Split or Dual
(Performance List, p. 147).
Try switching
Performances (p. 56) and
listening to the various
combinations of tones.



The key used as the split point plays the Tone in the Upper Part.



2

If you press [SPLIT] once more, the indicator light goes out, and the keyboard returns to the normal performance mode (Single).

When you want to switch Tones

• "Selecting Tones and Drum Sets" (p. 37)


When you want to change the Parts used for the Upper and Lower Parts

• "Changing the Two Parts Being Used" (p. 39)

When you want to change the key dividing the keyboard into two ranges


• "Changing the Split Point" (p. 40)

Playing two Tones from the keyboard (DUAL)



1 Press [DUAL], getting the indicator to light.

Try fingering the keyboard.



Just as in Split mode, two Parts are used.

The Tones selected for the Upper Part and Lower Part are played together when a key is pressed.

If you press [DUAL] once more, the indicator light goes out, and the keyboard returns to the normal performance mode (Single).

When you want to switch Tones

• "Selecting Tones and Drum Sets" (p. 37)


When you want to change the Parts used for the Upper and Lower Parts

• "Changing the Two Parts Being Used" (p. 39)

Selecting Tones and Drum Sets


Use the following procedure to switch Tones when Key Mode is set to Split or Dual.

Selecting Tones By Category (TONE CATEGORY)



- Make sure that the [TONE CATEGORY] indicator is lit.

 If the [TONE CATEGORY] indicator is not lit, press [TONE CATEGORY] once more.



The above figure is an example where the Upper Part is selected.

Press the numeric keys ([1]–[0]) a number of times until you can select the Category you want.



Press VALUE [-]/[+] to select a Tone or Drum Set in the currently selected Category.

Playing Two Tones on the Keyboard

Selecting Categories from the Full List

In Step 3, if you hold down [TONE CATEGORY] and press a numerical key ([1]–[0]), the Category selection screen is displayed.

The indicator will begin blinking, instead of lighting steadily.


Category Select PNO Piano: AC.PIANO

Press the numeric keys ([1]–[0]) a number of times, or press VALUE [-]/[+], to select the Category.


Pressing [TONE CATEGORY] or [EXIT] returns you to the original screen (the screen displayed in Step 2).

The indicator changes from blinking to lit.

Selecting Tones by Specifying the Group and Number



- **1** Press [TONE CATEGORY] to make the indicator goes out.



The above figure is an example where the Upper Part is selected.

- **3** Press [USER/PRESET] to select the group (User, Preset).
- Press the numeric keys ([1]–[0]) to specify the Tone or Drum Set number.
- Press [ENTER] to finalize the entry.

 The Tone number or Drum Set number appears in the display.

MEMO

If you make a mistake, press [EXIT] and specify the number once more.

HINT


Instead of using Steps 4 and 5, you can also switch Tones by pressing VALUE [-]/[+].

Changing the Two Parts Being Used

Two Parts (Upper and Lower) are used when Key Mode is set to Split or Dual. You can select which of the 16 Parts will be the Upper Part and which will be the Lower Part.


MEMO

These settings can be made for each Performance (p. 56) individually.



- **1** Press [EDIT], getting the indicator to light.
- **2** Use VALUE [-]/[+] to select "Tone/Drum/PFMCommon."
- **3** Press [ENTER].

Playing Two Tones on the Keyboard



Press [9] a number of times to select "Upper Part" or "Lower Part."

HINT

If you hold down [SHIFT] and press [9], you will return to the previous item.

- PERFORMANCE KEYBOARD Upper Part: 1
- PERFORMANCE KEYBOARD Lower Part: 16
- **5** Press VALUE [-]/[+] to select the value (1-16).
- Press [EDIT].

 The [EDIT] indicator goes out, and you are returned to the previous screen.

Which Part Is Used in Single Mode?

When Key Mode is set to Single, the Upper Part is used.

Therefore, take care not to press PART [◀]/[▶] and switch the Part while in Single Mode, or the "Upper Part" value will be overwritten.

Changing the Split Point

When Key Mode is set to Split, you can set the key that divides the keyboard into two separate ranges anywhere from C2 to C#7.




Lower

C4 (Split Point) Upper

MEMO

The split point can be set individually for each Performance (p. 56).



- **1** Press [EDIT], getting the indicator to light.
- **2**Use VALUE [-]/[+] to select "Tone/Drum/PFMCommon."
- **3** Press [ENTER].
- 4 Press [9] a number of times to select "Split Point."

PERFORMANCE KEYBOARD Split Point: C 4

HINT

If you hold down [SHIFT] and press [9], you will return to the previous item.

- **5** Press VALUE [-]/[+] to select the value (C-1–G9).
- 6 Press [EDIT].

The [EDIT] indicator goes out, and you are returned to the previous screen.

A quick way to change the Split Point

If you hold down [SPLIT] and press [EDIT], you can select the "Split Point" screen directly. Make settings as explained in steps 5–6 of the above procedure.

Also, if you want be able to change the split point quickly, by holding down [SPLIT] and pressing VALUE [-]/[+], you can change only the "Split Point" setting. When you release [SPLIT], the previous display will reappear.

Using the Convenient Functions in Performances

This section explains how to utilize the different functions that are often used in performances.

MEMO

For instructions on making detailed settings, refer to the reference pages in the column.

Creating Arpeggios from the Chords You Play (ARPEGGIO ON/OFF)


Just by playing a chord, you can play an arpeggio (a chord that is played one note at a time) using the notes making up that chord.

You can play arpeggios in all key ranges when Key Mode is set to Single or Dual.


When Key Mode is set to Split, you can play arpeggios in the Lower range.



Arpeggios can be produced only by playing the RS-5/9's keyboard. Arpeggios cannot be played using Note messages that arrive at the MIDI IN connector.



- Press [ARPEGGIO ON/OFF], getting the indicator to light.
- **2** Press the key as shown in the figure below.



The arpeggio is played with the sequence of notes, C3, E3, G3, E3, C3, E3, G3, E3, and so on.

Try playing some other chords, too.

If you press [ARPEGGIO ON/OFF] once more, the indicator light goes out, and the keyboard returns to the normal performance mode.

MEMO

- Arpeggio data is output from the MIDI OUT connector.
- The arpeggio On/Off setting can be made individually for each Performance (p. 56).

Continuing Arpeggios Without Having To Hold Down the Key

Hold down the [SHIFT] button and press [ARPEGGIO ON/OFF]. The [ARPEGGIO ON/OFF] indicator starts blinking, and you can then have the arpeggio be played without having to continue pressing the chord. To cancel Arpeggio Hold, hold down [SHIFT] and press [ARPEGGIO ON/OFF] once more.

Note also that if a pedal switch (such as the optional DP-2/6), or a foot switch (such as the optional BOSS FS-5U) is connected to the PEDAL HOLD jack, you can have arpeggios be played if you depress the pedal while pressing chords. In this way, you can play arpeggios without having to continue pressing the chord.

When you want to know more about the arpeggio settings

• "Chapter 5. Using the arpeggiator" (p. 75)

Using Multi-effects, Chorus, and Reverb

The RS-5/9 provides three independent internal effect channels.

Multi-Effect

This channel can provide 42 different effects, including distortion and rotary effects.

Chorus

This channel adds depth and dimension to sounds.

Reverb


This channel creates an artificial ambience around the sound.

Turning the Effects On and Off (EFFECTS ON/OFF)

When shipped from the factory, all three effects are set to ON.



The On/Off settings for each Effect affect the RS-5/9 as a whole (i.e., are system settings). This setting remains stored in memory even while the power is off.



Press [EFFECTS ON/OFF] to make the indicator blink.

The Multi-effects On/Off settings screen appears in the display.

- **2** Press VALUE [-]/[+] to turn the effect on or off.
- **3** Press [EFFECTS ON/OFF].

Next, the Chorus On/Off settings screen appears in the display.

Chorus Switch ON

- **4** Press VALUE [-]/[+] to turn the effect on or off.
- **5** Press [EFFECTS ON/OFF].

Then the Reverb On/Off settings screen appears in the display.

Reverb Switch ON

- **6** Press VALUE [-]/[+] to turn the effect on or off.
- Press [EFFECTS ON/OFF] to return to the original screen.

 The [EFFECTS ON/OFF] indicator lights up whenever any of the three effects is on.

When Using Multi-effects in Split or Dual Mode

The RS-5/9 cannot use more than one multi-effect at a time. Therefore, there is a "Source" parameter which is used for selecting the multi-effect settings.

Settings Values

UPPER:

The Upper Tone's multi-effect settings are used. The

multi-effect is applied only to the Upper Part.

LOWER:

The Lower Tone's multi-effect settings are used. The

multi-effect is applied only to the Lower Part.

PERFORMANCE: The Performance's multi-effect settings are used. The

same multi-effect is applied to all Parts (1–16).

Thus, you should note that depending on the Source setting, some Parts may not have multi-effects applied while in Split or Dual mode.


For more detailed information, refer to "Making Multi-Effects Settings" (p. 80).

MEMO

- You can return to the original screen during the operation by pressing [EXIT].
- If all three effects are turned off, the [EFFECTS ON/OFF] indicator light goes out.

Using the Convenient Functions in Performances

Setting the Amount of Chorus and Reverb



- **1** Set the chorus or reverb to ON (refer to previous section).
- **2** Press [EDIT], getting the indicator to light.
- **3** Use VALUE [-]/[+] to select "Performance Part."
- 4 Press [ENTER].
- **6** If setting the chorus, press [7]; if setting the reverb, press [8].

| PART | 1 | CHORUS |
|--------|--------|--------|
| Send | Level: | 0 |
| PART | 1 | REVERB |
| Connot | Level: | 4.G |

- 7 Use VALUE [-]/[+] to select the value (1-127).
- Press [EDIT].

 The [EDIT] indicator goes out, and you are returned to the previous screen.



Separate settings for the amount of chorus and reverb applied can be made for each individual Part in a Performance (p. 56).



- When Key Mode (p. 34) is set to Split or Dual, you can select only the Upper Part and the Lower Part.
- Note that even if the chorus or reverb is set to ON, no effect is applied if each Send Level is set to 0.




If you wish to make settings for other Parts, repeat steps 5–7.

sing the Convenient Functions in Performance

Changing the Multi-effect Type

Here's how to select the desired one of the 42 different Multi-effect settings.



- **1** Set Multi-effects to ON (p. 44).
- **2** Press [EDIT], getting the indicator to light.
- **3**Use VALUE [-]/[+] to select "Tone/Drum/PFMCommon."
- 4 Press [ENTER].
- **5** Press [6] a number of times to select "Type."

| F | |
|-----------|------------|
| (II TONE) | MIII TT-EV |
| <u> </u> | |
| Type:01 | STEREO EQI |

The figure above shows Source set to UPPER. You can see which multieffects settings are being used in the upper left of the display.

- $\boldsymbol{6}$ Press VALUE [-]/[+] to select the type.
- Press [EDIT].

 The [EDIT] indicator goes out, and you are returned to the previous screen.

When you want to know about the Multi-effects in greater detail

• "Chapter 6. Effect Settings" (p. 79)

MEMO

You can set the Multi-Effects Type for each Tone or Performance (p. 56) individually with the Source setting.

HINT

If you hold down [SHIFT] and press [6], you will return to the previous item.



When set to "00:THROUGH," the multi-effects are then not

Transposing All the Parts (TRANSPOSE ON/OFF)

This function moves the key range in half-step units. This is convenient in situations like the ones below.

When matching the vocalist's register

Sometimes melodies may extend outside a vocalist's register. Therefore, if you want to perform with the song changed to a different key, you can play the song in a new key while still using the same fingering as before.

When changing from a difficult key to one that is easy to play

You can use simple fingerings to play difficult songs that include numerous sharps or flats.

When playing with the tone of a transposed instrument


You can play the tones of a transposed instrument just as it is written in the score.

When Playing sounds outside the keyboard's range

While the RS-5 features a 61-key keyboard, with some songs you may want to play notes even higher or lower. Also, when playing a Drum Set etc., there may be percussion instruments that the RS-5/9's keyboard is not able to access. In such cases, you can use the Transpose function to play these notes.



The Transpose On/Off settings can be set individually for each Performance (p. 56).



- Press [TRANSPOSE ON/OFF] to light indicator.


 Transpose is set at the factory to play notes at one octave below what is played.
- If you press [TRANSPOSE ON/OFF] once more, the indicator light goes out, and the keyboard returns to the normal performance mode.

Setting the Amount of Transposition

You can set the amount of transposition that is to occur when Transpose is switched on. The setting is made in semitone units, and can specify a rise or lowering of up to three octaves.



The settings for the amount of transposition can be set individually for each Performance (p. 56).



- **1** Press [EDIT], getting the indicator to light.
- **2**Use VALUE [-]/[+] to select "Tone/Drum/PFMCommon."
- **3** Press [ENTER].
- Press [9] a number of times to select "Transpose."

PERFORMANCE KEYBOARD Transpose: -12

- **5** Press VALUE [-]/[+] to select the value (-36 to +36).
- **6** Press [EDIT].

The [EDIT] indicator goes out, and you are returned to the previous screen.

An easy way to set Transpose

You can select the "Transpose" screen directly by holding down [TRANSPOSE ON/OFF] and pressing [EDIT]. Make settings as explained in steps 5–6 of the above procedure.

Furthermore, to change the transposition even more rapidly, you can change only the "Transpose" setting by holding down [TRANSPOSE ON/OFF] and pressing VALUE [-]/[+]. When you release [TRANSPOSE ON/OFF], the previous display will reappear.

When you want to transpose a specific Part

• "Transposing a Specified Part (Key Shift)" (p. 69)

NOTE

Note messages from MIDI IN connector will not be transposed.

HINT

If you hold down [SHIFT] and press [9], you will return to the previous item.

Changing the Sound's Pitch in Real Time (Pitch Bend Lever)


The "height" of a sound is called "pitch."

While playing the keyboard, move the lever to the left to lower the pitch, or to the right to raise the pitch.

When shipped from the factory, this is set so that the pitch is changed up or down one whole step.



Pitch Bend is not applied to arpeggios.




Pitch Bend

You can set up to a two-octave pitch bend range, adjustable in half-steps.



The pitch bend range settings can be made for each individual Part in a Performance (p. 56).



- **1** Press [EDIT], getting the indicator to light.
- **2** Use VALUE [-]/[+] to select "Performance Part."
- **3** Press [ENTER].
- **5** Press [5] a number of times to select "Pitch Bend Range."

| PART 1 | | CONTROL |
|--------|------|-----------|
| Pitch | Bend | Range:+ 2 |



When Key Mode (p. 34) is set to Split or Dual, you can select only two Parts, the Upper Part and the Lower Part.

HINT

If you hold down [SHIFT] and press [5], you will return to the previous item.

- **6** Press VALUE [-]/[+] to select the value (0 to +24).
- Press [EDIT].
 The [EDIT] indicator goes out, and you are returned to the previous screen.



With a setting of 0, there will be no pitch bend effect.




If you wish to make settings for other Parts, repeat steps 4–6.

Adding a Vibrato Effect to the Sound (Modulation Lever)

While playing the keyboard, move the lever away from you to add a vibrato effect.



The effect is applied to both the Upper Part and Lower Part when Key Mode is set to Split and Dual.



Modulation

When you want to use the Modulation Lever to add effects other than vibrato

• "Using the Modulation Lever to modify the sound" (p. 71)

Changing the Tone with the Knobs

Using the six panel knobs, you can change the tone in real time.

When a knob is turned, the function assigned to the knob and its value appear temporarily in the display.






The effect is applied to both the Upper Part and Lower Part when Key Mode is set to Split and Dual.

Vibrato and Wah Effects (LFO)

The LFO, short for "low frequency oscillator," makes changes to the sound in periodic fashion. Changing the pitch with the LFO produces the "**vibrato effect**," and by changing the filter cutoff frequency with the LFO, you get what is called the "**wah effect**."



Confirm that the FILTER [LFO ON/OFF] is set to OFF.

When [LFO ON/OFF] is set to OFF, you can use the LFO 2 knob to change the vibrato effect.

MEMO

If this is set to ON, press [LFO ON/OFF] once more to switch it off.

2 Turn the LFO DEPTH knob.

Turning this to the right increases the depth of the undulating sound, while turning it to the left makes the undulation shallower and milder.

3 Turn the LFO RATE knob.

Turning this to the right (clockwise) increases the speed of the undulating sound, while turning it to the left (counterclockwise) slows the undulation down.

Press FILTER [LFO ON/OFF], causing the indicator to light up.

When [LFO ON/OFF] is set to ON, you can use the LFO 2 knob to change the vibrato effect.

5 Turn the LFO DEPTH knob.

Turning this to the right increases the depth of the undulating sound, while turning it to the left makes the undulation shallower and milder.

6 Turn the LFO RATE knob.

Turning this to the right (clockwise) increases the speed of the undulating sound, while turning it to the left (counterclockwise) slows the undulation down.


Changing the sound's volume (ENVELOPE)


The volume continues to change from the time a key is pressed to when it is released.

A: Attack Time: The time it takes after the key is pressed for a sound to reach full volume.

R: Release Time: The time it takes after the key is released for a sound to become inaudible.

Use the ENVELOPE 2 knob to change the A and R times.





T Turn the ENVELOPE ATTACK knob.

Turning this to the right (clockwise) increases the time it takes for the sound to rise, while turning it to the left (counterclockwise) shortens this time.


2 Turn the ENVELOPE RELEASE knob.

Turning this to the right increases the time it takes for the sound to disappear, while turning it to the left shortens this time.

Jsing the Convenient Functions in Performances

Changing the Brightness of the Sound and Adding Special Qualities (FILTER)

You can change the brightness of the sound and give the sound peculiar characteristics using the FILTER 2 knob.



1 Turn the FILTER CUTOFF knob.

Turning this to the right (clockwise) brightens the sound, while turning it to the left (counterclockwise) makes the sound seem darker.

2 Turn the FILTER RESONANCE knob.

Turning this to the right makes the special quality of the sound stronger, while turning it to the left reduces these characteristics.

[MANUAL] and [ARPEGGIO/CONTROL] Functions

When [ARPEGGIO/CONTROL] is set to ON, you then become able to control another parameter using the LFO ENVELOPE 4 knob (p. 74). What's more, when [ARPEGGIO ON/OFF] is set to ON, and [ARPEGGIO/CONTROL] is flashing, you can use the four knobs to change the arpeggio settings in real time (p. 74).


When you press [MANUAL], the parameters assigned to the six knobs are set to the values at the current knob positions (p. 74).

When you want to know about changing the tone in real time in greater detail

• "Chapter 4. Changing Tones in Real Time" (p. 71)

Changing the RS-5/9's Settings All At Once (Selecting Performances)

The group of Tones and Drum Sets assigned to the sixteen Parts is known as a "**Performance**."



You can record the Tone numbers assigned to Parts as well as the Key Mode, Arpeggio, Transpose, and other settings to the Performance.

If you store a group of settings in a Performance, you can then call up those settings instantly by simply selecting that Performance.


Performances, just like Tones, are divided into two groups.

User

Although this area comes provided with 128 prepared Performances, you can overwrite these with Performances that you create.


Preset

This area holds 128 prepared Performances; these cannot be overwritten or replaced. But you can call up preset Performance settings into the temporary area, modify them, and then store them in user memory.




Press [PERFORM/TONE] to call up the Performance selection screen.

When in Single Mode



When in Split or Dual Mode



- **2** Press [USER/PRESET] to select the group (User, Preset).
- Press the numeric keys ([1]–[0]) to specify the Performance number (1–128).
- **4** Press [ENTER] to finalize the entry.

When you want to know a Performance's name and number

• "Performance List" (p. 147)

When you want to know what settings can be stored in a Performance

• "Parameter List (Performance)" (p. 137)

When you want to store a Performance you have created to User memory

• "Saving Tone / Drum Set / Performance" (p. 113)

HINT

If "PERFORM" does not appear in the display, press [PERFORM/TONE] once more to switch to the Performance selection screen.

MEMO

If you make a mistake, press [EXIT] and specify the number once more.

HINT

Instead of using Steps 3 and 4, you can also switch Performances by pressing VALUE [-]/[+].

Easily Selecting the Performances You Like (FAVORITE PERFORM BANK)

You can call up your favorite Performances merely by pressing a single button.


Use Performances after registering them to the FAVORITE PERFORM BANK buttons below the display.

Registering Performances

Although the RS-5/9 comes with Performances already registered to the FAVORITE PERFORM BANK, you can change these to your own favorite Performances.

MEMO

The FAVORITE PERFORM BANK settings apply to the RS-5/9 as a whole (i.e., are system settings). This setting remains stored in memory even while the power is off.



- Select a Performance that you want to register (refer to previous section).
- Hold down [SHIFT] and press one of the FAVORITE PERFORM BANK buttons [1]–[8].

The Performance is registered, and "Completed" appears in the display.

The indicator on the button that was pressed lights up.

If the Performance is Not Saved

After selecting a Performance, if you change the Performance's settings and carry out Step 2 without saving these changes, the RS-5/9 jumps to the Save screen.

WRITE PERFORM[ENTER] Usr:001:BasicPerform

The Performance is saved while the Performance group and number are registered to the button at the same time.

- **3.** Press the numeric keys ([1]–[0]) to specify the Save destination number (1–128).
- **4.** Press [ENTER] to confirm the number.
- **5.** Press [ENTER] once more to execute the save.

The Performance is saved, and "Completed" appears in the display.

The Performance is saved while the Performance group and number are registered to the button at the same time.

MEMO

If you make a mistake, press [EXIT] and specify the number once again.

HINT

Instead of using Steps 3 and 4, you can also specify the number by pressing VALUE [-]/[+].

MEMO


To cancel a save or registration in progress, press [EXIT].

Easily Selecting Performances

1

Press one of the FAVORITE PERFORM BANK buttons [1]–[8], causing the button's indicator to light up.

The Performance registered to the button that is pressed is called up.



Using the Convenient Functions in Performances

Instantly Switching to Piano Mode

You can get the perfect settings for piano performances with the press of a single button.



NOTE

This feature is included only with the RS-9. It is not available with the RS-5.

1

Press [PIANO], getting the indicator to light.

The most suitable Performance for performing on the piano (Preset:127) is called up.




When [PIANO] is pressed, you cannot change the Performance that is called up.

Advanced Use

Chapter 1. An overview of the RS-5/9

Basic Organization of the RS-5/9

The RS-5/9 can be broadly divided into two sections: a **keyboard controller section** and a **sound generator section**. The two sections are connected internally by means of MIDI.



Keyboard Controller Section

This section includes the keyboard, the Pitch Bend/ Modulation Lever, the panel knobs, and any pedal connected to the rear panel. Actions such as pressing and releasing of keys on the keyboard, depressing a pedal, and so forth, are converted to MIDI messages and sent to the sound generator section, or to an external MIDI device.

Sound Generator Section

The sound generator section produces the sound. Here, MIDI messages received from the keyboard controller section or external MIDI device are converted to musical signals, which are then output as analog signals from the OUTPUT and PHONES jacks.

Classification of RS-5/9 Sound Types


When using the RS-5/9, you will notice that a variety of different categories come into play when handling sounds. What follows is a simple explanation of each sound category.

Tone

The individual sounds used when playing the RS-5/9 are referred to as "**Tones**." The 640 Tones stored in the RS-5/9's memory are divided into two types, with the memory containing 128 User Tones and 512 Preset Tones. Tones are assigned to each part of a performance.

Drum Set

Drum sets are groups of a number of different percussion instrument sounds. Since percussion instruments generally do not play melodies, there is no need for a percussion instrument sound to be able to play a scale on the keyboard. It is, however, more important that as many percussion instruments as possible be available to you at the same time. Therefore, the Drum sets are set up so that you can get different sets of percussion sounds by pressing different keys (note numbers). Drum sets are also assigned to each part of a performance.




Performance

A Performance is a collective set of assignments of the sixteen different Tones and Drum Sets. In Performances you can save whole collections of settings, including the tone numbers assigned to each of the Parts, along with Key Mode, Arpeggio, Transpose, and other settings.

Just like Tones, Performances are separated into two types, User and Preset, with 128 User Performances and 128 Preset Performances.

A maximum of two Parts can be handled simultaneously from the keyboard. Connecting an external sequencer allows you to work with up to sixteen Parts simultaneously, which lets you enjoy full ensemble performances.



About Memory

Memory refers to the area where Tones and settings are stored. The memory of the RS-5/9 is divided into three areas: **System Memory**, **User Memory**, and **Preset Memory**.

There is a **Temporary Area** within memory, into which data is placed when you select a tone or performance, and the data in the temporary area is what you are actually playing and editing.

System memory

System memory stores system setup settings that determine how the RS-5/9 functions.

User Memory

The contents of User Memory can be overwritten, and are used to store settings that you create. You can store 128 Tones and 128 Performances in the User Memory.

Preset Memory

The contents of Preset Memory cannot be rewritten. Preset Memory contains 512 tones and 128 performances.

The temporary area

When you select a Tone or Performance, whether to play it, or to change the settings, the selected Tone or Performance is called up to a temporary holding memory called the Temporary Area.

When a Performance is selected, the selected Performance is called up to the Temporary Area, and then it is played.

When a tone is selected, the selected Tone is called up to the Upper Part or Lower Part of the Performance in the Temporary Area, and then that is played. A Performance is called up to the Temporary Area at all times.

The Upper or Lower Parts may use any of the Parts 1-16. When the Key Mode is set to Single, the Upper Part is used. When Key Mode is set to Split or Dual, both the Upper and Lower Parts are used.

The data in memory will be preserved even if the power is turned off, and can be recalled at any time. However, the data in the temporary area will be lost when the power is turned off.

When changing Tone or Performance settings, you don't directly change the settings stored in memory, but rather the data called up to the Temporary Area. If you want to keep the changed data in the Temporary Area, you must then save that data to the User Memory.

As for System settings, changing these settings directly affects the data in memory, so the data is always updated. Therefore, you do not need to do anything to save this data.

Maximum Polyphony

The sound source of the RS-5/9 can produce up to 64 notes (voices) simultaneously. If data is received that attempts to play more than this number of voices, notes will be dropped out. When the number of requested voices exceeds 64, the RS-5/9 will give priority to the later-played notes, and will consecutively turn off the oldest sounding notes. An appropriate Voice Reserve setting should be made with respect to any Parts that you cannot do without.


* Some Tones use 2 voices to create a single Tone. For the number of voices used by each Tone, refer to "Tone List" (p. 148).

Preventing notes of an important Part from being cut off (Voice Reserve)

This setting specifies the number of voices that will be reserved for each Part when more than 64 voices are played simultaneously. For example if Voice Reserve is set to 6 for Part 1, Part 1 will always have 6 notes of sound-producing capacity available to it even if a total of more than 64 notes (total for all Parts) are being requested.

You can make separate Voice Reserve settings for each individual Part in a Performance.

- 1. Press [EDIT], getting the indicator to light.
- **2.** Use VALUE [-]/[+] to select "Performance Part."
- 3. Press [ENTER]
- **4.** Press PART [**◄**]/[**▶**] to select the Part.
- Press the numeric key [5] several times to select "Voice Reserve."




- * If you hold down [SHIFT] and press [5], you will return to the previous item.
- **6.** Use VALUE [-]/[+] to set the value.
- * It is not possible for the settings of all Parts to total more than 64. The remaining number of available voices will be displayed at (). You should check this readout as you set the Voice Reserve parameter.
- * If you wish to make settings for other Parts, repeat steps 4-6.
- 7. Press [EDIT].

The [EDIT] indicator goes out, and you are returned to the previous screen.

Modifying the Value of a Setting

To modify a value, use the VALUE [-]/[+] or [0]-[9] (numeric keys).



VALUE [-]/[+]

Pressing VALUE [+] increases the value, and VALUE [-] decreases it. Keep the button pressed for continuous adjustment. For faster value increases, keep VALUE [+] pressed down and press VALUE [-]. For decreasing value faster, keep VALUE [-] pressed down and press VALUE [+]. In addition, by holding down [SHIFT] and pressing VALUE [+] or [-], you can change the value ten units at a time.

[0]-[9] (Numeric Keys)

These allow you to specify the number directly when selecting Tones, Drum Sets, or Performances. When you enter the number, the number will blink. This indicates that the number has not yet been finalized. To finalize the number press the [ENTER] button.

[EXIT]

Press this in situations such as when you've make a mistake in pressing the numeric keys, when you want to cancel an operation, or when you want to return to a previous screen after settings have been made.

Convenient shortcuts

The RS-5/9 provides several convenient shortcuts.

* [**] + [##] means that you should hold down [**] and press [##].

Setting the Split Point (p. 40)

[SPLIT]+[EDIT]

The display will show the Split Point setting page.

[SPLIT] + VALUE [-]/[+]

The split point can be set. When you release [SPLIT], the previous display will reappear.

Setting the Arpeggio (p. 77)

[ARPEGGIO ON/OFF]+[EDIT]

The display will show the Arpeggio Style setting page. [ARPEGGIO ON/OFF] + VALUE [-]/[+]

The arpeggio style can be set. When you release [ARPEGGIO ON/OFF], the previous display will reappear.

Setting the Transpose (p. 48)

[TRANSPOSE ON/OFF]+[EDIT]

The display will show the Transpose setting page.

[TRANSPOSE ON/OFF] + VALUE [-]/[+]

The transpose can be set. When you release [TRANSPOSE ON/OFF], the previous display will reappear.


Setting the LCD Contrast (p. 16)

[SHIFT]+[PHRASE PREVIEW]

The display will show the LCD Contrast setting page.

If "Stuck" Notes Occur (PANIC)

If some operation causes sounds from the RS-5/9, or sounds from an external sound generator connected with a MIDI cable to fail to stop playing, use the Panic function.



When Sounds From the RS-5/9 Do Not Stop Playing

Hold down [SHIFT] and press [PANIC].
 Sounds from the RS-5/9 stop playing.
 The display will indicate "Panic! Now Muting." while the Panic function is being executed. When this message goes off, you can start playing.

Panic! Now Muting.

What to Do When an External Sound Generator Fails to Stop Sounding

1. Hold down [SHIFT] and press [PANIC] for more than a second.

Send the MIDI messages All Sound Off, Reset All Controllers, Hold1 (0), Hold2 (0), and Sostenuto (0) for all MIDI channels (Parts).

The display will indicate "Panic! Now Transmitting." while the Panic function is being executed. When this message goes off, you can start playing.

Panic! Now Transmitting.

Chapter 2. Part Volume and Pan Settings

You can make separate volume and pan (sound-image localization) settings for each individual Part in a Performance.

Level

Set the volume of each part. This is mainly used to achieve the volume balance between Parts when Key Mode is set to Split or Dual.

Value: 0-127

Par

When stereo output is used, this setting sets the pan position (stereo location) of each Part. With an increase in the value for L, more of the sound will be heard as coming from the left side. Similarly, more of the sound will originate at the right if the value of R is increased. When set to RANDOM, you obtain a specialized effect whereby the sound randomly moves left and right with each key stroke.

Value: RANDOM, L63-0-63R

- * In the case of a Drum Set, the pan position has been fixed for each percussion instrument (p. 112). When setting the pan for a Part to which a Drum Set is assigned, the panning of the entire drum set is moved.
- 1. Press [EDIT], getting the indicator to light.
- **2.** Use VALUE [-]/[+] to select "Performance Part."
- 3. Press [ENTER].
- **4.** Press PART [**◄**]/[**▶**] to select the Part.
- **5.** Press the numeric key [3] several times to select the item you wish to set.

| PART 1 | LEVEL |
|--------|-------|
| Level: | 100 |
| PART 1 | PAN |
| Pan: | Ø |

- **6.** Use VALUE [-]/[+] to set the value.
- 7. Press [EDIT].

hapter 3

Chapter 3. Mastering Use of the Performance Features

Playing single-note lines (Solo)

This function is effective when performing a solo using single-note Tone like sax and flute.

You can make separate Solo Switch settings for each individual Part in a Performance.

- **1.** Press [EDIT], getting the indicator to light.
- **2.** Use VALUE [-]/[+] to select "Performance Part."
- 3. Press [ENTER].
- **4.** Press PART [**◄**]/[**▶**] to select the Part.
- * When Key Mode (p. 34) is set to Split or Dual, you can select only two Parts, the Upper Part and the Lower Part.
- **5.** Press the numeric key [9] several times to select "Solo Switch."

PART 1 KEYBOARD Solo Switch: OFF

- * If you hold down [SHIFT] and press [9], you will return to the previous item.
- **6.** Use VALUE [-]/[+] to set "ON."
- 7. Press [EDIT].

The [EDIT] indicator goes out, and you are returned to the previous screen.

Smoothly Changing the Pitch of the Sound (Portamento)

Portamento is an effect which smoothly changes the pitch from the first-played key to the next-played key. With the Solo Switch (refer to the previous section) set to ON, portamento is especially effective when simulating playing techniques such as a violin glissandos.

Portamento can also be applied when Solo Switch is OFF. You can make separate Portamento settings for each individual Part in a Performance.

Portamento SW (Portamento Switch)

Specifies whether the portamento effect will be applied (ON) or not (OFF).

Value: OFF, ON

Portamento Time

When portamento is used, this specifies the time over which the pitch will change. Higher settings will cause the pitch change to the next note to take more time.

Value: 0-127

- * The Portamento Time setting is disabled when the Portamento Switch is off.
- 1. Press [EDIT], getting the indicator to light.
- **2.** Use VALUE [-]/[+] to select "Performance Part."
- 3. Press [ENTER].
- **4.** Press PART [**◄**]/[**▶**] to select the Part.
- * When Key Mode (p. 34) is set to Split or Dual, you can select only two Parts, the Upper Part and the Lower Part.
- **5.** Press the numeric key [9] several times to select the item you wish to set.

PART 1 KEYBOARD
Portamento Sw: OFF

PART 1 KEYBOARD
Portamento Time: 0

- * If you hold down [SHIFT] and press [9], you will return to the previous item.
- **6.** Use VALUE [-]/[+] to set the value.
- **7.** Press [EDIT].

Determining the Volume from the Force Used To Play the Keys (Velocity Sense)

You can specify how your keyboard playing dynamics will affect the volume.

You can make separate Velocity Sens settings for each individual Part in a Performance.

Velo Sens Depth (Velocity Sens Depth)


If this value is increased, small differences in your playing dynamics will make a large difference in the loudness of the sound. If this is decreased, even large differences in your playing dynamics will make only a small difference in the loudness of the sound.

Value: 0-127


Velo Sens Offset (Velocity Sens Offset)

The higher above 64 the value is set, the louder the sound produced, even as the keyboard is played with lesser force. The lower below 64 the value is set, the lower the sound produced, even as the keyboard is played with greater force.

Value: 0-127



- **1.** Press [EDIT], getting the indicator to light.
- **2.** Use VALUE [-]/[+] to select "Performance Part."
- 3. Press [ENTER].
- **4.** Press PART [**◄**]/[**▶**] to select the Part.
- * When Key Mode (p. 34) is set to Split or Dual, you can select only two Parts, the Upper Part and the Lower Part.
- **5.** Press the numeric key [9] several times to select the item you wish to set.



- * If you hold down [SHIFT] and press [9], you will return to the previous item.
- **6.** Use VALUE [-]/[+] to set the value.
- 7. Press [EDIT].

Transposing Performances

The RS-5/9 has two functions, "Transpose" and "Key Shift," that you can use to move the key range of what is being played in half-step units. The Transpose function transposes all Parts, whereas Key Shift transposes only specified Parts.

Transposing All Parts (TRANSPOSE ON/OFF)

For instructions on setting Transpose, refer to Quick Start (p. 48).

Transposing a Specified Part (Key Shift)

This is convenient in situations such as the following.

Layering Tones an octave apart

When the Keyboard Mode is Dual, you can create a richer sound by setting the two Tones to different octaves.

Having only the Tone of a selected Part be played at a lower pitch

If the Keyboard Mode is set to Split and you are playing a bass Tone in the lower Part, you can use the Key Shift function to play the bass at a lower pitch.

You can make separate Key Shift settings for each individual Part in a Performance.

- * Note messages from MIDI IN connector will also be transposed.
- * This setting is disabled when the Drum Set is assigned to the Part.
- 1. Press [EDIT], getting the indicator to light.
- **2.** Use VALUE [-]/[+] to select "Performance Part."
- 3. Press [ENTER].
- **4.** Press PART [**◄**]/[**▶**] to select the Part.
- * When Key Mode (p. 34) is set to Split or Dual, you can select only two Parts, the Upper Part and the Lower Part.
- **5.** Press the numeric key [4] several times to select "Key Shift."

| PART 1 | TUNE |
|------------|------|
| Key Shift: | 0 |

- * If you hold down [SHIFT] and press [4], you will return to the previous item.
- **6.** Press VALUE [-]/[+] to select the value (-24-+24).
- 7. Press [EDIT].
 The [EDIT] indicator goes out, and you are returned to the previous screen.

Adding Breadth to the Sound by Layering Tones with Different Pitches (Fine Tune)

When Tones with slightly different pitches are played together, it creates a sound with more fullness and breadth.

When Key Mode is set to Dual (p. 36), and the same Tone is

When Key Mode is set to Dual (p. 36), and the same Tone is assigned to both Parts (p. 37), make the Fine Tune setting for only one of the Parts.

* The effect whereby sounds with slightly different pitches are layered is called "**Detune**."

You can make separate Fine Tune settings for each individual Part in a Performance.

- 1. Press [EDIT], getting the indicator to light.
- **2.** Use VALUE [-]/[+] to select "Performance Part."
- 3. Press [ENTER].
- **4.** Press PART [**◄**]/[**▶**] to select the Part.
- * When Key Mode (p. 34) is set to Split or Dual, you can select only two Parts, the Upper Part and the Lower Part.
- Press the numeric key [4] several times to select "Fine Tune."

| PART | | TUNE |
|------|-------|-------|
| Fine | Tune: | 0cent |

- * If you hold down [SHIFT] and press [4], you will return to the previous item.
- **6.** Press VALUE [-]/[+] to select the value (-100 to +100).
- * One cent is 1/100th of a semitone.
- 7. Press [EDIT].

Changing to Pure Temperament or an Arabic scale (Scale Tune)

What are Equal Temperament, Pure Temperament, and Arabic scales?

Equal Temperament

This tuning divides the octave into 12 equal parts, and is the most widely used method of temperament used in Western music.

Pure Temperament

In comparison to Equal Temperament, Pure Temperament allows the three principal chords to have a purer sound. However, this effect is achieved only in one key, and the triads will become ambiguous if you transpose.

Arabic Scale

In comparison to Equal Temperament, E and B are 1/2 a semitone low, and C#, F# and G# are 1/2 a semitone high. The intervals of G–B, C–E, F–G#, A#–C# and D#–F# are neutral thirds (an interval midway between a major third and a minor third).

Making Scale Tune settings

You can adjust the Scale Tune settings to make a variety of scales. These settings allow you to make fine adjustments in 1 cent (1/100th of a semitone) to the pitch of each note C–B.

You can make separate Scale Tune settings for each individual Part in a Performance.

- 1. Press [EDIT], getting the indicator to light.
- **2.** Use VALUE [-]/[+] to select "Performance Part."
- 3. Press [ENTER].
- **4.** Press PART [**◄**]/[**▶**] to select the Part.
- **5.** Press numeric key [4] several times to select "Scale Tune C"-"Scale Tune B."

| PART | 1. | | TUNE |
|-------|--------|-----|------|
| Scale | : Tune | C : | 0 |

- * If you hold down [SHIFT] and press [4], you will return to the previous item.
- * You can press the key to directly select the name of the sound whose pitch you want to change.

- **6.** Press VALUE [-]/[+] to select the value (-64 to +63).
- * If you wish to make settings for other Parts, repeat steps 5-6.
- 7. Press [EDIT].

The [EDIT] indicator goes out, and you are returned to the previous screen.

Settings Example

| Note name | Equal Temperament | Just Temperament (tonic C) | Arabian Scale |
|--------------|----------------------|----------------------------|------------------|
| C | 0 | 0 | - 6 |
| C# | 0 | -8 | +45 |
| D | 0 | +4 | -2 |
| D# | 0 | +16 | -12 |
| E | 0 | -14 | -51 |
| F | 0 | -2 | -8 |
| F# | 0 | -10 | +43 |
| G | 0 | +2 | -4 |
| G# | 0 | +14 | +47 |
| A | 0 | -16 | 0 |
| A# | 0 | +14 | -10 |
| В | 0 | -12 | -49 |

^{*} In this example, the Arabic Scale can be played in the three keys of G, C, and F.


Chapter 4. Changing Tones in Real Time

You can use the RS-5/9's Pitch Bend lever, Modulation lever, and control knobs to make changes to the Tones in real time. You can also alter the Tones with a pedal connected to the PEDAL jack.

Changing the Pitch in Realtime (Pitch Bend Lever)

While playing the keyboard, move the lever to the left to lower the pitch, or to the right to raise the pitch.

For a more detailed explanation of the Pitch Bend lever, refer to Quick Start (p. 50).



Pitch Bend

Using the Modulation Lever to modify the sound

As set at the factory, moving the lever away from you as you press a key on the keyboard produces a vibrato effect.

You can add effects other than vibrato with the Modulation lever.



Modulation

MOD (Modulation Assign)

| Value | Tx CC# | Function/Parameter Changed |
|--------------------|--------|--|
| MODULATION | CC01 | Vibrato Effect |
| PORTAMENTO TIME | CC05 | Perform Part Portamento Time (p. 67) |
| VOLUME | CC07 | Perform Part Level (p. 66) |
| PAN | CC10 | Perform Part Pan (p. 66) |
| EXPRESSION | CC11 | Perform Part Level (p. 66) |
| PORTAMENTO | CC65 | Perform Part Portamento Switch (p. 67) |
| SOSTENUTO | CC66 | Holds the sound of the key being pressed |
| SOFT | CC67 | Softens the Tone |
| RESONANCE | CC71 | Tone Filter Resonance (p. 110) |
| RELEASE TIME | CC72 | Tone Envelope Release Time (p. 110) |
| ATTACK TIME | CC73 | Tone Envelope Attack Time (p. 110) |
| CUTOFF | CC74 | Tone Filter Cutoff (p. 110) |
| DECAY TIME | CC75 | Tone Envelope Decay Time (p. 110) |
| LFO RATE | CC76 | Tone LFO Rate (p. 110) |
| LFO DEPTH | CC77 | Tone LFO Depth (p. 110) |
| LFO DELAY | CC78 | Tone LFO Delay (p. 110) |
| CHO SEND LEVEL | CC93 | Perform Part Chorus Send Level (p. 108) |
| REV SEND LEVEL | CC91 | Perform Part Reverb Send Level (p. 109) |
| UP-LO BALANCE | CC07 | Perform Part Upper and Lower Levels (p. 66) |
| MFX | CC12 | Multi-Effects Parameter at |
| PARAMETER 1 | | Marker #1 (p. 81) |
| MFX | CC13 | Multi-Effects Parameter at |
| PARAMETER 2 | | Marker #2 (p. 81) |
| AFTERTOUCH | _ | |

"TxCC#" refers to the controller number sent from the MIDI OUT connector when the Modulation lever is moved. When set to AFTERTOUCH, a Channel Aftertouch message is sent. Receiving these controller numbers from the MIDI IN connector gives the same effect as moving the Modulation lever.

Set to AFTERTOUCH mainly when you want to control the external sound generator with Aftertouch messages.

^{*} This is applied to both the Upper Part and Lower Part when Key Mode is set to Dual.

Chapter 4. Changing Tones in Real Time

- * When set to MFX PARAMETER 1 or MFX PARAMETER 2, be sure to note the following.
- When the multi-effects Type is set to 01: STEREO EQ (p. 82) or 41: LOFI (p. 106), Level is changed regardless of whether MFX PARAMETER 1 or MFX PARAMETER 2 is selected.
- When the multi-effects Type is set to 22: 2VOICE PITCH SHIFTER (p. 96), the two parameters are changed simultaneously.
- When the multi-effects Type is set to 23: FBK PITCH SHIFTER (p. 97), the two parameters are changed simultaneously when MFX PARAMETER 1 is selected.
- he following describes which Part or Parts are enabled according to the Source setting (p. 80).

UPPER = Upper LOWER = Lower PERFORMANCE = All Parts

* When making the LFO RATE, LFO DEPTH or LFO DELAY settings, the effect achieved differs depending on whether [LFO ON/OFF] is on or off. When [LFO ON/OFF] is off, the LFO alters the pitch (vibrato effect). When [LFO ON/OFF] is on, the LFO changes the Filter Cutoff frequency (wal effect).

Different Modulation lever settings can be made for each individual Performance.

- **1.** Press [EDIT], getting the indicator to light.
- **2.** Use VALUE [-]/[+] to select "Tone/Drum/PFMCommon."
- 3. Press [ENTER].
- **4.** Press the numeric key [5] several times to select "MOD."


PERFORMANCE MOD CC01: MODULATION

- * If you hold down [SHIFT] and press [5], you will return to the previous item.
- **5.** Use VALUE [-]/[+] to set the value.
- 6. Press [EDIT].

Using a pedal to modify the sound

With an external pedal, such as an expression pedal (the optional EV-5,) pedal switch (the optional DP-2/6) or foot switch (the optional BOSS FS-5U) connected to the PEDAL CONTROL jack, you can then use the pedal to make changes in the Tone.

Just as with the Modulation lever, you can select the function affected when the pedal is pressed. The pedal will mainly be used for changing volume levels (VOLUME, EXPRESSION, and UP-LO BALANCE), sostenuto (SOSTENUTO), and as a soft pedal (SOFT).



* This is applied to both the Upper Part and Lower Part when Key Mode is set to Split and Dual.

For a description of the settings values, refer to (p. 71). To make the settings, select the "PEDAL" (Control Pedal Assign) in Step 4 above (p. 72).

PERFORMANCE PEDAL CC07: VOLUME

* When you want to apply the effect that causes the sounds being played to continue playing (called the "hold effect"), connect a pedal switch (the optional DP-2/6) or foot switch (the optional BOSS FS-5U) to the PEDAL HOLD jack. When Arpeggio is on, this changes to an Arpeggio Hold function. This allows you to play arpeggios without having to continue holding chords. However, when the Key Mode is set to Split, the Hold effect can be obtained with respect to what is played in the upper part of the keyboard, while Arpeggio Hold will apply to notes played in the lower part of the keyboard (p. 75).

Switching the Pedal's Polarity (Pedal Polarity)

Select the polarity of the pedal. On some pedals, the electrical signal output by the pedal when it is pressed or released is the opposite of other pedals. If your pedal has an effect opposite of what you expect, set this parameter to REVERSE. If you are using a Roland pedal (that has no polarity switch), set this parameter to STANDARD.

The Pedal Polarity setting affects the entire RS-5/9 (i.e., is a System setting). This setting remains stored in memory even while the power is off.

- 1. Press [EDIT], getting the indicator to light.
- **2.** Use VALUE [-]/[+] to select "System Setup."
- 3. Press [ENTER].
- **4.** Press numeric key [5] several times to select the parameter to be set.

If setting the polarity of the pedal connected to the PEDAL HOLD jack, select "CONTROL PEDAL Polarity."

If setting the polarity of the pedal connected to the PEDAL HOLD jack, select "HOLD PEDAL Polarity."

SYSTEM CONTROL PEDAL Polarity: STANDARD


SYSTEM HOLD PEDAL Polarity: STANDARD

- * If you hold down [SHIFT] and press [5], you will return to the previous item.
- **5.** Press VALUE [-]/[+] to set the value (STANDARD, REVERSE).
- **6.** Press [EDIT].

The [EDIT] indicator goes out, and you are returned to the previous screen.


Using a knob to modify the sound

You can use the six panel knobs to modify Tones in real time. Knob functions change depending on whether [ARPEGGIO/CONTROL] and/or [ARPEGGIO ON/OFF] are switched on or off.



* The effect is applied to both the Upper Part and Lower Part when Key Mode is set to Split and Dual.

When a knob is turned, the function assigned to the knob and its value appear temporarily in the display.



When [ARPEGGIO/CONTROL] is Off

The six knobs can be used to change the values of Tone parameters, as indicated on the panel.

LFO RATE Knob: Tone LFO Rate (p. 110)
LFO DEPTH Knob: Tone LFO Depth (p. 110)
ENVELOPE ATTACK Knob: Tone Envelope Attack Time
(p. 110)

ENVELOPE RELEASE Knob: Tone Envelope Release Time

(p. 110)

FILTER CUTOFF Knob: Tone Filter Cutoff (p. 110)
FILTER RESONANCE Knob: Tone Filter Resonance (p. 110)

- * The effect achieved with the two LFO knobs differs depending on whether [LFO ON/OFF] is switched on or off. When [LFO ON/OFF] is off, the LFO alters the pitch (vibrato effect). When [LFO ON/OFF] is on, the LFO changes the Filter Cutoff frequency (wah effect).
- * Pressing [LFO ON/OFF] when Key Mode is set to Split or Dual sets the same LFO Filter Sw value in both of the Part's Tones.

When [ARPEGGIO/CONTROL] is On

Using the four LFO and ENVELOPE knobs, you can control parameters that you select. The functions affected when the knobs are turned can be set in the same manner as with the Modulation lever.

For a description of the settings values, refer to (p. 71). To make the settings, select one of the "CONTROL 1–CONTROL 4" (Knob Assign) in Step 4 (p. 72).

PERFORMANCE CONTROL1 CC16:LFO FILTER RATE

* You can use the two FILTER panel knobs to change the parameter values for the Tone appearing in the display.

When [ARPEGGIO ON/OFF] is On

With [ARPEGGIO ON/OFF] set at ON, each press of [ARPEGGIO/CONTROL] takes you to the next state for the indicator, among three possible choices: lit, flashing, or extinguished.

When [ARPEGGIO/CONTROL] is flashing, you can control the Arpeggio parameters using the four LFO and ENVELOPE knobs.

C1: Accent Rate (p. 77)


C2: Shuffle Rate (p. 77)

C3: Octave Range (p. 77)

C4: Tempo (p. 76)

* You can use the two FILTER panel knobs to change the parameter values for the Tone appearing in the display.

Switching to the Value at the Current Knob Positions (MANUAL)



When you press [MANUAL], the parameters assigned to the six knobs are set to the values at the current knob positions.

* This is applied to both the Upper Part and Lower Part when Key Mode is set to Split and Dual.

Chapter 5. Using the arpeggiator

The RS-5/9's arpeggiator lets you produce an arpeggio (broken chord) simply by playing a chord.

When the Key Mode is Single or Dual, arpeggios can be played in all areas of the keyboard.

When the Key Mode is Split, chords played in the Lower area of the keyboard will be sounded as arpeggios.

- * Arpeggios can be produced only by playing the RS-5/9's keyboard. It is not possible to produce arpeggios with Note messages from the MIDI IN connector.
- * Arpeggio data are transmitted from MIDI OUT connector.

Turning the Arpeggio Function On and Off (ARPEGGIO ON/OFF)

You can set the Arpeggio ON/OFF for each Performance separately.

- **1.** Press the [ARPEGGIO ON/OFF] button, getting its indicator to light.
 - At ON, the keyboard in placed in Arpeggio mode.
- **2.** Press the [ARPEGGIO ON/OFF] button again, getting its indicator light to go out.
 - At OFF, the RS-5/9 operates in normal performance mode.
 - * Hold down the [SHIFT] button and press [ARPEGGIO ON/OFF]. The [ARPEGGIO ON/OFF] indicator starts blinking, and you can then have the arpeggio be played without having to continue pressing the chord. To cancel Arpeggio Hold, hold down [SHIFT] and press [ARPEGGIO ON/OFF] once more. Note also that if a pedal switch (such as the optional DP-2/6), or a foot switch (such as the optional BOSS FS-5U) is connected to the PEDAL HOLD jack, you can have arpeggios be played if you depress the pedal while pressing chords. In this way, you can play arpeggios without having to continue pressing the chord.
- * Pitch Bend is not applied to arpeggios.

Tip for Creating Arpeggio Patterns

There are a total of nine items that you can set to control arpeggiation, but the "Arpeggio Style" is the most important. The playback pattern of the arpeggio is determined mainly by this selection.

When you select an arpeggio style, the four parameters marked by an asterisk (*) in the list below will be set automatically. This allows you to call up the most appropriate pattern simply by selecting the arpeggio style. After selecting the arpeggio style, you can set Tempo and Octave Range etc. as appropriate. Normally you will specify the pattern in this way.

However, if this alone does not produce the pattern you want, try changing the settings for the four parameters marked with an asterisk below (Motif, Beat Ptrn, Shuffle Rate, and Accent Rate) to get the desired result.

Arpeggiator parameters you can set

Style (Arpeggio Style)

Sets the style of the arpeggio. Select from the following 45 options. For creating your own style, choose LIMITLESS.

| Value | our own style, choose LIMITLESS. |
|--|--|
| 1/4 | The rhythm will be divided in quarter notes. |
| 1/6 | The rhythm will be divided in quarter note triplets. |
| 1/8 | The rhythm will be divided in eighth notes. |
| 1/12 | The rhythm will be divided in eighth note triplets. |
| 1/16 | The rhythm will be divided in 16th notes. |
| 1/32 | The rhythm will be divided in 32nd notes. |
| PORTAMENTO A, B | A style using the portamento effect. |
| GLISSANDO | A glissando style. |
| SEQUENCE A-D | Styles for sequenced patterns. |
| ЕСНО | An echo-like style. |
| SYNTH BASS, HEAVY SLAP, LIGHT SLAP, WALK BASS | Styles appropriate for bass playing. |
| RHYTHM GTR A-E | Styles for guitar cutting. Styles B–E are effective when 3–4 notes are held. |
| 3 FINGER GTR | Three-finger guitar style. |
| STRUM GTR UP, STRUM GTR DOWN, STRUM GTR U&D | Guitar chords strummed both up and down. Effective when 5–6 notes are held. |
| PIANO BACKING, CLAVI CHORD | Styles for keyboard instrument backing. |
| WALTZ, SWING WALTZ | Styles in triple meter. |
| REGGAE | A reggae-type style. Effective when 3 notes are held. |
| PERCUSSION | Style effective for percussive instruments. |
| HARP | The playing style of a harp. |
| SHAMISEN | The playing style of a Shamisen. |
| BOUND BALL | A style suggestive of a bouncing ball. |
| | |

RANDOM

A style in which the notes sound in

random order.

Chapter 5. Using the arpeggiator

| BOSSANOVA | A style with bossanova guitar cutting. Hold 3–4 notes for best results. You can increase the tempo and use this as a Samba. |
|------------|---|
| SALSA | Typical salsa style. Hold 3–4 notes for best results. |
| MAMBO | Typical mambo style. Hold 3–4 notes for best results. |
| LATIN PERC | A rhythm style with Latin percussion instruments such as Clave, Cowbell, Clap, Bongo, Conga, Agogo etc. |
| SAMBA | Typical samba style. Use for rhythm patterns or bass lines. |
| TANGO | Typical tango rhythm style. Hold the root, 3rd and 5th of a triad etc. for best results. |
| HOUSE | A style for house piano backing. Hold 3–4 notes for best results. |
| LIMITLESS | The settings of all parameters can be freely combined without restriction. |
| | |

Motif *

Sets the order in which notes of the chord will sound.

* Depending on the Style settings (p. 75), some choices may not be available. For details on the possible values, refer to "Arpeggio Style List" (p. 155).

Value

| Value | |
|-------------------|---|
| SINGLE UP | Notes you press will be sounded individually, beginning from low to high. |
| SINGLE DOWN | Notes you press will be sounded individually, beginning from high to low. |
| SINGLE UP&DOWN | Notes you press will be sounded individually, from low to high, and then back down from high to low. |
| SINGLE RANDOM | Notes you press will be sounded individually, in random order. |
| DUAL UP | Notes you press will be sounded two at a time, beginning from low to high. |
| DUAL DOWN | Notes you press will be sounded two at a time, beginning from high to low. |
| DUAL UP&DOWN | Notes you press will be sounded two at a time, from low to high, and then back down from high to low. |
| DUAL RANDOM | Notes you press will be sounded two at a time, in random order. |
| TRIPLE UP | Notes you press will sound three at a time, from low to high. |
| TRIPLE DOWN | Notes you press will sound three at a time, from high to low. |
| TRIPLE UP&DOWN | Notes you press will sound three at a time, from low to high and then back down from high to low. |

| TRIPLE RANDOM | Notes you press will sound three at a time, in random order. |
|-----------------|--|
| NOTE ORDER | Notes will sound in the order that they were pressed. Up to 128 notes can be stored, so you can create mel- ody lines by pressing keys in the ap- propriate order. |
| GLISSANDO | Notes will be played in an ascending and descending chromatic scale between the lowest and the highest keys that are pressed. Simply press two notes, the lowest and highest. |
| CHORD | All notes that are pressed will sound simultaneously. |
| BASS+CHORD 1–5 | The lowest of the notes you play will sound, and the remaining notes will sound as a chord. |
| BASS+UP 1–8 | The lowest of the notes you play will sound, and the remaining notes will be arpeggiated. |
| BASS+RANDOM 1–3 | The lowest of the notes you play will sound, and the remaining notes will sound in random order. |
| TOP+UP 1–6 | The highest of the notes you play will sound, and the remaining notes will be arpeggiated. |
| BASS+UP+TOP | Simulated fingering of folk guitar's three-finger picking technique. |

Beat Ptrn (Beat Pattern) *

Select the beat pattern from the choices below. This setting will affect the location of the accent and length of the notes to determine the beat (rhythm).

* Depending on the Style settings (p. 75), some choices may not be available. For details on the possible values, refer to "Arpeggio Style List" (p. 155).

Value

1/4, 1/6, 1/8, 1/12, 1/16 1–3, 1/32 1–3, PORTA-A 01–11, PORTA-B 01–15, SEQ-A 1–7, SEQ-B 1–5, SEQ-C 1–2, SEQ-D 1–8, ECHO 1–3, MUTE 01–16, STRUM1–8, REGGAE1–2, REFRAIN1–2, PERC1–4, WALKBS, HARP, BOUND, RANDOM, BOSSA NOVA, SALSA 1–4, MAMBO 1–2, CLAVE, REV CLA, GUIRO, AGOGO, SAMBA, TANGO 1–4, HOUSE 1–2

* When PORTA-A 01–11 and PORTA-B 01–15 are selected, you can use Portamento time (p. 67) to control the portamento attack. In this case, it is not necessary to have Portamento Sw set to ON.

Tempo

Sets the speed of the arpeggio.

* With Sync Source (p. 77) set to MIDI, Tempo (=MIDI) appears in the display, and the RS-5/9 is synchronized to the clock of the external MIDI device.

Octave Range

Sets the key range in octaves over which arpeggio will take place. If you want the arpeggio to sound using only the notes that you actually play, set this parameter to 0. To have the arpeggio sound using the notes you play and notes 1 octave higher, set this parameter to +1. A setting of -1 will make the arpeggio sound using the notes you play and notes 1 octave lower.

Value: -3-+3

Key Velocity


This sets the velocity, or the force of the sound at the time a key is played. If you wish to use the velocity at which the notes are actually played, set this parameter to REAL. To use a constant velocity regardless of the force with which you play the keyboard, choose a desired value from 1–127.

Value: REAL, 1-127

Shuffle Rate *

This setting lets you modify the note timing to create shuffle rhythms. With a setting of 50%, the notes will sound at equal spacing. As this value is increased, the notes will become more "bouncy," as if they were dotted notes.

Value: 50-90%



* If the Beat Pattern (p. 76) is 1/4, there will be no shuffle effect even if the Shuffle Rate value is increased.

Accent Rate *

Modifies the strength of accents and the length of the notes to adjust the "groove" feel of the arpeggio. A setting of 100% will produce the most pronounced groove feel.

Value: 0-100%

Sync Source

This specifies how the tempo of the arpeggio will be determined. Ordinarily, you should set this to "INT." If you wish to record arpeggios on your sequencer, or to synchronize the arpeggiator to an external device for a live performance, set this to "MIDI."

Settings

INT: The arpeggiator will be synchronized to the tempo of the RS-5/9. Any MIDI Clock messages received from an external device will be ignored.

MIDI: Arpeggiator tempo will be synchronized to the MIDI Clock messages received from an external device. If MIDI Clock messages are not being received from an external device, the arpeggiator will not play.

* MIDI Clock is a message used to synchronize MIDI devices connected by a MIDI cable. If the RS-5/9 is connected to a MIDI device such as a sequencer, you can set the Sync Source setting to MIDI so that the arpeggio will play in synchronization with the sequencer playback. ("About MIDI" p. 118)

Creating a pattern

You can make separate Arpeggio settings for each Performance.

- 1. Press [EDIT], getting the indicator to light.
- **2.** Use VALUE [-]/[+] to select "Tone/Drum/PFMCommon."
- 3. Press [ENTER].
- **4.** Press the numeric key [0] several times to select the item you wish to set.

PERFORMANCE ARPEGGIO Style: 1/16

- * If you hold down [SHIFT] and press [0], you will return to the previous item.
- **5.** Use VALUE [-]/[+] to set the value.
- * If you wish to make settings for other Parts, repeat steps 4-5.
- 6. Press [EDIT].

The [EDIT] indicator goes out, and you are returned to the previous screen.

To make Arpeggio settings easily

By holding down [ARPEGGIO ON/OFF] and pressing [EDIT], you can select the "Style" display directly. Make settings as explained in steps 4–6 of the above procedure. Also, if you want be able to change the arpeggio style quickly, by holding down [ARPEGGIO ON/OFF] and pressing VALUE [-]/[+], you can change only the "Style" setting. When you release [ARPEGGIO ON/OFF], the previous display will reappear.

Using the Knobs to Change Patterns in Real Time

Using knobs C1-C4, you can change Patterns in real time.

- **1.** Press the [ARPEGGOP ON/OFF] button, getting its indicator to light.
 - Arpeggios can now be produced when chords are played.
- **2.** Press [ARPEGGIO/CONTROL] several times, getting its indicator to start blinking.
- * If the indicator lights, press [ARPEGGIO/CONTROL] again.
 Using knobs C1– C4, you can change each of the following parameter settings values in real time.
 - C1: Accent Rate (p. 77)
 - C2: Shuffle Rate (p. 77)
 - C3: Octave Range (p. 77)
 - C4: Tempo (p. 76)

When [ARPEGGIO ON/OFF] is set to ON, the [ARPEGGIO/CONTROL] indicator switches each time the button is pressed, cycling through lit, flashing, and off.

When the indicator is off, you can change the LFO Rate, LFO Depth, Envelope Attack, and Envelope Release in real time (p. 74).

When the indicator is lit, you can change the parameter you have set yourself in real time (p. 74).

Shapter 6

Chapter 6. Effect Settings

The RS-5/9 contains three effects processors: multi-effects, chorus, and reverb. Settings can be made separately for each effects processor.

There are 42 types of multi-effects, 8 types of chorus, and 8 types of reverb. You can use one of each type in a Performance.


Turning the Effect Function On and Off (EFFECTS ON/OFF)

In order to enable an effects processor (multi-effects, chorus, reverb), turn its switch on.

Turn these settings off when you wish to listen to the unprocessed sound as you create a sound, or when you wish to use external effect devices instead of the built-in effects.

The On/Off settings for each Effect affect the RS-5/9 as a whole (i.e., are system settings). This setting remains stored in memory even while the power is off.

When shipped from the factory, all three effects are set to ON.



1. Press [EFFECTS ON/OFF], getting its indicator to start blinking.

The Multi-effects On/Off settings screen appears in the display.

Multi-FX Switch ON

- **2.** Press VALUE [-]/[+] to turn the effect on or off.
- Press [EFFECTS ON/OFF].
 Next, the Chorus On/Off settings screen appears in the display.

Chorus Switch ON

4. Press VALUE [-]/[+] to turn the effect on or off.

5. Press [EFFECTS ON/OFF].

Next, the Reverb On/Off settings screen appears in the display.

Reverb Switch ON


- **6.** Press VALUE [-]/[+] to turn the effect on or off.
- **7.** Press [EFFECTS ON/OFF] to return to the original screen.

The [EFFECTS ON/OFF] indicator lights up whenever any of the three effects is on.

- * You can return to the original screen during the operation by pressing [EXIT].
- * If all three effects are turned off, the [EFFECTS ON/OFF] indicator light goes out.

The Effect Signal Path

The following figure shows the path followed by the effects signals.



* You can make this setting only when Source is set to PERFORMANCE in the Part's MULTI-FX Switch setting. When Source is set to UPPER or LOWER, the Upper or Lower Part's MULTI-FX SWITCH automatically goes on, and all other Parts are switched off.

Making Multi-Effects Settings

You can use only one type of multi-effect in a Performance. Be sure to start by setting the Source (Multi-Effects Source). Here, select the multi-effects settings to be used based on the particular application or purpose.

Afterwards, select the type, then set each of the parameters (p. 81).

You can select whether to have the multi-effects used (ON), or not used (OFF) in each individual Part only when Source is set to PERFORMANCE (p. 107).

Setting the Multi-Effects Source

Select the multi-effects settings that are to be used based on the particular application or purpose you have in mind.

You can make different Multi-Effects Source setting for each individual Performance.

Source (Multi-Effects Source)

Value:

UPPER: The Upper Tone's multi-effect settings are used.

The multi-effect is applied only to the Upper Part.

LOWER: The Lower Tone's multi-effect settings are used.

The multi-effect is applied only to the Lower Part.

PERFORMANCE: The Performance's multi-effect settings are used. The same multi-effect is

applied to all Parts (1–16).

Make each of the settings according to the desired purpose, as shown below.

Set to UPPER:

- When Key Mode is set to Single and you want to use the tone to which multi-effects are applied.
- When Key Mode is set to Split and you want to use the tone to which multi-effects are applied in the Upper Part.

Set to LOWER:

• When Key Mode is set to Split and you want to use the tone to which multi-effects are applied in the Lower Part.

Set to PERFORMANCE:

- When Key Mode is set to Split or Dual and you want to add the same multi-effects to the tones in both Parts.
- If you do not want the multi-effects to change when switching Tones or Drum Sets.
- **1.** Press [EDIT], getting the indicator to light.
- **2.** Use VALUE [-]/[+] to select "Tone/Drum/PFMCommon."
- 3. Press [ENTER].
- **4.** Press [6] a number of times to select "Source."

| PERFORMANCE | MULTI-FX |
|-------------|----------|
| Source: | UPPER |

- If you hold down [SHIFT] and press [6], you will return to the previous item.
- **5.** Use VALUE [-]/[+] to set the value.

6. Press [EDIT].

The [EDIT] indicator goes out, and you are returned to the previous screen.

Select the Type and Set Each Parameter

There are 42 types of multi-effects. You can select any one of these. After selecting the Type, you can change the values for each of the parameters.

- * When Source is set to UPPER or LOWER, the Type and parameter settings are used as the settings for the Tone or Drum Set assigned to that Part. When Source is set to PERFORMANCE, these settings apply to the Performance.
- **1.** Press [EDIT], getting the indicator to light.
- **2.** Use VALUE [-]/[+] to select "Tone/Drum/PFMCommon."
- 3. Press [ENTER].
- **4.** Press the numeric key [6] several times to select the item you wish to set.

| U TOME | MULTI-FX |
|------------|------------|
| Type:01 | STEREO EQ |
| PERFORMANC | E)MULTI-FX |
| Type:01 | STEREO EQ |

- * What is indicated in the upper-left part of the display will change depending on the value of the Source setting.
- * If you hold down [SHIFT] and press [6], you will return to the previous item.
- **5.** Use VALUE [-]/[+] to set the value.
 - * If you wish to make settings for other Parts, repeat steps 4-5.
- 6. Press [EDIT].

The [EDIT] indicator goes out, and you are returned to the previous screen.

Type (Multi-Effects Type)

Selections are made from the following 42 different multieffects.

Additionally, parameters for each of the multi-effects types can be found on the following pages.

Value:

| 00: | THROUGH | (p. 82) |
|-----|------------|---------|
| 01: | STEREO EQ | (p. 82) |
| 02: | OVERDRIVE | (p. 83) |
| 03: | DISTORTION | (p. 83) |

| 04: | PHASER | (p. 84) |
|-----|--|----------|
| 05: | SPECTRUM | (p. 84) |
| 06: | ENHANCER | (p. 85) |
| 07: | AUTO WAH | (p. 85) |
| 08: | ROTARY | (p. 86) |
| 09: | COMPRESSOR | (p. 87) |
| 10: | LIMITER | (p. 87) |
| 11: | HEXA-CHORUS | (p. 88) |
| 12: | TREMOLO CHORUS | (p. 88) |
| 13: | SPACE-D | (p. 89) |
| 14: | STEREO CHORUS | (p. 89) |
| 15: | STEREO FLANGER | (p. 90) |
| 16: | STEP FLANGER | (p. 91) |
| 17: | STEREO DELAY | (p. 92) |
| 18: | MODULATION DELAY | (p. 93) |
| 19: | TRIPLE TAP DELAY | (p. 94) |
| 20: | QUADRUPLE TAP DELAY | (p. 95) |
| 21: | TIME CONTROL DELAY | (p. 96) |
| 22: | 2VOICE PITCH SHIFTER | (p. 96) |
| 23: | FBK PITCH SHIFTER | (p. 97) |
| 24: | REVERB | (p. 98) |
| 25: | GATED REVERB | (p. 99) |
| 26: | OVERDRIVE \rightarrow CHORUS | (p. 99) |
| 27: | $OVERDRIVE \to FLANGER$ | (p. 100) |
| 28: | OVERDRIVE \rightarrow DELAY | (p. 100) |
| 29: | ${\tt DISTORTION} \to {\tt CHORUS}$ | (p. 101) |
| 30: | $DISTORTION \to FLANGER$ | (p. 101) |
| 31: | $DISTORTION \to DELAY$ | (p. 101) |
| 32: | $ENHANCER \to CHORUS$ | (p. 102) |
| 33: | $ENHANCER \to FLANGER$ | (p. 102) |
| 34: | $ENHANCER \rightarrow DELAY$ | (p. 103) |
| 35: | $CHORUS \to DELAY$ | (p. 103) |
| 36: | $FLANGER \to DELAY$ | (p. 104) |
| 37: | $\textbf{CHORUS} \rightarrow \textbf{FLANGER}$ | (p. 104) |
| 38: | CHORUS/DELAY | (p. 105) |
| 39: | FLANGER/DELAY | (p. 105) |
| 40: | CHORUS/FLANGER | (p. 105) |
| 41: | LOFI | (p. 106) |
| 42: | SLICER | (p. 106) |
| | | |

* Values for parameters marked with #1 or #2 can be changed in real time with the modulation lever or the knobs. For details, refer to (p. 71).

Send LevI to Cho (Multi-effect send level to chorus)

Sets the amount of the multi-effects sound that is sent to the chorus. Higher values result in more sound being sent.

Value: 0-127

* This parameter is included in all multi-effects types.

Send LevI to Rev (Multi-effect send level to reverb)

Sets the amount of the multi-effects sound that is sent to the reverb. Higher values result in more sound being sent.

Value: 0-127


* This parameter is included in all multi-effects types.

00: THROUGH

Effects are not applied. Select when creating Tones or Drum Sets that do not use multi-effects.

01: STEREO EQ (Stereo Equalizer)

This is a four-band stereo equalizer (low, mid x 2, high).



Low Freq (Low Frequency)

Select the frequency of the low range (200 Hz/400 Hz).

Value: 200, 400 [Hz]

Low Gain

Adjust the gain of the low frequency.

Value: -15- +15 [dB]

High Freq (High Frequency)

Select the frequency of the high range (4000 Hz/8000 Hz).

Value: 4000, 8000 [Hz]

High Gain

Adjust the gain of the high frequency.

Value: -15- +15 [dB]

Mid1 Freq (Middle 1 Frequency)

Adjust the frequency of Middle 1 (mid range).

Value: 200-8000 [Hz]

Mid1 Q (Middle 1 Q)

This parameter adjusts the width of the area around the Middle 1 Frequency that will be affected by the Gain setting. Higher values of Q will result in a narrower area being affected.

Value: 0.5, 1.0, 2.0, 4.0, 8.0

Mid1 Gain (Middle 1 Gain)

Adjust the gain for the area specified by the Middle 1 Frequency and Q settings.

Value: -15- +15 [dB]

Mid2 Freq (Middle 2 Frequency)

Adjust the frequency of Middle 2 (mid range).

Value: 200-8000 [Hz]

Mid2 Q (Middle 2 Q)

This parameter adjusts the width of the area around the Middle 2 Frequency that will be affected by the Gain setting. Higher values of Q will result in a narrower area being affected.

Value: 0.5, 1.0, 2.0, 4.0, 8.0

Mid2 Gain (Middle 2 Gain)

Adjust the gain for the area specified by the Middle 2 Frequency and Q settings.


Value: -15-+15 [dB]

Level (Output Level) #1, #2

Adjust the output level.

02: OVERDRIVE

This effect creates a soft distortion similar to that produced by vacuum tube amplifiers.



Drive #1

Adjust the degree of distortion. The volume will change together with the degree of distortion.

Value: 0-127

Level (Output Level)

Adjust the output level.

Value: 0-127

Low Gain

Adjust the gain of the low frequency range.

Value: -15-- +15 [dB]

High Gain

Adjust the gain of the high frequency range.

Value: -15-+15 [dB]

Amp Type (Amp Simulator Type)

Select the type of guitar amp.

Value

SMALL: small amp

BUILT-IN: single-unit type amp 2-STACK: large double stack amp 3-STACK: large triple stack amp


Pan (Output Pan) #2

Adjust the stereo location of the output sound. L64 is far left, 0 is center, and 63R is far right.

Value: L64-63R

03: DISTORTION

This effect produces a more intense distortion than Overdrive.



Drive #1

Adjust the degree of distortion. The volume will change together with the degree of distortion.

Value: 0-127

Level (Output Level)

Adjust the output level.

Value: 0-127

Low Gain

Adjust the gain of the low frequency range.

Value: -15-+15 [dB]

High Gain

Adjust the gain of the high frequency range.

Value: -15- +15 [dB]

Amp Type (Amp Simulator Type)

Select the type of guitar amp.

Value

SMALL: small amp

BUILT-IN: single-unit type amp 2-STACK: large double stack amp 3-STACK: large triple stack amp


Pan (Output Pan) #2

Adjust the stereo location of the output sound. L64 is far left, 0 is center, and 63R is far right.

Value: L64-63R

04: PHASER

A phaser adds a phase-shifted sound to the direct sound, producing a twisting modulation that creates spaciousness and depth.



Manual #1

Adjust the basic frequency from which the sound will be modulated.

Value: 100-8000 [Hz]

Rate #2

Adjust the frequency (period) of modulation.

Value: 0.05-10.00 [Hz]

Depth

Adjust the depth of modulation.

Value: 0-127

Resonance

Adjust the amount of feedback for the phaser.

Value: 0-127

Mix (Mix Level)

Adjust the ratio with which the phase-shifted sound is combined with the direct sound.

Value: 0-127

Pan (Output Pan)

Adjust the stereo location of the output sound. L64 is far left, 0 is center, and 63R is far right.

Value: L64-63R

Level (Output Level)


Adjust the output level.

Value: 0-127

05: SPECTRUM

Spectrum is a type of filter which modifies the timbre by boosting or cutting the level at specific frequencies.

It is similar to an equalizer, but has 8 frequency points fixed at locations most suitable for adding character to the sound.



Band I (Band 1 Gain)

Adjust the 250 Hz level. **Value:** -15– +15 [dB]

Band 2 (Band 2 Gain)

Adjust the 500 Hz level. **Value:** -15– +15 [dB]

Band 3 (Band 3 Gain)

Adjust the 1000 Hz level. **Value:** -15– +15 [dB]

Band 4 (Band 4 Gain)

Adjust the 1250 Hz level. **Value:** -15– +15 [dB]

Band 5 (Band 5 Gain)

Adjust the 2000 Hz level. **Value:** -15– +15 [dB]

Band 6 (Band 6 Gain)

Adjust the 3150 Hz level. **Value:** -15– +15 [dB]

Band 7 (Band 7 Gain)

Adjust the 4000 Hz level. **Value:** -15– +15 [dB]

Band 8 (Band 8 Gain)

Adjust the 8000 Hz level. **Value:** -15– +15 [dB]

Q

Simultaneously adjust the width of the adjusted areas for all the frequency bands.

Value: 0.5, 1.0, 2.0, 4.0, 8.0

Shapter 6

Pan (Output Pan) #1

Adjust the stereo location of the output sound. L64 is far left, 0 is center, and 63R is far right.

Value: L64-63R


Level (Output Level) #2

Adjust the output level.

Value: 0-127

06: ENHANCER

The Enhancer controls the overtone structure of the high frequencies, adding sparkle and tightness to the sound.



Sens (Sensitivity) #1

Adjust the sensitivity of the enhancer.

Value: 0-127

Mix (Mix Level) #2

Adjust the ratio with which the overtones generated by the enhancer are combined with the direct sound.

Value: 0-127

Low Gain

Adjust the gain of the low frequency range.

Value: -15-+15 [dB]

High Gain

Adjust the gain of the high frequency range.

Value: -15-+15 [dB]

Level (Output Level)

Adjust the output level.

Value: 0-127

07: AUTO WAH

The Auto Wah cyclically controls a filter to create cyclic change in timbre.



Filter Type

Select the type of filter.

Value

LPF: The wah effect will be applied over a wide frequency range. BPF: The wah effect will be applied over a narrow frequency range.

Sens (Sensitivity)

Adjust the sensitivity with which the filter is controlled.

Value: 0-127

Manual #1

Adjust the center frequency from which the effect is applied.

Value: 0-127

Peak

Adjust the amount of the wah effect that will occur in the area of the center frequency. Lower settings will cause the effect to be applied in a broad area around the center frequency. Higher settings will cause the effect to be applied in a more narrow range.

Value: 0-127

Rate #2

Adjust the frequency of the modulation.

Value: 0.05-10.00 [Hz]

Depth

Adjust the depth of the modulation.

Value: 0-127

Polarity

Sets the direction in which the frequency will change when the auto-wah filter is modulated. With a setting of Up, the filter will change toward a higher frequency. With a setting of Down, it will change toward a lower frequency.

Value: UP, DOWN


Level (Output Level)

Adjust the output level.

08: ROTARY

The Rotary effect simulates the sound of the rotary speakers often used with the electric organs of the past.

Since the movement of the high range and low range rotors can be set independently, the unique type of modulation characteristic of these speakers can be simulated quite closely. This effect is most suitable for electric organ Patches.



Low Slow (Low Frequency Slow Rate)

Adjust the slow speed (SLOW) of the low frequency rotor. **Value:** 0.05–10.00 [Hz]

Low Fast (Low Frequency Fast Rate)

Adjust the fast speed (FAST) of the low frequency rotor. **Value:** 0.05–10.00 [Hz]

Low Accel (Low Frequency Acceleration)

Adjust the time it takes the low frequency rotor to reach the newly selected speed when switching from fast to slow (or slow to fast) speed. Lower values will require longer times.

Value: 0-15

Low Level (Low Frequency Level)

Adjust the volume of the low frequency rotor.

Value: 0-127

High Slow (High Frequency Slow Rate)

Adjust the slow speed (SLOW) of the high frequency rotor.

Value: 0.05-10.00 [Hz]

High Fast (High Frequency Fast Rate)

Adjust the fast speed (FAST) of the high frequency rotor. **Value:** 0.05–10.00 [Hz]

High Accel (High Frequency Acceleration)

Adjust the time it takes the high frequency rotor to reach the newly selected speed when switching from fast to slow (or slow to fast) speed. Lower values will require longer times.

Value: 0-15

High Level (High Frequency Level)

Adjust the volume of the high frequency rotor.

Value: 0-127

Separation

Adjust the spatial dispersion of the sound.

Value: 0-127

Speed #1

Simultaneously switch the rotational speed of the low frequency rotor and high frequency rotor.

Value

SLOW: Slow down the rotation to the specified speed (the Low Slow/Hi Slow values).

FAST: Speed up the rotation to the specified speed (the Low Fast/Hi Fast values).


* When you want to use the pedal switch to switch the Rotary rotation speed, select MFX PARAMETER 1 in Control Pedal Assign (p. 73).

Level (Output Level) #2

Adjust the output level.

09: COMPRESSOR

The Compressor flattens out high levels and boosts low levels, smoothing out unevenness in volume.



Attack (Attack Time)

Adjust the attack time of an input sound.

Value: 0-127

Sustain

Adjust the time over which low level sounds are boosted until they reach the specified volume.

Value: 0-127

Post Gain

Adjust the output gain.

Value: 0, +6, +12, +18 [dB]

Low Gain

Adjust the low frequency gain.

Value: -15- +15 [dB]

High Gain

Adjust the high frequency gain.

Value: -15-+15 [dB]

Pan (Output Pan) #1

Adjust the stereo location of the output sound. L64 is far left, 0 is center, and 63R is far right.

Value: L64-63R

Level (Output Level) #2

Adjust the output level.

Value: 0-127

10: LIMITER

The Limiter compresses signals that exceed a specified volume level, preventing distortion from occurring.



Threshold (Threshold Level)

Adjust the volume at which compression will begin.

Value: 0-127

Ratio (Compression Ratio)

Adjust the compression ratio.

Value: 1.5:1, 2:1, 4:1, 100:1

Release (Release Time)

Adjust the time from when the volume falls below the Threshold Level until compression is no longer applied.

Value: 0-127

Post Gain

Adjust the output gain.

Value: 0, +6, +12, +18 [dB]

Low Gain

Adjust the low frequency gain.

Value: -15- +15 [dB]

High Gain

Adjust the high frequency gain.

Value: -15-+15 [dB]

Pan (Output Pan) #1

Adjust the stereo location of the output sound. L64 is far left, 0 is center, and 63R is far right.


Value: L64-63R

Level (Output Level) #2

Adjust the output level.

11: HEXA-CHORUS

Hexa-chorus uses a six-phase chorus (six layers of chorused sound) to give richness and spatial spread to the sound.



Pre Delay (Pre Delay Time)

Adjust the time delay from when the direct sound begins until the chorus sound is heard.

Value: 0.0-100 [ms]

Rate #1

Adjust the rate of modulation.

Value: 0.05-10.00 [Hz]

Depth

Adjust the depth of modulation.

Value: 0-127

Pre Delay Dev (Pre Delay Deviation)

Pre Delay determines the time from when the direct sound begins until the processed sound is heard. Pre Delay Deviation adjusts the differences in Pre Delay between each chorus sound.

Value: 0-20

Depth Dev (Depth Deviation)

Adjust the difference in modulation depth between each chorus sound.

Value: -20- +20

Pan Dev (Pan Deviation)

Adjust the difference in stereo location between each chorus sound. With a setting of 0, all chorus sounds will be in the center. With a setting of 20, each chorus sound will be spaced at 60 degree intervals relative to the center.

Value: 0-20

Balance (Effect Balance) #2

Adjust the volume balance between the direct sound and the chorus sound. With a setting of D100:0W only the direct sound will be output, and with a setting of D0:100W only the chorus sound will be output.

Value: D100:0W-D0:100W


Level (Output Level)

Adjust the output level.

Value: 0-127

12: TREMOLO CHORUS

Tremolo Chorus is a chorus effect with added Tremolo (cyclic modulation of volume).



Pre Delay (Pre Delay Time)

Adjust the time delay from when the direct sound begins until the chorus sound is heard.

Value: 0.0-100 [ms]

Chorus Rate

Adjust the modulation speed of the chorus effect.

Value: 0.05-10.00 [Hz]

Chorus Depth

Adjust the modulation depth of the chorus effect.

Value: 0-127

Tremolo Phase

Adjust the spread of the tremolo effect.

Value: 0-180 [deg]

Tremolo Rate #1

Adjust the modulation speed of the tremolo effect.

Value: 0.05-10.00 [Hz]

Tremolo Sep (Tremolo Separation)

Adjust the spread of the tremolo effect.

Value: 0-127

Balance (Effect Balance) #2

Adjust the volume balance between the direct sound and the tremolo chorus sound. With a setting of D100:0W only the direct sound will be output, and with a setting of D0:100W only the tremolo chorus sound will be output.

Value: D100:0W-D0:100W


Level (Output Level)

Adjust the output level.

Value: 0-127

13: SPACE-D

Space-D is a multiple chorus that applies two-phase modulation in stereo. It gives no impression of modulation, but produces a transparent chorus effect.



Pre Delay (Pre Delay Time)

Adjust the time delay from when the direct sound begins until the processed sound is heard.

Value: 0.0-100 [ms]

Rate #1

Adjust the rate of modulation.

Value: 0.05-10.00 [Hz]

Depth

Adjust the depth of modulation.

Value: 0-127

Phase

Adjust the spatial spread of the sound.

Value: 0-180 [deg]

Low Gain

Adjust the gain of the low frequency range.

Value: -15-+15 [dB]

High Gain

Adjust the gain of the high frequency range.

Value: -15-+15 [dB]

Balance (Effect Balance) #2

Adjust the volume balance between the direct sound and the chorus sound. With a setting of D100:0W only the direct sound will be output, and with a setting of D0:100W only the chorus sound will be output.

Value: D100:0W-D0:100W


Level (Output Level)

Adjust the output level.

Value: 0-127

14: STEREO CHORUS

This is a stereo chorus. A filter is provided so that you can adjust the timbre of the chorus sound.



Pre Delay (Pre Delay Time)

Adjust the time delay from when the direct sound begins until the processed sound is heard.

Value: 0.0-100 [ms]

Rate #1

Adjust the rate of modulation.

Value: 0.05-10.00 [Hz]

Depth

Adjust the depth of modulation.

Value: 0-127

Phase

Adjust the spatial spread of the sound.

Value: 0-180 [deg]

Filter Type

Select the type of filter.

Value

OFF: a filter will not be used

LPF: cut the frequency range above the cutoff frequency HPF: cut the frequency range below the cutoff frequency

Cutoff Freq (Cutoff Frequency)

Adjust the basic frequency of the filter.

Value: 200-8000 [Hz]

Low Gain

Adjust the gain of the low frequency range.

Value: -15-+15 [dB]

High Gain

Adjust the gain of the high frequency range.

Value: -15- +15 [dB]

Balance (Effect Balance) #2

Adjust the volume balance between the direct sound and the chorus sound. With a setting of D100:0W only the direct sound will be output, and with a setting of D0:100W only the chorus sound will be output.

Value: D100:0W-D0:100W


Level (Output Level)

Adjust the output level.

Value: 0-127

15: STEREO FLANGER

This is a stereo flanger. (The LFO has the same phase for left and right.) It produces a metallic resonance that rises and falls like a jet airplane taking off or landing. A filter is provided so that you can adjust the timbre of the flanged sound.



Pre Delay (Pre Delay Time)

Adjust the time delay from when the direct sound begins until the flanger sound is heard.

Value: 0.0-100 [ms]

Rate #1

Adjust the rate of modulation.

Value: 0.05-10.00 [Hz]

Depth

Adjust the depth of modulation.

Value: 0-127

Feedback (Feedback Level) #2

Adjust the amount (%) of the processed sound that is returned (fed back) into the input. Positive (+) settings will return the sound in phase, and negative (-) settings will return the sound in reverse phase.

Value: -98- +98 [%]

Phase

Adjust the spatial spread of the sound.

Value: 0-180 [deg]

Filter Type

Select the type of filter.

OFF: a filter will not be used

LPF: cut the frequency range above the cutoff frequency **HPF**: cut the frequency range below the cutoff frequency

Cutoff Freq (Cutoff Frequency)

Adjust the basic frequency of the filter.

Value: 200-8000 [Hz]

Low Gain

Adjust the gain of the low frequency range.

Value: -15- +15 [dB]

High Gain

Adjust the gain of the high frequency range.

Value: -15-+15 [dB]

Balance (Effect Balance)

Adjust the volume balance between the direct sound and the flanger sound. With a setting of D100:0W only the direct sound will be output, and with a setting of D0:100W only the flanger sound will be output.


Value: D100:0W-D0:100W

Level (Output Level)

Adjust the output level.

16: STEP FLANGER

The Step Flanger effect is a flanger in which the flanger pitch changes in steps.



Pre Delay (Pre Delay Time)

Adjust the time delay from when the direct sound begins until the flanger sound is heard.

Value: 0.0-100 [ms]

Rate

Adjust the rate of modulation.

Value: 0.05-10.00 [Hz]

Depth

Adjust the depth of modulation.

Value: 0-127

Feedback (Feedback Level) #1

Adjust the amount (%) of the flanger sound that is returned (fed back) into the input. Negative (-) settings will invert the phase.

Value: -98- +98 [%]

Phase

Adjust the spatial spread of the sound.

Value: 0-180 [deg]

Step Rate #2

Adjust the rate (period) of pitch change.

Value: 0.1–20.0 [Hz], note-value symbols

Step Rate parameter can be set as a note-value of a specified tempo. In this case, specify the value of the desired note. The Tempo (p. 76) setting changes to the basic tempo.

Low Gain

Adjust the gain of the low frequency range.

Value: -15-+15 [dB]

High Gain

Adjust the gain of the high frequency range.

Value: -15-+15 [dB]

Balance (Effect Balance)

Adjust the volume balance between the direct sound and the flanger sound. With a setting of D100:0W only the direct sound will be output, and with a setting of D0:100W only the chorus sound will be output.

Value: D100:0W-D0:100W


Level (Output Level)

Adjust the output level.


17: STEREO DELAY

This is a stereo delay.

When Feedback Mode is NORMAL:



When Feedback Mode is CROSS:



Delay Left (Delay Time Left)

Adjust the time from the direct sound until when the left delay sound is heard.

Value: 0.0-500 [ms]

Delay Right (Delay Time Right)

Adjust the time from the direct sound until when the right delay sound is heard.

Value: 0.0-500 [ms]

Feedback (Feedback Level) #1

Adjust the proportion (%) of the delay sound that is fed back into the effect. Negative (-) settings will invert the phase.

Value: -98- +98 [%]

Feedback Mode

Select the way in which delay sound is fed back into the effect.

Value

NORMAL: The left delay sound will be fed back into the left

delay, and the right delay sound into the right

delay.

CROSS: The left delay sound will be fed back into the

right delay, and the right delay sound into the

left delay.

Phase Left (Feedback Phase Left)

Select the phase of the left delay sound.

Value

NORMAL: Phase is not changed. INVERT: Phase is inverted.

Phase Right (Feedback Phase Right)

Select the phase of the right delay sound.

Value

NORMAL: Phase is not changed. INVERT: Phase is inverted.

HF Damp

Adjust the frequency above which sound fed back to the effect will be cut. If you do not want to cut the high frequencies of the feedback, set this parameter to BYPASS.

Value: 200-8000 [Hz], BYPASS

Low Gain

Adjust the gain of the low frequency range.

Value: -15-+15 [dB]

High Gain

Adjust the gain of the high frequency range.

Value: -15-+15 [dB]

Balance (Effect Balance) #2

Adjust the volume balance between the direct sound and the delay sound. With a setting of D100:0W only the direct sound will be output, and with a setting of D0:100W only the delay sound will be output.

Value: D100:0W-D0:100W


Level (Output Level)

Adjust the output level.


18: MODULATION DELAY

This effect adds modulation to the delayed sound, producing an effect similar to a flanger.

When Feedback Mode is NORMAL:



When Feedback Mode is CROSS:



Delay Left (Delay Time Left)

Adjust the time from the direct sound until when the left delay sound is heard.

Value: 0.0-500 [ms]

Delay Right (Delay Time Right)

Adjust the time from the direct sound until when the right delay sound is heard.

Value: 0.0–500 [ms]

Feedback (Feedback Level)

Adjust the proportion (%) of the delay sound that is fed back into the effect. Negative (-) settings will invert the phase.

Value: -98- +98 [%]

Feedback Mode

Select the way in which delay sound is fed back into the effect.

Value

NORMAL: The left delay sound will be fed back into the left

delay, and the right delay sound into the right

delay.

CROSS: The left delay sound will be fed back into the

right delay, and the right delay sound into the

left delay.

Rate #1

Adjust the speed of the modulation.

Value: 0.05-10.00 [Hz]

Depth

Adjust the depth of the modulation.

Value: 0-127

Phase

Adjust the spatial spread of the sound.

Value: 0-180 [deg]

HF Damp

Adjust the frequency above which sound fed back to the effect will be cut. If you do not want to cut the high frequencies of the feedback, set this parameter to BYPASS.

Value: 200-8000 [Hz], BYPASS

Low Gain

Adjust the gain of the low frequency range.

Value: -15-- +15 [dB]

High Gain

Adjust the gain of the high frequency range.

Value: -15-+15 [dB]

Balance (Effect Balance) #2

Adjust the volume balance between the direct sound and the modulation delay sound. With a setting of D100:0W only the direct sound will be output, and with a setting of D0:100W only the modulation delay sound will be output.


Value: D100:0W-D0:100W

Level (Output Level)

Adjust the output level.

19: TRIPLE TAP DELAY

The Triple Tap Delay produces three delay sounds; center, left and right.



Delay Center (Delay Time Center)

Adjust the time delay from the direct sound until when the center delay sound is heard.

Value: 200-1000 [ms], note-value symbols

Delay Left (Delay Time Left)

Adjust the time delay from the direct sound until when the left delay sound is heard.

Value: 200-1000 [ms], note-value symbols

Delay Right (Delay Time Right)

Adjust the time delay from the direct sound until when the right delay sound is heard.

Value: 200-1000 [ms], note-value symbols

Delay C, Delay L and Delay R parameters can be set as a note-value of a specified tempo. In this case, specify the value of the desired note. The Tempo (p. 76) setting changes to the basic tempo.

Feedback (Feedback Level) #1

Adjust the proportion (%) of the delay sound that is fed back into the effect. Negative (-) settings will invert the phase.

Value: -98- +98 [%]

Center Level

Adjust the volume of the center delay sound.

Value: 0-127

Left Level

Adjust the volume of the left delay sound.

 $\textbf{Value:}\ 0\text{--}127$

Right Level

Adjust the volume of the right delay sound.

Value: 0-127

HF Damp

Adjust the frequency above which sound fed back to the effect will be cut. If you do not want to cut the high frequencies of the feedback, set this parameter to BYPASS.

Value: 200-8000 [Hz], BYPASS

Low Gain

Adjust the gain of the low frequency range.

Value: -15- +15 [dB]

High Gain

Adjust the gain of the high frequency range.

Value: -15- +15 [dB]

Balance (Effect Balance) #2

Adjust the volume balance between the direct sound and the delay sound. With a setting of D100:0W only the direct sound will be output, and with a setting of D0:100W only the delay sound will be output.


Value: D100:0W-D0:100W

Level (Output Level)


Adjust the output level.

20: QUADRUPLE TAP DELAY

The Quadruple Tap Delay has four delays.



The stereo location of each delay sound is as follows.



Delay 1 (Delay Time 1)

Adjust the time delay from the direct sound until when delay 1 sound is heard.

Value: 200-1000 [ms], note-value symbols

Delay 2 (Delay Time 2)

Adjust the time delay from the direct sound until when delay 2 sound is heard.

Value: 200-1000 [ms], note-value symbols

Delay 3 (Delay Time 3)

Adjust the time delay from the direct sound until when delay 3 sound is heard.

Value: 200–1000 [ms], note-value symbols

Delay 4 (Delay Time 4)

Adjust the time delay from the direct sound until when delay 4 sound is heard.

Value: 200-1000 [ms], note-value symbols

Delay 1–4 parameters can be set as a note-value of a specified tempo. In this case, specify the value of the desired note. The Tempo (p. 76) setting changes to the basic tempo.

Level 1

Adjust the volume of delay 1 sound.

Value: 0-127

Level 2

Adjust the volume of delay 2 sound.

Value: 0-127

Level 3

Adjust the volume of delay 3 sound.

Value: 0-127

Level 4

Adjust the volume of delay 4 sound.

Value: 0-127

Feedback (Feedback Level) #1

Adjust the proportion (%) of the delay sound that is fed back into the effect. Negative (-) settings will invert the phase.

Value: -98- +98 [%]

HF Damp

Adjust the frequency above which sound fed back to the effect will be cut. If you do not want to cut the high frequencies of the feedback, set this parameter to BYPASS.

Value: 200-8000 [Hz], BYPASS

Balance (Effect Balance)

Adjust the volume balance between the direct sound and the delay sound. With a setting of D100:0W only the direct sound will be output, and with a setting of D0:100W only the delay sound will be output.


Value: D100:0W-D0:100W

Level (Output Level)

Adjust the output level.

21: TIME CONTROL DELAY

You can use the modulation lever and knobs to change the delay time and pitch in real time (p. 71). Lengthening the delay will lower the pitch, and shortening it will raise the pitch.



Delay (Delay Time) #1

Adjust the time delay from the direct sound until when each delay sound is heard.

Value: 200-1000 [ms]

Acceleration

This parameter adjusts the time over which the Delay Time will change from the current setting to a newly specified setting. The rate of change for the Delay Time directly affects the rate of pitch change.

Value: 0-15

Feedback (Feedback Level) #2

Adjust the proportion (%) of the delay sound that is fed back into the effect. Negative (-) settings will invert the phase.

Value: -98- +98 [%]

HF Damp

Adjust the frequency above which sound fed back to the effect will be cut. If you do not want to cut the high frequencies of the feedback, set this parameter to BYPASS.

Value: 200-8000 [Hz], BYPASS

Pan (Output Pan)

Adjust the stereo location of the delay sound. L64 is far left, 0 is center, and 63R is far right.

Value: L64-63R

Low Gain

Adjust the gain of the low frequency range.

Value: -15-+15 [dB]

High Gain

Adjust the gain of the high frequency range.

Value: -15-+15 [dB]

Balance (Effect Balance)

Adjust the volume balance between the direct sound and the delay sound. With a setting of D100:0W only the direct sound will be output, and with a setting of D0:100W only the delay sound will be output.

Value: D100:0W-D0:100W


Level (Output Level)

Adjust the output level.

Value: 0-127

22: 2VOICE PITCH SHIFTER

A Pitch Shifter shifts the pitch of the direct sound. This 2-voice pitch shifter has two pitch shifters, and can add two pitch shifted sounds to the direct sound.



CoarseA (Coarse Pitch A) #1

Adjust the pitch of Pitch Shift A in semitone steps (-2-+1 octaves).

Value: -24-+12 [semi]

Fine A (Fine Pitch A) #1

Make fine adjustments to the pitch of Pitch Shift A in 2-cent steps (-100–+100 cents).

One cent is 1/100th of a semitone.

Value: -100-+100 [cent]

Pan A (Output Pan A)

Adjust the stereo location of the Pitch Shift A sound. L64 is far left, 0 is center, and 63R is far right.

Value: L64-63R

Pre Delay A (Pre Delay Time A)

Adjust the time delay from when the direct sound begins until the Pitch Shift A sound is heard.

Value: 0.0-500 [ms]

CoarseB (Coarse Pitch B) #2

Adjust the pitch of Pitch Shift B in semitone steps (-2-+1 octaves).

Value: -24-+12 [semi]

Fine B (Fine Pitch B) #2

Make fine adjustments to the pitch of Pitch Shift B in 2-cent steps (-100-+100 cents).

One cent is 1/100th of a semitone.

Value: -100-+100 [cent]

Pan B (Output Pan B)

Adjust the stereo location of the Pitch Shift B sound. L64 is far left, 0 is center, and 63R is far right.

Value: L64-63R

Pre Delay B (Pre Delay Time B)

Adjust the time delay from when the direct sound begins until the Pitch Shift A sound is heard.

Value: 0.0-500 [ms]

Mode (Pitch Shifter Mode)

Higher settings of this parameter will result in slower response, but steadier pitch.

Value: 1, 2, 3, 4, 5

Lev Balance (Level Balance)

Adjust the volume balance between the Pitch Shift A and Pitch Shift B sounds.

Value: A100:0B-A0:100B

Balance (Effect Balance)

Adjust the volume balance between the direct sound and the pitch shift sound. With a setting of D100:0W only the direct sound will be output, and with a setting of D0:100W only the pitch shift sound will be output.

Value: D100:0W-D0:100W


Level (Output Level)

Adjust the output level.

Value: 0-127

23: FBK PITCH SHIFTER (Feedback Pitch Shifter)

This pitch shifter allows the pitch shifted sound to be fed back into the effect.



Coarse (Coarse Pitch) #1

Adjust the pitch of the pitch shifted sound in semitone steps (-2—+1 octaves).

Value: -24-+12 [semi]

Fine (Fine Pitch) #1

Make fine adjustments to the pitch of the pitch shifted sound in 2-cent steps (-2-+1 octaves).

Value: -100- +100 [cent]

Feedback (Feedback Level) #2

Adjust the proportion (%) of the processed sound that is fed back into the effect. Negative (-) settings will invert the phase.

Value: -98- +98 [%]

Pre Delay (Pre Delay Time)

Adjust the time delay from when the direct sound begins until the pitch shifted sound is heard.

Value: 0.0-500 [ms]

Mode (Pitch Shifter Mode)

Higher settings of this parameter will result in slower response, but steadier pitch.

Value: 1, 2, 3, 4, 5

Pan (Output Pan)

Adjust the stereo location of the pitch shifted sound. L64 is far left, 0 is center, and 63R is far right.

Value: L64-63R

Low Gain

Adjust the gain of the low frequency range.

Value: -15-+15 [dB]

High Gain

Adjust the gain of the high frequency range.

Value: -15- +15 [dB]

Balance (Effect Balance)

Adjust the volume balance between the direct sound and the pitch shift sound. With a setting of D100:0W only the direct sound will be output, and with a setting of D0:100W only the pitch shift sound will be output.

Value: D100:0W-D0:100W


Level (Output Level)

Adjust the output level.

Value: 0-127

24: REVERB

The Reverb effect adds reverberation to the sound, simulating an acoustic space.



Type (Reverb Type)

Select the type of Reverb effect.

Value

ROOM1: dense reverb with short decay
ROOM2: sparse reverb with short decay
STAGE1: reverb with greater late reverberation
STAGE2: reverb with strong early reflections
HALL1: reverb with clear reverberance
HALL2: reverb with rich reverberance

Pre Delay (Pre Delay Time)

Adjust the time delay from when the direct sound begins until the reverb sound is heard.

Value: 0.0-100 [ms]

Time (Reverb Time) #1

Adjust the time length of reverberation.

Value: 0-127

HF Damp

Adjust the frequency above which the reverberant sound will be cut. As the frequency is set lower, more of the high frequencies will be cut, resulting in a softer and more muted reverberance. If you do not want the high frequencies to be cut, set this parameter to BYPASS.

Value: 200-8000 [Hz], BYPASS

Low Gain

Adjust the gain of the low frequency range.

Value: -15- +15 [dB]

High Gain

Adjust the gain of the high frequency range.

Value: -15- +15 [dB]

Balance (Effect Balance) #2

Adjust the volume balance between the direct sound and the reverb sound. With a setting of D100:0W only the direct sound will be output, and with a setting of D0:100W only the reverb sound will be output.


Value: D100:0W-D0:100W

Level (Output Level)

Adjust the output level.

25: GATED REVERB

Gate Reverb is a special type of reverb in which the reverberant sound is cut off before its natural length.



Type (Gated Reverb Type)

Select the type of reverb.

Value

NORMAL: conventional gate reverb

REVERSE: backwards reverb

SWEEP1: the reverberant sound moves from right to left SWEEP2: the reverberant sound moves from left to right

Pre Delay (Pre Delay Time)

Adjust the time delay from when the direct sound begins until the reverb sound is heard.

Value: 0.0-100 [ms]

Gate Time

Adjust the time from when the reverb is heard until when it disappears.

Value: 5-500 [ms]

Low Gain

Adjust the gain of the low frequency range.

Value: -15- +15 [dB]

High Gain

Adjust the gain of the high frequency range.

Value: -15- +15 [dB]

Balance (Effect Balance) #1

Adjust the volume balance between the direct sound and the reverb sound. With a setting of D100:0W only the direct sound will be output, and with a setting of D0:100W only the reverb sound will be output.

Value: D100:0W-D0:100W


Level (Output Level) #2

Adjust the output level.

Value: 0-127

26: OVERDRIVE→CHORUS

This effect connects an overdrive and a chorus in series.



OD Drive

Adjust the degree of overdrive distortion. The volume will change together with the degree of distortion.

Value: 0-127

OD Pan (Overdrive Pan) #1

Adjust the stereo location of the overdrive sound. L64 is far

left, 0 is center, and 63R is far right.

Value: L64-63R

Chorus Delay (Chorus Pre Delay Time)

Adjust the time delay from when the direct sound begins until the chorus sound is heard.

Value: 0.0-100 [ms]

Chorus Rate

Adjust the modulation speed of the chorus effect.

Value: 0.05–10.00 [Hz]

Chorus Depth

Adjust the modulation depth of the chorus effect.

Value: 0-127

Chorus Bal (Chorus Balance) #2

Adjust the volume balance between the overdrive sound that is sent through the chorus and the overdrive sound that is not sent through the chorus. With a setting of "D100:0W," only the overdrive sound will be output. With a setting of "D0:100W," only the overdrive sound that is sent through the chorus will be output.


Value: D100:0W-D0:100W

Level (Output Level)

Adjust the output level.

27: OVERDRIVE→FLANGER

This effect connects an overdrive and a flanger in series.



OD Drive

Adjust the degree of overdrive distortion. The volume will change together with the degree of distortion.

Value: 0-127

OD Pan (Overdrive Pan) #1

Adjust the stereo location of the overdrive sound. L64 is far left, 0 is center, and 63R is far right.

Value: L64-63R

Flg Pre Dly (Flanger Pre Delay Time)

Adjust the time delay from when the direct sound begins until the flanger sound is heard.

Value: 0.0-100 [ms]

Flg Rate (Flanger Rate)

Adjust the modulation speed of the flanger effect.

Value: 0.05-10.00 [Hz]

Fig Dpt (Flanger Depth)

Adjust the modulation depth of the flanger effect.

Value: 0-127

Flg Feedback (Flanger Feedback Level)

Adjust the proportion (%) of the flanger sound that is fed back into the effect. Negative (-) settings will invert the phase.

Value: -98- +98 [%]

Flg Balance (Flanger Balance) #2

Adjust the volume balance between the overdrive sound that is sent through the flanger and the overdrive sound that is not sent through the flanger. With a setting of "D100:0W," only the overdrive sound will be output. With a setting of "D0:100W," only the overdrive sound that is sent through the flanger will be output.

Value: D100:0W-D0:100W


Level (Output Level)

Adjust the output level.

Value: 0-127

28: OVERDRIVE -> DELAY

This effect connects an overdrive and a delay in series.



OD Drive

Adjust the degree of overdrive distortion. The volume will change together with the degree of distortion.

Value: 0-127

OD Pan (Overdrive Pan) #1

Adjust the stereo location of the overdrive sound. L64 is far left, 0 is center, and 63R is far right.

Value: L64-63R

Delay Time

Adjust the time delay from when the direct sound begins until the delay sound is heard.

Value: 0.0-500 [ms]

Delay Feedback (Delay Feedback Level)

Adjust the proportion (%) of the delay sound that is fed back into the effect. Negative (-) settings will invert the phase.

Value: -98- +98 [%]

Delay HF Damp

Adjust the frequency above which delayed sound fed back to the effect will be cut. If you do not want to cut the high frequencies of the feedback, set this parameter to BYPASS.

Value: 200-8000 [Hz], BYPASS

Delay Bal (Delay Balance) #2

Adjust the volume balance between the overdrive sound that is sent through the delay and the overdrive sound that is not sent through the delay. With a setting of "D100:0W," only the overdrive sound will be output. With a setting of "D0:100W," only the overdrive sound that is sent through the delay will be output.

Value: D100:0W-D0:100W

Level (Output Level)

Adjust the output level.


Value: 0-127

29: DISTORTION—CHORUS

This effect connects distortion and chorus in series. The parameters are essentially the same as "26: OVERDRIVE \rightarrow CHORUS," with the exception of the following two.

OD Drive → Dist Drive (Specify the amount of distortion.)

OD Pan → Dist Pan (Specify the stereo location of the distortion sound.)




30: DISTORTION→FLANGER

This effect connects distortion and flanger in series. The parameters are essentially the same as in "27: OVERDRIVE → FLANGER," with the exception of the following two.

OD Drive → Dist Drive (Specify the amount of distortion.)

OD Pan → Dist Pan (Specify the stereo location of the distortion sound.)




31: DISTORTION→DELAY

This effect connects distortion and delay in series. The parameters are essentially the same as in "28: OVERDRIVE \rightarrow DELAY," with the exception of the following two.


OD Drive → Dist Drive (Specify the amount of distortion.)

OD Pan \rightarrow Dist Pan (Specify the stereo location of the distortion sound.)



32: ENHANCER→CHORUS

This effect connects an enhancer and a chorus in series.



Enhancer Sens (Enhancer Sensitivity) #1

Adjust the sensitivity of the enhancer.

Value: 0-127

Enhancer Mix (Enhancer Mix Level)

Adjust the ratio with which the overtones generated by the enhancer are combined with the direct sound.

Value: 0-127

Chorus Delay (Chorus Pre Delay Time)

Adjust the time delay from when the direct sound begins until the chorus sound is heard.

Value: 0.0-100 [ms]

Chorus Rate

Adjust the modulation speed of the chorus effect.

Value: 0.05-10.00 [Hz]

Chorus Depth

Adjust the modulation depth of the chorus effect.

Value: 0-127

Chorus Bal (Chorus Balance) #2

Adjust the volume balance between the enhancer sound that is sent through the chorus and the enhancer sound that is not sent through the chorus. With a setting of "D100:0W," only the enhancer sound will be output. With a setting of "D0:100W," only the enhancer sound that is sent through the chorus will be output.

Value: D100:0W-D0:100W


Level (Output Level)

Adjust the output level.

Value: 0-127

33: ENHANCER→FLANGER

This effect connects an enhancer and a flanger in series.



Enhancer Sens (Enhancer Sensitivity) #1

Adjust the sensitivity of the enhancer.

Value: 0-127

Enhancer Mix (Enhancer Mix Level)

Adjust the ratio with which the overtones generated by the enhancer are combined with the direct sound.

Value: 0-127

Flg Pre Dly (Flanger Pre Delay Time)

Adjust the time delay from when the direct sound begins until the flanger sound is heard.

Value: 0.0-100 [ms]

Flg Rate (Flanger Rate)

Adjust the modulation speed of the flanger effect.

Value: 0.05-10.00 [Hz]

Flg Depth (Flanger Depth)

Adjust the modulation depth of the flanger effect.

Value: 0-127

Flg Feedback (Flanger Feedback Level)

Adjust the proportion (%) of the flanger sound that is fed back into the effect. Negative (-) settings will invert the phase.

Value: -98- +98 [%]

Flg Balance (Flanger Balance) #2

Adjust the volume balance between the enhancer sound that is sent through the flanger and the enhancer sound that is not sent through the flanger. With a setting of "D100:0W," only the enhancer sound will be output. With a setting of "D0:100W," only the enhancer sound that is sent through the flanger will be output.

Value: D100:0W-D0:100W


Level (Output Level)

Adjust the output level.

Value: 0-127

34: ENHANCER→DELAY

This effect connects an enhancer and a delay in series.



Enhancer Sens (Enhancer Sensitivity) #1

Adjust the sensitivity of the enhancer.

Value: 0-127

Enhancer Mix (Enhancer Mix Level)

Adjust the ratio with which the overtones generated by the enhancer are combined with the direct sound.

Value: 0-127

Delay Time

Adjust the time delay from when the direct sound begins until the delay sound is heard.

Value: 0.0-500 [ms]

Delay Feedback (Delay Feedback Level)

Adjust the proportion (%) of the delay sound that is fed back into the delay input. Negative (-) settings will invert the phase.

Value: -98-+98 [%]

Delay HF Damp

Adjust the frequency above which delayed sound fed back to the delay input will be cut. If you do not want to cut the high frequencies of the delay feedback, set this parameter to BYPASS.

Value: 200-8000 [Hz], BYPASS

Delay Bal (Delay Balance) #2

Adjust the volume balance between the enhancer sound that is sent through the delay and the enhancer sound that is not sent through the delay. With a setting of "D100:0W," only the enhancer sound will be output. With a setting of "D0:100W," only the enhancer sound that is sent through the delay will be output.

Value: D100:0W-D0:100W


Level (Output Level)

Adjust the output level.

Value: 0-127

35: CHORUS→DELAY

This effect connects a chorus and a delay unit in series.



Chorus Delay (Chorus Pre Delay Time)

Adjust the time delay from when the direct sound begins until the chorus sound is heard.

Value: 0.0-100 [ms]

Chorus Rate

Adjust the modulation speed of the chorus effect.

Value: 0.05-10.00 [Hz]

Chorus Depth

Adjust the modulation depth of the chorus effect.

Value: 0-127

Chorus Bal (Chorus Balance) #1

Adjust the volume balance between the direct sound and the chorus sound. With a setting of "D100:0W," only the direct sound will be output. With a setting of "D0:100W," only the chorus sound will be output.

Value: D100:0W-D0:100W

Delay Time

Adjust the time delay from when the direct sound begins until the delay sound is heard.

Value: 0.0-500 [ms]

Delay Feedback (Delay Feedback Level)

Adjust the proportion (%) of the delay sound that is fed back into the delay input. Negative (-) settings will invert the phase.

Value: -98- +98 [%]

Delay HF Damp

Adjust the frequency above which delayed sound fed back to the delay input will be cut. If you do not want to cut the high frequencies of the feedback, set this parameter to BYPASS.

Value: 200-8000 [Hz], BYPASS

Delay Bal (Delay Balance) #2

Adjust the volume balance between the chorus sound that is sent through the delay and the chorus sound that is not sent through the delay. With a setting of "D100:0W," only the chorus sound will be output. With a setting of "D0:100W," only the chorus sound that is sent through the delay will be output.

Value: D100:0W-D0:100W


Level (Output Level)

Adjust the output level.

Value: 0-127

36: FLANGER→DELAY

This effect connects a flanger and a delay in series.



Flg Pre Delay (Flanger Pre Delay Time)

Adjust the time delay from when the direct sound begins until the flanger sound is heard.

Value: 0.0–100 [ms]

Flg Rate (Flanger Rate)

Adjust the modulation speed of the flanger effect.

Value: 0.05-10.00 [Hz]

Flg Depth (Flanger Depth)

Adjust the modulation depth of the flanger effect.

Value: 0-127

Flg Feedback (Flanger Feedback Level)

Adjust the proportion (%) of the flanger sound that is fed back into the effect. Negative (-) settings will invert the phase.

Value: -98- +98 [%]

Flg Balance (Flanger Balance) #1

Adjust the volume balance between the direct sound and the flanger sound. With a setting of "D100:0W," only the direct sound will be output. With a setting of "D0:100W," only the flanger sound will be output.

Value: D100:0W-D0:100W

Delay Time

Adjust the time delay from when the direct sound begins until the delay sound is heard.

Value: 0.0-500 [ms]

Delay Feedback (Delay Feedback Level)

Adjust the proportion (%) of the delay sound that is fed back into the delay input. Negative (-) settings will invert the phase.

Value: -98- +98 [%]

Delay HF Damp

Adjust the frequency above which delayed sound fed back to the delay input will be cut. If you do not want to cut the high frequencies of the delay feedback, set this parameter to BYPASS.

Value: 200-8000 [Hz], BYPASS

Delay Bal (Delay Balance) #2

Adjust the volume balance between the flanger sound that is sent through the delay and the flanger sound that is not sent through the delay. With a setting of "D100:0W," only the flanger sound will be output. With a setting of "D0:100W," only the flanger sound that is sent through the delay will be output.

Value: D100:0W-D0:100W


Level (Output Level)

Adjust the output level.

Value: 0-127

37: CHORUS→**FLANGER**

This effect connects a chorus and a flanger in series.



Cho Delay (Chorus Pre Delay Time)

Adjust the time delay from when the direct sound begins until the chorus sound is heard.

Value: 0.0-100 [ms]

Chorus Rate

Adjust the modulation speed of the chorus effect.

Value: 0.05-10.00 [Hz]

Chorus Depth

Adjust the modulation depth of the chorus effect.

Value: 0-127

Chorus Bal (Chorus Balance) #1

Adjust the volume balance between the direct sound and the chorus sound. With a setting of "D100:0W," only the direct sound will be output. With a setting of "D0:100W," only the chorus sound will be output.

Value: D100:0W-D0:100W

Flg Pre Delay (Flanger Pre Delay Time)

Adjust the time delay from when the direct sound begins until the flanger sound is heard.

Value: 0.0-100 [ms]

Flg Rate (Flanger Rate)

Adjust the modulation speed of the flanger effect.

Value: 0.05-10.00 [Hz]

Flg Depth (Flanger Depth)

Adjust the modulation depth of the flanger effect.

Value: 0-127

Flg Feedback (Flanger Feedback Level)

Adjust the proportion (%) of the flanger sound that is fed back into the effect. Negative (-) settings will invert the phase.

Value: -98- +98 [%]

Flg Balance (Flanger Balance) #2

Adjust the volume balance between the chorus sound and the chorus sound that is passed through the flanger. With a setting of "D100:0W," only the chorus sound will be output. With a setting of "D0:100W," only the chorus sound that passes through the flanger will be output.

Value: D100:0W-D0:100W


Level (Output Level)

Adjust the output level.

Value: 0-127


38: CHORUS/DELAY

This effect connects a chorus and a delay in parallel. The parameters are the same as for "35: CHORUS \rightarrow DELAY." However, the Delay Balance parameter adjusts the volume balance between the direct sound and the delay sound.




39: FLANGER/DELAY

This effect connects a flanger and a delay in parallel. The parameters are the same as for "36: FLANGER → DELAY." However, the Delay Balance parameter adjusts the volume balance between the direct sound and the delay sound.




40: CHORUS/FLANGER

This effect connects a chorus and a flanger in parallel. The parameters are the same as for "37: CHORUS → FLANGER." However, the Flanger Balance parameter adjusts the volume balance between the direct sound and the flanger sound.



41: LOFI

This effect intentionally degrades the audio quality to simulate a Lo-Fi sound. It is particularly effective on drums.



Bit Down

This setting lowers the audio quality. The audio quality will worsen as this setting is increased.

Value: 0-7

S-Rate Down (Sample-Rate Down)

This coarsens the output signal. The sound will become coarser as this setting is lowered.

Value: 32, 16, 8, 4 [kHz]

Post Gain

Adjusts the output signal. **Value:** 0, +6, +12, +18 [dB]

Low Gain

Adjust the gain of the low frequency range.

Value: -15-+15 [dB]

High Gain

Adjust the gain of the high frequency range.

Value: -15-+15 [dB]

Output

Specifies how the sound will be output. With a setting of "MONO," the output sound will be monaural.

Value: MONO, STEREO


Level (Output Level) #1 #2

Specifies the output volume from the Lo-Fi effect.

Value: 0-127

42: SLICER

By applying successive cuts to the sound, this effect turns a conventional sound into a sound that appears to be played as a backing phrase. This is especially effective when applied to sustain-type sounds.



Timing Pttern (Timing Pattern)

Select a pattern to specify the timing at which the sound will be cut.

Value: 1-34

Accent Pttern (Accent Pattern)

Specifies the location of the accents.

Value: 1-16

Accent Level

Adjusts the volume of the accents. As this setting is increased, the accent will be more pronounced.

Value: 0-127

Attack

Adjusts the attack speed of the sound. As this setting is increased, the attack will become faster.

Value: 1-10

Rate #1

This sets the period for the pattern.

Value: 0.05-10.00 [Hz], note-value symbols

Rate parameters can be set as a note-value of a specified tempo. In this case, specify the value of the desired note. The Tempo (p. 76) setting changes to the basic tempo.

Reset #2

This setting determines whether the pattern is reset (ON), or not (OFF) when sounds are played.

Value: OFF, ON

Level (Output Level)

Adjust the output level.

Setting Multi-Effects as On/Off for Individual Parts

You can specify whether to have multi-effects used (ON), or not used (OFF) for individual Parts only when Source is set to PERFORMANCE.

- **1.** Press [EDIT], getting the indicator to light.
- **2.** Use VALUE [-]/[+] to select "Performance Part."
- 3. Press [ENTER].
- **4.** Press PART []/[] to select the Part.
- **5.** Press the numeric key [6] several times to select "Switch."

PART 1 MFX:STEREO EQ Switch: OFF

- **6.** Press VALUE [-]/[+] to select the value (OFF, ON).
- 7. Press [EDIT].

The [EDIT] indicator goes out, and you are returned to the previous screen.

Making Chorus Settings

You can make different chorus settings for each individual Performance.

There are eight types of chorus. You can select any one of these. After selecting the Type, you can change the values for each of the parameters.

Furthermore, you can set the chorus depth (the amount applied) differently for each individual Part in a Performance.

Select the Type and Set Each Parameter

When you change the Chorus Type, eight different Chorus/ chorus parameters are changed automatically to the optimum values. Rather than setting the chorus parameters one by one, you can make the settings more easily by first setting the Chorus Type and then changing only the necessary parameters.

These settings can be made differently for each individual Performance.

- 1. Press [EDIT], getting the indicator to light.
- **2.** Use VALUE [-]/[+] to select "Tone/Drum/PFMCommon."

- **3.** Press [ENTER].
- **4.** Press the numeric key [7] several times to select the item you wish to set.

PERFORMANCE CHORUS
Type: CHORUS3

- * If you hold down [SHIFT] and press [7], you will return to the previous item.
- **5.** Use VALUE [-]/[+] to set the value.
- * If you wish to make settings for other Parts, repeat steps 4-5.
- **6.** Press [EDIT].

The [EDIT] indicator goes out, and you are returned to the previous screen.

Type (Chorus Type)

You can choose from 8 types of chorus.

Value:

CHORUS1-4:

General chorus settings. Adds

breadth and fullness to the sound.

FEEDBACK CHORUS: Chorus that produces a flanger-like

effect, creating a soft sound.

FLANGER:

This effect produces a rising and

falling sweep reminiscent of a jet

airplane.

SHORT DELAY:

This is a delay with a short delay

time

SHORT DELAY(FB):

This is a delay with a short delay time

and many repeats.

Pre-LPF (Chorus pre-low pass filter)

A low-pass filter can be applied to the sound coming into the chorus to cut the high frequency range. Higher values will cut more of the high frequencies, resulting in a more mellow chorus sound.

Value: 0-7

Level (Chorus Level)

Sets the amount of the chorus sound.

Value: 0-127

Feedback (Chorus Feedback Level)

Sets the level at which the chorus sound is re-input (fed back) into the chorus. By using feedback, a denser chorus sound can be created. Higher values result in a greater feedback level.

Delay (Chorus Delay Time)

Sets the delay time of the chorus effect.

Value: 0-127

Rate (Chorus Rate)

Sets the speed (frequency) at which the chorus sound is modulated. Higher values result in faster modulation.

Value: 0-127

Depth (Chorus Depth)

Sets the depth at which the chorus sound is modulated. Higher values result in deeper modulation.

Value: 0-127

Send levi to Rev (Chorus send level to reverb)

Sets the amount of chorus sound that will be sent to the reverb. Higher values result in more sound being sent.

Value: 0-127

Setting the Chorus Depth for Each Part

Send Level (Chorus send level)

Sets the amount of chorus effect applied in each Part.

Value: 0-127

- 1. Press [EDIT], getting the indicator to light.
- **2.** Use VALUE [-]/[+] to select "Performance Part."
- 3. Press [ENTER].
- **4.** Press PART [**◄**]/[**▶**] to select the Part.
- Press the numeric key [7] several times to select "Send Level"

PART 1 CHORUS Send Level: 0

- **6.** Use VALUE [-]/[+] to select the value (0–127).
- 7. Press [EDIT].

The [EDIT] indicator goes out, and you are returned to the previous screen.

Making Reverb Settings

You can make different Reverb settings for each individual Performance.

There are eight types of reverb. You can select any one of these. After selecting the Type, you can change the values for each of the parameters.

Furthermore, you can make different reverb depth (the amount applied) settings for each individual Part in a Performance.

Selecting the Type and Setting Each Parameter

When you change the Reverb Type, six different reverb parameters, including Reverb character, are changed automatically to the optimum values. Rather than setting the reverb parameters one by one, you can make the settings more easily by first setting the Reverb Type and then changing only the necessary parameters.

These settings can be made differently for each individual Performance.

- 1. Press [EDIT], getting the indicator to light.
- **2.** Use VALUE [-]/[+] to select "Tone/Drum/PFMCommon."
- 3. Press [ENTER].
- **4.** Press the numeric key [8] several times to select the item you wish to set.

| PERFORMANCE | REVERB |
|-------------|--------|
| Type: | HALL2 |

- * If you hold down [SHIFT] and press [8], you will return to the previous item.
- **5.** Use VALUE [-]/[+] to set the value.
 - * If you wish to make settings for other Parts, repeat steps 4-5.
- 6. Press [EDIT].

The [EDIT] indicator goes out, and you are returned to the previous screen.

Chapter 6

Type (Reverb Type)

You can choose from 8 types of reverb.

Value:

ROOM1–3: Simulates the reverberation of room

interiors. It produces a well-defined

and spacious reverberation.

HALL1, 2: Simulates the reverberation exhibited

by halls. They provide a deeper

reverberation than the Room reverbs.

PLATE: Simulates a plate reverb unit (a type of

artificial reverb that utilized a metal

plate).

DELAY: A standard delay, that produces echo

effects.

PANNING DELAY: This is a special delay in which the

delayed sound alternates between left and right. It is effective when you are

listening in stereo.

Character (Reverb Character)

Selects the type of reverb. 0–5 are reverb effects, and 6 and 7 are delay effects.

Value: 0-7

Pre-LPF (Reverb pre-low pass filter)

A low pass filter can be applied to the sound coming into the reverb to cut the high frequency range. Higher values will cut more of the high frequencies, resulting in a more mellow reverberation.

Value: 0-7

Level (Reverb Level)

Sets the amount of the reverberant sound. Higher values result in louder reverberation.

Value: 0-127

Time (Reverb Time)

Sets the time over which the reverberation will continue. Higher values result in longer reverberation.

Value: 0-127

Delay Feedback (Reverb Delay Feedback)

This parameter is available when the Reverb Character (Character) is set to 6, 7 or the Reverb Type (Type) is set to Delay or Panning Delay. It sets the way in which delays repeat. Higher values result in more delay repeats.

Value: 0-127

Setting the Reverb Depth of Each Individual Part

Send Level (Reverb send level)

Sets the amount of the reverb used in each Part.

Value: 0-127

- **1.** Press [EDIT], getting the indicator to light.
- 2. Use VALUE [-]/[+] to select "Performance Part."
- **3.** Press [ENTER].
- **4.** Press PART [**◄**]/[**▶**] to select the Part.
- **5.** Press the numeric key [8] several times to select "Send Level"

PART 1 REVERB Send Level: 40

- **6.** Use VALUE [-]/[+] to select the value (0-127).
- 7. Press [EDIT].

The [EDIT] indicator goes out, and you are returned to the previous screen.

Chapter 7. Creating your original Tone or Drum Set

Creating a Tone

You can modify the settings of a Preset Tone to create your own original Tone. A Tone that you create can be stored as a User Tone.

Tones feature ten different parameters, plus multi-effects parameters. To create your own Tone, you will modify these parameters.

- * Refer to the instructions for making the Tone multi-effects settings (p. 81).
- * You can use the knobs to change parameters other than the Tone Name in real time (p. 74).

Tone Parameters That Can Be Set

[1] TONE

Tone Name

You can change the name of the tone which you created. The number of characters in names is set at twelve.

Value: space, A--Z, a--z, 0--9,!"#\$%&'()*+,-./:;<=>
?@[\\]^_\{|\}

LFO Rate

Adjusts the modulation rate, or speed, of the LFO.

Value: -64-+63

LFO Depth

Specifies the depth of LFO.

Value: -64-+63

LFO Delay

This setting allows you to adjust the interval that is to pass from the moment a key is pressed until the moment that LFO begins to take effect.

Value: -64-+63

LFO Filter Sw (LFO filter switch)

This determines whether the LFO changes the filter cutoff frequency (ON) or the pitch (OFF). The parameter value is changed when FILTER [LFO ON/OFF] is pressed.

Value: OFF, ON

Wah Effect and Vibrato Effect

Changing the filter cutoff frequency with the LFO produces the "wah effect," and by changing the pitch with the LFO, you get what is called the "vibrato effect."

Filter Cutoff

Sets the frequency at which harmonics will be cut. This changes the brightness of the sound.

Value: -64-+63

Filter Resonance

Provides an adjustment for the amount of emphasis to be placed on the harmonics in the vicinity of the Cutoff Frequency. The sound takes on a peculiar effect.

Value: -64-+63

Envelope Attack (Envelope attack time)

Adjusts the time it takes for the initial portion of a sound (the 'attack') to be heard after a key is pressed.

Value: -64-+63

Envelope Decay (Envelope decay time)


Adjusts the time it will take for the sound to reach the "Sustain Level." The Sustain Level is the point at which most of the volume/cut-off frequency modifications have stabilized.

Value: -64-+63

Envelope Release (Envelope release time)

Adjusts the time it takes for the sound to fade away after a key is released.


Value: -64-+63



Chapter 7


Creating a Tone

- 1. Select the Tone you want to edit.
 - * When Key Mode is set to Split or Dual, press PART [◀]/
 [▶] to select the Part with the Tone you want to edit.



The figure above shows an example where the Upper Part is selected.

- **2.** Press [EDIT], getting the indicator to light.
- **3.** Use VALUE [-]/[+] to select "Tone/Drum/PFMCommon."
- 4. Press [ENTER].
- **5.** Press the numeric key [1] several times to select the item you wish to set.



- * If you hold down [SHIFT] and press [1], you will return to the previous item.
- **6.** Press [**◄**]/[**▶**] to move the cursor to the name's first character position.
 - * Note that when screens other than the Tone Name screen are displayed, pressing PART [◀]/[▶] switches the Part.
- **7.** Use VALUE [-]/[+] to set the value.
 - * If you wish to make settings for other Parts, repeat steps 5-7.
- 8. Press [EDIT].

The [EDIT] indicator goes out, and you are returned to the previous screen.

Creating a Drum Set

You can create your own Drum Set by editing the percussion instrument sounds in one of the Preset Drum Sets. A Drum Set that you create can be saved as a User Drum Set.

Five parameters (aspects) of a Drum Set can be modified. To create your own Drum Set, you will modify these parameters.

Drum Set Parameters That Can Be Set

[2] Drum (DRUMS)

DrumSet Name (Drum set name)

You can change the name of the drum set which you created. The number of characters in names is set at twelve.

Value: space, A--Z, a--z, 0--9,!"#\$%&'()*+,-./:;<=>
?@[\frac{1}{2}]^_\[\]

Pitch

Adjusts the pitch of the percussive sound in semitone steps.

Value: -60- +67

Level

Specifies the volume of the percussion instrument sound.

Value: 0-127

Pan

Allows you to set the panning (localization of sound image) for each sound (obtained only with a stereo output). With an increase in the value for L, more of the sound will be heard as coming from the left side. Similarly, more of the sound will originate at the right if the value of R is increased. When set to RANDOM, you obtain a specialized effect whereby the sound randomly moves left and right with each key stroke.

Value: RANDOM, L63-0-63R


Reverb Depth

Adjusts the depth of reverb.

 $\textbf{Value:}\ 0\text{--}127$


Creating a Drum Set

- 1. Select the Drum Set you wish to modify.
- * When Key Mode is set to Split or Dual, press PART [◀]/
 [▶] to select the Part with the Drum Set you want to edit.



The figure above shows an example where the Lower Part is selected.

- **2.** Press [EDIT], getting the indicator to light.
- **3.** Use VALUE [-]/[+] to select "Tone/Drum/PFMCommon."
- **4.** Press [ENTER].
- **5.** Press the numeric key [2] several times to select the item you wish to set.
- * If you hold down [SHIFT] and press [2], you will return to the previous item.
- **6.** Except for when you are naming the Drum Set, press a key to select the percussion instrument you want to edit.



- * If you wish to modify the percussion sound of a key which is outside the range of the keyboard, use the Transpose function (p. 48) to shift the range of the keyboard.
- **7.** Press [**◄**]/[**▶**] to move the cursor to the name's first character position.
 - * Note that when screens other than the Drum Set Name screen are displayed, pressing PART [◀]/[▶] switches the Part
- **8.** Use VALUE [-]/[+] to set the value.
 - * If you wish to make settings for other Parts, repeat steps 5–8.
- 9. Press [EDIT].

The [EDIT] indicator goes out, and you are returned to the previous screen.

hapter 8

Chapter 8. Saving Your Settings

Saving Tone / Drum Set / Performance

When the Tone settings are changed, the "." in the lower right of the LED display lights up, indicating that the settings for the selected Tone, Drum Set, or Performance have been changed.

When Tone settings are changed



| TONE: | | RS | Piano |
|-------|----|----|----------|
| Part | _1 | | User:PNO |

When Drum Set settings are changed



| DRUM1 | п п | RS | Por | Ki | t 1 |
|-------|--------|----|-----|------|-----|
| Part. | 10 | | Use | †" # | DRM |

When Performance settings are changed



| PERFORM: for | Tone |
|--------------|----------|
| Part 1 | User:001 |

If you select a different Tone, Drum Set, or Performance while the dot is lit, the current settings are deleted. If there are any settings you want to retain, save them to the User Memory.

* You can also save Tone, Drum Set, and Performance settings to an external sequencer (p. 115).

Assigning a name

Changing the name before saving is a convenient way to allow you to distinguish different settings.

- **1.** Select the Tone, Drum Set or Performance whose name you want to change (p. 23, 26, 29, 30, 56).
- * When changing Tone or Drum Set names, if Key Mode is set to Split or Dual, press PART [◀]/[▶] to select the Part whose Tone or Drum Set is to be edited.

Example: Upper can be edited

TONE: RS Piano L:10 (🏲 1 User:001

- **2.** Press [EDIT], getting the indicator to light.
- **3.** Use VALUE [-]/[+] to select "Tone/Drum/PFMCommon."
- 4. Press [ENTER].

5. When a Tone is being edited, press numeric key [1] several times to select "Tone Name." When a Drum Set is being edited, press numeric key [2] several times to select "DrumSet Name." When a Performance is being edited, press numeric key [3] to select "PERFORMANCE Name."

Tone Name [4PART)] PNO:RS Piano

DrumSet Name[4PART) RS Pop Kit 1

PERFORMANCE [4PART*]
Name: BasicPerform

- * By holding down [SHIFT] and pressing [1] or [2], you will return to the previous item.
- **6.** Press [**◄**]/[**▶**] to move the cursor to the name's first character position.
- **7.** Use VALUE [-]/[+] to set the value.

The following characters are available.

Value: space, A--Z, a--z, 0--9,!"#\$%&'()*+,-./:;< =>?@[\tilde{Y}]^_`{||}

- **8.** Repeat steps 6–7 to input the name.
- **9.** Press [EDIT].

The [EDIT] indicator goes out, and you are returned to the previous screen.

When inputting characters, you can perform the following operations conveniently by pressing FAVORITE PERFORM BANK [1]–[8].

- [1]: Displays a "." at the cursor position.
- [2]: Displays a space at the cursor position.
- [3]: Displays an "A" at the cursor position.
- [4]: Displays an "a" at the cursor position.
- [5]: Displays a "0" at the cursor position.
- [6]: Converts capital and lowercase characters.
- [7]: Inserts a space at the cursor position.
- [8]: Deletes a character at the cursor position and moves the following characters to the left.

Chapter 8. Saving Your Settings

How to Save

* When saving a Tone or Drum Set when Key Mode is set to Split or Dual, the Tone or Drum Set assigned to the selected Part is saved.

Notes



When data is being written to the User Memory, the message "KEEP POWER ON!" appears in the display; be sure not to turn off the power while this message is displayed.

If the power is turned off or interrupted while data is being written to memory, the internal data may become corrupted and you may not be able to turn the power back on. If you have confirmed that the internal data has been lost, or if a similar problem exists, consult the retailer from whom you purchased the instrument, or the nearest Roland Service Center. Note, however, that Roland assumes no liability, including compensation, for consequences arising from any loss of data.

- * We recommend that you use the Bulk Dump operation (p. 115) to save important data to an external sequencer.
- **1.** Press [UTILITY], getting the indicator to light.
- **2.** Press VALUE [-]/[+] to select "Write Tone/Drum" or "Write Performance."
- * When saving Tones or Drum Sets, select "Write Tone/Drum." When saving Performances, select "Write Performance."
- 3. Press [ENTER].

When saving Tones

WRITE TONE [ENTER] Usr:001:RS Piano

When saving Drum Sets

WRITE DRUM [ENTER] Usr:001:RS Pop Kit 1

When saving Performances

WRITE PERFORMCENTER]
Usr:001:BasicPerform

4. Press the numeric keys ([1]-[0]) to specify the save destination number.

Tone: 001–128
Drum set: 001, 002
Performance: 001–128

- * If you make a mistake, press [EXIT] and specify the number once again.
- * You can also specify the number by pressing VALUE [-]/[+]. In this case, there is no need to press [ENTER] in step 5.
- **5.** Press [ENTER] to finalize the number.
- **6.** Press [ENTER] once again to execute the Save operation. After the Save operation is finished, the display will indicate "Completed."

The [UTILITY] indicator goes out, and you are returned to the previous screen.

* If you change a Tone's/Drum Set's settings without having saved the Tone/Drum Set, and then attempt to save the Performance, the following message appears in the display. If this message does appear, save the Tone/Drum Set with the changed settings before saving the Performance.

Edited Tone/Drum Set Exists. Write Them.

Chapter 8

Saving settings on an external sequencer (Bulk Dump)

The act of transmitting Tone, Drum Set, Performance or System settings to an external MIDI device is called a "Bulk Dump." You can perform a bulk dump when two RS-5/9s are connected to each other, or when you wish to store Tone, Drum Set, Performance or System settings on an external MIDI device as a safety backup of your RS-5/9 data.

Setting the Device ID Number

When carrying out Bulk Dump, set the Device ID number. When shipped from the factory, this is set to "17." Normally, there is no need to change this number when transmitting data to a sequencer or other such device. If you do want to change it, use the following procedure to make the settings.

- * If you want to make settings simultaneously for two RS-5/9s, you must set the Device ID number of each to the same value.
- 1. Press [EDIT], getting the indicator to light.
- **2.** Use VALUE [-]/[+] to select "System Setup."
- 3. Press [ENTER].
- **4.** Press the numeric key [4] several times to select "Device ID#."

| SYSTEM | | MIDI |
|------------------|------|------|
| SYSTEM Device | ID#: | 17 |

- * If you hold down [SHIFT] and press [4], you will return to the previous item.
- **5.** Press VALUE [-]/[+] to select the value (17 to 32).
- 6. Press [EDIT].

The [EDIT] indicator goes out, and you are returned to the previous screen.

What kind of data is Bulk Dump?

This is data of the type called "Exclusive messages."

Bulk dump procedure

Types of bulk dump

Temporary: Settings of temporary area
User Tone: Settings of all User Tones
User Drum Set: Settings of all User Drum Sets
User Performance: Settings of all User Performances

System Setup: Settings of System Setup

However, the following system setup parameters will not be transmitted via bulk dump.

- GM System ON Sw
- GM2 System ON Sw
- Rx SysEx Sw
- Device ID#
- LCD Contrast

All: All five of the above settings

- Use a MIDI cable to connect the RS-5/9's MIDI OUT connector to the MIDI IN connector of the external sequencer.
- **2.** Press [UTILITY], getting the indicator to light.
- **3.** Use VALUE [-]/[+] to select "Bulk Dump."
- 4. Press [ENTER].
- **5.** Use the VALUE [-]/[+] to select the types of Bulk Dump.

BULK DUMP [ENTER] Temporary

- **6.** Put the external sequencer in record mode.
- **7.** Press [ENTER] to transmit the settings.

 The message "Transmitting..." appears in the display during transmission of the data.
 - * Do not press any key on the keyboard while Bulk Dump is in progress. Pressing a key sends Note messages from the MIDI OUT connector. To cancel the Bulk Dump, press [EXIT].

After the transmitting is finished, the display will indicate "Completed."

The [UTILITY] indicator goes out, and you are returned to the previous screen.

8. Stop the external sequencer.

Setting the System Exclusive Receive Switch

When returning saved settings to the RS-5/9, set the Exclusive Receive switch to ON. With the factory settings, this will be "ON."

- 1. Press [EDIT], getting the indicator to light.
- **2.** Use VALUE [-]/[+] to select "System Setup."
- 3. Press [ENTER].
- **4.** Press the numeric key [4] several times to select "System Exclusive."

| SYSTEM | MIDI | |
|--------|------------|----|
| System | Exclusive: | ON |

- * If you hold down [SHIFT] and press [4], you will return to the previous item.
- **5.** Use VALUE [-]/[+] to set "ON."
- 6. Press [EDIT].

The [EDIT] indicator goes out, and you are returned to the previous screen.

Restoring saved settings to the RS-5/9

* Be aware that when you restore data to the RS-5/9, the data in the RS-5/9 will be overwritten and lost.

Notes



When data is being written to the User Memory, the message "KEEP POWER ON!" appears in the display; be sure not to turn off the power while this message is displayed.

If the power is turned off or interrupted while data is being written to memory, the internal data may become corrupted, and you may not be able to turn the power back on. If you have confirmed that internal data has been lost, or if a similar problem exists, consult your Roland dealer or Roland Service. Note, however, that Roland assumes no liability, including compensation, for consequences arising from loss of data.

- Use a MIDI cable to connect the MIDI OUT connector of the external sequencer to the MIDI IN connector of the RS-5/9.
- Set the device ID number to the same setting as when you performed the bulk dump.
 System Setup Numeric Key [4]: Device ID (p. 115)
- **3.** Turn on the exclusive receive switch.

 System Setup Numeric Key [4]: System Exclusive (refer to the previous section)
- **4.** Transmit (play back) the data from the external sequencer.
 - When the transmitting is finished, you are returned to the previous screen.
- * Play back the external sequencer at the same tempo you used when performing the bulk dump. If you use a faster tempo, the data may not be restored correctly.

Chapter 9. Restoring the Original Settings

Restoring the Factory Settings (Factory Reset)

You can restore all User Performance, User Tone, User Drum Set and System Setup settings to the factory condition.

* If the RS-5/9's internal memory already contains important data that you have created, this operation will cause all of this data to be lost. Save data that you want to retain by sending the data to an external sequencer (p. 115).

Notes



When data is being written to the User Memory, the message "KEEP POWER ON!" appears in the display; be sure not to turn off the power while this message is being displayed.

If the power is turned off or interrupted while data is being written to memory, the internal data may become corrupted, and you may not be able to turn the power back on. If you have confirmed that internal data has been lost, or if a similar problem exists, consult your Roland dealer or Roland Service. Note, however, that Roland assumes no liability, including compensation, for consequences arising from loss of data.

Five types of Factory Reset are provided depending on the application.

User Tone: Settings of all User Tones

User Drum Set: Settings of all User Drum Sets

User Performance: Settings of all User Performances

System Setup: Settings of System Setup

All: All four of the above settings

1. Press [UTILITY], getting the indicator to light.

2. Use VALUE [-]/[+] to select "Factory Reset."

3. Press [ENTER].

4. Use the VALUE [-]/[+] to select the types of Factory Reset.

FACTORY [ENTER]

5. Press [ENTER].

A confirmation message appears.

Are you sure? YES=[ENTER]NO=[EXIT]

6. Press [ENTER] to execute the Factory Reset operation. After the Factory Reset operation is finished, the display will indicate "Completed."

The [UTILITY] indicator goes out, and you are returned to the previous screen.

Restoring GM/GM2 Basic Settings (GM/GM2 SYSTEM ON)

If no GM or GM2 System On message is included at the very beginning of a song you have created for use with a GM or GM2 sound generator, you must restore the RS-5/9's sound generator to the GM/GM2 basic settings before playback.

Additionally, you must also restore the sound generator settings to the GM or GM2 initial settings when creating songs for use with GM or GM2 sound generators.

- 1. Press [UTILITY], getting the indicator to light.
- **2.** Use VALUE [-]/[+] to select "Initialize."
- 3. Press [ENTER].
- **4.** Press VALUE [-]/[+] to select "GM System ON" or "GM2 System ON."

5. Press [ENTER] to execute the Initialize operation.

After the Initialize operation is finished, the display will indicate "Completed."

The [UTILITY] indicator will go dark.

When the RS-5/9 is functioning as a GM/GM2 system compatible sound module, the Performance Select display will be as follows.



PERFORM:Init Perform Part 1 GM:---

* To return to the normal settings mode after being set to the GM/GM2 basic settings, you can either switch Performances, or send a GM System Off from the external sound generator to the RS-5/9.

Chapter 10. Performing With An External MIDI Device


About MIDI

MIDI (Musical Instruments Digital Interface) is a standard specification that allows musical data to be exchanged between electronic musical instruments and computers. MIDI With a MIDI cable connecting MIDI devices that are equipped with MIDI connectors, you can play multiple instruments with a single keyboard, have multiple MIDI instruments perform in ensemble, program the settings to change automatically to match the performance as the song progresses, and more.

If you mainly use the RS-5/9 as a standalone keyboard instrument, you may really not need to know much at all about MIDI. However, the following MIDI-related information is provided so you can play the RS-5/9 using an external MIDI device, or master other advanced techniques.

MIDI connectors

The RS-5/9 has the following three types of MIDI connectors.



MIDI IN Connector

Performance messages from an external MIDI device are received here. The RS-5/9 that receives MIDI messages can output sounds, exchange tones, and perform other operations.

MIDI OUT Connector


These connectors transmit MIDI messages to external MIDI devices. The RS-5/9's MIDI OUT connector is used for sending the performance data of the keyboard controller section as well as data used for saving various settings (Bulk Dump; p. 115).

MIDI THRU Connector

MIDI messages received at MIDI IN connector are retransmitted without change from this connector to an external MIDI device. Use this in situations such as when you use multiple MIDI devices simultaneously.

MIDI Channels and Multi-timbral Sound Generators


MIDI transmits many types of data over a single MIDI cable. This is made possible by MIDI channels. MIDI channels allow messages intended for a given instrument to be distinguished from messages intended for another instrument. In some ways, MIDI channels are similar to television channels. By changing the channel on a TV receiver you can view the programs of different stations. This is because the television set has thus been directed to selectively display only the information being transmitted by a particular station. In the same way, MIDI also allows a device to select the information intended for that device out of the variety of information that is being transmitted to it.



MIDI uses sixteen channels, numbered 1–16. Set the receiving device so that it will receive only the channel that it needs to receive.

Example:

Set the RS-5/9 to send Channel 1 and Channel 2, then set sound module A to receive only Channel 1 and sound module B only Channel 2. With this setup, you can get an ensemble performance, with, for example, a guitar sound from sound module A and bass from sound module B.



When used as a sound module, the RS-5/9 can receive on up to sixteen MIDI channels. Sound modules like the RS-5/9 which can receive multiple MIDI channels simultaneously to play different sounds on each channel are called "multitimbral sound modules."

Chapter 10

MIDI messages used by the RS-5/9

MIDI uses various types of message to transmit a wide variety of information. MIDI messages are broadly divided into two different categories, those handled through individual MIDI channels (Channel messages), and messages that are not related to separate channels (System messages). The RS-5/9 mainly uses the following MIDI messages.

Channel messages

These are messages used for relating what is happening in a Performance. These comprise the bulk of MIDI messages.

Note On


This message is sent when a key is pressed. A Note-on message contains the following 3 types of information.

Note-on: A note has been played. Note number: which note was played

Velocity: The amount of force (velocity) used when the

note was played

The Note Numbers fall within the range of 0–127, with middle C (C4) as number 60.



Note number

Note Off

This message is sent when a key is released. When a Note-off message is received, that note will be turned off. A Note-off message contains the following 3 types of information.

Note-off: a note was released Note number: which note was released

Velocity: The force of the pull (velocity) used when the

note was released

Pitch Bend Change

This message transmits whatever motion is made by the Pitch Bend lever.

Aftertouch

These messages indicates how strongly the keyboard was pressed after playing a note. There are two types of Aftertouch message; Channel Aftertouch which applies to an entire channel, and Polyphonic Aftertouch which applies to an individual note.

The RS-5/9 cannot transmit Aftertouch messages when its keys are pressed. Instead, you can do this by transmitting the Aftertouch assigned to the Modulation lever, a pedal, or a knob.

Program Change

This message changes the instrument sound. You can switch Tones and Drums sets on the RS-5/9 using program numbers 1–128 (p. 121, 123).

Control Change

These are messages used for increasing performance expression. By assigning Modulation (CC# (Controller Number) 1), Pan (CC#10), Expression (CC#11), and other Control Change messages to the Modulation lever, pedals, and knobs, you can then use these controls to change Performances (p. 71).

Bank Select (CC#0, CC#32) switch Tones and Drum Sets, so these are used in combination with Program Change messages (p. 121, 123).

System messages

This category includes exclusive messages, messages used for synchronization, and messages that keep a MIDI system running correctly.

Exclusive messages

Exclusive messages are messages used for exchanging Tones and other set kinds of data between compatible devices from the same manufacturer.

If messages exchanged using MIDI were limited only to those conforming to the common MIDI standard, it would not be possible to transmit messages particular to one manufacturer or messages fixed for a certain device. Therefore, with a format having been determined by each manufacturer, a variety of different messages can then be exchanged.

With the RS-5/9, you can use Exclusive messages to store Tone settings and other data to sequencers (p. 115).

About MIDI Implementation Charts


Although a variety of messages for performances can be handled using MIDI, depending on the functions of the connected device, the messages that can be sent and received may differ. To see which types of MIDI message a device can transmit and receive, refer to the MIDI Implementation Chart that is included in the manual of each device. Messages which are marked by a circle in the charts of both devices can be transmitted between the two devices.

Playing Sounds from an External MIDI Sound Generator With the RS-5/9


By connecting the RS-5/9 to an external MIDI device with a MIDI cable and setting the channels, you can then produce sounds from the external MIDI device's sound generator by playing the RS-5/9's keyboard. You can switch the external MIDI sound generator's Tones from the RS-5/9 as well.

Connecting to External MIDI Sound Generators

Example 1: Connecting to one external MIDI sound generator




Example 2: Connecting to two external MIDI sound generators



* Messages received at the MIDI IN connector are output from the MIDI THRU connector unchanged.

Example 3: Connecting to three or more external MIDI sound generators



- * If you "daisy-chain" three or more MIDI devices using IN -> THRU -> IN -> THRU ..., the MIDI signal may become garbled, and data errors may occur. In such cases, use a MIDI Thru Box. MIDI Thru Boxes are devices that allow a single stream of MIDI data to be sent to a large number of MIDI devices without causing data errors.
- **1.** Before starting the connection procedure, make sure that the power to all devices has been turned off.
- **2.** After reading "Connecting the RS-5/9 to external equipment" (p. 14), connect an audio device/system or headphones.
- **3.** Connect the external MIDI sound device with the MIDI cable as shown in the figure below.
- **4.** As described in "Turning On the Power" (p. 15), turn on the power of each device.

Set the Keyboard Transmit Channel

When you have finished connecting the external MIDI device, match the keyboard's Transmit channel and the Receive channel for each of the external MIDI sound generator's Parts.

Settings

PART: Transmits performance data over the same channel as the performing Part's Receive channel (p. 122).

1–16: RS-5/9 performance data is sent over a selected channel.

Ordinarily, this is set to PART. Particularly when Key Mode is set to Split or Dual, the performance data from the Upper and Lower Parts are sent over separate channels. Therefore, you can control two external MIDI sound generators.

You might want to set these to Channels 1–16 in situations such as when you want to switch the RS-5/9's Parts as you play.

Chapter 1

Different keyboard Transmit channel settings can be made for each individual Performance.

- 1. Press [EDIT], getting the indicator to light.
- **2.** Use VALUE [-]/[+] to select "Tone/Drum/PFMCommon."
- 3. Press [ENTER].
- **4.** Press the numeric key [4] several times to select "Channel."

PERFORMANCE MIDI Tx Channel: PART

- **5.** Press VALUE [-]/[+] to select the value (1–16, PART).
- **6.** Press [EDIT].

The [EDIT] indicator goes out, and you are returned to the previous screen.

When the RS-5/9's keyboard is played, sounds are simultaneously played by the RS-5/9 and the external MIDI sound generator.

- * For instructions on setting each of the external MIDI sound generator's Part's Receive channel, refer to the owner's manual for each device.
- * If you want sounds to be played only by the external MIDI sound generator, set the Local control to OFF (p. 124).

Selecting sounds on another device using the RS-5/9

When you have finished making the connections and setting the channels, try switching the external MIDI sound generator's Tones from the RS-5/9.

When you switch the Tone or Drum Set with the buttons on the RS-5/9's panel, Bank Select (Controller Number 0, 32) and Program Change messages for the selected Tone or Drum Set are sent from the MIDI OUT connector. The Tone played by the external MIDI sound generator switches to the Tone corresponding to these MIDI messages.

If the RS-5/9 is connected to a GM2-compatible sound generator, then when choosing a GM2 format Tone, select a Preset Tone 257–512 or Drum Set 12–20.

With Preset Tones 1–128 and User Tones 1–128, the Program numbers output are the same as those for the corresponding Tones. If you want to switch the Tones with attention to the Program number, first set the Bank Select Transmit Switch to OFF (refer to the information below), and then you can select your Tones.

Tone switching messages are sent through the keyboard's Transmit channels (refer to the information below) in the following sequence.

- 1. Bank Select MSB (controller number 0) (BnH 00H mmH)
- 2. Bank Select LSB (controller number 32) (BnH 20H mmH)
- **3.** Program Change (CnH ppH)

n: MIDI channel number

mm, ll: Bank number

pp: Program number

- * MIDI messages are not transmitted when you select a different Tone or Drum Set by moving to a different Part.
- * These messages for sound selection are not transmitted when you select a Performance.
- * For Bank numbers and Program numbers sent with the selection of each Tone and Drum Set, refer to (p. 123), "Tone List" (p. 149, 150) and "Drum Set List" (p. 151–154).

Transmitting Only Program Numbers

If the external MIDI sound generator receives a Bank number for which no Tone has been assigned, an alternate Tone may be selected, or in some cases, there may be no sound played.

To ensure the proper Tone is selected, you may be better off selecting the Tone group for the external MIDI sound generator first, and then transmitting only the Program number. You can then switch tones within the same group. To transmit only the Program number, set the Bank Select Transmit Switch to OFF.

The Bank Select Transmit Switch affects the entire RS-5/9 (i.e., is a System setting). This setting remains stored in memory even while the power is off.

- 1. Press [EDIT], getting the indicator to light.
- **2.** Use VALUE [-]/[+] to select "System Setup."
- **3.** Press [ENTER].
- **4.** Press the numeric key [4] several times to select "Bank Select."

SYSTEM MIDI Tx Bank Select: ON


- * If you hold down [SHIFT] and press [4], you will return to the previous item.
- **5.** Use VALUE [-]/[+] to set "OFF."
- **6.** Press [EDIT].

The [EDIT] indicator goes out, and you are returned to the previous screen.

Playing the RS-5/9's Sound Generator from an External MIDI Device

Next, try playing the RS-5/9 from an external MIDI device.

Connecting External MIDI Device



- **1.** Before starting the connection procedure, make sure that the power to all devices has been turned off.
- **2.** After reading "Connecting the RS-5/9 to external equipment" (p. 14), connect an audio device/system or headphones.
- **3.** Connect the external MIDI sound generator with the MIDI cable as shown in the figure below.
- **4.** As described in "Turning On the Power" (p. 15), turn on the power of each device.

Setting the Receive Channel and Tone Change Receive Switch

When you have finished connecting the external MIDI device, match each Part's Receive channel with the external MIDI device's Transmit channel.

Also, to enable Tones to be switched from the external MIDI device, set the Tone Change Receive Switch for each Part to ON. Factory settings have this set to ON for all Parts.

Channel (Receive Channel)

If the Receive Channel is set to a value of 1–16, that Part will receive musical data on the specified channel.

Value: 1-16, OFF

* Since performance data cannot be received when the Receive channel is set to OFF, no sound is produced.

Tone Change (Tone Change Receive Switch)

Value: OFF, ON

* Tones cannot be switched from an external MIDI device if the Tone Change Receive Switch is set to OFF.

Different Receive Channel and Tone Change Receive Switch settings can be made for each individual Part in a Performance.

- 1. Press [EDIT], getting the indicator to light.
- 2. Use VALUE [-]/[+] to select "Performance Part."
- 3. Press [ENTER].
- **4.** Press PART [**◄**]/[**▶**] to select Part.
 - * When Key Mode (p. 34) is set to Split or Dual, you can select only the Upper Part and the Lower Part.
- **5.** Press numeric key [4] several times to select the parameter to be set.

| PART 1 Channel: | MIDI | R× 1 |
|------------------------|------|----------|
| PART 1 Tone Change: | MIDI | R× ON |

- * If you hold down [SHIFT] and press [4], you will return to the previous item.
- **6.** Use VALUE [-]/[+] to set the value.
- 7. Press [EDIT].

The [EDIT] indicator goes out, and you are returned to the previous screen.

* For instructions on setting the external MIDI device's Transmit channel, refer to the owner's manual for that device.

Selecting RS-5/9 Sounds from an External MIDI Device

Transmitting Bank Select (Controller Number 0, 32) and Program Change messages from the external MIDI device to the RS-5/9 allows you to switch Tones and Drum Sets.

- **1.** Transmit a value for the Bank Select MSB (controller number 0) (BnH 00H mmH) message to the RS-5/9.
- **2.** Transmit a value for the Bank Select LSB (controller number 32) (BnH 20H mmH) message to the RS-5/9.
- **3.** Transmit a Program Change (CnH ppH) to the RS-5/9.
- * With Bank Selects and Program Changes, you cannot switch Performances using an external MIDI device connected to the RS-5/9.

Bank Number/Program Number Correspondence Table

The MIDI messages transmitted by the external MIDI device will be received by the RS-5/9 to select Tones/Drum Sets as shown in the following table.

- If the Program numbers on your external MIDI device are referenced as values from 0 to 127, find the appropriate number by subtracting 1 from the number in the following correspondence chart.
- * When the RS-5/9 receives a Program Change message without receiving the Bank Select, it switches to the Tone or Drum Set with the same Bank number as the currently selected Tone or Drum Set.

Tone

| | | Bank Number | | Program |
|--------|---------|-------------|-----|---------|
| Group | Number | MSB | LSB | Number |
| User | 001–128 | 64 | 00 | 001–128 |
| Preset | 001–128 | 65 | 00 | 001–128 |
| Preset | 129–256 | 66 | 00 | 001–128 |

^{*} For Bank numbers and Program numbers corresponding to Preset Tone numbers 257–512, refer to (p. 149, 150).

Drum Set

| Group | Number | Bank Number | | Program |
|--------|---------|-------------|-----|----------|
| | | MSB | LSB | Number |
| User | 001,002 | 64 | 00 | 001, 002 |
| Preset | 001-011 | 65 | 00 | 001–011 |
| Preset | 012 | 120 | 00 | 001 |
| Preset | 013 | 120 | 00 | 009 |
| Preset | 014 | 120 | 00 | 017 |
| Preset | 015 | 120 | 00 | 025 |
| Preset | 016 | 120 | 00 | 026 |
| Preset | 017 | 120 | 00 | 033 |
| Preset | 018 | 120 | 00 | 041 |
| Preset | 019 | 120 | 00 | 049 |
| Preset | 020 | 120 | 00 | 057 |

Using an External MIDI Controller to Change the RS-5/9's Tones

Use of the Modulation lever, pedals, and control knobs to make changes to the RS-5/9's Tones in real time is explained in Chapter 4.


Transmitting Controller numbers set with Modulation Assign (p. 71), Control Pedal Assign (p. 73), and Knob Assign (p. 74) to the RS-5/9 achieves the same effect as working the Modulation lever, pedals, and knobs.

Chapter 11. Recording Performances on the RS-5/9 to an External Device

Recording to an External Sequencer

Now, try using an external sequencer to record your music onto multiple tracks, and then play back the recorded performance.

Connecting to an External Sequencer



- **1.** Before starting the connection procedure, make sure that the power to all devices has been turned off.
- **2.** After reading "Connecting the RS-5/9 to external equipment" (p. 14), connect an audio device/system or headphones.
- **3.** Connect the RS-5/9 and the external sequencer as shown in the figure.
- **4.** As described in "Turning On the Power" (p. 15), turn on the power of each device.

Making Settings Before Recording

When recording to an external sequencer, the following steps must be carried out.

- Set the RS-5/9's Local Control to OFF (refer to the next section).
- Turn on the external sequencer's Thru function (p. 125).
- Set the Performance (p. 125).
- Set the Device ID number (p. 125).


Setting the RS-5/9's Local Control to OFF

The setting that determines whether the keyboard controller section (p. 62) and sound generator section are separated is referred to as "Local Control."

When Local Control is on, playing the keyboard will produce sound, and moving the pitch bend lever will control the pitch.

When Local Control is off, playing the keyboard will not produce sound, and moving the pitch bend lever will not control pitch. The sound source of the RS-5/9 will produce sound only in response to messages received from an external MIDI device.

Sequencer



RS-5/9

The performance data from the RS-5/9's keyboard controller section is output from the MIDI OUT connector and recorded by the sequencer. This performance data is then also output back to the RS-5/9 from the sequencer's MIDI OUT connector and played by the RS-5/9's sound generator.

If Local Control were ON, each note would be played twice; once by the musical data from the keyboard controller section, and once again by the data sent from the sequencer. In order to prevent such double triggering, the Local Control setting is turned off to separate the keyboard controller section from the sound source section.

The Local Control setting affects the RS-5/9 as a whole (i.e., is a system setting). This setting remains stored in memory even while the power is off.

- 1. Press [EDIT], getting the indicator to light.
- 2. Use VALUE [-]/[+] to select "System Setup."

Shapter 11

- 3. Press [ENTER].
- **4.** Press [4] a number of times to select "Local Control."

SYSTEM MIDI Local Control: ON

- * If you hold down [SHIFT] and press [4], you will return to the previous item.
- **5.** Use VALUE [-]/[+] to set "OFF."
- 6. Press [EDIT].

The [EDIT] indicator goes out, and you are returned to the previous screen.

- * If your sequencer does not have a Thru function, set the RS-5/9's Local Control to ON.
- * Regardless of the Local Control setting, musical data from an external MIDI device is always received and will play the internal sound source.

Turning On the External Sequencer's Thru Function

Turn the sequencer's Thru function ON. The sequencer takes the performance data received at the MIDI IN connector and outputs the data unchanged from the MIDI OUT connector (refer to the previous section).

To determine whether or not your sequencer features a MIDI Thru function and for instructions on making the Thru function settings, refer to the owner's manual for your sequencer.

* If your sequencer does not have a Thru function, set the RS-5/9's Local Control to ON.

Setting the Performance

Before beginning to record, first make the Performance settings (select the Tones and Key mode, make any multi-effects, chorus, and reverb settings, set the knobs, and so on). The following settings are especially important.

Setting the Keyboard Send Channel to PART (p. 120)

If this is set to PART, your playing will be transmitted on the same channel as the Receive Channel of the Part that you are playing. When recording to a sequencer, set this to PART.

Setting the Receive Channel for Each Part (p. 122)

Setting the Tone Change Receive Switch for Each Part to ON (p. 122)

Setting the Device ID Number

Set the Device ID Number (p. 115) so that the Performance's settings are recorded at the beginning of the song (refer to the next section).

Recording

Recording the Performance's Settings at the Beginning of the Song

First, record the Performance settings at the beginning of the song. If this is done, playing back the song from the beginning will automatically set the RS-5/9 to the Performance settings that were used during recording (regardless of the Performance that was selected when playback began), ensuring that playback will use the correct sounds and settings.

- * Record the song at the tempo at which it is to be played back. If the tempo used for playback of a song is changed from the tempo selected at the time of recording, the RS-5/9 may not be able to correctly receive the settings for the recorded Performance, which may prevent proper playback of the performance data.
- 1. Press [UTILITY], getting the indicator to light.
- **2.** Use VALUE [-]/[+] to select "Bulk Dump."
- 3. Press [ENTER].
- **4.** Use VALUE [-]/[+] to select "Temporary."

| BULK | DUMP | CENTERI |
|-------|------|---------|
| Tempo | rary | |

- **5.** Put the external sequencer in record mode.
- **6.** Press [ENTER] to transmit the settings.

 The message "Transmitting..." appears in the display during transmission of the data.
- * Do not press any key on the keyboard while Bulk Dump is in progress. Pressing a key sends Note messages from the MIDI OUT connector. To cancel the Bulk Dump, press [EXIT].

After the transmitting is finished, the display will indicate "Completed."

The [UTILITY] indicator goes out, and you are returned to the previous screen.

7. Stop the external sequencer.

Recording Each Part Separately

Next we will record the musical data for each Part onto separate tracks of the sequencer. So as not to erase the Performance settings that we recorded at the beginning of the song, we will start recording the song from the following measure which recorded the Performance settings.

We will record tracks in the order of drums -> bass -> accompaniment -> melody, while listening to the tracks that were recorded on previous passes.

For example, assign Tones to each Part as shown below.

Drums: Part 10
Bass: Part 2
Accompaniment: Part 4
Melody: Part 1

- * Tone changes, and the actions of the Pitch Bend lever, Modulation lever, knobs, and other controls are also recorded.
- * It is not necessary to record the song at the tempo at which it is to be played back.

Listening to the Recorded Performance

When you finish recording all Parts, playback and listen to the result. Note the following when playing back a song.

* If you modify the settings of each Part (volume and panning etc.), you will need to re-record the modified Performance settings at the beginning of the song. (p. 125)

Set the System Exclusive Receive Switch to ON (p. 116)

When set to OFF, the Performance settings recorded at the beginning of the song cannot be received. With the factory settings, this will be "ON."

Set the Same Device ID Number Used for Recording (p. 115)

If not set to the same Device ID number, the Performance settings recorded at the beginning of the song cannot be received.

Make Sure to Start Playback at the Beginning of the Song

When playback of a song is started at any point other than the beginning, the Performance settings at the time of recording are not used, and the song is not played back correctly.

Playing Together with the Playback of a Recorded Performance


You can play the RS-5/9's keyboard along with a previous performance by playing while the recorded material is played back. In this case, select a Part that was not recorded for playing the keyboard.

Transposing Playback of Performances (Master Key Shift)

If you wish to transpose the playback of a song, use the Master Key Shift setting. This setting will transpose all Parts except for the Drum Part. You can specify a transposition of up to $\pm 1/2$ octaves in semitone steps.

The Master Key Shift setting is a system setting that is applied to the entire RS-5/9 (i.e., is a system setting). This setting remains stored in memory even while the power is off.

- 1. Press [EDIT], getting the indicator to light.
- **2.** Use VALUE [-]/[+] to select "System Setup."
- 3. Press [ENTER].
- **4.** Press the numeric key [4] several times to select "Master Key Shift."



- * If you hold down [SHIFT] and press [4], you will return to the previous item.
- **5.** Press VALUE [-]/[+] to select the value (-24 to +24).
- **6.** Press [EDIT].

The [EDIT] indicator goes out, and you are returned to the previous screen.

Enjoying Computer Music

You can use a computer and sequencer software instead of a hardware sequencer to record the music you play onto multiple tracks (perhaps over a number of sessions), and then play back the recorded result.


Connecting a Computer

When connecting the RS-5/9 to a computer, one of the following is required.

- USB MIDI interface cable (Roland ED UM-1)
- USB MIDI interface (Roland ED UM-2/4) and MIDI cable
- Interface equipped with a MIDI connector (Roland Super MPU ll) and MIDI Cable
- MIDI interface adapter and MIDI Cable

Connect the RS-5/9 to your computer using the method that is appropriate for your setup.

- 1. Before starting the connection procedure, make sure that the power to all devices has been turned off.
- 2. After reading "Connecting the RS-5/9 to external equipment" (p. 14), connect an audio device/system or headphones.
- **3.** Connect the RS-5/9 and the computer as shown below.
- 4. As described in "Turning On the Power" (p. 15), turn on the power of each device.



Making Settings Prior to Recording, Recording, and Listening to the Recorded Performance

You can record and listen to performances using the same procedures used with an external sequencer connected. Refer to (p. 124–126).

* When reading this portion, just replace "sequencer" with "sequencer software" or "computer" whenever it appears in the text.

Using the RS-5/9 as a GM/GM2 System-Compatible Sound Module

You can play back music data designed for GM and GM2 sound generators by connecting an external sequencer and using the RS-5/9 as a sound module.

- * For instructions on connecting the external sequencer, refer to (v. 124).
- * When the RS-5/9 receives a GS Reset message, the RS-5/9 is enabled for the GS format (a shared set of specifications proposed by Roland for standardization of multi-timbral sound modules). This permits playback of music data bearing the GS logo (GS music data). However, Roland's Sound Canvas Series (including the SC-8850 and SC-8820 models) feature a different sound module format and expanded tone map, so data created exclusively for the Sound Canvas Series may not play back properly on the RS-5/9.

Playing Back GM/GM2 Music Data

Be sure to note the following when playing back GM or GM2 music data.

Set the System Exclusive Receive Switch to ON (p. 116).

When set to OFF, GM System On and GM2 System On MIDI messages cannot be received. With the factory settings, this will be "ON."

Make Sure to Play Back from the Beginning of the Song

When playback of a song is started at any point other than the beginning, the sound generator settings are not reset to the GM and GM2 initial settings values, and the song is not played back correctly.

* If you want to play back a song in which a message resetting the sound generator to the initial settings values (GM Setup message or GM2 Setup message) was not recorded, you must first restore the RS-5/9's sound generator to the GM/GM2 basic settings (p. 117).

Set the GM System On Receive Switch or GM2 System On Receive Switch to ON

When set to OFF, GM System On and GM2 System On MIDI messages cannot be received. When shipped from the factory, both of these are set to "ON."

The GM System On Receive Switch and GM2 System On Receive Switch settings affect the RS-5/9 as a whole (i.e., are system settings). This setting remains stored in memory even while the power is off.

- 1. Press [EDIT], getting the indicator to light.
- **2.** Use VALUE [-]/[+] to select "System Setup."
- 3. Press [ENTER].
- **4.** Press [4] a number of times to select "GM SYSTEM." or "GM2 SYSTEM."

| SYSTEM GM SYSTEM: | MIDI | R× ON |
|-----------------------|------|----------|
| SYSTEM GM2 SYSTEM: | MIDI | R× ON |

- * If you hold down [SHIFT] and press [4], you will return to the previous item.
- **5.** Use VALUE [-]/[+] to set "ON."
- 6. Press [EDIT].

The [EDIT] indicator goes out, and you are returned to the previous screen.

Creating Songs for GM and GM2 System Sound Generators

The songs can be created in basically the same way as that described in "Recording to an External Sequencer" (p. 124–126). The main difference is that the following three issues need to be taken into account:

- Restoring the GM/GM2 basic settings
- · Limits on the Tones that can be used
- Instead of Performance settings, a GM Setup message or GM2 Setup message is recorded at the beginning of the song

Restoring the GM/GM2 Basic Settings

Before making the Performance settings (p. 125), reset the sound generator settings to the GM or GM2 initial settings (p. 117).

Tones That Can Be Used

You can only use the following GM/GM2-specified Tones. Although the Performance settings are made before recording, in this case, select your Tones from the following.

GM-Specified Tones

Tones: Tones in Preset:257–512 with a Bank Select LSB

of 0 (p. 149, 150)

Drum Sets: B1-A5 (Note Numbers 35-81) in Preset:12

* Assign Drum Sets to Part 10 and Tones to all other Parts.

GM2-Specified Tones

Tones: Preset:257–512
Drum Sets: Preset:12–20

* You can assign Drum Sets to as many as two Parts of your

Recording a GM Setup Message or GM2 Setup Message at the Beginning of the Song

The GM Setup message and GM2 Setup message are messages that reset the sound generator setting to the initial settings values for the GM System or GM2 System. When playing back songs for use with GM- and GM2-compatible sound generators, first record a GM Setup message or GM2 Setup message at the beginning of the song. If this data is included at the beginning of the song, the sound source will always be set appropriately, and the song will play back correctly.

- * Record the song at the tempo at which it is to be played back. If the tempo used for playback of a song is changed from the tempo selected at the time of recording, the RS-5/9 may not be able to correctly receive the GM or GM2 Setup message, which may prevent proper playback of the performance data.
- 1. Press [UTILITY], getting the indicator to light.
- **2.** Use VALUE [-]/[+] to select "Tx Setup."
- 3. Press [ENTER].
- **4.** Press VALUE [-]/[+] to select "GM Setup." or "GM2 Setup."

| Τ× | SETUP | CENTERI |
|----|-------|---------|
| GM | Setup | |

- **5.** Put the external sequencer in record mode.
- **6.** Press [ENTER] to transmit the settings.

The message "Transmitting..." appears in the display during transmission of the data.

After the transmitting is finished, the display will indicate "Completed."

The [UTILITY] indicator goes out, and you are returned to the previous screen.

7. Stop the external sequencer.

What is General MIDI Setup data?

General MIDI Setup data consists of MIDI messages such as the following.

- GM System On Message (System Exclusive Message: F0H 7EH 7FH 09H 01H F7H)
- The following values for Parts 1–16

Bank Select (CC#00 and CC#32: BnH 00H vvH BnH 20H vvH)

Program Change (CnH ppH)

Portamento Time (CC#05: BnH 05H vvH)

Volume (CC#07: BnH 07H vvH) Panning (CC#10:BnH 0AH vvH)

Portamento Switch On/Off (CC#65: BnH 41H vvH)

Filter Resonance (CC#71: BnH 47H vvH)
Release Time (CC#72: BnH 48H vvH)
Attack Time (CC#73: BnH 49H vvH)
Cutoff (CC#74: BnH 4AH vvH)

Decay Time(CC#75: BnH 4BH vvH) LFO Rate (CC#76: BnH 4CH vvH) LFO Depth (CC#77: BnH 4DH vvH) LFO Delay (CC#78: BnH 4EH vvH)

Reverb Send Level (CC#91: BnH 5BH vvH) Chorus Send Level (CC#93: BnH 5DH vvH)

Solo Switch On/Off (CC#126/CC#127: BnH 7EH 00H/BnH 7FH 00H)

Pitch Bend Range (RPN, CC#06, RPN Null: BnH 65H 00H BnH 64H 00H BnH 06H vvH BnH 65H 7FH BnH 64H 7FH)

Fine Tune

(RPN, CC#06, CC#38, RPN Null: BnH 65H 00H BnH 64H 01H BnH 06H vvH BnH 26H vvH BnH 65H 7FH BnH 64H 7FH)

Key Shift (RPN, CC#06, RPN Null: BnH 65H 00H BnH 64H 02H BnH 06H vvH BnH 65H 7FH BnH 64H 7FH)

- * CC#: Controller Number
 - n: MIDI channel
 - pp: Program number
 - vv: data
- * Depending on the connected GM or GM2 sound generator, certain MIDI data may not received.

The GM2 Setup message consists of the following MIDI data.

- GM2 System On Message (System Exclusive Message: F0H 7EH 7FH 09H 03H F7H)
- The following values for Parts 1–16

Contains the same data as that in the GM Setup message.

Appendices

Troubleshooting

If your system is not operating as you think it should be, first check the following points. If after checking these points the problem persists, consult your dealer or local Roland Service Station.

* If any sort of message is being displayed on the screen during an operation, refer to "Error Messages/Message List" (p. 135).

No Power

Is the AC Adapter plugged into the power socket correctly?

No Sound

Is the power for the connected amp and speakers turned on?

Is the volume turned down?

 Check the volume settings for the RS-5/9 and any connected amp or mixer.

Are the components properly connected? (p. 14, 120, 122, 124, 127)

If you are able to hear sound through headphones, this
may suggest a short in a cable or a malfunctioning amp
or mixer. Recheck connector cables and the connected
equipment.

If no sound is produced when you press keys on the keyboard, is Local control set to OFF?

• Set Local Control to ON (p. 124).

Do the transmission and reception channels match?

- If using the RS-5/9 to sound an external MIDI sound generator, check to make sure the channels being used for transmission by the keyboard are matched up with the channels used for reception by the relevant Parts on the external MIDI sound generator (p. 120).
- If using an external MIDI device to sound the RS-5/9, each Part's reception channel needs to be set so it matches the channels that will be used for transmission by the external MIDI device (p. 122).

Have the Part Level settings been lowered?

• Check the settings (p. 66).

Have you switched the RS-5/9 mode to that for listening to demo songs?

 Either press [EXIT], or simultaneously press [SHIFT] and [TRANSPOSE ON/OFF] to return to regular performance mode.

Are the effects settings correct?

 Check effects ON/OFF (p. 79), multi-effects levels (p. 82–106), and other related settings.

Are volume levels being lowered by pedal movements, or by MIDI messages (expression messages) received from an external MIDI device?

• Use the Panic function to raise the volume level (p. 65).

The Pitch is Off

Could Transpose be on?

• Press [TRANSPOSE ON/OFF] to turn Transpose off.

Are the Key Shift settings correct?

• Check the settings (p. 69).

Are the Scale Tune settings correct?

• Check the settings (p. 70).

Are the Master Key Shift settings correct?

• Check the settings (p. 126).

Are the Master Tune settings correct?

• Check the settings (p. 18).

Is it possible that an external MIDI device is constantly sending Pitch Bend messages?

 Use the Panic function to restore the original settings (p. 65).

Sounds Are Missing

Could a Solo switch be set to ON?

 When a Solo switch (p. 67) is on, only one sound is played even when more than one key is pressed. If you want multiple sounds to play simultaneously, set the Solo switch to OFF.

Some sounds are dropped when the number of voices simultaneously being played exceeds 64 voices.

• Set Voice Reserve higher for an important Part, to help assure that it will always be sounded (p. 64).

Effects Not Being Applied

Are the effects switches set to OFF?

• Check the settings (p. 79).

Are the Chorus settings correct?

• Check the Chorus Send Level (p. 108), Chorus Level (p. 107), and Chorus Depth (p. 108) settings.

Are the Reverb settings correct?

• Check the Reverb Send Level (p. 109) and Reverb Level (p. 109) settings.

Is the Multi-Effects Source set to LOWER while Key Mode is set to Single?

 The Part to which effects are applied is determined by the Multi-Effects Source setting. Therefore, when in Single mode, set the Multi-Effects Source to UPPER or PERFORMANCE (p. 80).

Is any Part's Multi-Effects switch set to OFF?

 When a Part's Multi-Effects Source is set to PERFORMANCE, set the Multi-Effects switch for the part being used to ON (p. 107).

Song Data Cannot Be Played Back Correctly

Is the GM System On Receive Switch or GM2 System On Receive Switch set to OFF?

• Set these Receive switches to ON (p. 128).

Did you start playback at some point other than the beginning of the song?

Songs meant for playback with GM System and GM2
 System sound generators have a GM/GM2 System On
 message recorded at the beginning of the song. If this
 message is not received, the song data may not play back
 correctly.

Are the Performance settings recorded at the beginning of the song?

 If the Performance settings are not recorded at the beginning of the song, the status of the Performance at the time of recording cannot be reproduced, which prevents proper playback. When recording a song, make sure to record the Performance settings at the beginning of the song (p. 125).

If playing back a song that you have created for playback on GM or GM2 System sound generators, has the GM Setup message or GM2 Setup message been recorded at the beginning of the song?

 If no GM Setup message or GM2 Setup message is recorded at the beginning of the song, the sound generator settings are not restored to initial GM System or GM2 System status, which prevents proper playback. When recording a song that is to be played back using a GM or GM2 System sound generator, make sure to record a GM Setup message or GM2 Setup message at the beginning of the song (p. 129).

Are you playing back GS Format song data?

When the RS-5/9 receives a GS Reset message, it enters a
mode that provides compatibility with GS Format song
data. While this means the RS-5/9 can then play back
music data bearing the GS logo (GS music data), music
data created expressly for use only with Roland's Sound
Canvas Series may not play back correctly.

Cannot Play Arpeggios

Is the MIDI clock being received when Sync Source (p. 77) is set to MIDI?

• Set the system so that the MIDI clock is received from the external MIDI device. Certain MIDI devices you may have connected may not send the MIDI clock to the RS-5/9 except during recording or playback.

Sound Does Not Stop When Key is Pressed

Is the Hold pedal polarity reversed?

• Check the HOLD PEDAL Polarity setting (p. 73).

MIDI Messages Not Received Correctly

Are the Receive channel settings correct?

• Check the settings (p. 122).

Is each Receive switch set correctly?

Check the Tone Change Receive switch (p. 122), GM
 System On Receive switch (p. 128), GM2 System On
 Receive switch (p. 128), and Exclusive Receive switch (p.
 116) settings.

Are Device ID number settings correct?

• Set the Device ID number (p. 115) used when the Exclusive message was recorded to the sequencer.

Is the sequencer playback tempo correct?

 Play back the data on the sequencer at the tempo used when the Exclusive message was recorded to the sequencer (p. 125).

MIDI Messages Not Transmitted Correctly

Are the transmission channel settings correct?

• Check the settings (p. 120).

Are the Bank Select transmission switch settings correct?

• Check the settings (p. 121).

Using Sequencer Software, Modulation Lever and Knob Movements Have No Effect on the Sound

Some types of sequencer software may not allow Soft Thru (i.e., data received at the MIDI IN connector is not sent from the MIDI OUT connector as is) for Exclusive messages.

 When recording Exclusive messages with such sequencer software, set Local Control to ON (p. 124).

ror Messages/Message List

Error Messages/Message List

This section explains the meaning of the various error messages and other messages that the RS-5/9 may display, and describes the measures to take when these appear.

Error and other messages appearing here are listed in alphabetical order.

Error Message List

BULK DUMP

Checksum Error

Cause: There is a mistake in the checksum value for the

received System Exclusive message.

Solution: Correct the checksum value.

MIDI Buffer Full

Cause: The data cannot be processed correctly due to an

excessive number of MIDI messages.

Solution: Reduce the number of MIDI messages being

received.

MIDI

Communication Error

Cause: There is a problem with the MIDI cable

connection.

Solution: Check to make sure no cable has been

disconnected, and that there are no shorts.

Receive Data Error

Cause: MIDI messages could not be received correctly.

Solution: If this same message continues to reappear, it

means that there is a mistake in the content of the

MIDI message.

User Memory Backup

Error

Cause: There is an error in the memory used for storage

of User Area and System Setup data.

Solution: Consult your dealer or local Roland service for

repair.

User Memory Damaged

Cause: User Memory data has been corrupted.

Solution: Carry out the Factory Reset operation (p. 21) to

restore the factory settings.

Message List

BULK DATA
Transmitting...

Bulk Dump is in progress.

BULK Receiving...
KEEP POWER ON!

Bulk data is being received. Do not turn off the power.

Canceled

Processing is canceled.

Completed

Processing is complete.

Edited Tone/Drum Set Exists. Write Them.

One or more tones have not been saved. Save the Tone or Drum Set data before changing the settings, then save the Performance once more.

GM SETUP
Transmitting...

GM Setup data is being transmitted.

GM2 SETUP Transmitting...

GM2 setup data is being transmitted.

Error Messages/Message List

Now Executing... KEEP POWER ON!

Processing is in progress. Do not turn off the power.

Now Resetting... KEEP POWER ON!

Factory Reset is in progress. Do not turn off the power.

Now Writing... KEEP POWER ON!

Data is being saved. Do not turn off the power.

Panic! Now Muting.

The Panic function has been activated. To get the sound to stop, the muting circuits have been engaged.

Panic! Now Transmitting.

The Panic function has been activated. Data for resuming sound now being transmitted.

Parameter List

Performance

Set Using the Panel Buttons

| Full Name of Parameter | Value | | |
|------------------------|---------------------|---------|--|
| Key Mode | SINGLE, DUAL, SPLIT | (p. 34) | |
| Arpeggio Switch | OFF, ON | (p. 75) | |
| Transpose Switch | OFF, ON | (p. 48) | |

Numeric Key [3] (PFM NAME/LEVEL/PAN)

| Parameter Name | Full Name of Parameter | Value | |
|----------------|------------------------|---------------------------|----------|
| Name | Performance Name | ASCII Character (max. 12) | (p. 113) |

Numeric Key [4] (MIDI/TUNE)

| Parameter Name | Full Name of Parameter | Value | |
|-----------------|------------------------|------------|----------|
| MIDI Tx Channel | MIDI Transmit Channel | 1–16, PART | (p. 120) |

Numeric Key [5] (CONTROL)

| Parameter Name | Full Name of Parameter | Value | |
|----------------|------------------------|-------|---------|
| MOD | Modulation Assign | * | (p. 71) |
| PEDAL | Control Pedal Assign | * | (p. 73) |
| CONTROL1 | Knob 1 Assign | * | (p. 74) |
| CONTROL2 | Knob 2 Assign | * | (p. 74) |
| CONTROL3 | Knob 3 Assign | * | (p. 74) |
| CONTROL4 | Knob 4 Assign | * | (p. 74) |

^{*} MODULATION, PORTAMENTO TIME, VOLUME, PAN, EXPRESSION, PORTAMENTO, SOSTENUTO, SOFT, RESONANCE, RELEASE TIME, ATTACK TIME, CUTOFF, DECAY TIME, LFO RATE, LFO DEPTH, LFO DELAY, CHO SEND LEVEL, REV SEND LEVEL, UP-LO BALANCE, MFX PARAMETER 1, MFX PARAMETER 2, AFTERTOUCH

Numeric Key [6] (MULTI-FX)

| Parameter Name | Full Name of Parameter | Value | |
|----------------|------------------------|---------------------------|---------|
| Source | Multi-Effects Source | UPPER, LOWER, PERFORMANCE | (p. 80) |
| Туре | Multi-Effects Type | *1 | (p. 81) |

^{*} When Source is set to PERFORMANCE, Type and parameter settings are set to the Performance settings.

^{*} Refer to (p. 142-146) the Type parameters.

^{*1 00} THROUGH, 01 STEREO EQ, 02 OVERDRIVE, 03 DISTORTION, 04 PHASER, 05 SPECTRUM, 06 ENHANCER, 07 AUTO WAH, 08 ROTARY, 09 COMPRESSOR, 10 LIMITER, 11 HEXA-CHORUS, 12 TREML CHORUS, 13 SPACE-D, 14 STEREO CHO, 15 STEREO FLNGR, 16 STEP FLANGER, 17 STEREO DELAY, 18 MODLT DELAY, 19 TRI TAP DELY, 20 QUAD TAP DLY, 21 T CTRL DELAY, 22 2V PCH SHIFT, 23 FBK PCH SIFT, 24 REVERB, 25 GATED REVERB, 26 OD>CHORUS, 27 OD>FLANGER, 28 OD>DELAY, 29 DIST>CHORUS, 30 DIST>FLANGER, 31 DIST>DELAY, 32 ENH>CHORUS, 33 ENH>FLANGER, 34 ENH>DELAY, 35 CHORUS>DELAY, 36 FLNGR>DELAY, 37 CHORUS>FLNGR, 38 CHORUS/DELAY, 39 FLNGR/DELAY, 40 CHORUS/FLNGR, 41 LOFI, 42 SLICER

Numeric Key [7] (CHORUS)

| Parameter Name | Full Name of Parameter | Value | |
|------------------|-----------------------------|--|----------|
| Туре | Chorus Type | CHORUS1, CHORUS2, CHORUS3, CHORUS4, FEEDBACK CHORUS, FLANGER, SHORT DELAY, SHORT DELAY(FB) | (p. 107) |
| Pre-LPF | Chorus Pre-Low Pass Filter | 0–7 | (p. 107) |
| Level | Chorus Level | 0–127 | (p. 107) |
| Feedback | Chorus Feedback Level | 0–127 | (p. 107) |
| Delay | Chorus Delay Time | 0–127 | (p. 108) |
| Rate | Chorus Rate | 0–127 | (p. 108) |
| Depth | Chorus Depth | 0–127 | (p. 108) |
| Send LevI to Rev | Chorus Send Level to Reverb | 0-127 | (p. 108) |

Numeric Key [8] (REVERB)

| Parameter Name | Full Name of Parameter | Value | |
|----------------|----------------------------|---|----------|
| Туре | Reverb Type | ROOM1, ROOM2, ROOM3, HALL1, HALL2, PLATE, DELAY, PANNING DELAY | (p. 109) |
| Character | Reverb Character | 0–7 | (p. 109) |
| Pre-LPF | Reverb Pre-Low Pass Filter | 0–7 | (p. 109) |
| Level | Reverb Level | 0–127 | (p. 109) |
| Time | Reverb Time | 0–127 | (p. 109) |
| Delay Feedback | Reverb Delay Feedback | 0-127 | (p. 109) |

Numeric Key [9] (KEYBOARD)

| Parameter Name | Full Name of Parameter | Value | |
|----------------|------------------------|----------|---------|
| Transpose | Transpose | -36- +36 | (p. 48) |
| Split Point | Split Point | C-1-G9 | (p. 40) |
| Upper Part | Upper Part | 1–16 | (p. 39) |
| Lower Part | Lower Part | 1–16 | (p. 39) |

Numeric Key [0] (ARPEGGIO)

| Parameter Name | Full Name of Parameter | Value | |
|----------------|------------------------|--|---------|
| Style | Arpeggio Style | *1 | (p. 75) |
| Motif | Motif | *2 | (p. 76) |
| Beat Ptrn | Beat Pattern | *3 | (p. 76) |
| Tempo | Tempo | 20–250 (When Sync Source is set to MIDI, Tempo(=MIDI) appears in the display.) | (p. 76) |
| Octave Range | Octave Range | -3- +3 | (p. 77) |
| Key Velocity | Key Velocity | 1–127, REAL | (p. 77) |
| Shuffle Rate | Shuffle Rate | 50–90 [%] | (p. 77) |
| Accent Rate | Accent Rate | 0–100 [%] | (p. 77) |
| Sync Source | Sync Source | INT, MIDI | (p. 77) |

^{*1 1/4, 1/6, 1/8, 1/12, 1/16, 1/32,} PORTAMENTO A–B, GLISSANDO, SEQUENCE A–D, ECHO, SYNTH BASS, HEAVY SLAP, LIGHT SLAP, WALK BASS, RHYTHM GTR A–E, 3 FINGER GTR, STRUM GTR UP, STRUM GTR DOWN, STRUM GTR U&D, PIANO BACKING, CLAVI CHORD, WALTZ, SWING WALTZ, REGGAE, PERCUSSION, HARP, SHAMISEN, BOUND BALL, RANDOM, BOSSA NOVA, SALSA, MAMBO, LATIN PERC, SAMBA, TANGO, HOUSE, LIMITLESS

^{*2} SINGLE UP, SINGLE DOWN, SINGLE UP&DOWN, SINGLE RANDOM, DUAL UP, DUAL DOWN, DUAL UP&DOWN, DUAL RANDOM, TRIPLE UP, TRIPLE UP, TRIPLE UP&DOWN, TRIPLE RANDOM, NOTE ORDER, GLISSANDO, CHORD, BASS+CHORD 1–5, BASS+UP 1–8, BASS+RANDOM 1–3, TOP+UP 1–6, BASS+UP+TOP

^{*3 1/4, 1/6, 1/8, 1/12, 1/16 1–3, 1/32 1–3,} PORTA-A 01–11, PORTA-B 01–15, SEQ-A 1–7, SEQ-B 1–5, SEQ-C 1–2, SEQ-D 1–8, ECHO 1–3, MUTE 01–16, STRUM1–8, REGGAE1–2, REFRAIN1–2, PERC1–4, WALKBS, HARP, BOUND, RANDOM, BOSSA NOVA, SALSA 1–4, MAMBO 1–2, CLAVE, REV CLA, GUIRO, AGOGO, SAMBA, TANGO 1–4, HOUSE 1–2

Performance Part

Numeric Key [3] (PFM NAME/LEVEL/PAN)

| Parameter Name | Full Name of Parameter | Value | |
|----------------|------------------------|-------------------|---------|
| Level | Level | 0-127 | (p. 66) |
| Pan | Pan | RANDOM, L63-0-63R | (p. 66) |

Numeric Key [4] (MIDI/TUNE)

| Parameter Name | Full Name of Parameter | Value | |
|----------------|----------------------------|-------------------|----------|
| Channel | Receive Channel | 1–16, OFF | (p. 122) |
| Tone Change | Tone Change Receive Switch | OFF, ON | (p. 122) |
| Key Shift | Key Shift | -24- +24 | (p. 69) |
| Fine Tune | Fine Tune | -100- +100 [cent] | (p. 69) |
| Scale Tune C-B | Scale Tune C-B | -64 +63 | (p. 70) |

Numeric Key [5] (CONTROL)

| Parameter Name | Full Name of Parameter | Value | |
|------------------|------------------------|--------------------|---------|
| Pitch Bend Range | Pitch Bend Range | 0-+24 | (p. 50) |
| Voice Reserve | Voice Reserve | 0–64 | (p. 64) |
| Tone Type | Tone Type | TONE, DRUM1, DRUM2 | (p. 31) |

Numeric Key [6] (MULTI-FX)

| Parameter Name | Full Name of Parameter | Value | |
|----------------|------------------------|---------|----------|
| Switch | Multi-Effects Switch | OFF, ON | (p. 107) |

^{*} These settings can be made only when Source (p. 80) is set to PERFORMANCE.

Numeric Key [7] (CHORUS)

| Parameter Name | Full Name of Parameter | Value | • | |
|----------------|------------------------|-------|--------|-----|
| Send Level | Chorus Send Level | 0-127 | (n. 16 | 181 |

Numeric Key [8] (REVERB)

| Parameter Name | Full Name of Parameter | Value | |
|----------------|------------------------|-------|----------|
| Send Level | Reverb Send Level | 0-127 | (p. 109) |

Numeric Key [9] (KEYBOARD)

| Parameter Name | Full Name of Parameter | Value | |
|------------------|------------------------|---------|---------|
| Solo Switch | Solo Switch | OFF, ON | (p. 67) |
| Portamento Sw | Portamento Switch | OFF, ON | (p. 67) |
| Portamento Time | Portamento Time | 0-127 | (p. 67) |
| Velo Sens Depth | Velocity Sens Depth | 0-127 | (p. 68) |
| Velo Sens Offset | Velocity Sens Offset | 0-127 | (p. 68) |

Tone

Numeric Key [1] (TONE)

| Parameter Name | Full Name of Parameter | Value | |
|------------------|------------------------|---------------------------|----------|
| Tone Name | Tone Name | ASCII Character (max. 12) | (p. 110) |
| LFO Rate | LFO Rate | -64 +63 | (p. 110) |
| LFO Depth | LFO Depth | -64- ÷63 | (p. 110) |
| LFO Delay | LFO Delay | -64- +63 | (p. 110) |
| LFO Filter Sw | LFO Filter Switch | OFF, ON | (p. 110) |
| Filter Cutoff | Filter Cutoff | -64- +63 | (p. 110) |
| Filter Resonance | Filter Resonance | -64- +63 | (p. 110) |
| Envelope Attack | Envelope Attack Time | -64 +63 | (p. 110) |
| Envelope Decay | Envelope Decay Time | -64 +63 | (p. 110) |
| Envelope Release | Envelope Release Time | -64 +63 | (p. 110) |

Numeric Key [6] (MULTI-FX)

| Parameter Name | Full Name of Parameter | Value | |
|----------------|------------------------|-------|---------|
| Туре | Multi-Effects Type | *1 | (p. 81) |

- * Type and parameter settings are set to the Tone's settings in the following cases:
 - When Source (p. 80) is set to UPPER and a Tone is assigned to the Upper Part
 - When Source (p. 80) is set to LOWER and a Tone is assigned to the Lower Part
- * Refer to (p. 142-146) the Type parameters.
- *1 00 THROUGH, 01 STEREO EQ, 02 OVERDRIVE, 03 DISTORTION, 04 PHASER, 05 SPECTRUM, 06 ENHANCER, 07 AUTO WAH, 08 ROTARY, 09 COMPRESSOR, 10 LIMITER, 11 HEXA-CHORUS, 12 TREML CHORUS, 13 SPACE-D, 14 STEREO CHO, 15 STEREO FLNGR, 16 STEP FLANGER, 17 STEREO DELAY, 18 MODLT DELAY, 19 TRI TAP DELY, 20 QUAD TAP DLY, 21 T CTRL DELAY, 22 2V PCH SHIFT, 23 FBK PCH SIFT, 24 REVERB, 25 GATED REVERB, 26 OD>CHORUS, 27 OD>FLANGER, 28 OD>DELAY, 29 DIST>CHORUS, 30 DIST>FLANGER, 31 DIST>DELAY, 32 ENH>CHORUS, 33 ENH>FLANGER, 34 ENH>DELAY, 35 CHORUS>DELAY, 36 FLNGR>DELAY, 37 CHORUS>FLNGR, 38 CHORUS/DELAY, 39 FLNGR/DELAY, 40 CHORUS/FLNGR, 41 LOFI, 42 SLICER

Drum Set

Numeric Key [2] (DRUMS)

| Parameter Name | Full Name of Parameter | Value | |
|----------------|------------------------|---------------------------|----------|
| DrumSet Name | Drum Set Name | ASCII Character (max. 12) | (p. 112) |
| Pitch | Pitch | -60- +67 | (p. 112) |
| Level | Level | 0–127 | (p. 112) |
| Pan | Pan | RANDOM, L63-0-63R | (p. 112) |
| Reverb Depth | Reverb Depth | 0–127 | (p. 112) |

Numeric Key [6] (MULTI-FX)

| Parameter Name | Full Name of Parameter | Value | |
|----------------|------------------------|-------|---------|
| Type | Multi-Effects Type | *1 | (p. 81) |

- * Type and parameter settings are set to the Drum Set's settings in the following cases:
 - When Source (p. 80) is set to UPPER and a Drum Set is assigned to the Upper Part
 - When Source (p. 80) is set to LOWER and a Drum Set is assigned to the Lower Part
- * Refer to (p. 142–146) the Type parameters.
- *1 00 THROUGH, 01 STEREO EQ, 02 OVERDRIVE, 03 DISTORTION, 04 PHASER, 05 SPECTRUM, 06 ENHANCER, 07 AUTO WAH, 08 ROTARY, 09 COMPRESSOR, 10 LIMITER, 11 HEXA-CHORUS, 12 TREML CHORUS, 13 SPACE-D, 14 STEREO CHO, 15 STEREO FLNGR, 16 STEP FLANGER, 17 STEREO DELAY, 18 MODLT DELAY, 19 TRI TAP DELY, 20 QUAD TAP DLY, 21 T CTRL DELAY, 22 2V PCH SHIFT, 23 FBK PCH SIFT, 24 REVERB, 25 GATED REVERB, 26 OD>CHORUS, 27 OD>FLANGER, 28 OD>DELAY, 29 DIST>CHORUS, 30 DIST>FLANGER, 31 DIST>DELAY, 32 ENH>CHORUS, 33 ENH>FLANGER, 34 ENH>DELAY, 35 CHORUS>DELAY, 36 FLNGR>DELAY, 37 CHORUS>FLNGR, 38 CHORUS/DELAY, 39 FLNGR/DELAY, 40 CHORUS/FLNGR, 41 LOFI, 42 SLICER

System

Set Using the Panel Buttons

| Full Name of Parameter | Value | |
|-----------------------------------|---|---------|
| Multi-Effects Switch | OFF, ON | (p. 79) |
| Chorus Switch | OFF, ON | (p. 79) |
| Reverb Switch | OFF, ON | (p. 79) |
| Favorite Performance Bank [1]–[8] | Performance Group and Number (Preset:1-128, User:1-128) | (p. 58) |

Numeric Key [4] (MIDI/TUNE)

| Parameter Name | Full Name of Parameter | Value | |
|------------------|---------------------------------|------------------------|----------|
| Local Control | Local Control | OFF, ON | (p. 124) |
| GM SYSTEM | GM System On Receive Switch | OFF, ON | (p. 128) |
| GM2 SYSTEM | GM2 System On Receive Switch | OFF, ON | (p. 128) |
| System Exclusive | System Exclusive Receive Switch | OFF, ON | (p. 116) |
| Bank Select | Bank Select Transmit Switch | OFF, ON | (p. 121) |
| Device ID# | Device ID Number | 17–32 | (p. 115) |
| Master Key Shift | Master Key Shift | -24 +24 | (p. 126) |
| Master Tune | Master Tune | 415.3-440.0-466.2 [Hz] | (p. 18) |

Numeric Key [5] (CONTROL)

| Parameter Name | Full Name of Parameter | Value | |
|---------------------|----------------------------|-------------------|---------|
| LCD Contrast | LCD Contrast | 1–8 | (p. 16) |
| CONTROL PEDAL Polar | ity Control Pedal Polarity | STANDARD, REVERSE | (p. 73) |
| HOLD PEDAL Polarity | Hold Pedal Polarity | STANDARD, REVERSE | (p. 73) |

Multi-Effect

01: STEREO EQ (Stereo Equalizer) (p. 82)

| Parameter Name | Full Name of Parameter | Value |
|----------------|------------------------|-------------------------|
| Low Freq | Low Frequency | 200, 400 [Hz] |
| Low Gain | Low Gain | -15 +15 [dB] |
| High Freq | High Frequency | 4000, 8000 [Hz] |
| High Gain | High Gain | -15- +15 [dB] |
| Mid1 Freq | Middle 1 Frequency | 200-8000 [Hz] |
| Mid1 Q | Middle 1 Q | 0.5, 1.0, 2.0, 4.0, 8.0 |
| Mid1 Gain | Middle 1 Gain | -15- +15 [dB] |
| Mid2 Freq | Middle 2 Frequency | 200-8000 [Hz] |
| Mid2 Q | Middle 2 Q | 0.5, 1.0, 2.0, 4.0, 8.0 |
| Mid2 Gain | Middle 2 Gain | -15- +15 [dB] |
| Level | Output Level | 0-127 |

02: OVERDRIVE (p. 83)

| Parameter Name | Full Name of Parameter | Value |
|----------------|------------------------|--------------------------------------|
| Drive | Drive | 0–127 |
| Level | Output Level | 0-127 |
| Low Gain | Low Gain | -15- +15 [dB] |
| High Gain | High Gain | -15- +15 [dB] |
| Amp Type | Amp Simulator Type | SMALL, BUILT-IN, 2-STACK, 3-STACK |
| Pan | Output Pan | L64-63R |

03: DISTORTION (p. 83)

| Parameter Name | Full Name of Parameter | Value |
|----------------|------------------------|--------------------------------------|
| Drive | Drive | 0-127 |
| Level | Output Level | 0-127 |
| Low Gain | Low Gain | -15- +15 [dB] |
| High Gain | High Gain | -15- +15 [dB] |
| Amp Type | Amp Simulator Type | SMALL, BUILT-IN, 2-STACK, 3-STACK |
| Pan | Output Pan | L64-63R |

04: PHASER (p. 84)

| Parameter Name | Full Name of Parameter | Value |
|----------------|------------------------|-----------------|
| Manual | Manual | 100-8000 [Hz] |
| Rate | Rate | 0.05-10.00 [Hz] |
| Depth | Depth | 0-127 |
| Resonance | Resonance | 0-127 |
| Mix | Mix Level | 0-127 |
| Pan | Output Pan | L64-63R |
| Level | Output Level | 0-127 |

05: SPECTRUM (p. 84)

| Parameter Name | Full Name of Parameter | Value |
|----------------|------------------------|-------------------------|
| Band 1 | Band 1 Gain | -15- +15 [dB] |
| Band 2 | Band 2 Gain | -15- +15 [dB] |
| Band 3 | Band 3 Gain | -15- +15 [dB] |
| Band 4 | Band 4 Gain | -15 +15 [dB] |
| Band 5 | Band 5 Gain | -15- +15 [dB] |
| Band 6 | Band 6 Gain | -15- +15 [dB] |
| Band 7 | Band 7 Gain | -15- +15 [dB] |
| Band 8 | Band 8 Gain | -15- +15 [dB] |
| Q | Q | 0.5, 1.0, 2.0, 4.0, 8.0 |
| Pan | Output Pan | L64-63R |
| Level | Output Level | 0–127 |

06: ENHANCER (p. 85)

| Parameter Name | Full Name of Parameter | Value |
|----------------|------------------------|---------------|
| Sens | Sensitivity | 0-127 |
| Mix | Mix Level | 0–127 |
| Low Gain | Low Gain | -15- +15 [dB] |
| High Gain | High Gain | -15- +15 [dB] |
| Level | Output Level | 0-127 |

07: AUTO WAH (p. 85)

| Parameter Name | Full Name of Parameter | Value |
|----------------|------------------------|-----------------|
| Filter Type | Filter Type | LPF, BPF |
| Sens | Sensitivity | 0-127 |
| Manual | Manual | 0-127 |
| Peak | Peak | 0-127 |
| Rate | Rate | 0.05-10.00 [Hz] |
| Depth | Depth | 0-127 |
| Polarity | Polarity | UP, DOWN |
| Level | Output Level | 0-127 |

08: ROTARY (p. 86)

| Parameter Name | Full Name of Parameter | Value |
|----------------|-----------------------------|-----------------|
| Low Slow | Low Frequency Slow Rate | 0.05-10.00 [Hz] |
| Low Fast | Low Frequency Fast Rate | 0.05-10.00 [Hz] |
| Low Accel | Low Frequency Acceleration | 0–15 |
| Low Level | Low Frequency Level | 0-127 |
| High Slow | High Frequency Slow Rate | 0.05-10.00 [Hz] |
| High Fast | High Frequency Fast Rate | 0.05-10.00 [Hz] |
| High Accel | High Frequency Acceleration | 0-15 |
| High Level | High Frequency Level | 0-127 |
| Separation | Separation | 0-127 |
| Speed | Speed | SLOW, FAST |
| Level | Output Level | 0–127 |

09: COMPRESSOR (p. 87)

| Parameter Name | Full Name of Parameter | Value |
|----------------|------------------------|----------------------|
| Attack | Attack Time | 0-127 |
| Sustain | Sustain | 0-127 |
| Post Gain | Post Gain | 0, +6, +12, +18 [dB] |
| Low Gain | Low Gain | -15- +15 [dB] |
| High Gain | High Gain | -15- +15 [dB] |
| Pan | Output Pan | L64-63R |
| Level | Output Level | 0-127 |

10: LIMITER (p. 87)

| Parameter Name | Full Name of Parameter | Value |
|----------------|------------------------|------------------------|
| Threshold | Threshold Level | 0-127 |
| Ratio | Compression Ratio | 1.5:1, 2:1, 4:1, 100:1 |
| Release | Release Time | 0-127 |
| Post Gain | Post Gain | 0, +6, +12, +18 [dB] |
| Low Gain | Low Gain | -15- +15 [dB] |
| High Gain | High Gain | -15- +15 [dB] |
| Pan | Output Pan | L64-63R |
| Level | Output Level | 0-127 |

11: HEXA-CHORUS (p. 88)

| Parameter Name | Full Name of Parameter | Value |
|----------------|------------------------|-----------------|
| Pre Delay | Pre Delay Time | 0.0-100 [ms] |
| Rate | Rate | 0.05-10.00 [Hz] |
| Depth | Depth | 0-127 |
| Pre Delay Dev | Pre Delay Deviation | 0–20 |
| Depth Dev | Depth Deviation | -20- +20 |
| Pan Dev | Pan Deviation | 0–20 |
| Balance | Effect Balance | D100:0W-D0:100W |
| Level | Output Level | 0-127 |

12: TREMOLO CHORUS (p. 88)

| Parameter Name | Full Name of Parameter | Value |
|----------------|------------------------|-----------------|
| Pre Delay | Pre Delay Time | 0.0-100 [ms] |
| Chorus Rate | Chorus Rate | 0.05-10.00 [Hz] |
| Chorus Depth | Chorus Depth | 0-127 |
| Tremolo Phase | Tremolo Phase | 0-180 [deg] |
| Tremolo Rate | Tremolo Rate | 0.05-10.00 [Hz] |
| Tremolo Sep | Tremolo Separation | 0-127 |
| Balance | Effect Balance | D100:0W-D0:100W |
| Level | Output Level | 0–127 |

13: SPACE-D (p. 89)

| Parameter Name | Full Name of Parameter | Value |
|----------------|------------------------|-----------------|
| Pre Delay | Pre Delay Time | 0.0-100 [ms] |
| Rate | Rate | 0.05-10.00 [Hz] |
| Depth | Depth | 0-127 |
| Phase | Phase | 0-180 [deg] |
| Low Gain | Low Gain | -15- +15 [dB] |
| High Gain | High Gain | -15- +15 [dB] |
| Balance | Effect Balance | D100:0W-D0:100W |
| Level | Output Level | 0-127 |

14: STEREO CHORUS (p. 89)

| Parameter Name | Full Name of Parameter | Value |
|----------------|------------------------|-----------------|
| Pre Delay | Pre Delay Time | 0.0-100 [ms] |
| Rate | Rate | 0.05-10.00 [Hz] |
| Depth | Depth | 0-127 |
| Phase | Phase | 0-180 [deg] |
| Filter Type | Filter Type | OFF, LPF, HPF |
| Cutoff Freq | Cutoff Frequency | 200-8000 [Hz] |
| Low Gain | Low Gain | -15- +15 [dB] |
| High Gain | High Gain | -15- +15 [dB] |
| Balance | Effect Balance | D100:0W-D0:100W |
| Level | Output Level | 0-127 |

15: STEREO FLANGER (p. 90)

| Parameter Name | Full Name of Parameter | Value |
|----------------|------------------------|-----------------|
| Pre Delay | Pre Delay Time | 0.0-100 [ms] |
| Rate | Rate | 0.05-10.00 [Hz] |
| Depth | Depth | 0-127 |
| Feedback | Feedback Level | -98- +98 [%] |
| Phase | Phase | 0-180 [deg] |
| Filter Type | Filter Type | OFF, LPF, HPF |
| Cutoff Freq | Cutoff Frequency | 200-8000 [Hz] |
| Low Gain | Low Gain | -15-+15 [dB] |
| Hìgh Gain | High Gain | -15-+15 [dB] |
| Balance | Effect Balance | D100:0W-D0:100W |
| Level | Output Level | 0-127 |

16: STEP FLANGER (p. 91)

| Parameter Name | Full Name of Parameter | Value |
|----------------|------------------------|--------------------------------------|
| Pre Delay | Pre Delay Time | 0.0-100 [ms] |
| Rate | Rate | 0.05-10.00 [Hz] |
| Depth | Depth | 0-127 |
| Feedback | Feedback Level | -98- +98 [%] |
| Phase | Phase | 0-180 [deg] |
| Step Rate | Step Rate | 0.1–20.0 [Hz], note-value symbols |
| Low Gain | Low Gain | -15- +15 [dB] |
| High Gain | High Gain | -15- +15 [dB] |
| Balance | Effect Balance | D100:0W-D0:100W |
| Level | Output Level | 0-127 |

17: STEREO DELAY (p. 92)

| Parameter Name | Full Name of Parameter | Value |
|----------------|------------------------|--------------------------|
| Delay Left | Delay Time Left | 0.0-500 [ms] |
| Delay Right | Delay Time Right | 0.0-500 [ms] |
| Feedback | Feedback Level | - 98- +98 [%] |
| Feedback Mode | Feedback Mode | NORMAL, CROSS |
| Phase Left | Feedback Phase Left | NORMAL, INVERT |
| Phase Right | Feedback Phase Right | NORMAL, INVERT |
| HF Damp | HF Damp | 200–8000 [Hz], BYPASS |
| Low Gain | Low Gain | -15- +15 [dB] |
| High Gain | High Gain | -15-+15 [dB] |
| Balance | Effect Balance | D100:0W-D0:100W |
| Level | Output Level | 0–127 |

18: MODULATION DELAY (p. 93)

| | | (/ |
|----------------|------------------------|--------------------------|
| Parameter Name | Full Name of Parameter | Value |
| Delay Left | Delay Time Left | 0.0-500 [ms] |
| Delay Right | Delay Time Right | 0.0-500 [ms] |
| Feedback | Feedback Level | -98- +98 [%] |
| Feedback Mode | Feedback Mode | NORMAL, CROSS |
| Rate | Rate | 0.05-10.00 [Hz] |
| Depth | Depth | 0-127 |
| Phase | Phase | 0-180 [deg] |
| HF Damp | HF Damp | 200–8000 [Hz], BYPASS |
| Low Gain | Low Gain | -15 +15 [dB] |
| High Gain | High Gain | -15 +15 [dB] |
| Balance | Effect Balance | D100:0WD0:100W |
| Level | Output Level | 0-127 |

19: TRIPLE TAP DELAY (p. 94)

| Parameter Name | Full Name of Parameter | Value |
|----------------|------------------------|--------------------------------------|
| Delay Center | Delay Time Center | 200–1000 [ms], note-value symbols |
| Delay Left | Delay Time Left | 200–1000 [ms], note-value symbols |
| Delay Right | Delay Time Right | 200–1000 [ms], note-value symbols |
| Feedback | Feedback Level | -98 +98 [%] |
| Center Level | Center Level | 0-127 |
| Left Level | Left Level | 0-127 |
| Right Level | Right Level | 0-127 |
| HF Damp | HF Damp | 200–8000 [Hz], BYPASS |
| Low Gain | Low Gain | -15- +15 [dB] |
| High Gain | High Gain | -15- +15 [dB] |
| Balance | Effect Balance | D100:0W-D0:100W |
| Level | Output Level | 0-127 |

20: QUADRUPLE TAP DELAY (p. 95)

| | | \1 <i>'</i> |
|----------------|------------------------|--------------------------------------|
| Parameter Name | Full Name of Parameter | Value |
| Delay 1 | Delay Time 1 | 200–1000 [ms], note-value symbols |
| Delay 2 | Delay Time 2 | 200–1000 [ms], note-value symbols |
| Delay 3 | Delay Time 3 | 200–1000 [ms], note-value symbols |
| Delay 4 | Delay Time 4 | 200–1000 [ms], note-value symbols |
| Level 1 | Level 1 | 0-127 |
| Level 2 | Level 2 | 0-127 |
| Level 3 | Level 3 | 0-127 |
| Level 4 | Level 4 | 0-127 |
| Feedback | Feedback Level | -98- +98 [%] |
| HF Damp | HF Damp | 200–8000 [Hz], BYPASS |
| Balance | Effect Balance | D100:0W-D0:100W |
| Level | Output Level | 0–127 |

21: TIME CONTROL DELAY (p. 96)

| Parameter Name | Full Name of Parameter | Value |
|----------------|------------------------|--------------------------|
| Delay | Delay Time | 200-1000 [ms] |
| Acceleration | Acceleration | 0-15 |
| Feedback | Feedback Level | -98 +98 [%] |
| HF Damp | HF Damp | 200–8000 [Hz], BYPASS |
| Pan | Output Pan | L64-63R |
| Low Gain | Low Gain | -15- +15 [dB] |
| High Gain | High Gain | -15- +15 [dB] |
| Balance | Effect Balance | D100:0W-D0:100W |
| Level | Output Level | 0–127 |

22: 2VOICE PITCH SHIFTER (p. 96)

| Parameter Name | Full Name of Parameter | Value |
|----------------|------------------------|-------------------|
| Coarse A | Coarse Pitch A | -24- +12 [semi] |
| Fine A | Fine Pitch A | -100-+100 [cent] |
| Pan A | Output Pan A | L64-63R |
| Pre Delay A | Pre Delay Time A | 0.0-500 [ms] |
| Coarse B | Coarse Pitch B | -24- +12 [semi] |
| Fine B | Fine Pitch B | -100- +100 [cent] |
| Pan B | Output Pan B | L64-63R |
| Pre Delay B | Pre Delay Time B | 0.0-500 [ms] |
| Mode | Pitch Shifter Mode | 1, 2, 3, 4, 5 |
| Lev Balance | Level Balance | A100:0B-A0:100B |
| Balance | Effect Balance | D100:0W-D0:100W |
| Level | Output Level | 0–127 |

23: FBK PITCH SHIFTER (Feedback Pitch Shifter) (p. 97)

| Parameter Name | Full Name of Parameter | Value |
|----------------|------------------------|-------------------|
| Coarse | Coarse Pitch | -24- +12 [semi] |
| Fine | Fine Pitch | -100- +100 [cent] |
| Feedback | Feedback Level | -98- +98 [%] |
| Pre Delay | Pre Delay Time | 0.0-500 [ms] |
| Mode | Pitch Shifter Mode | 1, 2, 3, 4, 5 |
| Pan | Output Pan | L64-63R |
| Low Gain | Low Gain | -15-+15 [dB] |
| High Gain | High Gain | -15- +15 [dB] |
| Balance | Effect Balance | D100:0W-D0:100W |
| Level | Output Level | 0-127 |

24: REVERB (p. 98)

| Parameter Name | Full Name of Parameter | Value |
|----------------|------------------------|--|
| Туре | Reverb Type | ROOM1, ROOM2, STAGE1, STAGE2, HALL1, HALL2 |
| Pre Delay | Pre Delay Time | 0.0-100 [ms] |
| Time | Reverb Time | 0-127 |
| HF Damp | HF Damp | 2008000 [Hz], BYPASS |
| Low Gain | Low Gain | -15- +15 [dB] |
| High Gain | High Gain | -15- +15 [dB] |
| Balance | Effect Balance | D100:0W-D0:100W |
| Level | Output Level | 0–127 |

25: GATED REVERB (p. 99)

| Parameter Name | Full Name of Parameter | Value |
|----------------|------------------------|------------------------------------|
| Туре | Gated Reverb Type | NORMAL, REVERSE, SWEEP1, SWEEP2 |
| Pre Delay | Pre Delay Time | 0.0-100 [ms] |
| Gate Time | Gate Time | 5-500 [ms] |
| Low Gain | Low Gain | -15- +15 [dB] |
| High Gain | High Gain | -15-+15 [dB] |
| Balance | Effect Balance | D100:0W-D0:100W |
| Level | Output Level | 0–127 |

26: OVERDRIVE→CHORUS (p. 99)

| Parameter Name | Full Name of Parameter | Value | | |
|----------------|------------------------|-----------------|--|--|
| OD Drive | Drive | 0-127 | | |
| OD Pan | Overdrive Pan | L64-63R | | |
| Chorus Delay | Chorus Pre Delay Time | 0.0-100 [ms] | | |
| Chorus Rate | Chorus Rate | 0.05-10.00 [Hz] | | |
| Chorus Depth | Chorus Depth | 0-127 | | |
| Chorus Bal | Chorus Bal | D100:0W-D0:100W | | |
| Level | Output Level | 0-127 | | |

27: OVERDRIVE→FLANGER (p. 100)

| Parameter Name | Full Name of Parameter | Value |
|----------------|------------------------|-----------------|
| OD Drive | Drive | 0–127 |
| OD Pan | Overdrive Pan | L64-63R |
| Flg Pre Delay | Flanger Pre Delay Time | 0.0-100 [ms] |
| Flg Rate | Flanger Rate | 0.05-10.00 [Hz] |
| Flg Depth | Flanger Depth | 0-127 |
| Flg Feedback | Flanger Feedback Level | -98- +98 [%] |
| Fig Balance | Flanger Balance | D100:0W-D0:100W |
| Level | Output Level | 0-127 |

28: OVERDRIVE→DELAY (p. 100)

| Parameter Name | Full Name of Parameter | Value |
|----------------|------------------------|--------------------------|
| OD Drive | Drive | 0-127 |
| OD Pan | Overdrive Pan | L64-63R |
| Delay Time | Delay Time | 0.0-500 [ms] |
| Delay Feedback | Delay Feedback Level | -98- +98 [%] |
| Delay HF Damp | Delay HF Damp | 200–8000 [Hz], BYPASS |
| Delay Bal | Delay Balance | D100:0W-D0:100W |
| Level | Output Level | 0-127 |

29: DISTORTION -> CHORUS (p. 101)

The parameters are essentially the same as "26: OVERDRIVE \rightarrow CHORUS," with the exception of the following two. OD Drive \rightarrow Dist Drive (Specify the amount of distortion.) OD Pan \rightarrow Dist Pan (Specify the stereo location of the distortion sound.)

30: DISTORTION→FLANGER (p. 101)

The parameters are essentially the same as in "27: OVERDRIVE \rightarrow FLANGER," with the exception of the following two. OD Drive \rightarrow Dist Drive (Specify the amount of distortion.) OD Pan \rightarrow Dist Pan (Specify the stereo location of the distortion sound.)

31: DISTORTION→DELAY (p. 101)

The parameters are essentially the same as in "28: OVERDRIVE \rightarrow DELAY," with the exception of the following two. OD Drive \rightarrow Dist Drive (Specify the amount of distortion.) OD Pan \rightarrow Dist Pan (Specify the stereo location of the distortion sound.)

32: ENHANCER→CHORUS (p. 102)

| Parameter Name | Full Name of Parameter | meter Value | | | |
|----------------|------------------------|-----------------|--|--|--|
| Enhancer Sens | Enhancer Sensitivity | 0-127 | | | |
| Enhancer Mix | Enhancer Mix Level | 0-127 | | | |
| Chorus Delay | Chorus Pre Delay Time | 0.0-100 [ms] | | | |
| Chorus Rate | Chorus Rate | 0.05-10.00 [Hz] | | | |
| Chorus Depth | Chorus Depth | 0-127 | | | |
| Chorus Bal | Chorus Balance | D100:0W-D0:100W | | | |
| Level | Output Level | 0-127 | | | |

33: ENHANCER→FLANGER (p. 102)

| Parameter Name | Full Name of Parameter | Value | | |
|----------------|------------------------|-----------------|--|--|
| Enhancer Sens | Enhancer Sensitivity | 0-127 | | |
| Enhancer Mix | Enhancer Mix Level | 0-127 | | |
| Flg Pre Delay | Flanger Pre Delay Time | 0.0-100 [ms] | | |
| Flg Rate | Flanger Rate | 0.05-10.00 [Hz] | | |
| Fig Depth | Flanger Depth | 0-127 | | |
| Flg Feedback | Flanger Feedback Level | -98- +98 [%] | | |
| Flg Balance | Flanger Balance | D100:0W-D0:100W | | |
| Level | Output Level | 0–127 | | |

34: ENHANCER→DELAY (p. 103)

| Parameter Name | Full Name of Parameter Value | | | | | |
|----------------|------------------------------|--------------------------|--|--|--|--|
| Enhancer Sens | Enhancer Sensitivity | 0–127 | | | | |
| Enhancer Mix | Enhancer Mix Level | 0-127 | | | | |
| Delay Time | Delay Time | 0.0-500 [ms] | | | | |
| Delay Feedback | Delay Feedback Level | -98- +98 [%] | | | | |
| Delay HF Damp | Delay HF Damp | 200–8000 [Hz], BYPASS | | | | |
| Delay Bal | Delay Balance | D100:0W-D0:100W | | | | |
| Level | Output Level | 0-127 | | | | |

35: CHORUS→DELAY (p. 103)

| Parameter Name | Full Name of Parameter | Value | | |
|----------------|------------------------|--------------------------|--|--|
| Chorus Delay | Chorus Pre Delay Time | 0.0-100 [ms] | | |
| Chorus Rate | Chorus Rate | 0.05-10.00 [Hz] | | |
| Chorus Depth | Chorus Depth | 0-127 | | |
| Chorus Bal | Chorus Balance | D100:0W-D0:100W | | |
| Delay Time | Delay Time | 0.0-500 [ms] | | |
| Delay Feedback | Delay Feedback Level | -98- +98 [%] | | |
| Delay HF Damp | Delay HF Damp | 200–8000 [Hz], BYPASS | | |
| Delay Bal | Delay Balance | D100:0W-D0:100W | | |
| Level | Output Level | 0-127 | | |

36: FLANGER→DELAY (p. 104)

| Parameter Name | Full Name of Parameter | Value |
|----------------|------------------------|----------------------------|
| Flg Pre Delay | Flanger Pre Delay Time | 0.0-100 [ms] |
| Flg Rate | Flanger Rate | 0.05-10.00 [Hz] |
| Flg Depth | Flanger Depth | 0-127 |
| Flg Feedback | Flanger Feedback Level | -98 +98 [%] |
| Fig Balance | Flanger Balance | D100:0W-D0:100W |
| Delay Time | Delay Time | 0.0-500 [ms] |
| Delay Feedback | Delay Feedback Level | -98- +98 [%] |
| Delay HF Damp | Delay HF Damp | 200–8000 [Hz], BY- PASS |
| Delay Bal | Delay Balance | D100:0W-D0:100W |
| Level | Output Level | 0-127 |

37: CHORUS→FLANGER (p. 104)

| Parameter Name | Full Name of Parameter | Value |
|----------------|------------------------|-----------------|
| Chorus Delay | Chorus Pre Delay Time | 0.0–100 [ms] |
| Chorus Rate | Chorus Rate | 0.05-10.00 [Hz] |
| Chorus Depth | Chorus Depth | 0-127 |
| Chorus Bal | Chorus Balance | D100:0W-D0:100W |
| Flg Pre Delay | Flanger Pre Delay Time | 0.0-100 [ms] |
| Flg Rate | Flanger Rate | 0.05-10.00 [Hz] |
| Flg Depth | Flanger Depth | 0-127 |
| Flg Feedback | Flanger Feedback Level | -98 +98 [%] |
| Flg Balance | Flanger Balance | D100:0W-D0:100W |
| Level | Output Level | 0-127 |

38: CHORUS/DELAY (p. 105)

The parameters are the same as for "35: CHORUS \rightarrow DELAY." However, the Delay Balance parameter adjusts the volume balance between the direct sound and the delay sound.

39: FLANGER/DELAY (p. 105)

The parameters are the same as for "36: FLANGER ightarrow DELAY." However, the Delay Balance parameter adjusts the volume balance between the direct sound and the delay sound.

40: CHORUS/FLANGER (p. 105)

The parameters are the same as for "37: CHORUS \rightarrow FLANGER." However, the Flanger Balance parameter adjusts the volume balance between the direct sound and the flanger sound.

41: LOFI (p. 106)

| Parameter Name | Full Name of Parameter | Value |
|----------------|------------------------|----------------------|
| Bit Down | Bit Down | 0–7 |
| S-Rate Down | Sample-Rate Down | 32, 16, 8, 4 [kHz] |
| Post Gain | Post Gain | 0, +6, +12, +18 [dB] |
| Low Gain | Low Gain | -15- +15 [dB] |
| High Gain | High Gain | -15- +15 [dB] |
| Output | Output | MONO, STEREO |
| Level | Output Level | 0-127 |

42: SLICER (p. 106)

| Parameter Name | Full Name of Parameter | Value |
|----------------|------------------------|--|
| Timing Pttern | Timing Pattern | 1–34 |
| Accent Pttern | Accent Pattern | 1–16 |
| Accent Level | Accent Level | 0-127 |
| Attack | Attack | 1–10 |
| Rate | Rate | 0.05-10.00 [Hz], note-value symbols |
| Reset | Reset | OFF, ON |
| Level | Output Level | 0–127 |

Performance List

| User Preset | | | | | | | | | | | |
|-------------|----------------------------|----------------|------------|---------------------------|------------------|------------|-----------------------------|----------------|------------|------------------------------|------------------|
| No. | Name | Key Mode | No. | Name | Key Mode | No. | Name | Key Mode | No. | Name | Key Mode |
| 001 | BasicPerform | SINGLE | 065 | Combine | SINGLE | 001 | BasicPerform | SINGLE | 065 | Combine | SINGLE |
| 002 | SlicingPower | DUAL | 066 | Morph Pad | SINGLE | 002 | SlicingPower | DUAL | 066 | Morph Pad | SINGLE |
| 003 | Lo-Fi Tekno | SPLIT | 067 | 5th Saws | SINGLE | 003 | Lo-Fi Tekno | SPLIT | 067 | 5th Saws | SINGLE |
| 004 | Rock Organ | SPLIT | 068 | 4th Sweep | SINGLE | 004 | Rock Organ | SPLIT | 068 | 4th Sweep | SINGLE |
| 005 | SoundTrk1912 | SPLIT | 069 | Saws Sweep | DUAL | 005 | SoundTrk1912 | SPLIT | 069 | Saws Sweep | DUAL |
| 006 | ARP Bs/Saws | SPLIT | 070 | RS Soundtrk | DUAL | 006 | ARP Bs/Saws | SPLIT | 070 | RS Soundtrk | DUAL |
| 007 | ARP DigiClav | SINGLE | 071 | StepMetalPad | DUAL | 007 | ARP DigiClav | SINGLE | 071 | StepMetalPad | DUAL |
| 800 | RS Pop Kit 1 | SINGLE | 072 | Running Saws | SINGLE | 800 | RS Pop Kit 1 | SINGLE | 072 | Running Saws | SINGLE |
| 009 | RS Strings | DUAL | 073 | Etherality | SINGLE | 009 | RS Strings | DUAL | 073 | Etherality | SINGLE DUAL |
| 010 | PowerBrass | DUAL | 074 | Step Flanger | DUAL | 010 | PowerBrass | DUAL | 074 075 | Step Flanger Step Saws | SINGLE |
| 011 | Bass/Piano | SPLIT | 075 076 | Step Saws Random Pad | SINGLE SINGLE | 011 012 | Bass/Piano ARP Bs/Tp | SPLIT SPLIT | 076 | Random Pad | SINGLE |
| 012 013 | ARP Bs/Tp RS Finale | SPLIT DUAL | 076 | RandomEnding | SINGLE | 013 | RS Finale | DUAL | 077 | RandomEnding | SINGLE |
| 013 | Rhm/JC Gtr | SPLIT | 078 | FlangeRandom | SINGLE | 014 | Rhm/JC Gtr | SPLIT | 078 | FlangeRandom | SINGLE |
| 015 | Big Blue | SINGLE | 079 | Slicer | SINGLE | 015 | Big Blue | SINGLE | 079 | Slicer | SINGLE |
| 016 | Arpgio Bell | DUAL | 080 | Sliced Sync | DUAL | 016 | Arpgio Bell | DUAL | 080 | Sliced Sync | DUAL |
| 017 | MG Split | SPLIT | 081 | Shock Wave | SINGLE | 017 | MG Split | SPLIT | 081 | Shock Wave | SINGLE |
| 018 | ARP SteelGtr | SINGLE | 082 | Techno Hit | SINGLE | 018 | ARP SteelGtr | SINGLE | 082 | Techno Hit | SINGLE |
| 019 | Chaotic | DUAL | 083 | Impact Hit | SINGLE | 019 | Chaotic | DUAL | 083 | Impact Hit | SINGLE |
| 020 | Alto Sax | SINGLE | 084 | Noise Hit | SINGLE | 020 | Alto Sax | SINGLE | 084 | Noise Hit | SINGLE |
| 021 | RS Dist Gtr | SINGLE | 085 | Minor Rave | SINGLE | 021 | RS Dist Gtr | SINGLE | 085 | Minor Rave | SINGLE |
| 022 | Twin Rave | DUAL | 086 | MinorIncidnt | SINGLE | 022 | Twin Rave | DUAL | 086 | MinorIncidnt | SINGLE |
| 023 | Air Heaven | DUAL | 087 | Tekno Saw | SINGLE | 023 | Air Heaven | DUAL | 087 | Tekno Saw | SINGLE |
| 024 | Twilight | DUAL | 088 | Teknoheadz | SINGLE | 024 | Twilight | DUAL | 088 | Teknoheadz | SINGLE |
| 025 | Jazz Scat | SINGLE | 089 | TeknoSplit | SPLIT | 025 | Jazz Scat | SINGLE | 089 | TeknoSplit | SPLIT SINGLE |
| 026 | Pad/NylonGtr | SPLIT | 090 | Vox Lead | SINGLE | 026 | Pad/NylonGtr | SPLIT SPLIT | 090 091 | Vox Lead 303 Reso | SINGLE |
| 027 | Happy Saws | SPLIT | 091 | 303 Reso | SINGLE | 027 028 | Happy Saws GR-300 | DUAL | 092 | Uillean Pipe | SINGLE |
| 028 | GR-300 | DUAL DUAL | 092 093 | Uillean Pipe Hichiriki | SINGLE SINGLE | 028 | Frog Pad | DUAL | 093 | Hichiriki | SINGLE |
| 029 030 | Frog Pad Angel Choir | DUAL | 093 | Quad Winds | SINGLE | 030 | Angel Choir | DUAL | 094 | Quad Winds | SINGLE |
| 030 | 7th Atmos | SINGLE | 095 | Tb Section | SINGLE | 031 | 7th Atmos | SINGLE | 095 | Tb Section | SINGLE |
| 031 | Brite Piano | SINGLE | 096 | TpTbSax Sect | DUAL | 032 | Brite Piano | SINGLE | 096 | TpTbSax Sect | DUAL |
| 033 | Warm Piano | DUAL | 097 | Sax Section | SINGLE | 033 | Warm Piano | DUAL | 097 | Sax Section | SINGLE |
| 034 | SA Rhodes | SINGLE | 098 | Fr.Horns | SINGLE | 034 | SA Rhodes | SINGLE | 098 | Fr.Horns | SINGLE |
| 035 | RS E.Piano | SINGLE | 099 | Big Band | SINGLE | 035 | RS E.Piano | SINGLE | 099 | Big Band | SINGLE |
| 036 | Dyno Phase | SINGLE | 100 | RS Brass | SINGLE | 036 | Dyno Phase | SINGLE | 100 | RS Brass | SINGLE |
| 037 | RS Crystal | SINGLE | 101 | OB Brass | SINGLE | 037 | RS Crystal | SINGLE | 101 | OB Brass | SINGLE |
| 038 | Hyper Bell | SINGLE | 102 | Warm Brass | SINGLE | 038 | Hyper Bell | SINGLE | 102 | Warm Brass | SINGLE |
| 039 | Chime Bells | DUAL | 103 | RS SawBrass1 | SINGLE | 039 | Chime Bells | DUAL | 103 | RS SawBrass1 | SINGLE |
| 040 | Air Crystal | DUAL | 104 | RS SawBrass2 | DUAL | 040 | Air Crystal | DUAL | 104 | RS SawBrass2 | DUAL |
| 041 | Air Bell | DUAL | 105 | RS Flute | SINGLE | 041 | Air Bell | DUAL | 105 | RS Flute | SINGLE |
| 042 | EP Heaven | SINGLE | 106 | Spectre | SPLIT | 042 | EP Heaven | SINGLE | 106 107 | Spectre Pipe Lead | SPLIT SPLIT |
| 043 | HyperBeliPad | DUAL SINGLE | 107 | Pipe Lead | SPLIT SINGLE | 043 044 | HyperBellPad Bell Heaven | DUAL SINGLE | 107 | Shmoog | SINGLE |
| 044 | Bell Heaven | | 108 109 | Shmoog RS Bs&Lead | SPLIT | 044 | RS SawsKey | DUAL | 109 | RS Bs&Lead | SPLIT |
| 045 046 | RS SawsKey ARP Pipe | DUAL DUAL | 110 | HardSyncLead | SINGLE | 046 | ARP Pipe | DUAL | 110 | HardSyncLead | SINGLE |
| 040 | Marc.Strings | SINGLE | 111 | Full Organ | SINGLE | 047 | Marc.Strings | SINGLE | 111 | Full Organ | SINGLE |
| 048 | Orchestral | SINGLE | 112 | Jazz Organ | SINGLE | 048 | Orchestral | SINGLE | 112 | Jazz Organ | SINGLE |
| 049 | OvertoneScan | SINGLE | 113 | DigitalOrgan | DUAL | 049 | OvertoneScan | SINGLE | 113 | DigitalOrgan | DUAL |
| 050 | Square Pad | SINGLE | 114 | Cheese Organ | SINGLE | 050 | Square Pad | SINGLE | 114 | Cheese Organ | SINGLE |
| 051 | Pipe Pad | SINGLE | 115 | Rocker Organ | SINGLE | 051 | Pipe Pad | SINGLE | 115 | Rocker Organ | SINGLE |
| 052 | Haunting | DUAL | 116 | Finger Bass | SINGLE | 052 | Haunting | DUAL | 116 | Finger Bass | SINGLE |
| 053 | RS Prologue | DUAL | 117 | Fretnot Bass | SINGLE | 053 | RS Prologue | DUAL | 117 | Fretnot Bass | SINGLE |
| 054 | OB Strings | SINGLE | 118 | SH101 Bs 1 | SINGLE | 054 | OB Strings | SINGLE | 118 | SH101 Bs 1 | SINGLE |
| 055 | Soft JP Str | SINGLE | 119 | SH101 Bs 2 | SINGLE | 055 | Soft JP Str | SINGLE | 119 | SH101 Bs 2 | SINGLE |
| 056 | JP Strings | SINGLE | 120 | Jungle Bass | SINGLE | 056 | JP Strings | SINGLE | 120 | Jungle Bass | SINGLE |
| 057 | JUNO Strings | SINGLE | 121 | JP-4 Bass | SINGLE | 057 | JUNO Strings | SINGLE | 121 | JP-4 Bass | SINGLE |
| 058 | RS Soft Pad | SINGLE | 122 | TB303 Bass | SINGLE | 058 | RS Soft Pad | SINGLE | 122 | TB303 Bass | SINGLE |
| 059 | MatrxStrings | DUAL | 123 | 303SqDstBass | SINGLE | 059 | MatrxStrings | DUAL SINGLE | 123 124 | 303SqDstBass RS Pop Kit 2 | SINGLE SINGLE |
| 060 | Heaven Pad | SINGLE | 124 | RS Pop Kit 2 | SINGLE | 060 | Heaven Pad | SINGLE | 125 | TR-909 Kit | SINGLE |
| 061 | Glass Orbit | SINGLE | 125 126 | TR-909 Kit Brush Kit | SINGLE SINGLE | 061 062 | Glass Orbit Metal 5thPad | DUAL | 126 | Brush Kit | SINGLE |
| 062 063 | Metal 5thPad Mystic Pad | DUAL SINGLE | 126 | RS Piano | SINGLE | 063 | Mystic Pad | SINGLE | 127 | RS Piano | SINGLE |
| 063 | Comb Saws | DUAL | 128 | Init Perform | SINGLE | 064 | Comb Saws | DUAL | 128 | Init Perform | SINGLE |
| 004 | Collin Gawa | DOAL | 120 | mac i ottofffi | SHOLL | 554 | | | | | == ' |

Tone List

| Us | er | | | | | | | Pr | eset | | | | | | |
|------------|----------------------------|--------|------------|------------|------------------------------|--------|------------|------------|------------------------------|--------|------------|------------|------------------------------|----------|------------|
| No. | Name | Voice | Category | No. | Name | Voice | Category | No. | Name | Voice | Category | No. | Name | Voice | Category |
| 001 | RS Piano | 4 | PNO | 065 | Orchestra 3 | 4 | ORC | 001 | RS Piano | 4 | PNO | 065 | P5 Bass | 1 | SBS |
| 002 | Bright Piano | 4 | PNO | 066 | Romantic Tp. | 1 | BRS | 002 | Bright Piano | 4 | PNO | 066 | RS SawBs.1 | 2 | SBS |
| 003 004 | Piano + Str Dyno Rhodes | 4 3 | PNO EP | 067 | Tp. Mar/Shk | 2 | BRS | 003 | Dance Piano | 2 | PNO | 067 | JP Bass | 2 | SBS |
| 005 | Tremolo Dyno | | EP | 068 069 | Cup Mute Tp. Twin Tps. | 1 2 | BRS BRS | 004 005 | Piano + Str Piano+Choir | 4 4 | PNO PNO | 068 | Square Bass | 2 | SBS |
| 006 | Phase Rhode | | EP . | 070 | Tuba + Horn | 2 | BRS | 006 | Dyno Rhodes | | EP | 069 070 | RS Sine Bass Jungle Bass | ; 2 1 | SBS SBS |
| 007 | SA E.Piano | 2 | EP | 071 | RS Fr.Horns | 2 | BRS | 007 | Tremolo Dyno | | EP | 071 | Ring Bass | 2 | SBS |
| 800 | StackE.Piano | 4 | EP | 072 | Lo Brass | 2 | BRS | 800 | Phase Rhode | s 4 | EP | 072 | - | | SBS |
| 009 | 60's E.Piano | 1. | EP. | 073 | Big Band | 2 | BRS | 009 | RS Rhodes | 4 | EP | 073 | Pedal Bass | 2 | SBS |
| 010 | Atk Clav. | 2 | KEY | 074 | Power Brass | 4 | BRS | 010 | SA E.Piano | 2 | EP | 074 | RS SawBs.2 | 2 | SBS |
| 011 012 | DigitalClav. El.Organ 1 | 2 4 | KEY ORG | 075 | Orch Brass LA Brass | 4 4 | BRS SBR | 011 | StackE.Piano | | EP | 075 | SH101Bass 1 | 2 | SBS |
| 013 | El.Organ 4 | 4 | ORG | 077 | | 4 | SBR | 012 013 | Hard FM EP Detuned EP | 4 4 | EP EP | 076 077 | SH101Bass 2 | 1 2 | SBS |
| 014 | El.Organ 6 | 2 | ORG | 078 | Jump Brass 2 | 2 | SBR | 014 | 60's E.Piano | 1 | EP | 078 | RS LightBs.1 Seq Bass | 2 | SBS SBS |
| 015 | Trem.Organ | 2 | ORG | 079 | OB Brass | 4 | SBR | 015 | Atk Clav. | 2 | KEY | 079 | RS LightBs.2 | 2 | SBS |
| 016 | Perc.Organ 2 | 4 | ORG | 080 | LoFi Brass | 2 | SBR | 016 | AnalogClav.1 | 1 | KEY | 080 | West End Bs. | 3 | SBS |
| 017 | Rock Organ 1 | 1 | ORG | 081 | Warm Brass | 4 | SBR | 017 | AnalogClav.2 | 1 | KEY | 081 | Bubble Bass | 2 | SBS |
| 018 | Cheese Organ | | ORG | 082 | SoaringHorns | 4 | SBR | 018 | DigitalClav. | 2 | KEY | 082 | RS Choir | 2 | VOX |
| 019 020 | D-50 Organ DigitalOrg.1 | 2 2 | ORG ORG | 083 084 | Sugar Keys | 2 4 | SYN | 019 | El.Organ 1 | 4 | ORG | 083 | Rich Choir | 4 | VOX |
| 021 | RequintoGtr. | 1 | AGT | 085 | RS SawsKeys Super Saws | 2 | SYN SYN | 020 021 | El.Organ 2 El.Organ 3 | 4 4 | ORG ORG | 084 085 | Mello Choir | 2 | VOX |
| 022 | SteelGtr.VSW | | AGT | 086 | Double Saws | 2 | BPD | 022 | El.Organ 4 | 4 | ORG | 086 | Jazz Scat JX8P Vox | 3 2 | VOX SPD |
| 023 | ResoGt/Slide | 2 | AGT | 087 | RS Prologue | 3 | SPD | 023 | El.Organ 5 | 4 | ORG | 087 | RS SynVox | 1 | SLD |
| 024 | Dulcimer | 2 | ETH | 088 | RS Crystal | 4 | BEL | 024 | El.Organ 6 | 2 | ORG | 088 | RS Strings | 4 | STR |
| 025 | Celtic Harp | 2 | PLK | 089 | Hyper Bell | 1 | BEL | 025 | Trem.Organ | 2 | ORG | 089 | Rich Strings | 4 | STR |
| 026 | JC ChorusGt. | _ | EGT | 090 | Warm Bell | 1 | BEL | 026 | Perc.Organ 2 | 4 | ORG | 090 | Marc.Strings | 4 | STR |
| 027 | Tele Rear | 2 | EGT | 091 | EP Heaven | 4 | SYN | 027 | Perc.Organ 3 | 4 | ORG | 091 | Oct Strings | 4 | STR |
| 028 029 | Fab 4 Guitar Half Drv. | 4 2 | EGT DGT | | RS Heaven | 2 | SPD | 028 | Perc.Organ 4 | 4 | ORG | 092 | Hybrid Str. | 4 | STR |
| 030 | Dazed Guitar | 2 | DGT | 093 094 | Heaven Pad RS Soft Pad1 | 1 3 | SPD SPD | 029 030 | Perc.Organ 5 | | ORG | 093 | Warm Strings | | STR |
| 031 | Atk A.Bass | 3 | BS | | Morph Pad | 4 | SPD | 030 | Rock Organ 1 Rock Organ 2 | | ORG ORG | 094 095 | RS SlowStr.1 RS SlowStr.2 | 2 3 | STR STR |
| 032 | Heart Bass | 1 | BS | 096 | Comb Strings | 4 | STR | 032 | Cheese Organ | | ORG | 096 | ContraBsSect | | STR |
| 033 | Mr.Smooth | 2 | BS | 097 | 4th Sweep | 4 | SPD | 033 | D-50 Organ | 2 | ORG | 097 | OB Strings | 3 | STR |
| 034 | TB303 Bass 2 | ? 1 | SBS | 098 | Mystic Pad | 4 | BPD | 034 | DigitalOrg.1 | 2 | ORG | 098 | Soft JP Str. | 3 | STR |
| 035 | Tee Bee | 4 | SBS | 099 | OvertoneScan | | SPD | 035 | DigitalOrg.2 | 2 | ORG | 099 | JP Strings | 4 | STR |
| 036 | TB303 Reso | 1 | SBS | 100 | Warm Sqr Pac | | SPD | 036 | RequintoGtr. | 1 | AGT | 100 | Matrix Str. | 4 | STR |
| 037 038 | JP-4 Bass P5 Bass | 1 | SBS SBS | 101 | JP8 Hollow | 4 | SPD | 037 | RS SteelGtr. | 2 | AGT | 101 | JUNO Strings | | STR |
| 039 | Square Bass | 2 | SBS | 102 | 7th Atmos. Dual Sgr&Saw | 2 | FX PLS | 038 039 | SteelGtr.VSW | | AGT | 102 | Digital Str. | 4 | STR |
| 040 | Jungle Bass | 1 | SBS | 104 | Step Saws | 4 | PLS | 040 | Nyfon+Steel ResoGt/Slide | 2 2 | AGT AGT | 103 104 | RS Flute Bamboo Flute | 1 2 | FLT |
| 041 | Pedal Bass | 2 | SBS | | RandomEnding | | PLS | 041 | Dulcimer | 2 | ETH | 105 | Nay | 2 | FLT FLT |
| 042 | SH101Bass 1 | 2 | SBS | 106 | Big Blue | 2 | PLS | 042 | Celtic Harp | 2 | PLK | 106 | Tin Whistle | 2 | FLT |
| 043 | SH101Bass 2 | 1 | SBS | 107 | RND Fl.Chord | 4 | PLS | 043 | Harp&Strings | 3 | PLK | 107 | Zampona | 2 | FLT |
| | West End Bs. | | SBS | | RS SquareLd1 | 2 | SLD | 044 | Andreas Cave | e 4 | PLK | 108 | Pure Lead | 4 | FLT |
| | RS Choir | 2 | VOX | 109 | 2600 Sine | 1 | SLD | | JC ChorusGt. | | EGT | | Pipe Lead | 3 | FLT |
| 046 | Mello Choir Jazz Scat | 2 | VOX VOX | | Shmoog | 2 | SLD | | Tele Rear | 2 | EGT | | BottleBlow 2 | 3 | FLT |
| 048 | RS SynVox | 3 1 | SLD | | CC Solo FM Lead 1 | 2 1 | SLD SLD | 047 048 | Strat Rear | 2 | EGT | | RS Alto Sax | 1 | SAX |
| 049 | RS Strings | 4 | STR | | PureFlatLead | 2 | SLD | 049 | Fab 4 Guitar 5th Overdry. | 4 2 | EGT DGT | | Blown Tenor Sax Section | 1 4 | SAX |
| 050 | Marc.Strings | 4 | STR | | MG Saw Ld. 1 | 1 | SLD | | Half Drv. | 2 | DGT | | Fat + Reed | 4 | SAX SAX |
| 051 | Oct Strings | 4 | STR | | MG Saw Ld. 2 | 1 | SLD | 051 | 5th Dist. | 2 | DGT | | Quad Wind | 4 | WND |
| 052 | RS SlowStr.1 | 2 | STR | | GR300 Lead 1 | | SLD | 052 | Dazed Guitar | 2 | DGT | | Uillean Pipe | 2 | ETH |
| 053 | • | 3 | STR | | MG 2 OSCs | 2 | SLD | 053 | Atk A.Bass | 3 | BS | 117 | Hichiriki | 2 | ETH |
| 054 | Soft JP Str. | 3 | STR | | Sync Lead | 1 | HLD | | Heart Bass | 1 | BS | 118 | Orchestra 2 | 4 | ORC |
| 055 | JP Strings | 4 | STR | | Dirty Sync | 2 | HLD | | Rock Bass | 2 | BS | 119 | Orchestra 3 | 4 | ORC |
| 056 057 | RS Flute Bamboo Flute | 1 2 | FLT | | Happy Saws | 4 | TEK | | Double Pick | 4 | BS | | Orchestra 4 | 4 | ORC |
| 058 | Tin Whistle | 2 | FLT FLT | | TwinOct.Rave MinorIncidnt | 4 | TEK | | Mr.Smooth | 2 | BS | | Henry IV | 4 | ORC |
| 059 | Zampona | 2 | FLT | | Minor Rave | 4 4 | TEK TEK | | TB303 Bass 1 TB303 Bass 2 | | SBS SBS | | Mariachi Tp. | 1 | BRS |
| 060 | RS Alto Sax | 1 | SAX | | Vox Lead | 2 | TEK | | Tee Bee | 4 | SBS | | Romantic Tp. Tp. Shake | 1 | BRS BRS |
| 061 | Blown Tenor | 1 | SAX | | Technoheadz | 4 | TEK | | 303 Sqr.Rev | 1 | SBS | | Tp. Mar/Shk | 2 | BRS |
| 062 | Sax Section | 4 | SAX | 126 | Impact Hit | 2 | HIT | | 303 SqDistBs | 2 | SBS | | Atk Trumpet | 2 | BRS |
| 063 | Uillean Pipe | 2 | ETH | | Techno Hit | 1 | HIT | 063 | TB303 Reso | 1 | SBS | | Cup Mute Tp. | | BRS |
| 064 | Orchestra 2 | 4 | ORC | 128 | P5 Noise | 1 | FX | 064 | JP-4 Bass | 1 | SBS | 128 | Twin Tps. | 2 | BRS |
| Voic | e: number of v | zoice | | | | | | Voic | e number of s | roico | | | | | |

Voice: number of voice User 1–128: MSB=64, LSB=0 Voice: number of voice Preset 1–128: MSB=65, LSB=0

Preset

| | | oice | Category | | | | /oic | | | Name Piano 1 | Voice | Category | LSB 0 | P(|
|---------------|-------------------------|--------|------------|---|----------|----------------------------|------|------------|-------------|---------------------------|--------|------------|----------|----|
| 29 | • | 2 | BRS BRS | | 93 94 | Mystic Pad OvertoneScan | 4 | BPD SPD | 257 258 | Piano 1 Piano 1w | 4 4 | PNO PNO | 1 | 1 |
| 30 | Twin Bones 2Tps + Tb | 1 | BRS | | 95 | Pipe Pad | 3 | SPD | 259 | Piano 1d | 4 | PNO | 2 | 1 |
| 31 32 | 2Tps+Tb+Sax | | BRS | | 96 | Warm Sqr Pad | | SPD | 260 | Piano 2 | 4 | PNO | 0 | 2 |
| 33 | Bones & Tuba | 4 | BRS | | 97 | JP8 Haunting | 4 | SPD | 261 | Piano 2w | 4 | PNO | 1 | 2 |
| 34 | Tuba + Horn | 2 | BRS | | 98 | JP8 Hollow | 4 | SPD | | Piano 3 | 1 | PNO | 0 | 3 |
| 35 | RS Fr.Horns | 2 | BRS | | 99 | Glass Orbit | 3 | BPD | 263 | Piano 3w | 1 | PNO | 1 | 3 |
| 36 | VoyagerBrass | 3 | BRS | | 00 | 7th Atmos. | 2 | FX | 264 | Honky-tonk | 2 | PNO | 0 | 4 |
| 37 | Lo Brass | 2 | BRS | | 01 | Dual Sqr&Saw | | PLS | | HonkyTonk w | | PNO | 1 | 4 |
| 38 | RS TbSection | 2 | BRS | | 02 | Halo Step | 4 | PLS | 266 | E.Piano 1 | 2 | EP | 0 | 5 |
| 39 | Big Band | 2 | BRS | | 03 | Step Saws | 4 | PLS | | St.Soft EP | 2 | EP | 1 | 5 |
| 40 | Power Brass | 4 | BRS | | 04 | Step Metal | 4 | BPD | 268 | FM+SA EP | 2 | EP | 2 | 5 |
| 41 | BrassSection | 4 | BRS | | 05 | Random Pad | 2 | PLS | 269 | Wurly | 2 | EP | 3 | 5 |
| 42 | Quad Brass | 4 | BRS | | 06 | RandomEnding | | PLS | 270 | E.Piano 2 | 2 | EP | 0 | 6 |
| 43 | Brass + Sax | 4 | BRS | | 07 | Big Blue | 2 | PLS | 271 | Detuned EP 2 | | EP | 1 | e |
| 44 | Orch Brass | 4 | BRS | | 08 | LFO Pad | 2 | PLS | 272 | EP Legend | 2 | EP | 2 | 6 |
| 45 | LA Brass | 4 | SBR | | 09 | RND Fl.Chord | 4 | PLS | 273 | St.FM EP | 2 | EP | 3 | 6 |
| 46 | P5 Brass | 4 | SBR | | 10 | Etherality | 4 | PLS | 274 | EP Phase | 2 | EP. | 4 | (|
| 47 | Poly Brass | 4 | SBR | | 11 | RS SquareLd1 | | SLD | 275 | Harpsichord | 1 | KEY | 0 | 7 |
| 47 48 | Fat SynBrass | 4 | SBR | | 12 | Sine Lead | 1 | SLD | 276 | Coupled Hps. | 2 | KEY | 1 | - |
| 40 49 | MKS Brass | 2 | SBR | | 13 | 2600 Sine | 1 | SLD | 277 | Harpsi.w | 1 | KEY | 2 | - |
| 49 | Stack Brass | 4 | SBR | | 14 | RS SquareLd2 | | SLD | 278 | Harpsi.o | 2 | KEY | 3 | - |
| | | | SBR | | | Shmoog | . 1 | SLD | 279 | Clav. | 1 | KEY | 0 | |
| 51 | Jump Brass 2 | 2 4 | SBR | | 15 16 | CC Solo | 2 | SLD | 280 | Pulse Clav | 2 | KEY | 1 | |
| 52 | OB Brass | | | | | | | | | | 1 | KEY | 0 | |
| 53 | JUNO Brass | 2 | SBR | | 17 | FM Lead 1 | 1 | SLD | 281 | Cleakenenial | | BEL | | 1 |
| 54 | LoFi Brass | 2 | SBR | | 18 | FM Lead 2 | 2 | SLD | 282 | Glockenspiel | 1 | | 0 | |
| 55 | Reso Brass | 2 | SBR | | 19 | JP8 PulseLd1 | 1 | SLD | 283 | Music Box | 1 | BEL | 0 | 1 |
| 56 | Warm Brass | 4 | SBR | | 20 | JP8 PulseLd2 | 2 | SLD | 284 | Vibraphone | | MLT | 0 | 1 |
| 57 | SoaringHorns | 4 | SBR | | 21 | Soft SawLead | | SLD | 285 | Vibraphone w | | MLT | 1 | |
| 58 | DeepSynBrass | | SBR | | 22 | PureFlatLead | 2 | SLD | 286 | Marimba | 1 | MLT | 0 | 1 |
| 59 | Sugar Keys | 2 | SYN | | 23 | MG Square 2 | 1 | HLD | 287 | Marimba w | 1 | MLT | 1 | 1 |
| 60 | RS Pipe Keys | 3 | SYN | | 24 | Unison SqrLd | 4 | SLD | 288 | Xylophone | 1 | MLT | 0 | 1 |
| 61 | RS SawsKeys | 4 | SYN | | 25 | Dist Square | 1 | HLD | 289 | Tubular-bell | 1 | BEL | 0 | 1 |
| 62 | • | 2 | SYN | | 26 | RS Digi Lead | 1 | SLD | 290 | Church Bell | 1 | BEL | 1 | 1 |
| 63 | Super Saws | 2 | SYN | | 27 | 260 RingLead | | HLD | 291 | Carillon | 1 | BEL | 2 | |
| 64 | | 2 | BPD | | 28 | MG Saw Ld. 1 | | SLD | 292 | Santur | 1 | PLK | 0 | |
| 65 | Poly Saws | 4 | SYN | | 29 | MG Saw Ld. 2 | | SLD | 293 | Organ 1 | 2 | ORG | 0 | |
| 66 | Polysynth 2 | 2 | BPD | | 30 | GR300 Lead 1 | | SLD | 294 | Trem. Organ | 2 | ORG | 1 | |
| 67 | | 4 | SPD | | 31 | GR300 Lead 2 | | SLD | 295 | 60's Organ1 | 1 | ORG | 2 | |
| 68 | • | 3 | SPD | | 32 | | 2 | SLD | 296 | Organ 4 | 2 | ORG | 3 | |
| 69 | • | 4 | BEL | | 33 | FatSolo Lead | 4 | SLD | 297 | Organ 2 | 2 | ORG | 0 | |
| 70 | Hyper Bell | 1 | BEL | | 34 | | 4 | HLD | 298 | Chorus Or.2 | 2 | ORG | 1 | |
| 71 | | 1 | BEL | | 35 | CrowdingLead | | HLD | 299 | Perc. Organ | 2 | ORG | 2 | |
| 72 | | 4 | BEL | | 36 | Sync Lead | . 1 | HLD | 300 | Organ 3 | 2 | ORG | 0 | |
| 73 | | 4 | BPD | | 37 | DualSyncLead | | HLD | 301 | Church Org.1 | | ORG | 0 | |
| | Bell Heaven | 2 | SYN | | 38 | | 2 | HLD | | Church Org.2 | | ORG | 1 | |
| | EP Heaven | 4 | SYN | | 239 | = | 4 | HLD | | Church Org.3 | | ORG | 2 | |
| 76 | RS Heaven | 2 | SPD | | 40 | • | 3 | HLD | | Reed Organ | 1 | ORG | 0 | |
| 77 | • | 2 | SYN | | 241 | | 4 | TEK | | Puff Organ | 2 | ORG | 1 | |
| 78 | | 1 | SPD | | 42 | | | TEK | | Accordion Fr | 1 | ACD | 0 | |
| 79 | RS Soft Pad1 | 3 | SPD | 2 | 243 | | 4 | TEK | | Accordion It | 1 | ACD | 1 | |
| 80 | RS Soft Pad2 | 4 | SPD | 2 | 244 | Minor Rave | 4 | TEK | 308 | Harmonica | 1 | HRM | 0 | |
| B1 | Saw Strings | 3 | SPD | 2 | 45 | Vox Lead | 2 | TEK | 309 | Bandoneon | 2 | ACD | 0 | |
| 82 | Spectre | 4 | BPD | 2 | 246 | Waspy Synth | 2 | TEK | 310 | Nylon-str.Gt | 1 | AGT | 0 | |
| 83 | Morph Pad | 4 | SPD | 2 | 247 | Technoheadz | 4 | TEK | 311 | Ukulele | 1 | AGT | 1 | |
| 84 | Comb Strings | 4 | STR | 2 | 248 | | 2 | PLS | 312 | Nylon Gt.o | 2 | AGT | 2 | |
| 35 | Combine | 2 | BPD | 2 | 249 | Cheese Saw | 1 | PLS | 313 | Nylon Gt.2 | 1 | AGT | 3 | |
| 36 | Soft Sweep | 4 | SPD | 2 | 250 | Acid Guitar | 2 | TEK | 314 | Steelstr.Gt | 1 | AGT | 0 | |
| 87 | Saws Sweep | 3 | SPD | 2 | 251 | BOG | 3 | TEK | 315 | 12-str.Gt | 2 | AGT | 1 | |
| 88 | CelestialPad | 3 | BPD | 2 | 252 | Impact Hit | 2 | HIT | 316 | Mandolin | 2 | AGT | 2 | |
| 89 | 4th Sweep | 4 | SPD | 2 | 253 | Double Hit | 2 | HIT | 317 | Steel + Body | 2 | AGT | 3 | |
| 90 | 5th Saws | 4 | BPD | 2 | 254 | Techno Hit | 1 | HIT | 318 | Jazz Gt. | 1 | EGT | 0 | |
| 91 | | 4 | BPD | 2 | 255 | Shock Wave | 2 | HIT | 319 | Pedal Steel | 1 | EGT | 1 | |
| | 7th Bell Pad | 2 | BPD | | 256 | | 1 | FX | 320 | Clean Gt. | 1 | EGT | 0 | |
| | | | | | | | | | | | | | | |
| oi | ce: number of v | oice | | I | ?re | set 129–256: MS | SB= | 66, LSB=0 | Pre: PC: | set 257–320: N Program | | | | |

Preset

| No. | Name V | oice | Category | LSB | PC | No. | Name V | oioo | Catagory | LCD | DC | N. | Nama | V-! | 0-4 | | |
|------------|-------------------------|--------|------------|--------|----------|------------|---------------------------|-----------|-----------------|--------|----------|------------|------------------------------|--------|------------|--------|------------|
| 321 | Chorus Gt. | 2 | EGT | 1 | 28 | 385 | | oice 1 | Category BRS | LSB | PC | No. | Name | Voice | Category | LSB | PC |
| 322 | Mid Tone GTR | | EGT | 2 | 28 | 386 | French Horns Fr.Horn 2 | 2 | BRS | 0 1 | 61 | 449 | Sitar | 1 | PLK | 0 | 105 |
| 323 | Muted Gt. | 1 | EGT | 0 | 29 | 387 | Brass 1 | 2 | BRS | 0 | 61 62 | 450 451 | Sitar 2 | 2 1 | PLK FRT | 1 0 | 105 |
| 324 | Funk Pop | 1 | EGT | 1 | 29 | 388 | Brass 2 | 2 | BRS | 1 | 62 | 452 | Banjo Shamisen | 1 | PLK | 0 | 106 107 |
| 325 | Funk Gt.2 | 2 | EGT | 2 | 29 | 389 | Synth Brass1 | 2 | SBR | 0 | 63 | 453 | Koto | 1 | PLK | 0 | 107 |
| 326 | Jazz Man | 2 | EGT | 3 | 29 | 390 | Pro Brass | 2 | SBR | 1 | 63 | 454 | Taisho Koto | 2 | PLK | 1 | 108 |
| 327 | Overdrive Gt | 1 | DGT | 0 | 30 | 391 | Oct SynBrass | 2 | SBR | 2 | 63 | 455 | Kalimba | 1 | PLK | 0 | 109 |
| 328 | Guitar Pinch | 2 | DGT | 1 | 30 | 392 | Jump Brass | 1 | SBR | 3 | 63 | 456 | Bagpipe | 1 | ETH | 0 | 110 |
| 329 | DistortionGt | 1 | DGT | 0 | 31 | 393 | Syn.Brass 2 | 2 | SBR | 0 | 64 | 457 | Fiddle | 1 | STR | 0 | 111 |
| 330 | Feedback Gt | 2 | DGT | 1 | 31 | 394 | SynBrass sfz | 1 | SBR | 1 | 64 | 458 | Shanai | 1 | ETH | 0 | 112 |
| 331 | Dist Rtm GTR | 1 | DGT | 2 | 31 | 395 | Velo Brass 1 | 2 | SBR | 2 | 64 | 459 | Tinkle Bell | 1 | BEL | 0 | 113 |
| 332 | Gt.Harmonics | 1 | EGT | 0 | 32 | 396 | Soprano Sax | 1 | SAX | 0 | 65 | 460 | Agogo | 1 | PRC | 0 | 114 |
| 333 | Gt.Feedback | 1 | EGT | 1 | 32 | 397 | Alto Sax | 1 | SAX | 0 | 66 | 461 | Steel Drums | 1 | MLT | 0 | 115 |
| 334 | Acoustic Bs. | 2 | BS | 0 | 33 | 398 | Tenor Sax | 2 | SAX | 0 | 67 | 462 | Woodblock | 1 | PRC | 0 | 116 |
| 335 | Fingered Bs. | 1 | BS | 0 | 34 | 399 | Baritone Sax | 1 | SAX | 0 | 68 | 463 | Castanets | 1 | PRC | 1 | 116 |
| 336 | Finger Slap | 2 | BS | 1 | 34 | 400 | Oboe | 1 | WND | 0 | 69 | 464 | Taiko | 1 | PRC | 0 | 117 |
| 337 | Picked Bass | 1 | BS | 0 | 35 | 401 | English Horn | 1 | WND | 0 | 70 | 465 | Concert BD | 1 | PRC | 1 | 117 |
| 338 | Fretless Bs. | 1 | BS | 0 | 36 | 402 | Bassoon | 1 | WND | 0 | 71 | 466 | Melo. Tom 1 | 1 | PRC | 0 | 118 |
| 339 | Slap Bass 1 | 1 | BS | 0 | 37 | 403 | Clarinet | 1 | WND | 0 | 72 | 467 | Melo. Tom 2 | 1 | PRC | . 1 | 118 |
| 340 | Slap Bass 2 | 1 | BS | 0 | 38 | 404 | Piccolo | 1 | FLT | 0 | 73 | 468 | Synth Drum | 1 | PRC | 0 | 119 |
| 341 | Synth Bass 1 | 1 | SBS | 0 | 39 | 405 | Flute | 1 | FLT | 0 | 74 | 469 | 808 Tom | 2 | PRC | 1 | 119 |
| 342 | SynthBass101 | 1 | SBS | 1 | 39 | 406 | Recorder | 1 | FLT | 0 | 75 | 470 | Elec Perc | 1 | PRC | 2 | 119 |
| 343 | Acid Bass Clavi Bass | 1 2 | SBS SBS | 2 | 39 | 407 | Pan Flute | 1 | FLT | 0 | 76 | 471 | Reverse Cym | | PRC | 0 | 120 |
| 344 345 | Hammer | 2 | SBS | 3 4 | 39 | 408 | Bottle Blow | 2 | FLT | 0 | 77 | 472 | Gt.FretNoise | 1 | AGT | 0 | 121 |
| 346 | Synth Bass 2 | 2 | SBS | 0 | 39 40 | 409 410 | Shakuhachi Whistle | 2 | ETH | 0 | 78 | 473 | Gt.Cut Noise | 1 | AGT | 1 | 121 |
| 347 | Beef FM Bass | 2 | SBS | 1 | 40 | 411 | Ocarina | 1 | FLT FLT | 0 0 | 79 | 474 | String Slap | 1 | AGT | 2 | 121 |
| 348 | Rubber Bass | 2 | SBS | 2 | 40 | 412 | Square Wave | 2 | HLD | 0 | 80 81 | 475 | Breath Noise Fl.Key Click | 1 | FX | 0 | 122 |
| 349 | Attack Pulse | 1 | SBS | 3 | 40 | 413 | MG Square | 1 | HLD | 1 | 81 | 476 477 | Seashore | 1 | FX SFX | 1 0 | 122 123 |
| 350 | Violin | 1 | STR | 0 | 41 | 414 | Sine Wave | 1 | HLD | 2 | 81 | 477 | Rain | 1 | SFX | 1 | 123 |
| 351 | Slow Violin | 1 | STR | 1 | 41 | 415 | Saw Wave | 2 | HLD | 0 | 82 | 479 | Thunder | 1 | SFX | 2 | 123 |
| 352 | Viola | 1 | STR | 0 | 42 | 416 | OB2 Saw | 1 | HLD | 1 | 82 | 480 | Wind | 1 | SFX | 3 | 123 |
| 353 | Cello | 1 | STR | 0 | 43 | 417 | Doctor Solo | 2 | HLD | 2 | 82 | 481 | Stream | 2 | SFX | 4 | 123 |
| 354 | Contrabass | 1 | STR | 0 | 44 | 418 | Natural Lead | 2 | HLD | 3 | 82 | 482 | Bubble | 2 | SFX | 5 | 123 |
| 355 | Tremolo Str | 1 | STR | 0 | 45 | 419 | SequencedSaw | 2 | HLD | 4 | 82 | 483 | Bird | 2 | SFX | 0 | 124 |
| 356 | PizzicatoStr | 1 | STR | 0 | 46 | 420 | Syn.Calliope | 2 | SLD | 0 | 83 | 484 | Dog | 1 | SFX | 1 | 124 |
| 357 | Harp | 1 | PLK | 0 | 47 | 421 | Chiffer Lead | 2 | SLD | 0 | 84 | 485 | HorseGallop | 1 | SFX | 2 | 124 |
| 358 | Yang Qin | 2 | PLK | 1 | 47 | 422 | Charang | 2 | HLD | 0 | 85 | 486 | Bird 2 | 1 | SFX | 3 | 124 |
| 359 | Timpani | 1 | PRC | 0 | 48 | 423 | Wire Lead | 2 | HLD | 1 | 85 | 487 | Telephone 1 | 1 | SFX | 0 | 125 |
| 360 | Strings | 1 | STR | 0 | 49 | 424 | Solo Vox | 2 | SLD | 0 | 86 | 488 | Telephone 2 | 1 | SFX | 1 | 125 |
| 361 | Orchestra | 3 | ORC | 1 | 49 | 425 | 5th Saw Wave | 2 | HLD | 0 | 87 | 489 | DoorCreaking | 1 | SFX | 2 | 125 |
| 362 | 60s Strings | 2 | STR | 2 | 49 | 426 | Bass & Lead | 2 | HLD | 0 | 88 | 490 | Door | 1 | SFX | 3 | 125 |
| 363 | Slow Strings | 1 | STR | 0 | 50 | 427 | Delayed Lead | 2 | HLD | 1 | 88 | 491 | Scratch | 1 | SFX | 4 | 125 |
| 364 | Syn.Strings1 | 1 | STR | 0 | 51 | 428 | Fantasia | 2 | SYN | 0 | 89 | 492 | Wind Chimes | 2 | SFX | 5 | 125 |
| 365 | Syn.Strings3 | 2 | STR | 1 | 51 | 429 | Warm Pad | 1 | SPD | 0 | 90 | 493 | Helicopter | 1 | SFX | 0 | 126 |
| | Syn.Strings2 | 2 | SPD | 0 | 52 | 430 | Sine Pad | 2 | SPD | 1 | 90 | | Car-Engine | 1 | SFX | 1 | 126 |
| 367 | Choir Aahs | 1 | VOX | 0 | 53 | | Polysynth | 2 | SYN | 0 | 91 | | Car-Stop | 1 | SFX | 2 | 126 |
| 368 | | 1 | VOX | 1 | 53 | 432 | Space Voice | 1 | VOX | 0 | 92 | | Car-Pass | 1 | SFX | 3 | 126 |
| 369 370 | Voice Oohs Humming | 1 | VOX | 0 | 54 54 | 433 | Itopia | 2 | VOX | 1 | 92 | 497 | Car-Crash | 2 | SFX | 4 | 126 |
| 371 | SynVox | 1 | VOX VOX | 1 0 | 54 55 | 434 435 | Bowed Glass Metal Pad | 2 | SPD | 0 | 93 | 498 | Siren | 1 | SFX | 5 | 126 |
| 372 | Analog Voice | 1 | VOX | 1 | 55 | | Halo Pad | 2 2 | BPD | 0 | 94 | | Train | 1 | SFX | 6 | 126 |
| 373 | OrchestraHit | 2 | HIT | 0 | 56 | 437 | Sweep Pad | 1 | BPD SPD | 0 0 | 95 06 | | Jetplane | 2 | SFX | 7 | 126 |
| 374 | Bass Hit | 2 | HIT | 1 | 56 | 438 | Ice Rain | 2 | SYN | 0 | 96 97 | | Starship Burst Noise | 2 | SFX | 8 | 126 |
| 375 | 6th Hit | 2 | HIT | 2 | 56 | 439 | Soundtrack | 2 | SPD | 0 | 98 | | Applause | 2 2 | SFX | 9 | 126 |
| 376 | Euro Hit | 2 | HIT | 3 | 56 | 440 | Crystal | 2 | BEL. | 0 | 99 | | Laughing | 1 | SFX SFX | 0 1 | 127 127 |
| 377 | Trumpet | 1 | BRS | 0 | 57 | 441 | Syn Mallet | 1 | BEL | 1 | 99 | | Screaming | 1 | SFX | 2 | 127 |
| 378 | Dark Trumpet | 1 | BRS | 1 | 57 | | Atmosphere | 2 | AGT | Ö | 100 | | Punch | 1 | SFX | 3 | 127 |
| 379 | Trombone | 1 | BRS | 0 | 58 | 443 | Brightness | 2 | SYN | 0 | 101 | | Heart Beat | 1 | SFX | 4 | 127 |
| 380 | Trombone 2 | 2 | BRS | 1 | 58 | 444 | Goblin | 2 | PLS | 0 | 102 | | Footsteps | 1 | SFX | 5 | 127 |
| 381 | Bright Tb | 1 | BRS | 2 | 58 | | Echo Drops | 1 | BPD | 0 | 103 | | Gun Shot | 1 | SFX | 0 | 128 |
| 382 | Tuba | 1 | BRS | 0 | 59 | 446 | Echo Bell | 2 | BPD | 1 | 103 | | Machine Gun | 1 | SFX | 1 | 128 |
| 383 | MutedTrumpet | 1 | BRS | 0 | 60 | 447 | Echo Pan | 2 | BPD | 2 | 103 | | Lasergun | 1 | SFX | 2 | 128 |
| 384 | MuteTrumpet2 | 1 | BRS | 1 . | 60 | 448 | Star Theme | 2 | BPD | 0 | 104 | | Explosion | 2 | SFX | 3 | 128 |
| | | | | | | | | | | | | | | | | | |

Voice: number of voice

Preset 321–512: MSB=121 PC: Program Number

Drum Set List

| | Preset | | | | | | | | | | | |
|---------------------|------------------------------|------------------|---------------------|------------|----------------------------|--------------|----------------------------|----------|---------------|---------|------------------------------|--------------|
| Note No. | 001 RS Pop Kit 1 | (PC: 1) | 002 RS Pop Kit 2 | (PC: 2) | 003 STANDARD 2 | (PC: 3) | 004 STANDARD 3 | (PC:4) | 005 R&B | (PC: 5) | 006 DANCE | (PC:6) |
| 25 | Snare Roll | | | | Snare Roll | | | | | | | |
| 26 | FingerSnaps2 | | % | | Finger Snap | | | | % | | | |
| 27 | High-Q | | | | High-Q | | | | | | | |
| 28 | Slap | [EVO7] | | | Slap ScratchPush | [EXC7] | | | | | Scrtch Push2 | [EXC7] |
| 29 | ScratchPush ScratchPull | [EXC7] [EXC7] | | | ScratchPull | [EXC7] | | | | | Scrtch Pull2 | [EXC7] |
| 30 | Sticks | [LXO7] | | | Sticks | [LXO7] | | | | | | |
| 31 | SquareClick | | | | SquareClick | | | | | | | |
| 33 | MetronmClick | | | | MetronmClick | | | | | | | |
| 34 | Metronm Bell | | | | Metronm Bell | | | | D0 D 15: 1 | | 000 O DD | |
| 35 | Pop Kick 1 | *3 | Pop Kick 3 | *3 | Std.2 Kick1 | | Std.3 Kick1 Std.3 Kick2 | *2 *2 | R&B Kick % | | 909 Comp BD Elec Kick 2 | |
| C2 36 | Pop Kick 2 Cross Stick | *3 *2 | Pop Kick 4 % | *3 | Std.2 Kick2 Side Stick | | SIU.3 KICKZ | 2 | % | | LIEC MON Z | |
| 38 | Pop Snare 1 | *2 | Pop Snare 3 | *2 | Std.2 Snare1 | | Piccolo SD2 | | % | | House SD | |
| 39 | Ghost Note | *2 | % | _ | 808 Clap | | | | % | | 909 HandClap | |
| 40 | Pop Snare 2 | *2 | Pop Snare 4 | *2 | Std.2 Snare2 | | Std.3 Snare2 | | R&B Snare | | Elec. Snare3 | |
| 41 | PopLoTomFla | m *2 | % | | Real Tom 6 | *2 | | | % | | Synth Drum 2 | *2 |
| 42 | PopClHiHat 1 | | PopClHiHat 2 | [EXC1] *2 | Jazz CHH | [EXC1] | Close HiHat3 | [EXC1] | % | | CR78 CHH Synth Drum 2 | [EXC1] *2 |
| 43 | PopLowTom | *2 | % DanBdUillat 0 | IEVC11*2 | Real Tom 6 Pedal HiHat | *2 [EXC1] | Pedal HiHat3 | [EXC1] | % % | | 808 CHH 1 | [EXC1] |
| 44 45 | PopPdHiHat 1 PopMdTomFla | | PopPdHiHat 2 % | [EXCI] 3 | Real Tom 4 | *2 | redai riii iato | [LXC1] | % | | Synth Drum 2 | *2 |
| 45 | PopOpHiHat 1 | | PopOpHiHat 2 | 2[EXC1] *3 | Jazz OHH | [EXC1] | Open HiHat3 | [EXC1] | % | | CR78 OHH | [EXC1] |
| 47 | PopMidTom | *2 | % | | Real Tom 4 | *2 | | | % | | Synth Drum 2 | *2 |
| C3 48 | PopHiTomFla | | % | | Real Tom 1 | *2 | | | % | | Synth Drum 2 | *2 |
| 49 | PopCymbal 2 | *2 | % | | Crash Cym.1 | | | | % | | 808 Crash | ** |
| 50 | PopHighTom | *2 | % | | Real Tom 1 | *2 | | | % % | | Synth Drum 2 606 RideCym. | *2 |
| 52 51 | Pop Ride 1 | *2 *2 | % | | Ride Cymbal ChinaCymbal | | | | % | | ReverseCymb | 1 |
| J.E. | PopCymbal 1 Pop Ride 2 | *2 | % % | | Ride Bell | | | | % | | | |
| 53 54 | Tambourine | 2 | 70 | | Tambourine | | | | | | Shake Tambrr | 1 |
| 55 | PopSplashCy | m | % | | Splash Cym. | | | | % | | Splash Cym.2 | |
| 56 | ChaChaBell | *2 | % | | Cowbell | | | | % | | 808 Cowbel | |
| 57 | RockCrashCy | m *2 | % | | Crash Cym.2 | | | | % | | | |
| — 58 | Vibraslap | | | | Vibraslap | | | | 9/ | | | |
| 59 | RockRideCyn | | % | | Ride Cymbal High Bongo | | | | % % | | | |
| C4 60 | Pop Hi Bongo Pop Lo Bongo | | % | | Low Bongo | | | | % | | | |
| 62 61 | PopCongaSla | | % | | HiConga Mute |) | | | % | | | |
| 63 | PopCongaOp | | % | | HiCongaOpen | Į. | | | % | | | |
| 64 | Pop Lo Conga | | % | | LoCongaOper | ו | | | % | | | |
| 65 | PopHiTimbale | | % | | High Timbale | | | | % | | | |
| 66 | PopLoTimbal | е | % | | Low Timbale | | | | % % | | | |
| 67 | Pop Agogo Pop Agogo | | % % | | Agogo Agogo | | | | % | | | |
| — <u>68</u> | Pop Shaker2 | | % | | Cabasa | *2 | | | % | | | |
| 70 | Pop Shaker1 | *2 | % | | Maracas | | | | % | | | |
| 71 | ShortWhistle | [EXC2] | | | ShortWhistle | [EXC2] | | | | | | |
| C5 72 | Long Whistle | [EXC2] | | | Long Whistle | [EXC2] | | | 0/ | | | |
| 73 | Pop Quide1 | [EXC3] | % | | Short Guiro | [EXC3] | | | % % | | | |
| 74 | Pop Quide2 | [EXC3] *2 | % | | Long Guiro Claves | [EXC3] | | | % | | | |
| 75 76 | Pop Claves Woodblock | 2 | /0 | | Woodblock | | | | 70 | | | |
| | Woodblock | | | | Woodblock | | | | | | | |
| 77 78 | Mute Cuica | [EXC4] | | | Mute Cuica | [EXC4] | | | | | Hoo | [EXC4] |
| 79 | Open Cuica | [EXC4] | | | Open Cuica | [EXC4] | | | | | Hoo | [EXC4] |
| 80 | MuteTriangle | | | | MuteTriangle | [EXC5] | | | | | | |
| 81 | OpenTriangle | | | | OpenTriangle | [EXC5] | | | 0/ | | 626 Shaker | |
| 82_ 83 | Pop Shaker3 | | % | | Shaker Jingle Bell | | | | % | | UZU GHAREI | |
| | Jingle Bell Bell Tree | | % | | Bar Chimes | | | | % | | Bell Tree | |
| C6 84 | Castanets | | 70 | | Castanets | | | | | | | |
| — <u> 85</u> 86 | Mute Surdo | [EXC6] | | | Mute Surdo | [EXC6] | | | | | | |
| 87 | Open Surdo | [EXC6] | | | Open Surdo | [EXC6] | | | | | | |
| 88 | Applause 2 | *2 | | | Applause 2 | *2 | | | | | | |
| | - | | | | | | | | | | | |

^{*} User:001 and User:002 contain the same data as Preset:001 and Preset:004, respectively. (User 001, 002: MSB=64, LSB=0)

^{*} See p. 154 for information concerning Note Nos. 0–24 and 89–127.

^{*2:} Tones which are created using two voices.

^{*3:} Tones which are created using three voices.

 $[\]hbox{[EXC]:} \ \ \hbox{Percussion sound of the same number will not be heard at}$

the same time.

^{%:} Same as the percussion sound of "001: RS Pop Kit 1."
Blank: Same as the percussion sound of "003: STANDARD 2."

PC: Program Number

Preset 001–006: MSB=65, LSB=0

Drum Set List

| | Preset | | | | | | | | | | |
|----------------------------|--|---|---|------------------|---|---|--|--------------------|----------------------------|---|----------------------|
| No <u>te N</u> | | (PC: 7) | 008 HIP HOP | (PC: 8) | 009 TECHNO | (PC: 9) | 010 TR-909 | (PC: 10) | Note No. | 011 RHYTHM FX | (PC:11) |
| 26 28 28 | FingerSnaps2 | | FingerSnaps2 | | FingerSnaps2 | | FingerSnaps2 | | 21 23 | RevBsAtkNoiz RevClnGtMtUp RevDstGCutUp | |
| 29 31 32 | | [EXC7] [EXC7] | Scrtch Push2 Scrtch Pull2 | [EXC7] | Scrtch Push2 Scrtch Pull2 | [EXC7] [EXC7] | Scrtch Push2 Scrtch Pull2 | [EXC7] | C1 24 25 26 27 28 | Click Pop Drop Wood Slap Syn.Drops Rev.Hi-Q ShortWhistle | |
| 35 | HipHop BD2 | | | | | | Techno BD2 | | ²⁹ 30 | lce Block Digi Tambrn. | *2 |
| C2 36 38 40 | House SD | *2 | HipHop BD1 808 Rimshot Whack SD 2 909 HandClap HipHop SD2 | | Techno BD1 808 Rimshot Techno SD 1 707 Claps MG Blip | | 909 BD2 909 Rim 909 SD 1 909 HandClap 909 SD 2 | *2 | 33 33 34 35 | Alias Tambourine Noise Slap Rev.Kick 1 Rev.Kick 1 | *2 |
| 41 42 | 909 Tom 707 CHH 1 | [EXC1] | 909 Tom Room CHH | [EXC1] | 808 Tom 2 707 CHH 1 | *2 [EXC1] | 909 Tom 707 CHH 1 | [EXC1] | C2 36 37 | Rev.ConBD Rev.PowerBD1 | |
| 43 45 | | [EXC1] | 909 Tom Pedal HiHat | [EXC1] | 808 Tom 2 CR78 CHH | *2 [EXC1] | 909 Tom 707 CHH 2 | [EXC1] | 40 39 | Rev.Elec.BD1 RevBrBsDrum | |
| 47 | 909 Tom | [EXC1] | 909 Tom R8 OHH 2 909 Tom | [EXC1] | 808 Tom 2 909 OHH 808 Tom 2 | *2 [EXC1] *2 | 909 Tom 909 OHH 909 Tom | [EXC1] | 41 42 | Rev.909BD2 Rev.909BD2 Rev.HpHpBD1 | |
| C3 48 49 50 51 | 909 Tom | *2 | 909 Tom 909 Crash 909 Tom | | 808 Tom 2 909 Crash 808 Tom 2 | *2 *2 | 909 Tom 909 Crash 909 Tom 909 RideCym. | *2 | 44 45 47 | Rev.HpHpBD1 Rev.HpHpBD1 Rev.Tech BD2 Rev.Snare 1 | |
| 53 54 55 55 | Splash Cym.2 808 Cowbel | ı | Shake Tambrn Splash Cym.2 808 Cowbel | | ReverseCymb Shake Tambrr Splash Cym.2 808 Cowbel | | Tambourine 2 Splash Cym.2 808 Cowbel | 2 | C3 48 49 50 51 52 | Rev.Snare 1 Rev.Snare 2 Rev.Std1SD1 Rev.808SD Rev.909SD1 | |
| 57 59 | 909 Crash | | | | 909 Crash | | RideCym Edge | <u>.</u> | 53 54 | Rev.CR78SD1 Rev.Tech SD2 Rev.HpHpSD2 | |
| C4 60 61 62 63 64 | 808 Conga | | | | CR78 HiBongo CR78 LoBongo 808 Conga 808 Conga 808 Conga | | | | 55 56 57 59 59 | Rev.HpHpSD2 Rev.HpHpSD2 Rev House SD Rev House SD Rev.Snare 1 | |
| 65 67 68 69 71 | | | 808 Maracas | | 808 Maracas | | 808 Maracas | | 61 62 64 65 66 | Rev.Hi-Q Rev.Tom 1 Rev.Tom 1 Rev.Tom 1 Rev.Tom 2 | |
| C5 72 73 | | *************************************** | | | | | | ••••• | 67 68 | Rev.Sticks Rev.Slap | |
| 74 76 | CR78 Guiro | [EXC3] | CR78 Guiro 808 Clave | [EXC3] | CR78 Guiro 808 Clave | [EXC3] | CR78 Guiro 808 Clave | [EXC3] | 71 70 71 C5 72 | ReverseCymbl Rev.Cymbal2 Rev.606Cym. Rev.RideCym. | |
| 77 79 80 | Hoo | [EXC4] [EXC4] | Ноо Ноо | [EXC4] [EXC4] | Ноо Ноо | [EXC4] | Ноо Ноо | [EXC4] [EXC4] | 74 74 75 | Rev.ClosedHH Rev.707CH Rev.808CHH Rev.Open HH1 | |
| 81 82 83 | 626 Shaker | | 626 Shaker | | 626 Shaker | | 626 Shaker | | 77 78 | Rev.Open HH2 Rev.808OHH Rev.CR-78OHH | |
| C6 84 86 88 | | | Bell Tree | | Bell Tree | | Bell Tree | | 81 82 83 C6 84 | Rev.CR-78OHH Rev.HpHpSD2 Shaker Rev.Slap Rev.Tombrn 2 | |
| | 54 for information (except 011: RHY | | | | [EXC]: Percus heard Blank: Same a "003: S | ssion sour at the san as the per STANDA um Numb | ne time. cussion sound RD 2." er | number will not be | 85 86 | Rev.ShakeTmb Rev.707Crash Rev.Belltree Rev.Guiro Rev.GunShot Rev.Lasergun VeloNoiseFX St.NoiseClap Swish Tape Stop 1 Missile Space Birds FlyingMonstr Voice 1 Hoo | *2 *2 *2 *2 |

| | Preset | | | | | | | | | | | |
|----------------------------|--|----------------------------|--|------------------------|--|----------|--|------------------------|---|------------------------|--|----------|
| Note No. | 012 STANDARD 1 | (PC: 1) | 013 ROOM | (PC: 9) | 014 POWER | (PC: 17) | 015 ELECTRONIC | (PC: 25) | 016 TR-808 | (PC: 26) | 017 JAZZ | (PC: 33) |
| 25 26 27 | Snare Roll FingerSnaps2 High-Q | | Finger Snap | | | | Finger Snap | | | | Finger Snap | |
| 28 29 30 | Slap ScratchPush ScratchPull Sticks | [EXC7] [EXC7] | | | | | Scrtch Push2 Scrtch Pull2 | [EXC7] | Scrtch Push2 Scrtch Pull2 | [EXC7] [EXC7] | | |
| 31 32 33 34 35 | SquareClick MetronmClick Metronm Bell Mix Kick | | Room Kick 2 | | Power Kick2 | | Elec Kick 2 | | 808 Kick 1 | | Jazz Kick 2 | |
| C2 36 37 | Std.1 Kick2 Side Stick | | Room Kick 1 | | Power Kick1 | | Elec Kick 1 | *2 | 808 Kick 2 808 Rimshot | | Jazz Kick 1 | |
| 38 40 | Std.1 Snare1 909 HandClap LD Snare M | | Room Snare 1 808 Clap Room Snare 2 | | Dance Snare1 808 Clap Power Snare1 | | Elec. Snare1 808 Clap Elec. Snare2 | | 808 Snare 1 808 Clap 808 Snare 2 | ** | Jazz Snare 1 Hand Clap2 Jazz Snare 2 | |
| 41 42 | Real Tom 6 Close HiHat2 Real Tom 6 | *2 [EXC1] *2 | Room Tom 5 Room CHH Room Tom 5 | *2 [EXC1] *2 | Rock Tom 4 Rock Tom 4 | *2 *2 | Synth Drum 2 Jazz CHH Synth Drum 2 | [EXC1] *2 | 808 Tom 2 808 CHH 2 808 Tom 2 | *2 [EXC1] *2 | Jazz CHH | [EXC1] |
| 44 45 46 | Pedal HiHat2 Real Tom 4 Open HiHat2 | [EXC1] *2 [EXC1] | Pedal HiHat Room Tom 2 R8 OHH 2 | [EXC1] *2 [EXC1] | Rock Tom 4 | *2 | Pedal HiHat Synth Drum 2 Jazz OHH | [EXC1] *2 [EXC1] | 808 CHH 1 808 Tom 2 808 OHH | [EXC1] *2 [EXC1] | Pedal HiHat Jazz OHH | [EXC1] |
| 47 C3 48 | Real Tom 4 Real Tom 1 | *2 *2 | Room Tom 2 | *2 *2 | Rock Tom 4 Rock Tom 1 | *2 *2 | Synth Drum 2 Synth Drum 2 | *2 | 808 Tom 2 808 Tom 2 | *2 *2 | | |
| 50 51 | Crash Cym.1 Real Tom 1 Ride Cymbal | *2 | Room Tom 2 | *2 | Rock Tom 1 | *2 | Synth Drum 2 | | 808 Crash 808 Tom 2 606 RideCym | *2 | RideCymMidli | า |
| 52 53 54 | ChinaCymbal Ride Bell Tambourine | | | | | | ReverseCymb |)i | CR78 Tmb | | | |
| 55 56 57 58 | Splash Cym.2 Cowbell Crash Cym.2 Vibraslap | | Splash Cym. | | | | Splash Cym. | | 808 Cowbel 909 Crash | | | |
| 59 C4 60 61 | Ride Cymbal High Bongo Low Bongo | | | | | | | | RideCym Edg CR78 HiBong CR78 LoBong | 0 | RideCym Edg | e |
| 62 64 | HiConga Mute HiCongaOper LoCongaOper High Timbale | ı | | | | | | | 808 Conga 808 Conga 808 Conga | | | |
| 65 67 — 68 | Low Timbale Agogo Agogo | | | | | | | | | | | |
| 69 71 | Cabasa Maracas ShortWhistle | *2 [EXC2] | | | | | | | 808 Maracas | | | |
| C5 72 73 74 75 | Long Whistle Short Guiro Long Guiro Claves | [EXC2] [EXC3] [EXC3] | | | | | | | CR78 Guiro 808 Clave | [EXC3] | | |
| 76 77 78 | Woodblock Woodblock Mute Cuica | [EXC4] | | | | | | | Ноо | [EXC4] | | |
| 79 80 81 82 | Open Cuica MuteTriangle OpenTriangle Shaker Jingle Bell | [EXC4] [EXC5] [EXC5] | | | | | | | Hoo 626 Shaker | [EXC4] | | |
| C6 84 85 | Bell Tree Castanets Mute Surdo | [EXC6] | | | | | | | | | | |
| 88 87 | Open Surdo Applause 2 | [EXC6] *2 | | | | | | | | | Applause | *2 |

^{*} See p. 154 for information concerning Note Nos. 0–24 and 89–127.

^{*2:} Tones which are created using two voices.

[[]EXC]: Percussion sound of the same number will not be heard at

the same time.

Blank: Same as the percussion sound of "012: STANDARD 1."

PC: Program Number Preset 012–017: MSB=120, LSB=0

| Note No. 25 26 27 29 30 31 32 33 34 35 C2 36 37 38 40 | BRUSH Finger Snap Jazz Kick 2 Jazz Kick 1 | | ORCHESTRA Finger Snap Jazz CHH Pedal HiHat Jazz OHH Ride Cymbal | [EXC1] [EXC1] [EXC1] |
|--|--|--------------|--|----------------------------|
| 26 27 28 29 30 31 32 33 34 35 C2 36 37 38 39 | Jazz Kick 2 | | Jazz CHH Pedal HiHat Jazz OHH | [EXC1] |
| 29 30 31 32 33 34 35 C2 36 37 38 39 | | | Pedal HiHat Jazz OHH | [EXC1] |
| 30 31 32 33 34 35 C2 36 37 38 | | | Jazz OHH | |
| 30 31 32 33 34 35 C2 36 37 38 | | | Ride Cymbal | |
| 32 33 34 35 C2 36 37 38 | | | | |
| 34 35 C2 36 37 38 | | | | |
| 35 C2 36 37 38 39 | | | | |
| C2 36 37 38 39 | | | Jazz Kick 1 | |
| 38 | | | Concert BD | |
| 39 | Brush Tap | | ConcertSnare | |
| 40 | Brush Slap | | Castanets | |
| | Brush Swirl | | ConcertSnare | |
| 41 42 | Lite Tom 4 Brush CHH | *2 [EXC1] | Timpani Timpani | |
| 43 | Lite Tom 4 | *2 | Timpani | |
| 45 | Pedal HiHat Lite Tom 4 | [EXC1] *2 | Timpani Timpani | |
| 47 46 | Brush OHH | [EXC1] | Timpani | |
| <u> </u> | Lite Tom 4 | *2 | Timpani | |
| C3 48 49 | Lite Tom 4 Brush Crash | *2 | Timpani Timpani | |
| 50 | Lite Tom 4 | *2 | Timpani | |
| 52 51 | Ride Cym In | | Timpani Timpani | |
| 53 | Brush RideBl | | Timpani | |
| 54 | | | Splash Cym. | |
| 55 56 | | | Opiasii Oyiii. | |
| 57 58 | | | ConcertCym.2 | |
| 50 | RideCym Edge | | ConcertCym.1 | |
| C4 60 | | | | |
| — <u>61</u> | | | | |
| 64 63 | | | | |
| | | | | |
| 65 66 | | | | |
| 67 68 | | | | |
| 69 | | | | |
| 71 70 | | | | |
| C5 72 | *************************************** | | | |
| — [73 | | | | |
| 74 75 | | | | |
| 76 | | | | |
| 77 78 | | | | |
| 79 | | | | |
| <u>80</u> | | | | |
| 82 | | | | |
| 83 | | | | |
| C6 84 — 85 | | | | |
| 86 | | | | |
| 88 | Applause | *2 | Applause | *2 |
| | t column for in | | • • | es which are o |

| * | See the right column for information |
|---|--------------------------------------|
| | concerning Note Nos. 0-24 and 89- |
| | 127, (except 020: SFX). |

created using two voices.

*3: Tones which are created using three voices.

[EXC]: Percussion sound of the same number will not be heard at the same time.

Same as the percussion sound of "012: STANDARD 1."

Program Number Preset 018-020: MSB=120, LSB=0

Note No. 0-24, 89-127

| Note No. | SFX | (, | | Note No. | | | |
|-----------------|--|--------------|-----|----------------|---|----------|---|
| 29 30 | MG Blip Tape Stop 2 Scrtch Push2 | *2 [EXC1] | C-1 | 0 | Mix Kick Std.1 Kick2 Std.3 Kick1 | *2 | |
| 32 33 34 | Scrtch Pull2 Finger Snap FingerSnaps2 | [EXC1] | | 4 3 | Std.3 Kick2 Room Kick 1 | *2 | |
| 35 | Gtr.Feedback Dist.CutNoiz | | | 5 6 7 | Room Kick 2 Power Kick1 Power Kick2 | | |
| 37 38 39 | Bass Slide Pick Scrape High-Q | | | 8 9 10 | Jazz Kick 1 Concert BD Elec Kick 1 | *2 | |
| 41 42 | Slap ScratchPush ScratchPull | [EXC7] | C0 | 12 | Elec Kick 2 808 Kick 1 808 Kick 2 | | |
| 43 44 45 | Sticks SquareClick MetronmClick | | | 14 16 | 909 BD2 909 Comp BD HipHop BD1 | *2 | |
| 47 | Metronm Bell Gt.FretNoise Gt.Cut Noise | | | 17 18 | HipHop BD2 Techno BD1 | | |
| 48 | Gt.Cut Noise String Slap | | | 19 20 21 | Techno BD2 R&B Kick | *3 | |
| 52 51 | FI.Key Click Laughing | | | 23 | Pop Kick 1 Pop Kick 2 Pop Kick 3 | *3 *3 | |
| 53 54 | Screaming Punch Heart Beat | | C1 | 24 | Pop Kick 4 | *3 | • |
| 56 | Footsteps | | | | | | |

020

Footsteps

Applause DoorCreaking Door Scratch Wind Chimes

Car-Engine Car-Stop Car-Pass Car-Crash

Jetplane

Helicopter Starship

Gun Shot Machine Gun Lasergun Explosion

Dog HorseGallop Bird

Rain

Kitty Bird 2 Growl Applause 2

Encore

Ghost

Submarine

Emergency!

Abduction

7th Atmos.

Angklung

UFO FX

Big Shot

Wind 2

Hoo

Telephone 1 Telephone 2 Burst Noise

Thunder Wind Seashore Stream Bubble

70

80

85

90

*2

*2

*2

*2

*2

*2

*2

*2

[EXC2] *2

[EXC2] *2

[EXC2] *2

[EXC2] *2

*2

(PC: 57)

| | 89 | Std.1 Snare1 | |
|-----|---------------------|------------------------------|----------|
| | 90 | LD Snare M | |
| | 91 | Std.2 Snare1 | |
| | 92 | Std.2 Snare2 | |
| | 93 | Piccolo SD2 | |
| | 95 | Std.3 Snare2 | |
| | | Room Snare 1 | |
| C7 | 96 | Room Snare 2 | |
| | 97 | Dance Snare1 | |
| | 98 | Power Snare1 Jazz Snare 1 | |
| | 100 | Jazz Snare 1 Jazz Snare 2 | |
| | | Brush Tap | |
| | 101 102 | Brush Slap | |
| | 103 | Brush Swirl | |
| | 104 | ConcertSnare | |
| | 105 | Elec. Snare1 | |
| | 106 | Elec. Snare2 | |
| | 107 | Elec. Snare3 | |
| C8 | 108 | 808 Snare 1 | |
| Co. | 109 | 808 Snare 2 | |
| | 110 | 909 Snare 1 | |
| | 111 | 909 SD 1 | |
| | 112 | 909 SD 2 | |
| | 113 | CR78 SD 1 | |
| | 114 | Whack SD 2 | |
| | 115 | HipHop SD2 | |
| | 116 | Techno SD 1 | |
| | 117 | MG Blip | |
| | 118 119 | House SD | |
| | | House SD | |
| C9 | | R&B Snare | *2 |
| | 121 | Pop Snare 1 | *2 |
| | 122 | Pop Snare 2 | *2 |
| | 123 124 | Pop Snare 3 Pop Snare 4 | *2 *2 |
| | | Rev. Snare | 2 |
| | 125 126 | Cross Stick | *2 |
| | | Ghost Note | *2 |
| | 127 | 5.7001 71010 | - |
| | | | |

Arpeggio Style List

| Style | Motif | Beat Pattern |
|----------------|---|---|
| 1/4 | all | 1/ 4 |
| /6 | all | 1/6 |
| /8 | all | 1/ 8 |
| /12 | all | 1/12 |
| /16 | all | 1/16 1–3 |
| /32 | SINGLE UP, SINGLE DOWN, SINGLE UP&DOWN, SINGLE RANDOM, DUAL UP, DUAL DOWN, DUAL UP&DOWN, DUAL RANDOM, NOTE ORDER, GLISSANDO, BASS+UP 1–8, BASS+RANDOM 1–3, TOP+UP 1–6 | 1/32 1–3 |
| PORTAMENTO A | all | PORTA-A 01-11 |
| ORTAMENTO B | all | PORTA-B 01-15 |
| SLISSANDO | GLISSANDO | 1/16 1–3, 1/32 1–3 |
| EQUENCE A | all | SEQ-A 1-7 |
| EQUENCE B | all | SEQ-B 1-5 |
| SEQUENCE C | SINGLE UP, SINGLE DOWN, SINGLE UP&DOWN, SINGLE RANDOM, DUAL UP, DUAL DOWN, DUAL UP&DOWN, DUAL RANDOM, NOTE ORDER, GLISSANDO, BASS+UP 1–8, BASS+RANDOM 1–3, TOP+UP 1–6 | SEQ-C 1–2 |
| SEQUENCE D | all | SEQ-D 1-8 |
| СНО | SINGLE UP, SINGLE DOWN, SINGLE UP&DOWN, SINGLE RANDOM, DUAL UP, DUAL DOWN, DUAL UP&DOWN, DUAL RANDOM, NOTE ORDER | ECHO 1-3 |
| SYNTH BASS | BASS+UP 2 | SEQ-A 1, SEQ-C 1 |
| HEAVY SLAP | BASS+UP 5, TOP+UP 5 | MUTE 02, 03 |
| IGHT SLAP | BASS+UP 5, TOP+UP 5 | MUTE 02, 03 |
| VALK BASS | SINGLE UP, SINGLE DOWN, SINGLE UP&DOWN, SINGLE RANDOM, NOTE ORDER, GLISSANDO | REFRAIN 1, WALKBS |
| RHYTHM GTR 1 | SINGLE UP, SINGLE DOWN, SINGLE UP&DOWN, SINGLE RANDOM, DUAL UP, DUAL DOWN, DUAL UP&DOWN, DUAL RANDOM, NOTE ORDER, BASS+UP 1–8, BASS+RANDOM 1–3, TOP+UP 1–6 | MUTE 01, 04 |
| RHYTHM GTR 2 | CHORD | MUTE 07, 13, 14 |
| RHYTHM GTR 3 | CHORD | MUTE 08, 12, 15 |
| RHYTHM GTR 4 | CHORD | MUTE 09, 10, 11, 16 |
| RHYTHM GTR 5 | SINGLE UP, SINGLE DOWN | STRUM 1-6 |
| FINGER GTR | BASS+UP+TOP | SEQ-A 7 |
| STRUM GTR UP | SINGLE UP | STRUM 7-8 |
| STRUM GTR DOWN | SINGLE DOWN | STRUM 7-8 |
| STRUM GTR U&D | SINGLE UP&DOWN | STRUM 7-8 |
| PIANO BACKING | CHORD | MUTE 12, REFRAIN 2 |
| CLAVI CHORD | BASS+CHORD 4, BASS+CHORD 5 | MUTE 05, 06 |
| VALTZ | BASS+CHORD 2, BASS+UP 2, BASS+RANDOM 2, TOP+UP 2 | 1/ 6, 1/12 |
| SWING WALTZ | BASS+CHORD 2, BASS+UP 2, BASS+RANDOM 2, TOP+UP 2 | 1/16 1–3 |
| REGGAE | CHORD, BASS+CHORD 1 | REGGAE 1-2 |
| PERCUSSION | SINGLE UP, SINGLE DOWN, SINGLE UP&DOWN, SINGLE RANDOM, DUAL UP, DUAL DOWN, DUAL UP&DOWN, DUAL RANDOM, NOTE ORDER, BASS+UP 1-8, BASS+RANDOM 1-3, TOP+UP 1-6 | PERC 1-4 |
| HARP | SINGLE UP, SINGLE DOWN, SINGLE UP&DOWN, GLISSANDO | HARP |
| SHAMISEN | TOP+UP 4-6 | SEQ-A 2 |
| BOUND BALL | SINGLE UP, SINGLE DOWN, SINGLE UP&DOWN, SINGLE RANDOM, DUAL UP, DUAL DOWN, DUAL UP&DOWN, DUAL RANDOM, NOTE ORDER, GLISSANDO | BOUND |
| RANDOM | SINGLE RANDOM, DUAL RANDOM, BASS+RANDOM 1-3 | 1/ 4, 1/6, 1/8, 1/12, 1/16 1–3, 1/32 1–3, RANDOM |
| BOSSA NOVA | all | BOSSA NOVA |
| SALSA | all | SALSA 1–4 |
| ИАМВО | all | MAMBO 1-2 |
| ATIN PERC | SINGLE UP, SINGLE DOWN, SINGLE UP&DOWN, SINGLE RANDOM, DUAL UP, DUAL DOWN, DUAL UP&DOWN, DUAL RANDOM, NOTE ORDER, GLISSANDO | CLAVE, REV CLA, GUIRO, AGOGO |
| SAMBA | all | SAMBA |
| TANGO | all | TANGO 1–4 |
| HOUSE | all | HOUSE 1-2 |
| LIMITLESS | all | all |

^{*} all: there is no restriction on the value which can be set

Model: RS-5/9 (64-voice synthesizer (conforms to General MIDI 2 System))

Date: Oct. 13, 2000 Version: 1.00

1. Receive data

■Channel Voice Messages

* Not received when the Part parameter Rx Channel is set to OFF.

●Note off

 Status
 2nd byte
 3rd byte

 8nH
 kkH
 vvH

 9nH
 kkH
 vVH

 n = MIDI channel number:
 0H - FH (ch.1 - ch.16)

 kk = note number:
 00H - 7CH (0 - 124)

 vv = note off velocity:
 00H - 7FH (0 - 127)

* The velocity values of Note Off messages are ignored.

●Note on

 Status
 2nd byte
 3rd byte

 9nH
 kkH
 vrH

 n = MIDI channel number:
 0H - FH (tch.1 - ch.16)

 kk = note number:
 00H - 7CH (0 - 124)

 vv = note on velocity:
 01H - 7FH (1 - 127)

●Control Change

OBank Select (Controller number 0, 32)

| <u>Status</u> | 2nd byte | | 3rd byte |
|---------------|----------|--------|----------|
| BnH | 00H | | mmH |
| BnH | 20H | | llH |
| 3 (177) | | OT T T | |

n = MIDI channel number: 0H - FH (ch.1 - ch.16

mm, ll = Bank number: 00H 00H - 7FH 7FH (bank.1 - bank.16384)

- * Bank Select is not received when "GM1 System On" is received. If "GM System Off" is received, then reception of Bank Select is enabled.
- Bank Select processing will be suspended until a Program Change message is received.
- * The Tones and Drum Sets corresponding to each Bank Select are as follows.

Tone

| BANK SELECT MSB | BANK SELECT LSB | PROGRAM NUMBER | TONE GROUP | TONE NUMBER |
|--------------------------------|--------------------------|---|---------------------------------------|--|
| 000 - 032 064 065 066 | 000 000 000 000 | 001 - 128 001 - 128 001 - 128 001 - 128 001 - 128 | Preset (GM) User Preset Preset Preset | 257 - 512 001 - 128 001 - 128 129 - 256 |
| 121 | 000 - 009 | 001 - 128 | Preset(GM) | 257 - 512 |

Drum Set

| BA MS | NK SELECT B | BANK SELECT LSB | PROGRAM NUMBER | DRUMSET GROUP | DRUMSET NUMBER |
|----------------------|----------------|--------------------------|--|--|--|
| === | ========= | | | ========== | |
| 00 06 06 12 | 4 5 | 000 000 000 000 | 001 - 057 001 - 002 001 - 011 001 - 057 | Preset (GM) User Preset Preset (GM) | 012 - 020 001 - 002 001 - 011 012 - 020 |

OModulation (Controller number 1)

 Status
 2nd byte
 3rd byte

 BnH
 01H
 vvH

 n = MIDI channel number:
 0H - FFH (ch.1 - ch.16)

 vv = Modulation depth:
 00H - 7FH (0 - 127)

OPortamento Time (Controller number 5)

 Status
 2nd byte

 BnH
 05H
 vvH

 n = MIDI channel number:
 0H - FFH (ch.1 - ch.16)

 vv = Portamento Time:
 00H - 7FH (0 - 127)

- This adjusts the rate of pitch change when Portamento is ON or when using the Portamento Control. When Portamento Time is 0, portamento will be OFF.
- Portamento Time, a Part parameter, is modified.

OData Entry (Controller number 6, 38)

 Status
 2nd byte
 3rd byte

 BnH
 06H
 mmH

 BnH
 26H
 IIH

 n = MIDI channel number:
 0H - FH (ch.1 - ch.16)

 mm, ll = the value of the parameter specified by RPN/NRPN

 mm = MSB. II = LSB

OVolume (Controller number 7)

 Status
 2nd byte
 3rd byte

 BnH
 07H
 vvH

 n = MIDI channel number:
 0H - FFH (ch.1 - ch.16)

 vv = Volume:
 00H - 7FH (0 - 127)

- * Volume messages are used to adjust the volume balance of each Part.
- * Level, a Part parameter, is modified.

OPan (Controller number 10)

 Status
 2nd byte
 3rd byte

 BnH
 0AH
 vvH

 n = MIDI channel number:
 0H - FH (ch.1 - ch.16)

vv = pan: 00H - 40H - 7FH (Left - Center - Right)

- * Pan, a Part parameter, is modified.
- * For Drum Parts, this is a relative adjustment of each Instrument's pan setting.

OExpression (Controller number 11)

 Status
 2nd byte
 3rd byte

 BnH
 0BH
 vH

 n = MIDI channel number:
 0H - FH (ch.1 - ch.16)

 vv = Expression:
 00H - 7FH (0 - 127)

 It can be used independently from Volume messages. Expression messages are used for musical expression within a performance; e.g., expression pedal movements, crescendo and despressed.

OEffect Control 1 (Controller number 12)

 Status
 2nd byte
 3rd byte

 BnH
 0CH
 vvH

 n = MIDI channel number:
 0H - FFH (ch.1 - ch.16)

 vv = Control value:
 00H - 7FH (0 - 127)

OEffect Control 2 (Controller number 13)

 Status
 2nd byte
 3rd byte

 BnH
 0DH
 vvH

 n = MIDI channel number:
 0H - FH (ch.1 - ch.16)

 vv = Control value:
 00H - 7FH (0 - 127)

OHold 1 (Controller number 64)

 $\begin{tabular}{lll} Status & 2nd byte \\ BnH & 40H & vvH \\ n = MIDI channel number: & 0H - FH (ch.1 - ch.16) \\ \end{tabular}$

 $vv = Control \ value:$ 00H - 7FH (0 - 127) 0-63 = OFF, 64-127 = ON

OPortamento (Controller number 65)

 Status
 2nd byte
 3rd byte

 BnH
 41H
 vvH

 n = MIDI channel number:
 0H - FH (ch.1 - ch.16)

vv = Control value: 00H - 7FH (0 - 127) 0-63 = OFF, 64-127 = ON

* Portamento Switch, a Part parameter, is modified.

OSostenuto (Controller number 66)

 Status
 2nd byte
 3rd byte

 BnH
 42H
 vvH

 n = MIDI channel number:
 0H - FH (ch.1 - ch.16)

vv = Control value: 00H - 7FH (0 - 127) 0-63 = OFF, 64-127 = ON

OSoft (Controller number 67)

 Status
 2nd byte
 3rd byte

 BnH
 43H
 vvH

 n = MIDI channel number:
 0H - FH (ch.1 - ch.16)

vv = Control value: 00H - 7FH (0 - 127) 0-63 = OFF, 64-127 = ON

OResonance (Controller number 71)

 Status
 2nd byte
 3rd byte

 BnH
 47H
 vvH

n=MIDI channel number: 0H - FH (ch.1 - ch.16) vv = Resonance value (relative change): 00H - 40H - 7FH (-64 - 0 - +63)

* Filter Resonance, a Tone parameter, is modified.

ORelease Time (Controller number 72)

 Status
 2nd byte
 3rd byte

 BnH
 48H
 vvH

n=MIDI channel number: 0H - FH (ch.1 - ch.16) vv = Release Time value (relative change): 00H - 40H - 7FH (-64 - 0 - +63)

* Envelope Release, a Tone parameter, is modified.

OAttack time (Controller number 73)

Status 2nd byte 3rd byte
BnH 49H vvH

n=MIDI channel number: 0H - FH (ch.1 - ch.16) vv = Attack time value (relative change): 00H - 40H - 7FH (-64 - 0 - +63)

* Envelope Attack, a Tone parameter, is modified.

OCutoff (Controller number 74)

 Status
 2nd byte
 3rd byte

 BnH
 4AH
 vvH

n = MIDI channel number: 0H - FH (ch.1 - ch.16) vv = Cutoff value (relative change): 00H - 40H - 7FH (-64 - 0 - +63)

* Filter Cutoff, a Tone parameter, is modified.

ODecay Time (Controller number 75)

 Status
 2nd byte
 3rd byte

 BnH
 4BH
 vvH

n = MIDI channel number: 0H - FH (ch.1 - ch.16) vv = Decay Time value (relative change): 00H - 40H - 7FH (-64 - 0 - +63)

* Envelope Decay, a Tone parameter, is modified.

OVibrato Rate (Controller number 76)

 Status
 2nd byte
 3rd byte

 BnH
 4CH
 vvH

n=MIDI channel number: 0H - FH (ch.1 - ch.16) vv=Vibrato Rate value (relative change): 00H - 40H - 7FH (-64 - 0 - +63)

* LFO Rate, a Tone parameter, is modified.

OVibrato Depth (Controller number 77)

 Status
 2nd byte
 3rd byte

 BnH
 4DH
 vvH

n = MIDI channel number: 0H - FH (ch.1 - ch.16) vv = Vibrato Depth Value (relative change): 00H - 40H - 7FH (-64 - 0 - +63)

* LFO Depth, a Tone parameter, is modified.

OVibrato Delay (Controller number 78)

 Status
 2nd byte
 3rd byte

 BnH
 4EH
 vvH

n = MIDI channel number: 0H - FH (ch.1 - ch.16)

vv = Vibrato Delay value (relative change): 00H - 40H - 7FH (-64 - 0 - +63)

* LFO Delay, a Tone parameter, is modified.

OPortamento control (Controller number 84)

 Status
 2nd byte
 3rd byte

 BnH
 54H
 kkH

 n = MIDI channel number:
 0H - FFH (ch.1 - ch.16)

 kk = source note number:
 00H - 7FH (0 - 127)

- A Note-on received immediately after a Portamento Control message will change continuously in pitch, starting from the pitch of the Source Note Number.
- * If a voice is already sounding for a note number identical to the Source Note Number, this voice will continue sounding (i.e., legato) and will, when the next Note-on is received, smoothly change to the pitch of that Note-on.

* The rate of the pitch change caused by Portamento Control is determined by the Portamento Time value.

OEffect 1 (Reverb Send Level) (Controller number 91)

 Status
 2nd byte
 3rd byte

 BnH
 5BH
 vvH

 n = MIDI channel number:
 0H - FH (ch.1 - ch.16)

 vv = Reverb Send Level:
 00H - 7FH (0 - 127)

* Reverb Send Level, a Part parameter, is modified.

OEffect 3 (Chorus Send Level) (Controller number 93)

 Status
 2nd byte
 3rd byte

 BnH
 5DH
 vvH

 n = MIDI channel number:
 0H - FFH (ch.1 - ch.16)

 vv = Chorus Send Level:
 00H - 7FH (0 - 127)

* Chorus Send Level, a Part parameter, is modified.

ORPN MSB/LSB (Controller number 100, 101)

<<< RPN >>>

The RPN (Registered Parameter Number) messages are expanded control changes, and each function of an RPN is described by the MIDI Standard.

To use these messages, you must first use RPN MSB and RPN LSB messages to specify the parameter to be controlled, and then use Data Entry messages to specify the value of the specified parameter. Once an RPN parameter has been specified, all Data Entry messages received on that channel will modify the value of that parameter. To prevent accidents, it is recommended that you set RPN Null (RPN Number = 7FH/7Fh) when you have finished setting the value of the desired parameter.

This device receives the following RPNs. $\,$

RPN Data entry

 MSB LSB
 MSB LSB
 Explanation

 00H 00H
 mmH llH
 Pitch Bend Sensitivity

mm: 00H - 18H (0 - 24 semitones)
ll: ignored (processed as 00H)
specify up to 2 octaves in semitone steps
* Pitch Bend Range, a Part parameter, is

modified.

00H 01H mmH llH Master Fine Tuning

mm, ll: 00 00H - 40 00H - 7F 7FH (-100 - 0 - +99.99 cents)

-100 - 0 - +99.99 cents)
Fine Tune, a Part parameter, is modified.

00H 02H mmH llH Master Coarse Tuning

mm: 28H - 40H - 58H (-24 - 0 - +24 semitones)

ll: ignored (processed as 00H)

 Key Shift, a Part parameter, is modified.
 However, the setting is disabled if the drum set is already assigned to the Part.

Modulation Depth Range mm, ll: 00 00H - 06 00H (0 - 16384 * 600 / 16384 cent)

7FH 7FH --- RPN nul

mmH llH

00H 05H

Set condition where RPN and NRPN are unspecified. The data entry messages after set RPN null will be ignored. (No Data entry messages are required after RPN null). Settings already made will not change.

mm, ll: ignored

Program Change

Status 2nd byte CnH ppH

 $\begin{aligned} n &= MIDI \text{ channel number:} & 0H - FH \text{ (ch.1 - ch.16)} \\ pp &= Program \text{ number:} & 00H - 7FH \text{ (prog.1 - prog.128)} \end{aligned}$

- * Not received when Rx Tone Change, a Part parameter, is set to OFF.
- After a Program Change message is received, the sound will change beginning with the next Note-on. Voices already sounding when the Program Change message was received will not be affected.

Pitch Bend Change

 Status
 2nd byte
 3rd byte

 EnH
 IIH
 mmH

 n = MIDI channel number:
 0H - FH (ch.1 - ch.16)

mm, ll = Pitch Bend value: $00\ 00H - 40\ 00H - 7F\ 7FH\ (-8192 - 0 - +8191)$

■Channel Mode Messages

* Not received when Rx Channel, a Part parameter, is set to OFF.

•Ail Sounds Off (Controller number 120)

 Status
 2nd byte
 3rd byte

 BnH
 78H
 00H

 n = MIDI channel number:
 0H - FH (ch.1 - ch.16)

 When this message is received, all currently-sounding notes on the corresponding channel will be turned off immediately.

●Reset All Controllers (Controller number 121)

 Status
 2nd byte
 3rd byte

 BnH
 79H
 00H

 n = MIDI channel number:0H - FH (ch.1 - ch.16)

* When this message is received, the following controllers will be set to their reset values.

<u>Controller</u> Reset value Pitch Bend Change +/-0 (center) Polyphonic Key Pressure 0 (off) Channel Pressure 0 (off) Modulation 0 (off) Expression 127 (max) Hold 1 0 (off) Sostenuto 0 (off)

RPN unset; previously set data will not change NRPN unset; previously set data will not change

•All Notes Off (Controller number 123)

 Status
 2nd byte
 3rd byte

 BnH
 7BH
 00H

 n = MIDI channel number:
 0H - FH (ch.1 - ch.16)

 When All Notes Off is received, all notes on the corresponding channel will be turned off. However if Hold 1 or Sostenuto is ON, the sound will be continued until these are turned off.

OMNI OFF (Controller number 124)

 $\begin{tabular}{lll} Status & 2nd byte \\ BnH & 7CH & 00H \\ n = MIDI \ channel \ number: & 0H - FH \ (ch.1 - ch.16) \\ \end{tabular}$

* The same processing will be carried out as when All Notes Off is received.

●OMNI ON (Controller number 125)

 Status
 2nd byte
 3rd byte

 BnH
 7DH
 00H

 n = MIDI channel number:
 0H - FH (ch.1 - ch.16)

 OMNI ON is only recognized as "All notes off"; the Mode doesn't change (OMNI OFF remains).

●MONO (Controller number 126)

 Status
 2nd byte
 3rd byte

 BnH
 7EH
 mmH

 n = MIDI channel number:
 0H - FH (ch.1 - ch.16)

 mm=mono number:
 00H - 10H (0 - 16)

- * The same processing will be carried out as when All Sounds Off and All Notes Off is received, and the corresponding channel will be set to Mode 4 (M=1) regardless of the value of "mono number".
- Solo Sw, a Part parameter, is switched ON.

POLY (Controller number 127)

 Status
 2nd byte
 3rd byte

 BnH
 7FH
 00H

 n = MIDI channel number:
 0H - FH (ch.1 - ch.16)

- The same processing will be carried out as when All Sounds Off and All Notes Off is received, and the corresponding channel will be set to Mode 3.
- Solo Sw, a Part parameter, is switched OFF.

■System Realtime Message

Timing Clock

Status F8H

* Received when Sync Source is MIDI. When received Timing Clock, Arpeggio will played with tempo of intervals of this message.

●Start

Status

FAH

 Received when Sync Source is MIDI. When received this message, Arpeggio will be started from the first.

●Continue

<u>Status</u>

 Received when Sync Source is MIDI. If received this message when stopped Arpeggio by received "Stop," Arpeggio will be started from continued from the stopped position.

●Stop

Status

 Received when Sync Source is MIDI. When received this message, Arpeggio will be stopped.

Active Sensing

<u>Statu</u>

FEH

When Active Sensing is received, the unit will begin monitoring the intervals of all further messages. While monitoring, if the interval between messages exceeds 420 ms, the same processing will be carried out as when All Sounds Off, All Notes Off and Reset All Controllers are received, and message interval monitoring will be halted.

■System Exclusive Message

| Status | Data byte | Status |
|--------|---------------|--------|
| F0H | iiH, ddH,,eeH | F7H |

F0H: System Exclusive Message status

ii = ID number: an ID number (manufacturer ID) to indicate the manufacturer whose

Exclusive message this is, Roland's manufacturer ID is 41H, ID numbers 7EH and 7FH are extensions of the MIDI standard; Universal Non-realtime Messages (7EH) and Universal Realtime Messages

dd,..., ee = data: 00H - 7FH (0 - 127) F7H: EOX (End Of Exclusive)

The System Exclusive Messages received by the RS-5/9 are; Universal Non-realtime System Exclusive messages, Universal Realtime System Exclusive messages, Global Parameter Control, Data Requests (RQ1), and Data Set (DT1).

* Not received when Rx System Exclusive, a System parameter, is set to OFF.

●Universal Non-realtime System Exclusive Messages

Oldentity Request Message

| Status | Data byte | Status |
|-------------|--------------------------------|----------------|
| F0H | 7EH, dev, 06H, 01H | F7H |
| | | |
| <u>Byte</u> | Explanation | |
| FOH | Exclusive status | |
| 7EH | ID number (Universal Non-rea | ltime Message) |
| dev | Device ID (dev: 10H - 1FH, 7FI | H) |
| 06H | Sub ID#1 (General Information | 1) |
| 01H | Sub ID#2 (Identity Request) | |
| F7H | EOX (End Of Exclusive) | |
| | | |

* When this message is received, Identity Reply message (p. 164) will be transmitted.

System Exclusive messages related to mode settings

OTurn General MIDI 1 System On

| <u>Status</u> | <u>Data byte</u> | <u>Status</u> |
|---------------|------------------------------|-----------------|
| F0H | 7EH, 7FH, 09H, 01H | F7H |
| | | |
| <u>Byte</u> | Explanation | |
| F0H | Exclusive status | |
| 7EH | ID number (Universal Non-rea | altime Message) |
| 7FH | Device ID (Broadcast) | |
| 09H | Sub ID#1 (General MIDI Mess | age) |
| 01H | Sub ID#2 (General MIDI 1 On) | |
| F7H | EOX (End Of Exclusive) | |

- * When this message is received, GM1-compliant messages will thereafter be accepted, and the tone mapping will conform with GM1 specifications.
- This message causes Bank Select and NRPN not to be received.
- * $\,$ Not received when Rx GM System On, a System parameter, is set to OFF.
- There must be an interval of at least 50 ms between this message and the next message.

OTurn General MIDI 2 System On

| <u>Status</u> | Data byte | Status |
|---------------|------------------------------|----------------|
| F0H | 7EH, 7FH, 09H, 03H | F7H |
| | | |
| <u>Byte</u> | Explanation | |
| F0H | Exclusive status | |
| 7EH | ID number (Universal Non-rea | ltime Message) |
| 7FH | Device ID (Broadcast) | |
| 09H | Sub ID#1 (General MIDI Messa | ge) |
| 03H | Sub ID#2 (General MIDI 2 On) | |
| F7H | EOX (End Of Exclusive) | |
| | | |

- * When this message is received, GM2-compliant messages will thereafter be accepted, and the tone mapping will conform with GM2 specifications.
- Not received when Rx GM2 System On, a System parameter, is set to OFF.
- * There must be an interval of at least 50 ms between this message and the next message.

OTurn General MIDI System Off

| <u>Status</u> F0H | <u>Data byte</u> 7EH, 7FH, 09H, 02H | <u>Status</u> F7H | |
|----------------------|--|--|--|
| <u>Byte</u> F0H | Explanation Exclusive status | | |
| 7EH | ID number (Universal No | ID number (Universal Non-realtime Message) | |
| 7FH | Device ID (Broadcast) | | |
| 09H | Sub ID#1 (General MIDI n | nessage) | |
| 02H | Sub ID#2 (General MIDI C | Off) | |
| F7H | EOX (End of exclusive) | | |
| | | | |

- When this message is received, the device's internal status is reset to its native mode, thus exiting GM mode.
- There must be an interval of at least 50 ms between this message and the next message.

| ○GS reset | | |
|-------------|---|---------------|
| Status | Data byte | <u>Status</u> |
| F0H | 41H, dev, 42H, 12H, 40H, 00H, 7FH, 00H, 41H | F7H |
| | | |
| <u>Byte</u> | Explanation | |
| F0H | Exclusive status | |
| 41H | ID number (Roland) | |
| dev | Device ID (dev: 10H - 1FH) | |
| 42H | Model ID (GS) | |
| 12H | Command ID (DT1) | |
| 40H | Address MSB | |
| 00H | Address | |
| 7FH | Address LSB | |
| H00 | Data (GS reset) | |
| 41H | Checksum | |
| F7H | EOX (End Of Exclusive) | |
| | | |

^{*} There must be an interval of at least 50 ms between this message and the next message.

●Universal Realtime System Exclusive Messages

OMaster volume

| Status | <u>Data byte</u> | Status |
|-------------|--|--------|
| F0H | 7FH, 7FH, 04H, 01H, llH, mmH | F7H |
| | | |
| <u>Byte</u> | Explanation | |
| F0H | Exclusive status | |
| 7FH | ID number (universal realtime message) | |
| 7FH | Device ID (Broadcast) | |
| 04H | Sub ID#1 (Device Control messages) | |
| 01H | Sub ID#2 (Master Volume) | |
| llH | Master volume lower byte | |
| mmH | Master volume upper byte | |
| F7H | EOX (End Of Exclusive) | |
| | | |

 * $\,$ The lower byte (llH) of Master Volume will be handled as 00H.

OMaster Fine Tuning

| <u>Status</u> | Data byte | Status |
|---------------|--|--------|
| F0H | 7FH, 7FH, 04H, 03H, llH, mmH | F7H |
| | | |
| <u>Byte</u> | Explanation | |
| F0H | Exclusive status | |
| 7FH | ID number (universal realtime message) | |
| 7FH | Device ID (Broadcast) | |
| 04H | Sub ID#1 (Device Control) | |
| 03H | Sub ID#2 (Master Fine Tuning) | |
| llH | Master Fine Tuning LSB | |
| mmH | Master Fine Tuning MSB | |
| F7H | EOX (End Of Exclusive) | |
| | | |

mm, ll: 00 00H - 40 00H - 7F 7FH (-100 - 0 - +99.9 [cents])

Master Tune, a System parameter, is modified.

OMaster Coarse Tuning

| Simuoto: Cours | · · · · · · · · · · · · · · · · · · · | |
|----------------|--|---------------|
| Status | Data byte | <u>Status</u> |
| F0H | 7FH, 7FH, 04H, 04H, llH, mmH | F7 |
| | | |
| <u>Byte</u> | Explanation | |
| F0H | Exclusive status | |
| 7FH | ID number (universal realtime message) | |
| 7FH | Device ID (Broadcast) | |
| 04H | Sub ID#1 (Device Control) | |
| 04H | Sub ID#2 (Master Coarse Tuning) | |
| llH | Master Coarse Tuning LSB | |
| mmH | Master Coarse Tuning MSB | |
| F7H | EOX (End Of Exclusive) | |
| | | |

llH: ignored (processed as 00H)

mmH: 28H - 40H - 58H (-24 - 0 - +24 [semitones])

* Master Key Shift, a System parameter, is modified.

●Global Parameter Control

The following parameters for Global Parameter Control are defined in GM2.

| OReverb Parameters | | | |
|--------------------|--|-------------|--|
| Status | Data byte | Status | |
| F0H | 7FH, 7FH, 04H, 05H, 01H, 01H, | F7H | |
| | 01H, 01H, 01H, ppH, vvH | | |
| | | | |
| <u>Byte</u> | Explanation | | |
| F0H | Exclusive status | | |
| 7FH | ID number (universal realtime message) | | |
| 7FH | Device ID (Broadcast) | | |
| 04H | Sub ID#1 (Device Control) | | |
| 05H | Sub ID#2 (Global Parameter Control) | | |
| 01H | Slot path length | | |
| 01H | Parameter ID width | | |
| 01H | Value width | | |
| 01H | Slot path MSB | | |
| 01H | Slot path LSB (Effect 0101: Reverb) | | |
| ррН | Parameter to be controlled. | | |
| vvH | Value for the parameter. | | |
| | pp = 0 Reverb Type | | |
| | vv = 00H Small Room | | |
| | vv = 01H Medium Room | | |
| | vv = 02H Large Room | | |
| | vv = 03H Medium Hall | | |
| | vv = 04H Large Hall | | |
| | vv = 08H Plate | | |
| | * Reverb Type, a Common parameter, is | s modified. | |
| | | | |

pp = 1 Reverb Time vv = 00H - 7FH 0 - 127

EOX (End Of Exclusive)

* Reverb Time, a Common parameter, is modified.

OChorus Parameters

| Status F0H | <u>Data byte</u> 7FH, 7FH, 04H, 05H, 01H, 01H, 01H, 01H, 02H, ppH, vvH | Status F7H |
|---------------|--|------------------------|
| <u>Byte</u> | Explanation | |
| F0H | Exclusive status | |
| 7FH | ID number (universal realtime message) | |
| 7FH | Device ID (Broadcast) | |
| 04H | Sub ID#1 (Device Control) | |
| 05H | Sub ID#2 (Global Parameter Control) | |
| 01H | Slot path length | |
| 01H | Parameter ID width | |
| 01H | Value width | |
| 01H | Slot path MSB | |
| 02H | Slot path LSB (Effect 0102: Chorus) | |
| ррН | Parameter to be controlled. | |
| vvH | Value for the parameter. | |
| | pp = 0 Chorus Type | |
| | vv = 0 Chorus1 | |
| | vv = 1 Chorus2 | |
| | vv = 2 Chorus3 | |
| | vv = 3 Chorus4 | |
| | vv = 4 FB Chorus | |
| | vv = 5 Flanger | |
| | * Chorus Type, a Common parameter, i | s modified. |
| | pp = 1 Mod Rate | |
| | vv = 00H - 7FH (0 - 127) | |
| | * Chorus Rate, a Common parameter, is | modified. |
| | pp = 2 Mod Depth | |
| | vv = 00H - 7FH (0 - 127) | |
| | * Chorus Depth, a Common parameter, | is modified. |
| | pp = 3 Feedback | |
| | vv = 00H - 7FH (0 - 127) | |
| | * Chorus Feedback, a Common parame | ter, is modified. |
| | pp = 4 Send To Reverb | |
| | vv = 00H - 7FH (0 - 127) | |
| | * Chorus Send To Reverb, a Common p | arameter, is modified. |
| F7H | EOX (End Of Exclusive) | |

OChannel Pressure

| 9 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - | | |
|---|---|--------|
| Status | Data byte | Status |
| F0H | 7FH, 7FH, 09H, 01H, 0nH, ppH, rrH | 7FH |
| | | |
| <u>Byte</u> | Explanation | |
| F0H | Exclusive status | |
| 7FH | ID number (universal realtime message) | |
| 7FH | Device ID (Broadcast) | |
| 09H | Sub ID#1 (Controller Destination Setting) | |
| 01H | Sub ID#2 (Channel Pressure) | |
| 0nH | MIDI Channel (00 - 0F) | |
| ррН | Controlled parameter | |
| rrH | Controlled range | |
| | pp = 0 Pitch Control | |
| | rr = 28H - 58H (-24 - +24 [semitones]) | |
| | pp = 1 Filter Cutoff Control | |
| | rr = 00H - 7FH (-9600 - +9450 [cents]) | |
| | pp = 2 Amplitude Control | |
| | rr = 00H - 7FH (0 - 200%) | |
| | pp = 3 LFO Pitch Depth | |
| | rr = 00H - 7FH (0 - 600 [cents]) | |
| | pp = 4 LFO Filter Depth | |
| | rr = 00H - 7FH (0 - 2400 [cents]) | |
| | pp = 5 LFO Amplitude Depth | |
| | rr = 00H - 7FH (0 - 100%) | |
| F7H | EOX (End Of Exclusive) | |
| | | |

F7H

| ○Controller |
|-------------|
|-------------|

| Status | <u>Data byte</u> | Status |
|-------------|---|--------|
| F0H | 7FH, 7FH, 09H, 03H, 0nH, ccH, ppH, rrH | F7H |
| | | |
| <u>Byte</u> | Explanation | |
| FOH | Exclusive status | |
| 7FH | ID number (universal realtime message) | |
| 7FH | Device ID (Broadcast) | |
| 09H | Sub ID#1 (Controller Destination Setting) | |
| 03H | Sub ID#2 (Control Change) | |
| 0nH | MIDI Channel (00 - 0F) | |
| ccH | Controller number (01 - 1F, 40 - 5F) | |
| ррН | Controlled parameter | |
| rrH | Controlled range | |
| | pp = 0 Pitch Control | |
| | rr = 28H - 58H (-24 - +24 [semitones]) | |
| | pp = 1 Filter Cutoff Control | |
| | rr = 00H - 7FH (-9600 - +9450 [cents]) | |
| | pp = 2 Amplitude Control | |
| | rr = 00H - 7FH (0 - 200%) | |
| | pp = 3 LFO Pitch Depth | |
| | rr = 00H - 7FH (0 - 600 [cents]) | |
| | pp = 4 LFO Filter Depth | |
| | rr = 00H - 7FH (0 - 2400 [cents]) | |
| .* | pp = 5 LFO Amplitude Depth | |
| | rr = 00H - 7FH (0 - 100%) | |
| F7H | EOX (End Of Exclusive) | |

OScale/Octave Tuning Adjust

| <u>Status</u> | <u>Data byte</u> | <u>Status</u> |
|---------------|---|---------------|
| F0H | 7EH, 7FH, 08H, 08H, ffH, ggH, hhH, ssH | F7 |
| | | |
| <u>Byte</u> | Explanation | |
| F0H | Exclusive status | |
| 7EH | ID number (Universal Non-realtime Message) | |
| 7FH | Device ID (Broadcast) | |
| 08H | Sub ID#1 (MIDI Tuning Standard) | |
| 08H | Sub ID#2 (scale/octave tuning 1-byte form) | |
| ffH | Channel/Option byte 1 | |
| | bits 0 to 1 = channel 15 to 16 | |
| | bit 2 to 6 = Undefined | |
| ggH | Channel byte 2 | |
| | bits 0 to 6 = channel 8 to 14 | |
| hhH | Channel byte 3 | |
| | bits 0 to 6 = channel 1 to 7 | |
| ssH | 12 byte tuning offset of 12 semitones from C to B | |
| | 00H = -64 [cents] | |
| | 40H = 0 [cents] (equal temperament) | |
| | 7FH = +63 [cents] | |
| F7H | EOX (End Of Exclusive) | |
| | | |

OKey-based Instrument Controllers

| <u>Status</u> | <u>Data byte</u> | Status |
|---------------|---|--------|
| F0H | 7FH, 7FH, 0AH, 01H, 0nH, kkH, nnH, vvH | F7H |
| | | |
| <u>Byte</u> | Explanation | |
| F0H | Exclusive status | |
| 7FH | ID number (universal realtime message) | |
| 7FH | Device ID (Broadcast) | |
| 0AH | Sub ID#1 (Key-Based Instrument Control) | |
| 01H | Sub ID#2 (Controller) | |
| 0nH | MIDI Channel (00 - 0F) | |
| kkH | Key Number | |
| nnH | Control Number | |
| vvH | Value | |
| | nn = 07H Level | |
| | vv = 00H - 7FH (0 - 200%) (Relative) | |
| | * Level, a Drum Set parameter, is modified. | |
| | nn = 0AH Pan | |
| | vv = 00H - 7FH (Left - Right) (Absolute) | |
| | * Pan, a Drum Set parameter, is modified. | |
| | nn = 5BH Reverb Send | |
| | vv = 00H - 7FH (0 - 127) (Absolute) | |
| | * Reverb Send, a Drum Set parameter, is modified. | |
| | nn = 5D Chorus Send | |
| | vv = 00H - 7FH (0 - 127) (Absolute) | |
| : | : | |

EOX (End Of Exclusive)

●Data transmission

This instrument can use exclusive messages to exchange many varieties of internal settings with other devices.

The model ID of the exclusive messages used by this instrument is 00H 3CH.

ORequest data 1 (RQ1)

Status

Data byte

This message requests the other device to transmit data. The address and size indicate the type and amount of data that is requested.

When a Data Request message is received, if the device is in a state in which it is able to transmit data, and if the address and size are appropriate, the requested data is transmitted as a Data Set 1 (DT1) message. If the conditions are not met, nothing is transmitted.

| F0H | 41H, dev, 00H, 3CH, 11H, aaH, bbH, | F7H |
|-------------|------------------------------------|-----|
| | ccH, ddH, ssH, ttH, uuH, vvH, sum | |
| | | |
| <u>Byte</u> | <u>Remarks</u> | |
| F0H | Exclusive status | |
| 41H | ID number (Roland) | |
| dev | Device ID (dev: 10H - 1FH, 7FH) | |
| H00 | model ID #1 (RS-5/9) | |
| 3CH | model ID #2 (RS-5/9) | |
| 11H | command ID (RQ1) | |
| aaH | address MSB | |
| bbH | address | |
| ccH | address | |
| ddH | address LSB | |
| ssH | size MSB | |
| ttH | size | |
| uuH | size | |
| vvH | size LSB | |
| sum | checksum | |
| F7H | EOX (End Of Exclusive) | |
| | | |
| | | |

- * The size of data that can be transmitted at one time is fixed for each type of data. And data requests must be made with a fixed starting address and size. Refer to the address and size given in "Parameter Address Map" (p. 165).
- * For the checksum, refer to (p. 170).

OData set 1 (DT1)

This is the message that actually performs data transmission, and is used when you wish to transmit the data.

| <u>Status</u> F0H | Data byte Status 41H, dev, 00H, 10H, 12H, aaH, bbH, ccH, ddH, eeH, ffH, sum F7H |
|----------------------|---|
| <u>Byte</u> | Explanation |
| F0H | Exclusive status |
| 41H | ID number (Roland) |
| dev | Device ID (dev: 10H - 1FH, 7FH) |
| H00 | model ID #1 (RS-5/9) |
| 3CH | model ID #2 (RS-5/9) |
| 12H | Command ID (DT1) |
| aaH | Address MSB |
| bbH | Address |
| ccH | Address |
| ddH | Address LSB |
| eeH | Data: the actual data to be sent. Multiple bytes of data are |
| | transmitted in order starting from the address. |
| : | : |
| ffH | Data |
| sum | Checksum |
| F7H | EOX (End Of Exclusive) |
| | |

- * The amount of data that can be transmitted at one time depends on the type of data, and data will be transmitted from the specified starting address and size. Refer to the address and size given in "Parameter Address Map" (p. 165).
- Data larger than 128 bytes will be divided into packets of 128 bytes or less, and each packet will be sent at an interval of about 40 ms.
- * Regarding the checksum, please refer to (p. 170)

2. Data Transmission

■Channel Voice Messages

Note off

Status 2nd byte 3rd byte 8nH kkH vvH n = MIDI channel number: 0H - FH (ch.1 - ch.16) kk = note number: 0CH - 78H (12 - 120) 00H - 7FH (0 - 127) vv = note off velocity:

Note on

<u>Status</u> 2nd byte 3rd byte vvHn = MIDI channel number: 0H - FH (ch.1 - ch.16) 0CH - 78H (12 - 120) kk = note number: vv = note on velocity: 01H - 7FH (1 - 127)

●Control Change

OBank Select (Controller number 0, 32)

Status 2nd byte 3rd byte BnH 00H mmH llН BnH 20H n = MIDI channel number: 0H - FH (ch.1 - ch.16)

00H 00H - 7FH 7FH (bank.1 - bank.16384)

* Sent when the tones are switched using the panel controls, but not sent when the System parameter Tx Bank Select is set to OFF.

This message is transmitted when "Send GM/GM2 Setup" is executed.

OModulation (Controller number 1)

Status 2nd byte 0H - FH (ch.1 - ch.16) n = MIDI channel number: 00H - 7FH (0 - 127) vv = Modulation depth:

* Sent when the Common parameter Modulation/Pedal/C1-C4 Assign is set to

OPortamento Time (Controller number 5)

2nd byte 3rd byte n = MIDI channel number: 0H - FH (ch.1 - ch.16) 00H - 7FH (0 - 127) vv = Portamento Time:

* Sent when the Common parameter Modulation/Pedal/C1-C4 Assign is set to PORTAMENTO TIME.

* This message is transmitted when "Send GM/GM2 Setup" is executed.

OData Entry (Controller number 6, 38)

2nd byte 3rd byte Status BnH 06H mmH 26H n = MIDI channel number: 0H - FH (ch.1 - ch.16) mm, ll = the value of the parameter specified by RPN/NRPN

* This message is transmitted when "Send GM/GM2 Setup" is executed.

OVolume (Controller number 7)

<u>Status</u> 2nd byte 3rd byte BnH 07H vvH n = MIDI channel number: 0H - FH (ch.1 - ch.16) 00H - 7FH (0 - 127)

* Sent when the Common parameter Modulation/Pedal/C1-C4 Assign is set to VOLUME or UP-LO BALANCE.

* This message is transmitted when "Send GM/GM2 Setup" is executed.

OPan (Controller number 10)

2nd byte 3rd byte Status vvH BnH 0AH n = MIDI channel number: 0H - FH (ch.1 - ch.16)

00H - 40H - 7FH (Left - Center - Right)

* Sent when the Common parameter Modulation/Pedal/C1-C4 Assign is set to PAN.

* This message is transmitted when "Send GM/GM2 Setup" is executed.

OExpression (Controller number 11)

2nd byte vvH 0H - FH (ch.1 - ch.16) n = MIDI channel number: 00H - 7FH (0 - 127) vv = Expression:

* Sent when the Common parameter Modulation/Pedal/C1-C4 Assign is set to

OEffect Control 1 (Controller number 12)

Status 2nd byte 0CH 0H - FH (ch.1 - ch.16) n = MIDI channel number: vv = Control value: 00H - 7FH (0 - 127)

* Sent when the Common parameter Modulation/Pedal/C1-C4 Assign is set to MFX

OEffect Control 2 (Controller number 13)

Status 2nd byte 3rd byte BnH 0DH νvΗ n = MIDI channel number: 0H - FH (ch.1 - ch.16) vv = Control value: 00H - 7FH (0 - 127)

Sent when the Common parameter Modulation/Pedal/C1-C4 Assign is set to MFX PARAMETER 2.

OHold 1 (Controller number 64)

2nd byte Status 3rd byte BnH 40H vvH n = MIDI channel number: 0H - FH (ch.1 - ch.16)

* Sent when the HOLD pedal is operated with the Common parameter Arpeggio Switch set to OFF.

OPortamento (Controller number 65)

3rd byte Status 2nd byte 41H vvH n = MIDI channel number: 0H - FH (ch.1 - ch.16)

00H - 7FH (0 - 127) 0-63 = OFF, 64-127 = ON vv = Control value:

* Sent when the Common parameter Modulation/Pedal/C1-C4 Assign is set to

* This message is transmitted when "Send GM/GM2 Setup" is executed.

OSostenuto (Controller number 66)

2nd byte vvH n = MIDI channel number: 0H - FH (ch.1 - ch.16)

00H - 7FH (0 - 127) 0-63 = OFF, 64-127 = ON vv = Control value:

* Sent when the Common parameter Modulation/Pedal/C1-C4 Assign is set to SOSTENUTO.

OSoft (Controller number 67)

Status 2nd byte 3rd byte 43H vvH n = MIDI channel number: 0H - FH (ch.1 - ch.16)

00H - 7FH (0 - 127) 0-63 = OFF, 64-127 = ON vv = Control value:

* Sent when the Common parameter Modulation/Pedal/C1-C4 Assign is set to SOFT.

OHold 2 (Controller number 69)

 $\begin{array}{ccc} \underline{Status} & \underline{2nd \ byte} \\ BnH & 45H & vvH \\ n = MIDI \ channel \ number: & 0H - FH \ (ch.1 - ch.16) \end{array}$

vv = Control value:

00H - 7FH (0 - 127) 0-63 = OFF, 64-127 = ON

* Sent when the Panic function is activated.

OResonance (Controller number 71)

 Status
 2nd byte
 3rd byte

 BnH
 47H
 vvH

n = MIDI channel number: 0H - FH (ch.1 - ch.16) vv = Resonance value (relative change): 00H - 40H - 7FH (-64 - 0 - +63)

- Sent when the Common parameter Modulation/Pedal/C1-C4 Assign is set to RESONANCE.
- * This message is transmitted when "Send GM/GM2 Setup" is executed.

ORelease Time (Controller number 72)

 Status
 2nd byte
 3rd by

 BnH
 48H
 vvH

n = MIDI channel number: 0H - FH (ch.1 - ch.16) vv = Release Time value (relative change): 00H - 40H - 7FH (-64 - 0 - +63)

- Sent when the Common parameter Modulation/Pedal/C1-C4 Assign is set to RELEASE TIME.
- * This message is transmitted when "Send GM/GM2 Setup" is executed.

OAttack time (Controller number 73)

 Status
 2nd byte
 3rd byte

 BnH
 49H
 vvH

n = MIDI channel number: OH - FH (ch.1 - ch.16) VV = Attack time value (relative change): OOH - 4OH - 7FH (-64 - 0 - +63)

- Sent when the Common parameter Modulation/Pedal/C1-C4 Assign is set to ATTACK TIME.
- * $\,$ This message is transmitted when "Send GM/GM2 Setup" is executed.

OCutoff (Controller number 74)

 Status
 2nd byte
 3rd byte

 BnH
 4AH
 vvH

 n = MIDI channel number:
 0H - FH (ch.1 - ch.16)

 vv = Cutoff value (relative change):
 00H - 40H - 7FH (-64 - 0 - +63)

- * Sent when the Common parameter Modulation/Pedal/C1-C4 Assign is set to CUTOFF.
- * This message is transmitted when "Send GM/GM2 Setup" is executed.

ODecay Time (Controller number 75)

 Status
 2nd byte
 3rd byte

 BnH
 4BH
 vvH

 $n = MIDI \ channel \ number: \\ v = Decay \ Time \ value \ (relative \ change): \\ 00H - 40H - 7FH \ (-64 - 0 - +63)$

- Sent when the Common parameter Modulation/Pedal/C1-C4 Assign is set to DECAY TIME.
- * This message is transmitted when "Send GM/GM2 Setup" is executed.

OVibrato Rate (Controller number 76)

 Status
 2nd byte
 3rd byte

 BnH
 4CH
 vvH

- Sent when the Common parameter Modulation/Pedal/C1-C4 Assign is set to LFO RATE.
- * This message is transmitted when "Send GM/GM2 Setup" is executed.

OVibrato Depth (Controller number 77)

 Status
 2nd byte
 3rd byte

 BnH
 4DH
 vvH

 $n = MIDI \ channel \ number: \\ vv = Vibrato \ Depth \ Value \ (relative \ change): \\ 00H - 40H - 7FH \ (-64 - 0 - +63)$

- Sent when the Common parameter Modulation/Pedal/C1-C4 Assign is set to LFO DEPTH.
- * This message is transmitted when "Send GM/GM2 Setup" is executed.

OVibrato Delay (Controller number 78)

 Status
 2nd byte
 3rd byte

 BnH
 4EH
 vvH

 $n = MIDI \ channel \ number: \\ vv = Vibrato \ Delay \ value \ (relative \ change): \\ 00H - 40H - 7FH \ (-64 - 0 - +63)$

- * Sent when the Common parameter Modulation/Pedal/C1-C4 Assign is set to LFO DELAY
- * This message is transmitted when "Send GM/GM2 Setup" is executed.

OPortamento control (Controller number 84)

 Status
 2nd byte
 3rd byte

 BnH
 54H
 kkH

 n = MIDI channel number:
 0H - FFH (ch.1 - ch.16)

 kk = source note number:
 00H - 7FH (0 - 127)

OEffect 1 (Reverb Send Level) (Controller number 91)

 Status
 2nd byte
 3rd byte

 BnH
 5BH
 vvH

 n = MIDI channel number:
 0H - FFH (ch.1 - ch.16)

 vv = Reverb Send Level:
 00H - 7FH (0 - 127)

- * Sent when the Common parameter Modulation/Pedal/C1-C4 Assign is set to REV
- This message is transmitted when "Send GM/GM2 Setup" is executed.

OEffect 3 (Chorus Send Level) (Controller number 93)

 Status
 2nd byte
 3rd byte

 BnH
 5DH
 vvH

 n = MIDI channel number:
 0H - FH (ch.1 - ch.16)

 vv = Chorus Send Level:
 00H - 7FH (0 - 127)

- * Sent when the Common parameter Modulation/Pedal/C1-C4 Assign is set to CHO SEND LEVEL
- * This message is transmitted when "Send GM/GM2 Setup" is executed.

ORPN MSB/LSB (Controller number 100, 101)

 Status
 2nd byte
 3rd byte

 BnH
 65H
 mmH

 BnH
 64H
 llH

 n = MIDI channel number:
 0H - FH (ch.1 - ch.16)

 mm=upper byte of parameter number specified by RPN

 ll=lower byte of parameter number specified by RPN

* This message is transmitted when "Send GM/GM2 Setup" is executed.

<<< RPN >>>

The RPN (Registered Parameter Number) messages are expanded control changes, and each function of an RPN is described by the MIDI Standard.

To use these messages, you must first use RPN MSB and RPN LSB messages to specify the parameter to be controlled, and then use Data Entry messages to specify the value of the specified parameter. Once an RPN parameter has been specified, all Data Entry messages received on that channel will modify the value of that parameter. To prevent accidents, it is recommended that you set RPN Null (RPN Number = 7FH/7Fh) when you have finished setting the value of the desired parameter.

This device transmits the following RPNs.

| RPN | Data entry | |
|---------|------------|--|
| MSB LSB | MSB LSB | Explanation |
| 00H 00H | mmH llH | Pitch Bend Sensitivity |
| | | mm: 00H - 18H (0 - 24 semitones) |
| | | 11: 00H |
| 00H 01H | mmH llH | Master Fine Tuning |
| | | mm, Il: 00 00H - 40 00H - 7F 7FH |
| | | (-100 - 0 - +99.99 cents) |
| 00H 02H | mmH llH | Master Coarse Tuning |
| | | mm: 28H - 40H - 58H (-24 - 0 - +24 semitor |
| | | II. OOTT |

11: 00H

7FH 7FH --- RPN null

Set condition where RPN and NRPN are

unspecified.

Settings already made will not change.

mm, ll: ignored

●Program Change

Status CnH

2nd byte ррН

n = MIDI channel number:

0H - FH (ch.1 - ch.16)

pp = Program number:

00H - 7FH (prog.1 - prog.128)

* This message is transmitted when tone change is made on the panel or "Send GM/GM2 Setup" is executed.

●Channel Pressure

<u>Status</u>

2nd byte

n = MIDI channel number: 0H - FH (ch.1 - ch.16)

vv = Channel Pressure:

00H - 7FH (0 - 127)

* Sent when the Common parameter Modulation/Pedal/C1-C4 Assign is set to AFTERTOUCH.

●Pitch Bend Change

Status

2nd byte

EnH ШН

3rd byte

n = MIDI channel number:

0H - FH (ch.1 - ch.16) mm, II = Pitch Bend value: 00 00H - 40 00H - 7F 7FH (-8192 - 0 - +8191)

■Channel Mode Messages

•All Sounds Off (Controller number 120)

2nd byte <u>Status</u> 78H BnH n = MIDI channel number

3rd byte H00

:0H - FH (ch.1 - ch.16)

* Sent when the Panic function is activated.

●Reset All Controllers (Controller number 121)

2nd byte Status 3rd byte BnH 79H 00H :0H - FH (ch.1 - ch.16) n = MIDI channel number

■System Realtime Message

Active sensing

<u>Status</u> FEH

■System exclusive messages

The System Exclusive Messages transmitted by the RS-5/9 are; Universal Non-realtime System Exclusive messages and Data Set (DT1).

●Universal Non-realtime System Exclusive Message

Oldentity Reply Message (RS-5)

Receiving Identity Request Message, the RS-5 send this message.

| <u>Status</u> | <u>Data byte</u> | <u>Status</u> |
|-----------------|--|---------------|
| F0H | 7EH, dev, 06H, 02H, 41H, 3CH, 01H, | F7H |
| | 00H, 00H, 00H, 01H, 00H, 00H | |
| | | |
| <u>Byte</u> | Explanation | |
| F0H | Exclusive status | |
| 7EH | ID number (Universal Non-realtime Mess | age) |
| dev | Device ID (dev: 10H - 1FH) | |
| 06H | Sub ID#1 (General Information) | |
| 02H | Sub ID#2 (Identity Reply) | |
| 41H | ID number (Roland) | |
| 3CH 01H | Device family code (RS-5) | |
| 00H 00H | Device family number code (RS-5) | |
| 00H 01H 00H 00H | Software revision level | |
| | | |

Oldentity Reply Message (RS-9)

Receiving Identity Request Message, the RS-9 send this message.

EOX (End of Exclusive)

| Status | Data byte | Status |
|-----------------|--|--------|
| F0H | 7EH, dev, 06H, 02H, 41H, 3CH, 01H, | F7H |
| | 00H, 00H, 01H, 01H, 00H, 00H | |
| | | |
| <u>Byte</u> | Explanation | |
| F0H | Exclusive status | |
| 7EH | ID number (Universal Non-realtime Mess | sage) |
| dev | Device ID (dev: 10H - 1FH) | |
| 06H | Sub ID#1 (General Information) | |
| 02H | Sub ID#2 (Identity Reply) | |
| 41H | ID number (Roland) | |
| 3CH 01H | Device family code (RS-9) | |
| 00H 00H | Device family number code (RS-9) | |
| 01H 01H 00H 00H | Software revision level | |
| F7H | EOX (End of Exclusive) | |
| | | |

OTurn General MIDI 1 System On

| Status | Data byte | <u>status</u> |
|-------------|------------------------------|----------------|
| F0H | 7EH, 7FH, 09H, 01H | F7H |
| | | |
| <u>Byte</u> | Explanation | |
| F0H | Exclusive status | |
| 7EH | ID number (Universal Non-rea | ltime Message) |
| 7FH | Device ID (Broadcast) | |
| 09H | Sub ID#1 (General MIDI Messa | ige) |
| 01H | Sub ID#2 (General MIDI 1 On) | |
| F7H | EOX (End Of Exclusive) | |

^{*} This message is transmitted when "Send General MIDI 1 Setup" is executed.

OTurn General MIDI 2 System On

| Status | <u>Data byte</u> <u>Status</u> | | | | |
|-------------|--|-----|--|--|--|
| F0H | 7EH, 7FH, 09H, 03H | F7H | | | |
| | | | | | |
| <u>Byte</u> | Explanation | | | | |
| F0H | Exclusive status | | | | |
| 7EH | ID number (Universal Non-realtime Message) | | | | |
| 7FH | Device ID (Broadcast) | | | | |
| 09H | Sub ID#1 (General MIDI Message) | | | | |
| 03H | Sub ID#2 (General MIDI 2 On) | | | | |
| F7H | EOX (End Of Exclusive) | | | | |

^{*} This message is transmitted when "Send General MIDI 2 Setup" is executed.

^{*} Sent when the Panic function is activated.

^{*} This will be transmitted constantly at intervals of approximately 250ms.

●Data transmission

OData set 1 (DT1)

 Status
 Data byte
 Status

 F0H
 41H, dev, 00H, 3CH, 12H, aaH, bbH, F7H ccH, ddH, eeH, ... ffH, sum

Byte Explanation F0H Exclusive status 41H ID number (Roland) dev Device ID (dev: 10H - 1FH) 00H Model ID #1 (RS-5/9) 3СН Model ID #2 (RS-5/9) 12H Command ID (DT1) Address MSB aaH bbH Address ccH Address ddH Address LSB

eeH Data: the actual data to be sent. Multiple bytes of data are

transmitted in order starting from the address.

ffH Data sum Checksum

F7H EOX (End Of Exclusive)

- * The amount of data that can be transmitted at one time depends on the type of data, and data will be transmitted from the specified starting address and size. Refer to the address and size given in "Parameter Address Map" (p. 165).
- Data larger than 128 bytes will be divided into packets of 128 bytes or less, and each packet will be sent at an interval of about 40 ms.
- * Regarding the checksum, please refer to (p. 170)

3. Parameter Address Map

RS-5/9 (Model ID=00H 3CH)

Data for addresses marked with # are transmitted after separation into two bytes. If the
original data's most significant bit is 1, 01H and the remaining seven bits are transmitted
as is. When the most significant bit is 0, 00H and the remaining seven bits are
transmitted as is.

For example, if the original data is BCH, since BCH is expressed in binary notation as 10111100, 01H is sent in the first byte. In the next byte, the remaining 0111100 (or 3CH) is sent as is. However, during reception, the data is ignored if the two bytes are not received together.

| Start | |
|--|--|
| Address | Description |
| 00 00 00 00 | System Setup |
| 01 00 00 00 | Temporary Performance |
| 02 00 00 00 02 01 00 00 : 02 0F 00 00 | Temporary Tone (Part 1) Temporary Tone (Part 2) : Temporary Tone (Part 16) |
| 03 00 00 00 03 01 00 00 | Temporary DrumSet 1 Temporary DrumSet 2 |
| 04 00 00 00 04 01 00 00 : 04 7F 00 00 | User Performance 1 User Performance 2 : User Performance 128 |
| 05 00 00 00 05 01 00 00 : 05 7F 00 00 | User Tone 1 User Tone 2 : : User Tone 128 |
| 06 00 00 00 06 01 00 00 | User DrumSet 1 User DrumSet 2 |

■1. System Setup

| Offs | Address | | Description | |
|-------|---------|------------------------|--|----------------------------|
| ====: | 00 00 | 0000 000a | Bank Select Transmit Switch | 0 - 1 |
| | 00 01 | | | (OFF, ON) |
| | 00 01 | Oaaa aaaa | Master Key Shift | 40 - 88 (-24 - +24) |
| Ħ | 00 02 | 0000 aaaa 0bbb bbbb | Master Tune | 24 - 2024 |
| | 00 04 | 0000 000a | Control Pedal Polarity | (415.3 - 466.2) 0 - 1 |
| | 00 05 | 0000 000a | Hold Pedal Polarity | (NORMAL, REVERSE) 0 - 1 |
| | | | _ · | (NORMAL, REVERSE) |
| | 00 06 | 0000 000a | MFX Master Switch | 0 - 1 (OFF, ON) |
| | 00 07 | 0000 000a | Chorus Master Switch | 0 - 1 |
| | 00 08 | 0000 000a | Reverb Master Switch | (OFF, ON) 0 - 1 |
| | 00 09 | 0000 000a | Favorite Performance 1 Group | (OFF, ON) 0 - 1 |
| | | | • | (USER, PRESET) |
| | A0 00 | 0000 000a | Favorite Performance 2 Group | 0 - 1 (USER, PRESET) |
| | 00 OB | 0000 000a | Favorite Performance 3 Group | 0 - 1 |
| | 00 OC | 0000 000a | Favorite Performance 4 Group | (USER, PRESET) 0 - 1 |
| | 00 0D | 0000 000a | Favorite Performance 5 Group | (USER, PRESET) |
| | | | • | 0 - 1 (USER, PRESET) |
| | 00 OE | 0000 000a | Favorite Performance 6 Group | 0 - 1 (USER, PRESET) |
| | 00 OF | 0000 000a | Favorite Performance 7 Group | 0 - 1 |
| | 00 10 | 0000 000a | Favorite Performance 8 Group | (USER, PRESET) 0 - 1 |
| | 00 11 | Олла дала | | (USER, PRESET) |
| | | Vaaa aaaa | Favorite Performance 1 Number | 0 - 127 (1 - 128) |
| | 00 12 | Oaaa aaaa | Favorite Performance 2 Number | 0 - 127 (1 - 128) |
| | 00 13 | Oaaa aaaa | Favorite Performance 3 Number | 0 - 127 |
| | 00 14 | Oaaa aaaa | Favorite Performance 4 Number | (1 - 128) 0 - 127 |
| | 00 15 | Oaaa aaaa | | (1 - 128) |
| | 00 15 | vaaa aaaa | Favorite Performance 5 Number | 0 - 127 (1 - 128) |
| | 00 16 | Oaaa aaaa | Favorite Performance 6 Number | 0 - 127 (1 - 128) |
| | 00 17 | Oaaa aaaa | Favorite Performance 7 Number | 0 - 127 |
| | 00 18 | Oaaa aaaa | Favorite Performance 8 Number | (1 - 128) 0 - 127 |
| | | | | (1 - 128) |
| | 00 19 | 0000 000a | Current Performance Group | 0 - 1 (USER, PRESET) |
| | 00 1A | Oaaa aaaa | Current Performance Number | 0 - 127 |
| | | | ==================================== | (1 - 128) |
| | | Total Size | | |

■2. Performance

| Offset | |
|---|--|
| Address | Description |
| ======================================= | |
| 00 00 10 00 11 00 | Performance Part 1 Performance Part 2 Performance Part 2 |
| 1F 00 | : Performance Part 16 |

●2-1. Performance Common

| t | · · · · · · · · · · · · · · · · · · · |
|------------------------------------|---|
| Offset Address | Description |
| 00 00 Oaaa aaaa | |
| 00 01 Oaaa aaaa | (ASCII) Performance Name 2 32 - 125 |
| 00 02 Daaa aaaa | Performance Name 3 32 - 125 |
| 00 03 Oaaa aaaa | Performance Name 4 32 - 125 |
| 00 04 0aaa aaaa | (ASCII) Performance Name 5 32 - 125 |
| 00 05 Oaaa aaaa | (ASCII) Performance Name 6 32 - 125 |
| 00 05 Daaa aaaa | (ASCII) |
| i | Performance Name 7 32 - 125 (ASCII) |
| 00 07 Oasa asaa | Performance Name 8 32 - 125 (ASCII) |
| 00 08 Oaaa aaaa | (ASCII) |
| 00 09 Oasa aaaa | Performance Name 10 32 - 125 (ASCII) |
| 00 0A Oaaa aaaa | Performance Name 11 32 - 125 (ASCII) |
| 00 OB Oaaa aaaa | |
| 00 0C 0000 0aaa | Chorus Type (CHORUS1,, SHORT DELAY(FB)) |
| 00 0D 0000 0aaa | Chorus Pre LPF |
| 00 OE Oaaa aaaa | Chorus Pre LPF 0 - 7 (0 - 7) Chorus Level 0 - 127 |
| 00 OF Oaaa aaaa | Chorus Feedback (0 - 127) 0 - 127 (0 - 127) |
| 00 10 Oaaa aaaa | Chorus Delay 0 - 127 |
| 00 11 Oaaa aaaa | (0 - 127) Chorus Rate 0 - 127 |
| 00 12 Oaaa aaaa | (0 - 127) |
| 00 13 Oaaa aaaa | (0 - 127) Chorus Send Level to Reverb 0 - 127 |
| 00 13 0444 4444 00 14 0000 0444 | (0 - 127) |
| | (ROOM1,, PANNING DELAY) |
| | (0 - 7) |
| 00 16 0000 Oaaa | Reverb Pre LPF 0 - 7 (0 - 7) |
| 00 17 Oaaa aaaa | 40 1221 |
| 00 18 Daaa aaaa | Reverb Time 0 - 127 (0 - 127) |
| 00 19 Oaaa aaaa | (0 - 127) |
| 00 1B 0000 00aa | (UPPER, LOWER, PERFORM) |
| 00 1C 00aa aaaa | MFX Type 0 - 42 (THROUGH,, SLICER) |
| 00 1D Oaaa aaaa | |
| 00 1E Oaaa aaaa | MFX Parameter 2 0 - 127 |
| 00 1F Oaaa aaaa | MFX Parameter 3 0 - 127 (0 - 127) |
| . 00 20 Oaaa aaaa | |
| 00 21 Oaaa aaaa | MFX Parameter 5 0 - 127 |
| 00 22 Oaaa aaaa | MFX Parameter 6 (0 - 127) |
| 00 23 Oaaa aaaa | MFX Parameter 6 0 - 127 (0 - 127) MFX Parameter 7 0 - 127 |
| 00 24 Caaa aaaa | (0 - 127) MFX Parameter 8 0 - 127 |
| 00 25 Oaaa aaaa | (0 - 127) MFX Parameter 9 0 - 127 |
| 00 26 Oaaa aaaa | (0 - 127) MFX Parameter 10 0 - 127 |
| 00 27 0aaa aaaa | MFX Parameter 10 0 - 127 0 - 127 0 - 127 MFX Parameter 11 0 - 127 0 - 127 MFX Parameter 11 0 - 127 0 - 127 MFX Parameter 12 0 - 127 0 |
| 00 28 Oaaa aaaa | (0 - 127) MFX Parameter 12 0 - 127 |
| 00 29 Oaaa aaaa | (0 - 127) |
| 00 2A Daaa aaaa | MFX Parameter 14 0 - 127 |
| 00 2B Oaaa aaaa | (0 - 127) |
| 00 2C Oaaa aaaa | (0 - 127) |
| 00 2D Oaaa aaaa | (0 - 127) |
| 00 2D 0aaa aaaa | (0 - 127) |
| | |
| 00 2F Oaaa aaaa | (0 - 127) |
| 00 30 Oaaa aaaa | MFX Parameter 20 0 - 127 (0 - 127) |
| 00 31 Oaaa aaaa | /0 - 127) |
| 00 32 Oaaa aaaa | MFX Send Level to Chorus 0 - 127 (0 - 127) |
| 00 33 0000 aaaa | Transmit Channel (1 - 16, PART) |
| 00 34 Oaaa aaaa | Transpose 28 - 100 (-36 - +36) |
| 00 35 Oaaa aaaa | (C-1 - G9) |
| 00 36 0000 aaaa | (PART1 - PART16) |
| 00 37 0000 aaaa | (PART1 - PART16) |
| 00 38 000a aaaa | Modulation Assign 0 - 21 (MODULATION,, AFTERTOUCH) |
| 00 39 000a aaaa | Control Pedal Assign 0 - 21 (MODULATION,, AFTERTOUCH) |
| 00 3A 000a aaaa | C1 Knob Assign 0 - 21 (MODULATION,, AFTERTOUCH) |
| 00 3B 000a aaaa | C2 Knob Assign 0 - 21 (MODULATION,, AFTERTOUCH) |
| 00 3C 000a aaaa | C3 Knob Assign (MODULATION,, AFTERTOUCH) |
| 00 3D 000a aaaa | C4 Knob Assign 0 - 21 (MODULATION,, AFTERTOUCH) |
| 00 3E 00aa aaa | A Arpeggio Style 0 - 44 |
| 00 3F 00aa aaa | (1/4,, LIMITLESS) Arpeggio Motif (CINCLE UP. DASCUUD.EDD) |
| 00 40 Oaaa aaaa | (SINGLE UP,, BASS+UP+TOP) Arpeggio Beat Pattern 0 - 114 |
| # 00 41 0000 0000 | (1/4,, HOUSE2) 1 Arpeggio Tempo |
| 00 43 0000 0aa | |
| 1 | (-3 - +3) |

| 00 44 | Daaa aaaa | Arpeggio Key Velocity | 0 - 127 |
|---|---------------|-----------------------|-----------------------|
| 00 45 | Oaaa aaaa | Arpeggio Shuffle Rate | (0 - 127) |
| 00 45 | uaaa aaaa | Arpeggio Snuffle Rate | (50 -90[8]) |
| 00 46 | Oaaa aaaa | Arpeggio Accent Rate | 0 - 100 |
| 00 47 | 0000 000a | Arpeggio Sync Source | (0 - 100[%]) |
| | | | (INT, MIDI) |
| 00 48 | 0000 000a | Arpeggio Switch | 0 - 1 (OFF, ON) |
| 00 49 | 0000 000a | Transpose Switch | 0 - 1 |
| | | | (OFF, ON) |
| 00 4A | 0000 00aa | Keyboard Mode | (SINGLE, SPLIT, DUAL) |
| ======================================= | ========= | | |
| 00 00 00 4B | Total Size | | ļ |

●2-2. Performance Part

| Off | Address | | Description | |
|-----|---------|------------------------|--|--------------------------------|
| | 00 00 | 0000 00aa | Tone Group | 0 - 2 |
| # | 00 01 | 0000 000a | Tone Number | (USER, PRESET, GM) 0 - 255 |
| | 00 03 | Oaaa aaaa Oaaa aaaa | Level | (1 - 256) 0 - 127 |
| | 00 04 | Oaaa aaaa | Pan | (0 - 127) 0 - 127 |
| | 00 05 | Oaaa aaaa | Chorus Send Level | (RANDOM, L63 - 63R) 0 - 127 |
| | 00 06 | Oaaa aaaa | Reverb Send Level | (0 - 127) 0 - 127 |
| | 00 07 | 0000 000a | MFX Switch | (0 - 127) 0 - 1 |
| | 00 08 | 000a aaaa | Receive Channel | (OFF, ON) 0 - 16 |
| | 00 09 | 0000 000a | Tone Change Receive Switch | (1 - 16, OFF) 0 - 1 |
| | 00 OA | Oaaa aaaa | Key Shift | (OFF, ON) 40 - 88 |
| # | 00 OB | 0000 000a | Fine Tune | (-24 - +24) 28 - 228 |
| | 00 OD | Obbb bbbb Oaaa aaaa | Scale Tune C | (-100 - +100[cent]) 0 - 127 |
| | 00 OE | Oaaa aaaa | Scale Tune C# | (-64 - +63) 0 - 127 |
| | 00 OF | Oaaa aaaa | Scale Tune D | (-64 - +63) 0 - 127 |
| | 00 10 | Oaaa aaaa | Scale Tune D# | (-64 - +63) 0 - 127 |
| | 00 11 | Oaaa aaaa | Scale Tune E | (-64 - +63) 0 - 127 |
| | 00 12 | Oaaa aaaa | Scale Tune F | (-64 - +63) 0 - 127 |
| | 00 13 | Oaaa aaaa | Scale Tune F# | (-64 - +63) 0 - 127 |
| | 00 14 | Oaaa aaaa | Scale Tune G | (-64 - +63) 0 - 127 |
| | 00 15 | Oaaa aaaa | Scale Tune G# | (-64 - +63) 0 - 127 |
| | 00. 16 | Oaaa aaaa | Scale Tune A | (-64 - +63) 0 - 127 |
| | 00 17 | Oaaa aaaa | Scale Tune A# | (-64 - +63) 0 - 127 |
| | 00 18 | Oaaa aaaa | Scale Tune B | (-64 - +63) 0 - 127 |
| | 00 19 | 0000 000a | Solo Switch | (-64 - +63) 0 - 1 |
| | 00 1A | 0000 000a | Portamento Switch | (OFF, ON) 0 - 1 |
| | 00 1B | Oaaa aaaa | Portamento Time | (OFF, ON) 0 - 127 |
| | 00 1C | Oaaa aaaa | Velocity Sense Depth | (0 - 127) 0 - 127 |
| | 00 1D | Oaaa aaaa | Velocity Sense Offset | (0 - 127) 0 - 127 |
| | 00 1E | Oaaa aaaa | Pitch Bend Range | (0 - 127) 64 - 88 |
| | 00 1F | 000a aaaa | Voice Reserve | (0 - 24) 0 - 64 |
| | 00 20 | 0000 00aa | Tone Type | (0 - 64) 0 - 2 |
| | | ======== | ==================================== | (TONE, DRUM1, DRUM2) |

■3. Tone

| Off | set Address | | Description | |
|-----|----------------|-----------|-----------------|-------------------------------|
| | 00 00 | 0000 00aa | Original Group | 1 - 2 |
| | | | | (PRESET, GM) |
| # | 00 01 | 0000 000a | Original Number | 0 - 255 |
| | | Oaaa aaaa | | (1 - 256) |
| | 00 04 | Oaaa aaaa | Tone Name 1 | 32 - 125 |
| | | | _ | (ASCII) |
| | 00 05 | Oaaa aaaa | Tone Name 2 | 32 - 125 |
| | | | | (ASCII) |
| | 00 06 | Oaaa aaaa | Tone Name 3 | 32 - 125 (ASCII) |
| | 00 07 | 0 | Tone Name 4 | (ASCII) 32 - 125 |
| | 00 07 | Oaaa aaaa | Tone Name 4 | (ASCII) |
| | 00 08 | Oaaa aaaa | Tone Name 5 | 32 - 125 |
| | 00 08 | Vada adad | Totte Name 5 | (ASCII) |
| | 00 09 | Oaaa aaaa | Tone Name 6 | 32 - 125 |
| | 00 05 | vada adaa | TOTIE WARRE D | (ASCII) |
| | 40 OD | Oaaa aaaa | Tone Name 7 | 32 - 125 |
| | | | | (ASCII) |
| | 00 OB | Oaaa aaaa | Tone Name 8 | 32 - 125 |
| | | | | (ASCII) |
| | 00 OC | Oaaa aaaa | Tone Name 9 | 32 - 125 |
| | | | | (ASCII) |
| | 00 OD | Oaaa aaaa | Tone Name 10 | 32 - 125 |
| | | | | (ASCII) |
| | 00 OE | Oaaa aaaa | Tone Name 11 | 32 - 125 |
| | | | | (ASCII) |
| | 00 OF | Oaaa aaaa | Tone Name 12 | 32 - 125 |
| | | | | (ASCII) |
| | 00 10 | 00aa aaaa | MFX Type | 0 - 42 |
| | 00 11 | Oaaa aaaa | MFX Parameter 1 | (THROUGH,, SLICER) 0 - 127 |
| | 00 11 | Vada dada | Mrx Parameter 1 | (0 - 127) |
| | 00 12 | Oaaa aaaa | MFX Parameter 2 | 0 - 127 |
| | 00 12 | oudu adaa | mn rarameter z | (0 - 127) |
| | 00 13 | Oaaa aaaa | MFX Parameter 3 | 0 - 127 |
| | -3 -2 | | | (0 - 127) |
| | 00 14 | Oaaa aaaa | MFX Parameter 4 | 0 - 127 |
| | | | | (0 - 127) |

| 00 | 15 Oaaa | aaaa MF | K Parameter | 5 | 0 - 127 (0 - 127) |
|----------|-----------|----------|----------------------------|-------------|------------------------|
| 0.0 | 16 Oaaa | aaaa MF | K Parameter | 6 | 0 - 127 (0 - 127) |
| 00 | 17 Oaaa | aaaa MF | K Parameter | 7 | 0 - 127 |
| 00 | 18 Caaa | aaaa MF | K Parameter | 8 | (0 - 127) 0 - 127 |
| 00 | 19 0aaa | aaaa MF | K Parameter | 9 | (0 - 127) 0 - 127 |
| 00 | lA Oaaa | aaaa MFI | K Parameter | 10 | (0 - 127) 0 - 127 |
| 0.0 | 1B Oaaa | aaaa MF | K Parameter | 11 | (0 - 127) 0 - 127 |
| 00 | 1C Oaaa | aaaa MF | K Parameter | 12 | (0 - 127) 0 - 127 |
| 00 | 1D Oaaa | aaaa MF | K Parameter | 13 | (0 - 127) 0 - 127 |
| 00 | lE Oaaa | aaaa MF | K Parameter | 14 | (0 - 127) 0 - 127 |
| 00 | | | K Parameter | 15 | (0 - 127) 0 - 127 |
| 00 | | | X Parameter | | (0 - 127) 0 - 127 |
| 00 | | | x rarameter X Parameter | | (0 - 127) |
| | | | | | 0 - 127 (0 - 127) |
| 00 | | | X Parameter | | 0 ~ 127 (0 - 127) |
| 00 | | | X Parameter | | 0 - 127 (0 - 127) |
| 00 | | | X Parameter | | 0 - 127 (0 - 127) |
| 00 | 25 Oaaa | aaaa MF | X Send Leve | l to Reverb | 0 - 127 (0 - 127) |
| 00 | 26 Oaaa | aaaa MF | X Send Leve | l to Chorus | 0 - 127 (0 - 127) |
| 00 | 27 Oaaa | aaaa LF |) Rate | | 0 - 127 (-64 - +63) |
| 00 | 28 0aaa | aaaa LF | O Depth | | 0 - 127 (-64 - ÷63) |
| 00 | 29 0aaa | aaaa LF | O Delay | | 0 - 127 |
| 00 | 2A 0000 | 000a LF | O Filter Sw | itch | 0 - 1 |
| 00 | 2B Oaaa | aaaa Cu | toff Freque | ncy | (OFF, ON) 0 - 127 |
| 00 | 2C Daaa | aaaa Re | sonance | | (-64 - ÷63) 0 - 127 |
| 00 | 2D Oaaa | aaaa At | tack Time | | (-64 - +63) 0 - 127 |
| 00 | 2E Daaa | aaaa De | cay Time | | (-64 - +63) 0 - 127 |
| 00 | 2F Oaas | aaaa Re | lease Time | | (-64 - +63) 0 - 127 |
| | | | | | (-64 - +63) |
| 00 00 00 | 30 Tota | l Size | | | |
| | | | | | |

■4. DrumSet

| 1 - 2 00 00 0000 00as 0riginal Group (PRSST, GN) 0 - 1 00 00 0 0000 00as 0riginal Number 0 - 1 0 0 0 0 0 0 0 0 0 | Offset Address | | Description | |
|--|-------------------|-----------|--------------------------|----------------------|
| On On On On One On | | | | |
| 00 01 0 000 aaaa | 00 00 | 0000 00aa | Original Group | |
| 00 02 | 00 01 | 0000 aaaa | Original Number | 0 - 10 |
| 00 03 0 0aaa aaaa DrumSet Name 2 32 - 125 | 00 02 | Oaaa aaaa | DrumSet Name 1 | 32 - 125 |
| Columber Columber | 00.03 | 0 | DrumSot Namo 3 | |
| Casciliant Cas | | | | (ASCII) |
| 00 05 | 00 04 | Oaaa aaaa | DrumSet Name 3 | |
| 00 06 | 00 05 | Oaaa aaaa | DrumSet Name 4 | 32 - 125 |
| One | 00 06 | Oaaa aaaa | DrumSet Name 5 | 32 - 125 |
| 00 08 | 00 07 | Oaaa aaaa | DrumSet Name 6 | 32 - 125 |
| One | 00 08 | Oaaa aaaa | DrumSet Name 7 | 32 - 125 |
| ASCIT 32 - 125 | 00 09 | 0000 0000 | DrumSet Name 8 | (ASCII) 32 - 125 |
| On OB | | | | (ASCII) |
| On Oc | į. | | | · (ASCII) |
| ASCIT A | | Jaaa aaaa | Drumset Name 10 | |
| O O D O O O O O O O O O O O O O O O O | 00 0C | Oaaa aaaa | DrumSet Name 11 | |
| O O E | 00 00 | Oaaa aaaa | DrumSet Name 12 | 32 - 125 |
| O O F Oaaa aaaa | 00 0E | Oaaa aaaa | MFX Type | 0 - 42 |
| On 10 | 00 OF | Oaaa aaaa | MFX Parameter 1 | 0 - 127 |
| 00 11 | 00 10 | Oaaa aaaa | MFX Parameter 2 | 0 - 127 |
| 00 12 | 00 11 | Oaaa aaaa | MFX Parameter 3 | |
| 00 13 | | | | (0 - 127) |
| 00 14 | | | | (0 - 127) |
| 00 15 | | | 1 | (0 - 127) |
| 00 16 | | | 1 | (0 - 127) |
| 00 17 | | ļ | 1 | (0 - 127) |
| 00 18 | | | | (0 - 127) |
| 00 18 | 00 17 | Oaaa aaaa | MFX Parameter 9 | 0 - 127 (0 - 127) |
| 00 19 | 00 18 | Oaaa aaaa | MFX Parameter 10 | 0 - 127 |
| 00 1A | 00 19 | Oaaa aaaa | MFX Parameter 11 | 0 - 127 |
| 00 1B | 00 1A | Oaaa aaaa | MFX Parameter 12 | 0 - 127 |
| 00 1C | 00 1B | Oaaa aaaa | MFX Parameter 13 | 0 - 127 |
| 00 1D | 00 1C | Oaaa aaaa | MFX Parameter 14 | 0 - 127 |
| 00 1E Oaaa aaaa MFX Parameter 16 0 - 127 | 00 1D | Oaaa aaaa | MFX Parameter 15 | 0 ~ 127 |
| | 00 1E | Oaaa aaaa | MFX Parameter 16 | 0 - 127 |
| 00 1F 0aaa aaaa MFX Parameter 17 0 - 127 | | | | (0 - 127) 0 - 127 |
| 00 20 0aaa aaaa MFX Parameter 18 0 - 127) | | | | (0 - 127) |
| 00 21 | | | | (0 - 127) |
| (0 - 127) | | | | (0 - 127) |
| 00 22 | | | | (0 - 127) |
| 00 23 Oaaa aaaa MFX Send Level to Reverb 0 - 127 | 00 23 | Oaaa aaaa | MFX Send Level to Reverb | 0 - 127 |

| 00 24 0aaa | a aaaa MFX Send Leve | |
|--------------------|----------------------|-------------------------------------|
| 01 nn 0aaa | a aaaa Pitch | (0 - 127) 0 - 127 (-60 - ±67) |
| 02 nn Caaa | aaaa Level | (0 - 127) |
| 03 nn 0aaa | a aaaa Pan | 0 - 127 (RANDOM, L63 - 63R) |
| 04 nn 0aaa | a aaaa Reverb Depth | 0 - 127 (0 - 127) |
| 00 00 05 00 Tota | :====== :1 Size | (nn = 00 - 7F : Note Number) |

■Arpeggio Parameter List

●Arpeggio Style

| value | parameter | value | parameter | value | parameter |
|-------|--------------|-------|----------------|-------|------------------|
| 0 | 1/4 | 15 | HEAVY SLAP | 30 | SWING WALTZ |
| 1 | 1/6 | 16 | LIGHT SLAP | 31 | REGGAE |
| 2 | 1/8 | 17 | WALK BASS | 32 | PERCUSSION |
| 3 | 1/12 | 18 | RHYTHM GTR A | 33 | HARP |
| 4 | 1/16 | 19 | RHYTHM GTR B | 34 | SHAMISEN |
| 5 | 1/32 | 20 | RHYTHM GTR C | 35 | BOUND BALL |
| 6 | PORTAMENTO A | 21 | RHYTHM GTR D | 36 | RANDOM |
| 7 | PORTAMENTO B | 22 | RHYTHM GTR E | 37 | BOSSA NOVA |
| 8 | GLISSANDO | 23 | 3 FINGER GTR | 38 | SALSA |
| 9 | SEQUENCE A | 24 | STRUM GTR UP | 39 | MAMBO |
| 10 | SEQUENCE B | 25 | STRUM GTR DOWN | 40 | LATIN PERCUSSION |
| 11 | SEQUENCE C | 26 | STRUM GTR U&D | 41 | SAMBA |
| 12 | SEQUENCE D | 27 | PIANO BACKING | 42 | TANGO |
| 13 | ECHO | 28 | CLAVI CHORD | 43 | HOUSE |
| 14 | SYNTH BASS | 29 | WALTZ | 44 | LIMITLESS |

●Arpeggio Motif

| value | parameter | value | parameter | value | parameter |
|-----------------------------------|---|----------------------------------|--|--|---|
| 0 1 1 2 3 4 5 6 | SINGLE UP SINGLE DOWN SINGLE UPEDOWN SINGLE RANDOM DUAL UP DUAL DOWN DUAL UP&DOWN | 13 14 15 16 17 18 | GLISSANDO CHORD BASS+CHORD 1 BASS+CHORD 2 BASS+CHORD 3 BASS+CHORD 4 BASS+CHORD 5 | 26 27 28 29 30 31 32 | BASS+UP 7 BASS+UP 8 BASS+RANDOM 1 BASS+RANDOM 2 BASS+RANDOM 3 TOP+UP 1 TOP+UP 2 |
| 7 8 9 10 11 12 | DUAL RANDOM TRIPLE UP TRIPLE DOWN TRIPLE UP&DOWN TRIPLE RANDOM NOTE ORDER | 20 21 22 23 24 25 | BASS+UP 1 BASS+UP 2 BASS+UP 3 BASS+UP 4 BASS+UP 5 BASS+UP 6 | 33 34 35 36 37 | TOP+UP 3 TOP+UP 4 TOP+UP 5 TOP+UP 6 BASS+UP+TOP |

Arpeggio Beat Pattern

| value | parameter | value | parameter | value | parameter |
|---|--|---|---|---|---|
| 0 1 1 2 3 3 4 4 5 6 6 7 7 8 8 9 10 11 12 13 14 4 15 16 6 17 7 8 20 22 23 3 24 4 25 5 26 27 28 9 30 1 32 2 3 3 3 4 3 3 5 6 3 7 7 8 8 3 9 | 1/ 4 1/ 6 1/ 8 1/ 12 1/ 18 1/ 12 1/ 16 1 1/ 16 1 1/ 16 1 1/ 16 1 1/ 16 1 1/ 16 1 1/ 16 1 1/ 16 1 1/ 16 1 1/ 16 1 1/ 12 1 1/ 32 | 40 41 42 43 445 46 47 48 49 50 51 52 53 54 55 60 61 62 63 64 65 67 71 72 73 74 75 77 | SEQ-A 5 SEQ-A 6 SEQ-A 7 SEQ-B 1 SEQ-B 1 SEQ-B 2 SEQ-B 3 SEQ-B 4 SEQ-B 5 SEQ-C 1 SEQ-D 1 SEQ-D 0 SEQ-D 1 SEQ-D 7 SEQ-D 4 SEQ-D 5 SEQ-D 7 SEQ-D 6 SEQ-D 7 SEQ-D 6 SEQ-D 7 SEQ-D 8 SEQ-D 7 SEQ-D 6 SEQ-D 7 SEQ-D 6 SEQ-D 7 SEQ-D 6 SEQ-D 7 SEQ-D 7 SEQ-D 7 SEQ-D 7 SEQ-D 8 SEQ-D 7 SEQ-D 8 SEQ-D 7 SEQ-D 9 SEQ-D 1 SEQ-D 7 SEQ-D 1 SEQ-D 7 SEQ-D 8 SEQ-D 7 SEQ-D 8 SEQ-D 7 SEQ-D 9 SEQ-D 1 SEQ-D | 80 81 82 83 84 85 86 87 88 89 90 91 92 93 94 95 100 101 102 103 104 105 106 1107 1108 1107 1112 1113 1114 | STRUM 4 STRUM 5 STRUM 6 STRUM 6 STRUM 7 STRUM 8 REGGAE 1 REGGAE 2 REFRAIN 2 PERC 1 PERC 2 PERC 3 PERC 4 WALKES HARP BOUND RANDOM BOSSA NOVA SALSA 1 SALSA 1 SALSA 2 SALSA 4 MAMBO 1 MAMBO 2 CLAVE REV CLA GUIRO AGOGO SAMBA TANGO 1 TANGO 2 TANGO 3 TANGO 4 HOUSE 1 HOUSE 2 |

■Modulation Assign / Control Pedal Assign / Knob Assign Parameter List

| value parameter | value parameter | value parameter |
|--|--|--|
| 0 MODULATION 1 PORTAMENTO TIME 2 VOLUME 3 PAN 4 EXPRESSION 5 PORTAMENTO 6 SOSTENUTO 7 SOFT | 8 RESONANCE 9 RELEASE TIME 10 ATTACK TIME 11 CUTOFF 12 DECAY TIME 13 LFO RATE 14 LFO DETH 15 LFO DELAY | 16 CHO SEND LEVEL 17 REV SEND LEVEL 18 UP-LO BALANCE 19 MFX PARAMETER 1 20 MFX PARAMETER 2 21 AFTERTOUCH |

4. Supplementary material

Decimal and Hexadecimal table

In MIDI documentation, data values and addresses/sizes of exclusive messages etc. are expressed as hexadecimal values for each 7 bits.

The following table shows how these correspond to decimal numbers.

| Dec. | Hex. | Dec. | Hex. | Dec. | Hex. | Dec. | Hex. |
|----------|------------|----------|------------|----------|------|------------|------|
| j 0 j | 00н | 32 | 20H | 64 | 40H | 96 | 60H |
| 1 | 01H | 33 | 21H | 65 | 41H | 97 | 61H |
| 2 | 02H | 34 | 22H | 66 | 42H | 98 | 62H |
| 3 | 03H | 35 | 23H | 67 | 43H | 99 | 63H |
| 4 | 04H | 36 | 24H | 68 | 44H | 100 | 64H |
| 5 | 05H | 37 | 25H | 69 | 45H | 101 | 65H |
| 6 | 06H | 38 | 26H | 70 | 46H | 102 | 66H |
| 7 | 07H | 39 | 27H | 71 | 47H | 103 | 67H |
| 8 | 08H | 40 | 28H | 72 | 48H | 104 | 68H |
| 9 | 09H | 41 | 29H | 73 | 49H | 105 | 69H |
| 10 | HA0 | 42 | 2AH | 74 | 4AH | 106 | 6AH |
| 11 | 0BH | 43 | 2BH | 75 | 4BH | 107 | 6BH |
| 12 | 0CH | 44 | 2CH | 76 | 4CH | 108 | 6CH |
| 13 | 0 DH | 45 | 2DH | 77 | 4DH | 109 | 6DH |
| 14 | 0EH | 46 | 2EH | 78 | 4EH | 110 | 6EH |
| 15 | 0FH | 47 | 2FH | 79 | 4FH | 111 | 6FH |
| 16 | 1.0H | 48 | 30H | 80 | 50H | 112 | 70H |
| 17 | 11H | 49 | 31H | 81 | 51H | 113 | 71H |
| 18 | 12H | 50 | 32H | 82 | 52H | 114 | 72H |
| 19 | 13H | 51 | 33H | 83 | 53H | 115 | 73H |
| 20 | 14H | 52 | 34H | 84 | 54H | 116 | 74H |
| 21 | 15H | 53 | 35H | 85 | 55H | 117 | 75H |
| 22 | 16H | 54 | 36H | 86 | 56H | 118 | 76H |
| 23 | 17H | 55 | 37H | 87 | 57H | 119 | 77H |
| 24 | 18H | 56 | 38H | 88 | 58H | 120 | 78H |
| 25 26 | 19H | 57 | 39H | 89 | 59H | 121 | 79H |
| | 1AH | 58 | 3AH | 90 | 5AH | 122 | 7AH |
| 27 28 | 1BH 1CH | 59 | 3BH | 91 | 5BH | 123 | 7BH |
| 28 | | 60 61 | 3CH | 92 | 5CH | 124 | 7CH |
| 30 | 1DH 1EH | 62 | 3DH 3EH | 93 | 5DH | 125 | 7DH |
| 31 | 1EH 1FH | 63 | 3EH 3FH | 94 95 | 5EH | 126 127 | 7EH |
| 1 21 | TLH | . 63 | JFH | 1 82 | 5FH | 12/ | 7FH |

- Decimal values such as MIDI channel, bank select, and program change are listed as one(1) greater than the values given in the above table.
- * A 7-bit byte can express data in the range of 128 steps. For data where greater precision is required, we must use two or more bytes. For example, two hexadecimal numbers aa bbH expressing two 7-bit bytes would indicate a value of aa x 128 + bb.
- In the case of values which have a +- sign, 00H = -64, 40H = +- 0, and 7FH = +63, so that the decimal expression would be 64 less than the value given in the above chart. In the case of two types, 00 00H = -8192, 40 00H = +- 0, and 7F 7FH = +8191. For example if aa bbH were expressed as decimal, this would be aa bbH 40 00H = aa x 128 + bb 64 x 128.
- * Data marked "nibbled" is expressed in hexadecimal in 4-bit units. A value expressed as a 2-byte nibble 0a 0bH has the value of a x 16 + b.

<Example 1> What is the decimal expression of 5AH? From the preceding table, 5AH = 90

<Example 2> What is the decimal expression of the value 12 34H given as hexadecimal for each 7 bits?

From the preceding table, since 12H = 18 and 34H = 52 $18 \times 128 + 52 = 2356$

<Example 3> What is the decimal expression of the nibbled value 0A 03 09 0D? From the preceding table, since 0AH = 10, 03H = 3, 09H = 9, 0DH = 13 ($(10 \times 16 + 3) \times 16 + 9) \times 16 + 13 = 41885$

<Example 4> What is the nibbled expression of the decimal value 1258?

Since from the preceding table, 0=00H, 4=04H, 14=0EH, 10=0AH, the answer is 00 04 0E 0AH.

●Examples of actual MIDI messages

<Example 1> 92 3E 5F

9nH is the Note-on status, and n is the MIDI channel number. Since 2H=2, 3EH=62, and 5FH=95, this is a Note-on message with MIDI CH=3, note number 62 (note name is D4), and velocity 95.

<Example 2> CE 49

CnH is the Program Change status, and n is the MIDI channel number. Since EH = 14 and 49H = 73, this is a Program Change message with MIDI CH = 15, program number 74 (Flute in GS).

<Example 3> EA 00 28

EnH is the Pitch Bend Change status, and n is the MIDI channel number. The 2nd byte (00H=0) is the LSB and the 3rd byte (28H=40) is the MSB, but Pitch Bend Value is a signed number in which 40 00H (= $64 \times 128 + 0 = 8192$) is 0, so this Pitch Bend Value is 28 00H - 40 00H = $40 \times 128 + 0 - (64 \times 128 + 0) = 5120 - 8192 = -3072$

If the Pitch Bend Sensitivity is set to 2 semitones, -8192 (00 00H) will cause the pitch to change -200 cents, so in this case -200 x (-3072) / (-8192) = -75 cents of Pitch Bend is being applied to MIDI channel 11.

<Example 4> B3 64 00 65 00 06 0C 26 00 64 7F 65 7F

BnH is the Control Change status, and n is the MIDI channel number. For Control Changes, the 2nd byte is the control number, and the 3rd byte is the value. In a case in which two or more messages consecutive messages have the same status, MIDI has a provision called "running status" which allows the status byte of the second and following messages to be omitted. Thus, the above messages have the following meaning.

| B3 64 00 | MIDI ch.4, lower byte of RPN parameter number: | 00H |
|------------|---|-----|
| (B3) 65 00 | (MIDI ch.4) upper byte of RPN parameter number: | 00H |
| (B3) 06 0C | (MIDI ch.4) upper byte of parameter value: | 0CH |
| (B3) 26 00 | (MIDI ch.4) lower byte of parameter value: | 00H |
| (B3) 64 7F | (MIDI ch.4) lower byte of RPN parameter number: | 7FH |
| (B3) 65 7F | (MIDI ch.4) upper byte of RPN parameter number: | 7FH |

In other words, the above messages specify a value of 0C 00H for RPN parameter number 00 00H on MIDI channel 4, and then set the RPN parameter number to 7F 7FH.

RPN parameter number 00 00H is Pitch Bend Sensitivity, and the MSB of the value indicates semitone units, so a value of 0CH = 12 sets the maximum pitch bend range to \div 12 semitones (1 octave). (On GS sound sources the LSB of Pitch Bend Sensitivity is ignored, but the LSB should be transmitted anyway (with a value of 0) so that operation will be correct on any device.)

Once the parameter number has been specified for RPN or NRPN, all Data Entry messages transmitted on that same channel will be valid, so after the desired value has been transmitted, it is a good idea to set the parameter number to 7F 7FH to prevent accidents. This is the reason for the (B3) 64 7F (B3) 65 7F at the end.

It is not desirable for performance data (such as Standard MIDI File data) to contain many events with running status as given in <Example 4>. This is because if playback is halted during the song and then rewound or fast-forwarded, the sequencer may not be able to transmit the correct status, and the sound source will then misinterpret the data. Take care to give each event its own status.

It is also necessary that the RPN or NRPN parameter number setting and the value setting be done in the proper order. On some sequencers, events occurring in the same (or consecutive) clock may be transmitted in an order different than the order in which they were received. For this reason it is a good idea to slightly skew the time of each event (about 1 tick for TPQN = 480).

TPQN: Ticks Per Quarter Note

●Example of an Exclusive message and calculating a

Roland Exclusive messages (RQ1, DT1) are transmitted with a checksum at the end (before F7) to make sure that the message was correctly received. The value of the checksum is determined by the address and data (or size) of the transmitted exclusive message.

OHow to calculate the checksum

(hexadecimal numbers are indicated by 'H')

The checksum is a value derived by adding the address, size and checksum itself and inverting the lower 7 bits.

Here's an example of how the checksum is calculated. We will assume that in the exclusive message we are transmitting, the address is aa bb ccH and the data or size is dd ee ffH.

aa + bb + cc + dd + ee + ff = sumsum / 128 = quotient ... remainder 128 - remainder = checksum

<Example 1> Setting REVERB TYPE of PERFORMANCE COMMON to ROOM 3 (DT1) According to the "Parameter Address Map" (p. 165), the start address of Temporary Performance is 01 00 00 00H, the offset address of PERFORMANCE COMMON is 00 00H, and the address of REVERB TYPE is 00 14H. Therefore the address of CHORUS TYPE of PERFORMANCE COMMON is:

ROOM 3 has the value of 02H.

So the system exclusive message should be sent is;

| F0 | 41 | 10 | 00 3C | 12 | 01 00 00 14 | 02 | ?? | F7 |
|---------|-----------|---------|--------|--------|-------------|----------------------|--------------|-----|
| (1) | (2) | (3) | (4) | (5) | address | data | checksum | (6) |
| (1) Exc | lusive S | tatus | (2) ID | (Rolan | d) | (3) De | vice ID (17) | |
| (4) Mo | del ID (I | RS-5/9) | (5) Co | mmano | l ID (DT1) | (6) End of Exclusive | | |

Then calculate the checksum

01H + 00H + 00H + 14H + 02H = 1 + 0 + 0 + 20 + 2 = 23 (sum) 23 (sum) / 128 = 0 (quotient) ... 23 (remainder) checksum = 128 - 23 (remainder) = 105 = 69H

Therefore the start address of Performance Part 3 in USER:03 is;

This means that F0 41 10 00 3C 12 01 00 00 14 02 69 F7 is the message should be sent.

<Example 2> Getting the data (RQ1) of Performance Part 3 in USER:03 According to the "Parameter Address Map" (p. 165), the start address of USER:03 is 04 02 00 00H, and the offset address of Performance Part 3 is 12 00H.

As the size of Performance Part is 00 00 00 21H, the system exclusive message should be sent is;

| F0 | 41 | 10 | 00 3C . 11 | | 00 00 00 21 | ?? | F7 |
|---------|----------|-------|--------------|---------|---------------|----------|-----|
| (1) | (2) | (3) | (4) (5) | address | data | checksum | (6) |
| (1) Eve | lucive S | tatue | (2) ID (Rola | nd) | (3) Device ID | (17) | |

(6) End of Exclusive

(5) Command ID (RQ1)

Then calculate the checksum.

(4) Model ID (RS-5/9)

04H + 02H + 12H + 00H + 00H + 00H + 00H + 21H = 4 + 2 + 18 + 0 + 0 + 0 + 0 + 33 = 57 (sum) 57 (sum) / 128 = 0 (quotient) ... 57 (remainder) checksum = 128 - 57 (remainder) = 71 = 47H

This means that F0 41 10 00 3C 11 04 02 12 00 00 00 00 21 47 F7 is the message should be sent.

<Example 3> Getting Temporary Performance data (RQ1)

According to the "Parameter Address Map" (p. 165), the start address of Temporary Performance is assigned as following:

01 00 00 00H Temporary Performance Common 01 00 10 00H Temporary Performance Part 1 01 00 1F 00H Temporary Performance Part 16

As the data size of Performance Part is 00 00 00 21H, summation of the size and the start address of Part 16 at Temporary Performance will be;

```
01 00 1F 00H
+) 00 00 00 21H
01 00 1F 21H
```

And the size that have to be got should be;

```
01 00 1F 21H
-) 01 00 00 00H
00 00 1F 21H
```

Therefore the system exclusive message should be sent is:

```
10
                       00 3C
                                11
                                       01 00 00 00
                                                        00 00 1F 21
                                                                                   F7
(1)
        (2)
                (3)
                        (4)
                                (5)
                                         address
                                                                     checksum
(1) Exclusive Status
                         (2) ID (Roland)
                                                       (3) Device ID (17)
(4) Model ID (RS-5/9)
                         (5) Command ID (RQ1)
                                                       (6) End of Exclusive
```

Then calculate the checksum

```
01H + 00H + 00H + 00H + 00H + 00H + 1FH + 21H = 1 + 0 + 0 + 0 + 0 + 0 + 31 + 33 = 65 (sum)
65 (sum) / 128 = 0 (quotient) ... 65 (remainder)
checksum = 128 - 65 (remainder) = 63 = 3FH
```

This means that F0 41 10 00 3C 11 01 00 00 00 00 1F 21 3F F7 is the message should be

<Example 4> When Producing the Combined Temporary Performance Data and All Temporary Tone and Drum Set Data (RQ1)

The data produced is the same as that when transmitting Bulk Dump:Temporary in

According to the "Parameter Address Map" (p. 165), the start address of the above all parameters is assigned as following:

```
01 00 00 00H
                   Temporary Performance Common
02 00 00 00H
                   Temporary Tone (Part 1)
02 01 00 00H
                   Temporary Tone (Part 2)
02 0F 00 00H
                   Temporary Tone (Part 16)
03 00 00 00H
                   Temporary DrumSet 1
03 01 00 00H
                  Temporary DrumSet 2
```

As the data size of Drum Set is 00 00 05 00H, summation of the size and the start address of Temporary DrumSet 2 will be;

```
+) 00 01 00 00H
03 01 05 00H
03 01 05 00H
```

And the size that have to be got should be;

```
03 01 05 00H
-) 01 00 00 00H
02 01 05 00H
```

(4) Model ID (RS-5/9)

Therefore the system exclusive message should be sent is;

| F0 | 41 | 10 | 00 3C | 11 | 01 00 00 00 | 02 01 05 00 | ?? | F7 |
|---------|-----------|-------|--------|---------|-------------|---------------|----------|-----|
| (1) | (2) | (3) | (4) | (5) | address | data | checksum | (6) |
| (1) Exc | clusive S | tatus | (2) ID | (Roland | d) | (3) Device ID | (17) | |

(6) End of Exclusive

(5) Command ID (RQ1)

Then calculate the checksum.

```
01H + 00H + 00H + 00H + 02H + 01H + 05H + 00H = 1 + 0 + 0 + 0 + 2 + 1 + 5 + 0 = 9 (sum)
9 (sum) / 128 = 0 (quotient) ... 9 (remainder)
checksum = 128 - 9 (remainder) = 119 = 77H
```

This means that F0 41 10 00 3C 11 01 00 00 00 02 01 05 00 77 F7 is the message should be sent.

●The Scale Tune Feature

The scale Tune feature allows you to finely adjust the individual pitch of the notes from C through B. Though the settings are made while working with one octave, the fine adjustments will affect all octaves. By making the appropriate Scale Tune settings, you can obtain a complete variety of tuning methods other than equal temperament. As examples, three possible types of scale setting are explained below.

OEqual Temperament

This method of tuning divides the octave into 12 equal parts. It is currently the most widely used form of tuning, especially in occidental music. On RS-5/9, the default settings for the Scale Tune feature produce equal temperament.

OJust Temperament (Tonic C)

The three main chords resound much more beautifully than with equal temperament, but this benefit can only be obtained in one key. If transposed, the chords tend to become ambiguous. The example given involves settings for a key in which C is the keynote.

OArabian Scale

By altering the setting for Scale Tune, you can obtain a variety of other tunings suited for ethnic music. For example, the settings introduced below will set the unit to use the Arabian Scale.

Example Settings

| Note name | Equal Temperament | Just Temperament (Tonic C) | Arabian Scale |
|-----------|-------------------|----------------------------|---------------|
| C | 0 | 0 | -6 |
| C# | 0 | -8 | +45 |
| D | 0 | +4 | -2 |
| D# | 0 | +16 | -12 |
| E | 0 | -14 | -51 |
| F | 0 | -2 | -8 |
| F# | 0 | -10 | +43 |
| G | 0 | +2 | -4 |
| G# | 0 | +14 | +47 |
| Α | 0 | -16 | 0 |
| A# | 0 | +14 | -10 |
| В | 0 | 12 | -49 |

The values in the table are given in cents. Convert these values to hexadecimal, and transmit them as Exclusive data.

For example, to set the tune (C-B) of the Part 1 Arabian Scale, send the following data: F0 41 10 42 12 40 11 40 3A 6D 3E 34 0D 38 6B 3C 6F 40 36 0F 76 F7

●ASCII Code Table

Tone Name and Performance Name, etc., of MIDI data are described the ASCII code in the table below.

| D | Н | Char | D | Н | Char | D | Н | Char |
|----|------|-----------------------|----|------|--------|-----|-----|------------------|
| 32 | 20H | SP | 64 | 40H | @ | 96 | 60H | · i |
| 33 | 21H | 1 1 | 65 | 41H | A | 97 | 61H | a |
| 34 | 22H | u l | 66 | 42H | В | 98 | 62H | b |
| 35 | 23H | # | 67 | 43H | l c | 99 | 63H | c |
| 36 | 24H | \$ % | 68 | 44H | D | 100 | 64H | d |
| 37 | 25H | 8 | 69 | 45H | E | 101 | 65H | e |
| 38 | 26H | · & | 70 | 46H | F | 102 | 66H | e f |
| 39 | 27H | , | 71 | 47H | G | 103 | 67H | q |
| 40 | 28H | (| 72 | .48H | н | 104 | 68H | g h |
| 41 | 29H |) | 73 | 49H | I | 105 | 69H | i |
| 42 | 2AH | * | 74 | 4AH | J | 106 | 6AH | j |
| 43 | 2BH | + | 75 | 4BH | K | 107 | 6BH | i j k 1 |
| 44 | 2CH | . , | 76 | 4CH | L | 108 | 6CH | 1 |
| 45 | 2DH | - 1 | 77 | 4 DH | M | 109 | 6DH | m |
| 46 | 2EH | 1 . 1 | 78 | 4EH | N | 110 | 6EH | n |
| 47 | 2FH | / | 79 | 4FH | 0 | 111 | 6FH | 0 |
| 48 | 30H | 0 | 80 | 50H | P | 112 | 70H | p |
| 49 | 31H | 1 | 81 | 51H | Q R | 113 | 71H | q |
| 50 | 32H | 2 | 82 | 52H | R | 114 | 72H | r |
| 51 | 33H | 3 | 83 | 53H | s | 115 | 73H | s |
| 52 | 34H | 4 | 84 | 54H | T | 116 | 74H | t |
| 53 | 35H | 1 2 3 4 5 | 85 | 55H | ן ט | 117 | 75H | u |
| 54 | 36H | 6 | 86 | 56H | V | 118 | 76H | v |
| 55 | 37H | 7 | 87 | 57H | W | 119 | 77H | w |
| 56 | 38H | 8 | 88 | 58H | X | 120 | 78H | × |
| 57 | 39H | 9 | 89 | 59H | Y | 121 | 79H | У |
| 58 | 3AH | : | 90 | 5AH | Z | 122 | 7AH | z |
| 59 | 3BH | ; | 91 | 5BH | [[| 123 | 7BH | [] |
| 60 | 3CH | < | 92 | 5CH | \ | 124 | 7CH |]] [|
| 61 | 3 DH | = | 93 | 5DH | 1 1 | 125 | 7DH |] } |
| 62 | 3EH | > | 94 | 5EH | ^ | | + | ++ |
| 63 | 3FH | ? | 95 | 5FH | | | | |

D: decimal

H: hexadecimal

"SP" is space.

64 Voice Synthesizer

Model RS-5/9

MIDI Implementation Chart

Version: 1.00

Date: Oct. 12, 2000

| | Function | Transmitted | Recognized | Remarks |
|---------------------|---|---|--|--|
| Basic Channel | Default Changed | 1–16 1–16 | 1–16 1–16 | |
| Mode | Default Messages Altered | Mode 3 X ******** | Mode 3 Mode 3, 4 (M = 1) | * 2 |
| Note Number : | True Voice | 0–127 | 0–127 0–127 | |
| Velocity | Note On Note Off | 0 | 0 | |
| After Touch | Key's Channel's | X O | O *1 O *1 | |
| Pitch Bend | t | 0 | O *1 | |
| Control Change | 0, 32 15 6, 38 7 10 11 12 13 13 64 65 66 67 72 73 74 75 76 77 78 84 91 93 98, 99 100, 101 | 00000000000000000000000000000000000000 | O 11 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 | Bank select Modulation Portamento time Data entry Volume Panpot Expression Effect control 1 Effect control 2 Hold 1 Portamento Sostenuto Soft Hold 2 Resonance Release time Attack time Cutoff Decay time Vibrato depth Vibrato depth Vibrato delay Portamento propose effects 1 General purpose effects 3 NRPN LSB, MSB RPN LSB, MSB RPN LSB, MSB |
| Program Change | : True Number | O ******* | O *1 0–127 | Program No. 1–128 |
| System E | xclusive | 0 | O *1 | |
| System Common | : Song Position : Song Select : Tune Request | X X X | X X X | |
| System Real Time | : Clock : Commands | X X | O *1 O *1 | |
| Aux Messages | : All Sound Off : Reset All Controllers : Local On/Off : All Notes Off : Active Sensing : System Reset | 0 0 X X 0 X | O (120, 126, 127) O X O (123–127) O X | |
| Notes | | * 1 O X is selectable. * 2 Recognized as M=1 (* 3 Transmit data only w | even if M≠1. hen using the Setup Send o | command. |

Mode 1 : OMNI ON, POLY Mode 3 : OMNI OFF, POLY Mode 2 : OMNI ON, MONO Mode 4 : OMNI OFF, MONO O : Yes X : No

Specifications

Specifications

RS-5/9: 64-voice synthesizer (conforms to General MIDI 2 System)

Keyboard

RS-5: 61 keys (with velocity) RS-9: 88 keys (with velocity)

Parts

16

Maximum Polyphony

64 voices

• Wave Memory

32 M bytes (16-bit linear equivalent)

• Preset Memory

Tones: 512 (RS-5/9 Original: 256, General MIDI 2: 256)

Performances: 128

Drum Sets: 20 (RS-5/9 Original: 11, General MIDI 2: 9)

User Memory

Tones: 128
Performances: 128
Drum Sets: 2

• Effects

Multi-Effects: 42 types
Reverb: 8 types
Chorus: 8 types

• Arpeggiator

45 styles

Controllers

Pitch Bend/Modulation Lever

Control Knobs: 6

Display

20 characters, 2 lines (Backlit LCD) 7 segments, 3 characters (LED)

Connectors

Output Jacks (L (MONO), R)

Headphones Jack

MIDI Connectors (IN, OUT, THRU)

Hold Pedal Jack

Control Pedal Jack

• Power Supply

DC 9V (AC Adaptor)

Current Draw

600 mA

Dimensions

RS-5: 1033 (W) x 294 (D) x 103 (H) mm 40-11/16 (W) x 11-5/8 (D) x 4-1/16 (H) inches

RS-9: 1395 (W) x 294 (D) x 108 (H) mm 54-15/16 (W) x 11-5/8 (D) x 4-1/4 (H) inches

Weight

RS-5: 6.0 kg / 13 lbs 4 oz (excluding AC adaptor)
RS-9: 10.8kg / 23 lbs 13 oz (excluding AC adaptor)

Accessories

Owner's Manual

AC Adaptor (ACI/ACB Series)

Music Stand / 2 Screws for the music stand (RS-9)

Options

Pedal Switch: DP-2/6
Foot Switch: BOSS FS-5U
Expression Pedal: EV-5

* In the interest of product improvement, the specifications and/ or appearance of this unit are subject to change without prior notice.

Index

| Numerics 2VOICE PITCH SHIFTER (Multi-FX) |
|--|
| Α |
| ACCENT knob |
| Accent Rate (Arpeggio) |
| Aftertouch |
| Arabic Scale |
| [ARPEGGIO ON/OFF] |
| [ARPEGGIO/CONTROL]74 |
| ATTACK knob |
| AUTO WAH (Multi-FX) |
| В |
| Bank Select Transmit Switch |
| Beat Pattern (Arpeggio) |
| Bulk Dump |
| С |
| Category |
| Channel |
| Receive |
| Transmit |
| Channel messages |
| Chorus |
| On/Off |
| Settings |
| CHORUS/DELAY (Multi-FX) 105 |
| CHORUS/FLANGER (Multi-FX) 105 |
| CHORUS->DELAY (Multi-FX) |
| CHORUS->FLANGER (Multi-FX) 104 |
| COMPRESSOR (Multi-FX) |
| CONTROL 1-CONTROL 4 |
| Control Change |
| Control Pedal Assign |
| CONTROL PEDAL Polarity |
| CUTOFF knob |
| D |
| Demo songs |
| DEPTH knob 52 |
| Detune |
| Device ID Number |
| DISTORTION (Multi-FX) |
| DISTORTION->CHORUS (Multi-FX) 101 |
| DISTORTION->DELAY (Multi-FX) 101 |
| DISTORTION->FLANGER (Multi-FX) 101 |
| Drum Set |
| Assigning a name |
| Creating |
| Saving |
| Selecting (Single) 29 |
| Selecting (Split and Dual) |
| |
| Dual |

| E | |
|---------------------------------|--------|
| Effect | |
| On/Off | 44, 79 |
| Signal Path | 80 |
| ENHANCER (Multi-FX) | 85 |
| ENHANCER->CHORUS (Multi-FX) | 102 |
| ENHANCER->DELAY (Multi-FX) | 103 |
| ENHANCER->FLANGER (Multi-FX) | 102 |
| ENTER Button | 11 |
| ENVELOPE | |
| Equal Temperament | |
| Exclusive messages | |
| [EXIT] | 64 |
| F | |
| Factory Reset | 21 117 |
| FAVORITE PERFORM BANK | |
| FBK PITCH SHIFTER (Multi-FX) | |
| FILTER | |
| Fine Tune | |
| FLANGER/DELAY (Multi-FX) | |
| FLANGER->DELAY (Multi-FX) | |
| TEM VOLICE PERMIT (WILLIAM) | 101 |
| G | |
| GATED REVERB (Multi-FX) | 99 |
| GM/GM2 Setup Message | 129 |
| GM/GM2 SYSTEM ON | |
| GM/GM2 System On Receive Switch | 128 |
| н | |
| ++ HEXA-CHORUS (Multi-FX) | oc |
| HOLD PEDAL Polarity | |
| TIOLD TEDAL FORTHLY | 70 |
| l | |
| Initialize | 117 |
| • • | |
| K | |
| Key Mode | |
| Key Shift | |
| Key Velocity (Arpeggio) | |
| Knob | |
| Knob Assign | 74 |
| L | |
| _ LCD Contrast | 16 |
| Level (Drum Set) | |
| Level (Part) | |
| LFO | |
| [LFO ON/OFF] | 52 |
| LIMITER (Multi-FX) | 87 |
| Local Control | |
| LOFI (Multi-FX) | |
| Lower Part | |
| | |

| M |
|---|
| [MANUAL] |
| Master Key Shift |
| Master Tuning |
| Maximum Polyphony |
| Memory |
| MIDI |
| Modulation Assign |
| MODULATION DELAY (Multi-FX) |
| Modulation Lever |
| Motif (Arpeggio) |
| Multi-Effects |
| On/Off |
| On/Off for Individual Parts 107 |
| Settings |
| Multi-Effects Type |
| Multi-timbral sound modules |
| N |
| Name |
| Note Off |
| Note On |
| Numeric Keys 64 |
| 0 |
| OCTAVE knob |
| Octave Range (Arpeggio) |
| OVERDRIVE (Multi-FX) |
| OVERDRIVE->CHORUS (Multi-FX) |
| |
| OVERDRIVE->DELAY (Multi-FX) |
| OVERDRIVE->DELAY (Multi-FX) 100 |
| OVERDRIVE->DELAY (Multi-FX) |
| OVERDRIVE->DELAY (Multi-FX) |
| OVERDRIVE->DELAY (Multi-FX) 100 OVERDRIVE->FLANGER (Multi-FX) 100 P Pan (Drum Set) 112 |
| OVERDRIVE->DELAY (Multi-FX) 100 OVERDRIVE->FLANGER (Multi-FX) 100 P Pan (Drum Set) 112 Pan (Part) 66 |
| OVERDRIVE->DELAY (Multi-FX) 100 OVERDRIVE->FLANGER (Multi-FX) 100 P Pan (Drum Set) 112 Pan (Part) 66 Panic function 65 |
| OVERDRIVE->DELAY (Multi-FX) 100 OVERDRIVE->FLANGER (Multi-FX) 100 P Pan (Drum Set) 112 Pan (Part) 66 Panic function 65 Part 28, 39 |
| OVERDRIVE->DELAY (Multi-FX) 100 OVERDRIVE->FLANGER (Multi-FX) 100 P Pan (Drum Set) 112 Pan (Part) 66 Panic function 65 Part 28, 39 PEDAL 73 |
| OVERDRIVE->DELAY (Multi-FX) 100 OVERDRIVE->FLANGER (Multi-FX) 100 P Pan (Drum Set) 112 Pan (Part) 66 Panic function 65 Part 28, 39 PEDAL 73 Pedal Polarity 73 |
| OVERDRIVE->DELAY (Multi-FX) 100 OVERDRIVE->FLANGER (Multi-FX) 100 P Pan (Drum Set) 112 Pan (Part) 66 Panic function 65 Part 28, 39 PEDAL 73 |
| OVERDRIVE->DELAY (Multi-FX) 100 OVERDRIVE->FLANGER (Multi-FX) 100 P Pan (Drum Set) 112 Pan (Part) 66 Panic function 65 Part 28, 39 PEDAL 73 Pedal Polarity 73 [PERFORM/TONE] 23, 26, 29–30, 57 Performance |
| OVERDRIVE->DELAY (Multi-FX) 100 OVERDRIVE->FLANGER (Multi-FX) 100 P Pan (Drum Set) 112 Pan (Part) 66 Panic function 65 Part 28, 39 PEDAL 73 Pedal Polarity 73 [PERFORM/TONE] 23, 26, 29–30, 57 Performance Assigning a name 113 |
| OVERDRIVE->DELAY (Multi-FX) 100 OVERDRIVE->FLANGER (Multi-FX) 100 P Pan (Drum Set) 112 Pan (Part) 66 Panic function 65 Part 28, 39 PEDAL 73 Pedal Polarity 73 [PERFORM/TONE] 23, 26, 29–30, 57 Performance |
| OVERDRIVE->DELAY (Multi-FX) 100 OVERDRIVE->FLANGER (Multi-FX) 100 P Pan (Drum Set) 112 Pan (Part) 66 Panic function 65 Part 28, 39 PEDAL 73 Pedal Polarity 73 [PERFORM/TONE] 23, 26, 29–30, 57 Performance Assigning a name 113 Easily Selecting 58 Saving 113 Selecting 56 |
| OVERDRIVE->DELAY (Multi-FX) 100 OVERDRIVE->FLANGER (Multi-FX) 100 P 112 Pan (Drum Set) 112 Pan (Part) 66 Panic function 65 Part 28, 39 PEDAL 73 Pedal Polarity 73 [PERFORM/TONE] 23, 26, 29–30, 57 Performance Assigning a name 113 Easily Selecting 58 Saving 113 Selecting 56 What is a performance? 62 |
| OVERDRIVE->DELAY (Multi-FX) 100 OVERDRIVE->FLANGER (Multi-FX) 100 P Pan (Drum Set) 112 Pan (Part) 66 Panic function 65 Part 28, 39 PEDAL 73 Pedal Polarity 73 [PERFORM/TONE] 23, 26, 29–30, 57 Performance Assigning a name 113 Easily Selecting 58 Saving 113 Selecting 56 What is a performance? 62 PHASER (Multi-FX) 84 |
| OVERDRIVE->DELAY (Multi-FX) 100 OVERDRIVE->FLANGER (Multi-FX) 100 P Pan (Drum Set) 112 Pan (Part) 66 Panic function 65 Part 28, 39 PEDAL 73 Pedal Polarity 73 [PERFORM/TONE] 23, 26, 29–30, 57 Performance Assigning a name 113 Easily Selecting 58 Saving 113 Selecting 56 What is a performance? 62 PHASER (Multi-FX) 84 [PHRASE PREVIEW] 33 |
| OVERDRIVE->DELAY (Multi-FX) 100 OVERDRIVE->FLANGER (Multi-FX) 100 P 112 Pan (Drum Set) 112 Pan (Part) 66 Panic function 65 Part 28, 39 PEDAL 73 Pedal Polarity 73 [PERFORM/TONE] 23, 26, 29–30, 57 Performance Assigning a name 113 Easily Selecting 58 Saving 113 Selecting 56 What is a performance? 62 PHASER (Multi-FX) 84 [PHRASE PREVIEW] 33 [PIANO] 60 |
| OVERDRIVE->DELAY (Multi-FX) 100 OVERDRIVE->FLANGER (Multi-FX) 100 P 112 Pan (Drum Set) 112 Pan (Part) 66 Panic function 65 Part 28, 39 PEDAL 73 Pedal Polarity 73 [PERFORM/TONE] 23, 26, 29–30, 57 Performance Assigning a name 113 Easily Selecting 58 Saving 113 Selecting 56 What is a performance? 62 PHASER (Multi-FX) 84 [PHRASE PREVIEW] 33 [PIANO] 60 Pitch (Drum Set) 112 |
| OVERDRIVE->DELAY (Multi-FX) 100 OVERDRIVE->FLANGER (Multi-FX) 100 P 112 Pan (Drum Set) 112 Pan (Part) 66 Panic function 65 Part 28, 39 PEDAL 73 Pedal Polarity 73 [PERFORM/TONE] 23, 26, 29–30, 57 Performance Assigning a name 113 Easily Selecting 58 Saving 113 Selecting 56 What is a performance? 62 PHASER (Multi-FX) 84 [PHRASE PREVIEW] 33 [PIANO] 60 Pitch (Drum Set) 112 Pitch Bend Change 119 |
| OVERDRIVE->DELAY (Multi-FX) 100 OVERDRIVE->FLANGER (Multi-FX) 100 P 112 Pan (Drum Set) 112 Pan (Part) 66 Panic function 65 Part 28, 39 PEDAL 73 Pedal Polarity 73 [PERFORM/TONE] 23, 26, 29–30, 57 Performance Assigning a name 113 Easily Selecting 58 Saving 113 Selecting 56 What is a performance? 62 PHASER (Multi-FX) 84 [PHRASE PREVIEW] 33 [PIANO] 60 Pitch (Drum Set) 112 Pitch Bend Change 119 Pitch Bend Lever 50 |
| OVERDRIVE->DELAY (Multi-FX) 100 OVERDRIVE->FLANGER (Multi-FX) 100 P 112 Pan (Drum Set) 112 Pan (Part) 66 Panic function 65 Part 28, 39 PEDAL 73 Pedal Polarity 73 [PERFORM/TONE] 23, 26, 29–30, 57 Performance Assigning a name 113 Easily Selecting 58 Saving 113 Selecting 56 What is a performance? 62 PHASER (Multi-FX) 84 [PHRASE PREVIEW] 33 [PIANO] 60 Pitch (Drum Set) 112 Pitch Bend Change 119 Pitch Bend Lever 50 Portamento 67 |
| OVERDRIVE->DELAY (Multi-FX) 100 OVERDRIVE->FLANGER (Multi-FX) 100 P 112 Pan (Drum Set) 112 Pan (Part) 66 Panic function 65 Part 28, 39 PEDAL 73 Pedal Polarity 73 [PERFORM/TONE] 23, 26, 29–30, 57 Performance Assigning a name 113 Easily Selecting 58 Saving 113 Selecting 56 What is a performance? 62 PHASER (Multi-FX) 84 [PHRASE PREVIEW] 33 [PIANO] 60 Pitch (Drum Set) 112 Pitch Bend Change 119 Pitch Bend Lever 50 Portamento 67 Power 15 |
| OVERDRIVE->DELAY (Multi-FX) 100 OVERDRIVE->FLANGER (Multi-FX) 100 P 112 Pan (Drum Set) 112 Pan (Part) 66 Panic function 65 Part 28, 39 PEDAL 73 Pedal Polarity 73 [PERFORM/TONE] 23, 26, 29–30, 57 Performance Assigning a name 113 Easily Selecting 58 Saving 113 Selecting 56 What is a performance? 62 PHASER (Multi-FX) 84 [PHRASE PREVIEW] 33 [PIANO] 60 Pitch (Drum Set) 112 Pitch Bend Change 119 Pitch Bend Lever 50 Portamento 67 Power 15 Preset 26, 30, 56 |
| OVERDRIVE->DELAY (Multi-FX) 100 OVERDRIVE->FLANGER (Multi-FX) 100 P 112 Pan (Drum Set) 112 Pan (Part) 66 Panic function 65 Part 28, 39 PEDAL 73 Pedal Polarity 73 [PERFORM/TONE] 23, 26, 29–30, 57 Performance Assigning a name 113 Easily Selecting 58 Saving 113 Selecting 56 What is a performance? 62 PHASER (Multi-FX) 84 [PHRASE PREVIEW] 33 [PIANO] 60 Pitch (Drum Set) 112 Pitch Bend Change 119 Pitch Bend Lever 50 Portamento 67 Power 15 |

| Q | |
|--|-----------|
| QUADRUPLE TAP DELAY (Multi-FX) | 95 |
| R | |
| RATE knob | 50 |
| Receive Channel | |
| RELEASE knob | |
| REMOLO CHORUS (Multi-FX) | عرب وي |
| RESONANCE knob | |
| Reverb | 50 |
| On/Off | 44 70 |
| Settings | |
| REVERB (Multi-FX) | 100 |
| Reverb Depth (Drum Set) | عر 110 |
| POTADY (Mark: EV) | 114 |
| ROTARY (Multi-FX) | 80 |
| S | |
| Scale Tune | 70 |
| [SHIFT] | |
| Shortcuts | |
| SHUFFLE knob | |
| Shuffle Rate (Arpeggio) | |
| | |
| Single | 34 |
| Sala Switch | 100 |
| Solo Switch | 67 |
| Source (Multi-Effects) | الا |
| SPACE-D (Multi-FX) | 85 |
| SPECTRUM (Multi-FX) | |
| Split | |
| Split Point | 40 |
| STEP FLANGER (Multi-FX) | 91 |
| STEREO CHORUS (Multi-FX) | 89 |
| STEREO DELAY (Multi-FX) | 92 |
| STEREO EQ (Multi-FX) | 82 |
| STEREO FLANGER (Multi-FX) | |
| Style (Arpeggio) | |
| Switch (Multi-Effects, for Individual Parts) | |
| Sync Source (Arpeggio) | |
| System Exclusive Receive Switch | |
| System messages | 119 |
| Т | |
| | - |
| Tempo (Arpeggio) | |
| TEMPO knob | 78 |
| THROUGH (Multi-FX) | 82 |
| TIME CONTROL DELAY (Multi-FX) | 96 |
| Tone | 446 |
| Assigning a name | |
| Category | |
| Creating | |
| Saving | |
| Selecting (Single) | 23 |
| Selecting (Split and Dual) | 37 |
| What is a tone? | 62 |
| [TONE CATEGORY] | |
| Tone Change Receive Switch | |
| Tone Search function | |
| Tone Type | 31 |

Index

| Transmit Channel | 120 |
|-----------------------------|------------|
| Transpose | |
| All the Parts | |
| Specified Part | |
| TRIPLE TAP DELAY (Multi-FX) | 94 |
| Tuning | 18 |
| Tx Setup | 129 |
| Type (Multi-Effects) | 81 |
| U | |
| Upper Part | 34, 40 |
| User | 26, 30, 56 |
| [USER/PRESET] | |
| V | |
| VALUE [-]/[+] | 64 |
| Velocity Sense | |
| Vibrato Effect | |
| Voice Reserve | |
| Volume | 16 |
| W | |
| Wah Effect | 52, 110 |

| I | n | d | е | × |
|---|---|---|---|---|
| Į | n | d | е | X |

Memo

dev

Information

When you need repair service, call your nearest Roland Service Center or authorized Roland distributor in your country as shown below.



EGYPT

Al Fanny Trading Office P.O. Box 2904, El Horrieh Heliopolos, Cairo, TEL: (02) 4185531

REUNION

Maison FO - YAM Marcel 25 Rue Jules Hermann, Chaudron - BP79 97 491 Ste Clotilde Cedex, RELINION ISLAND TEL: 28 29 16

SOUTH AFRICA

That Other Music Shop (PTY) Ltd. 11 Melle St., Braamfontein, Johannesbourg
Republic of SOUTH AFRICA

P.O.Box 32918, Braamfontein 2017 Republic of SOUTH AFRICA TEL: (011) 403 4105

Paul Bothner (PTY) Ltd. 17 Werdmuller Centre Claremont Republic of SOUTH AFRICA

P.O. Box 23032 Claremont, Cape Town SOUTH AFRICA, 7735 TEL: (021) 674 4030



CHINA

Beijing Xinghai Musical Instruments Co., Ltd.
6 Huangmuchang Chao Yang
District, Beijing, CHINA
TEL: (010) 6774 7491

HONG KONG

Tom Lee Music Co., Ltd. Service Division 22-32 Pun Shan Street, Tsuen Wan, New Territories, HONG KONG TEL: 2415 0911

Rivera Digitec (India) Pvt. Ltd. 409, Nirman Kendra Mahalaxmi Flats Compound Off. Dr. Edwin Moses Road, Mumbai-400011, TEL: (022) 498 3079

INDONESIA

PT Citra IntiRama J1. Cideng Timur No. 15J-150 Jakarta Pusat INDONESIA TEL: (021) 6324170

KOREA

Cosmos Corporation 1461-9, Seocho-Dong, Seocho Ku, Seoul, KOREA TEL: (02) 3486-8855

MALAYSIA

Bentley Music SDN BHD 140 & 142, Jalan Bukit Bintang 55100 Kuala Lumpur, MALAYSIA TEL: (03) 2443333

PHILIPPINES

G.A. Yupangco & Co. Inc. 339 Gil J. Puyat Avenue
Makati, Metro Manila 1200,
PHILIPPINES TEL: (02) 899 9801

SINGAPORE

Swee Lee Company 150 Sims Drive. SINGAPORE 387381 TEL: 748-1669

CRISTOFORI MUSIC PTE

Blk 3014, Bedok Industrial Park E, #02-2148, SINGAPORE 489980 TEL: 243 9555

TAIWAN

ROLAND TAIWAN ENTERPRISE CO., LTD. Room 5, 9fl. No. 112 Chung Shan N.Road Sec.2, Taipei, TAIWAN, TEL: (02) 2561 3339

THAILAND

Theera Music Co. , Ltd. 330 Verng NakornKasem, Soi 2, Bangkok 10100, THAILAND TEL: (02) 2248821

VIETNAM

Saigon Music 138 Tran Quang Khai St., District 1 Ho Chi Minh City VIETNAM TEL: (08) 844-4068

AUSTRALIA NEW ZEALAND

AUSTRALIA

Roland Corporation Australia Pty., Ltd. 38 Campbell Avenue Dee Why West, NSW 2099 AUSTRÁLIA TEL: (02) 9982 8266

NEW ZEALAND

Roland Corporation (NZ) Ltd. 97 Mt. Eden Road, Mt. Eden, Auckland 3, NEW ZEALAND TEL: (09) 3098 715

CENTRAL/LATIN **AMERICA**

ARGENTINA

Instrumentos Musicales S.A. Florida 656 2nd Floor Office Number 206A Buenos Aires ARGENTINA, CP1005 TEL: (54-11) 4- 393-6057

BRA7IL

Roland Brasil Ltda Rua San Iose, 780 Sala B Parque Industrial San Jose Cotia - Sao Paulo - SP, BRAZIL TEL: (011) 4615 5666

COSTA RICA

JUAN Bansbach Instrumentos Musicales Ave.1. Calle 11, Apartado 10237, San Jose, COSTA RICA TEL: (506)258-0211

Comercial Fancy Il S.A. Avenida Rancagua #0330 Providencia Santiago, CHILE TEL: 56-2-373-9100

EL SALVADOR

OMNI MUSIC 75 Avenida Notre YY Alameda. Juan Pablo 2, No. 4010 San Salvador, EL SALVADOR TEL: (503) 262-0788

MEXICO

Casa Veerkamp, s.a. de c.v. Av. Toluca No. 323, Col. Olivar de los Padres 01780 Mexico D.F. MEXICO TEL: (525) 668 04 80

La Casa Wagner de Guadalajara s.a. de c.v. Av. Corona No. 202 S.J. Guadalajara, Jalisco Mexico C P 44100 MEXICO TEL: (3) 613 1414

ΡΔΝΔΜΔ

SUPRO MUNDIAL, S.A. Boulevard Andrews, Albrook, Panama City. REP. DE PANAMA TEL: (507) 315-0101

PARAGUAY

Distribuidora De Instrumentos Musicales J.E. Olear y ESQ. Manduvira Edeficio, El Dorado Planta Baja Asuncion PARAGUAY TEL: 595-21-492147

PERU

VIDEO Broadcast S.A. Portinari 199 (ESQ. HALS), San Borja, Lima 41, REP. OF PERU TEL: 51-14-758226

URUGUAY

Todo Musica S.A. Cuareim 1844, Montevideo, URUGUAY, CP11200 TEL: 5982-924-2335

VENEZUELA

Musicland Digital C.A. Av. Francisco de Miranda, Centro Parque de Cristal, Nivel C2 Local 20 Caracas VENEZUELA TEL: (02) 285 9218

EUROPE

AUSTRIA

Roland Austria GES.M.B.H. Siemensstrasse 4, P.O. Box 74. A-6063 RUM, AUSTRIA TEL: (0512) 26 44 260

BELGIUM/HOLLAND/ LUXEMBOURG

Roland Benelux N. V. Houtstraat 3, B-2260, Oevel (Westerlo) BELGIUM TEL: (014) 575811

DENMARK

Roland Scandinavia A/S Nordhavnsvej 7, Postbox 880, DK-2100 Copenhagen DENMARK TEL: (039)16 6200

FRANCE

Roland France SA 4, Rue Paul Henri SPAAK, Parc de l'Esplanade, F 77 462 St. Thibault, Lagny Cedex FRANCE TEL: 01 600 73 500

FINLAND

Roland Scandinavia As, Filial Finland Lauttasaarentie 54 B Fin-00201 Helsinki, FINLAND TEL: (9) 682 4020

GERMANY

Roland Elektronische Musikinstrumente HmbH. Oststrasse 96, 22844 Norderstedt, GERMANY TEL: (040) 52 60090

GREECE

STOLLAS S.A. Music Sound Light 155, New National Road 26422 Patras, GREECE TEL: 061-435400

HUNGARY

Intermusica Ltd. Warehouse Area 'DEPO' Pf.83 H-2046 Torokbalint, HUNGARY TEL: (23) 511011

IRELAND

Roland Ireland Audio House, Belmont Court, Donnybrook, Dublin 4. Republic of IRELAND TEL: (01) 2603501

ITALY

Roland Italy S. p. A. Viale delle Industrie 8, 20020 Arese, Milano, ITALY TEL: (02) 937-78300

NORWAY

Roland Scandinavia Avd. Kontor Norge Lilleakerveien 2 Postboks 95 Lilleaker N-0216 Oslo NORWAY TEL: 273 0074

POLAND

P. P. H. Brzostowicz UL. Gibraltarska 4. PL-03664 Warszawa POLAND TEL: (022) 679 44 19

PORTUGAL

Tecnologias Musica e Audio, Roland Portugal, S.A. Cais Das Pedras, 8/9-1 Dto 4050-465 PORTO PORTUGAL. TEL: (022) 608 00 60

ROMANIA

FBS LINES Piata Libertatii 1. RO-4200 Gheorghehi TEL: (066) 164-609

RUSSIA

Slami Music Company Sadojava-Triumfalnaja st., 16 103006 Moscow, RUSSIA TEL: 095 209 2193

SPAIN

Roland Electronics de España, S. A. Calle Bolivia 239, 08020 Barcelona, SPAIN TEL: (93) 308 1000

SWEDEN

Roland Scandinavia A/S SWEDISH SALES OFFICE Danvik Center 28, 2 tr. S-131 30 Nacka SWEDEN TEL: (08) 702 0020

SWITZERLAND

Roland (Switzerland) AG Musitronic AG Gerberstrasse 5, Postfach, CH-4410 Liestal, SWITZERLAND TEL: (061) 921 1615

UKRAINE

TIC-TAC Mira Str. 19/108 P.O. Box 180 295400 Munkachevo, UKRAINE TEL: (03131) 414-40

UNITED KINGDOM

Roland (U.K.) Ltd. Atlantic Close, Swansea Enterprise Park, SWANSEA SA7 9FJ, UNITED KINGDOM TEL: (01792) 700139

MIDDLE EAST

BAHRAIN

Moon Stores
Bab Al Bahrain Road, P.O. Box 20077 State of BAHRAIN TEL: 211 005

CYPRUS

Radex Sound Equipment Ltd. 17 Diagorou St., P.O. Box 2046, Nicosia CYPRUS TEL: (02) 453 426

IRAN

MOCO, INC. No.41 Nike St.Dr.Shariyati Ave. Roberoye Cerahe Mirdamad Tehran, IRAN TEL: 285 4169

ISRAEL

Halilit P. Greenspoon & Sons Ltd. 8 Retzif Ha'aliya Hashnya St. Tel-Aviv-Yafo ISRAEL TEL: (03) 6823666

JORDAN

AMMAN Trading Agency Prince Mohammed St. P.O. Box 825 Amman 11118 JORDAN TEL: (06) 4641200

KUWAIT

Easa Husain Al-Yousifi Abdullah Salem Street, Safat KUWAIT TEL: 5719499

LEBANON

A. Chahine & Fils P.O. Box 16-5857 Gergi Zeidan St. Chahine Building, Achrafieh Beirut, LEBANON TEL: (01) 335799

QATAR Al Emadi Co. (Badie Studio & Stores) P.O. Box 62, DOHA OATAR TEL: 4423-554

SAUDI ARABIA

aDawliah Universal Electronics APL Corniche Road, Aldossary Bldg., 1st Floor SAUDI ARABIA

P.O.Box 2154, Alkhobar 31952 SAUDI ARABIA TEL: (03) 898 2081

SYRIA

Technical Light & Sound Center Khaled Ibn Al Walid St. P.O. Box 13520 Damascus - SYRIA TEL: (011) 2235 384

TURKEY

Barkat muzik aletleri ithalat ve ihracat Ltd Sti Siraselviler cad.Guney is hani 84-86/6, Taksim. Istanbul. TURKEY TEL: (0212) 2499324

U.A.E.

Zak Electronics & Musical Instruments Co. L.L.C. Zabeel Road, Al Sherooq Bldg., No. 14, Grand Floor DUBAI U.A.E. TEL: (04) 3360715

NORTH AMERICA

CANADA

Roland Canada Music Ltd. (Head Office) 5480 Parkwood Way Richmond B. C., V6V 2M4 CANADA TEL: (0604) 270 6626

Roland Canada Music Ltd. (Toronto Office) Unit 2, 109 Woodbine Downs Blvd, Etobicoke, ON M9W 6Y1 CANADA TEL: (0416) 213 9707

U. S. A.

Roland Corporation U.S. 5100 S. Eastern Avenue Los Angeles, CA 90040-2938, U. S. A. TEL: (323) 890 3700

For EU Countries



This product complies with the requirements of European Directive 89/336/EEC.

For the USA

FEDERAL COMMUNICATIONS COMMISSION RADIO FREQUENCY INTERFERENCE STATEMENT

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses, and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to accordance with the instructions, may cause harmful interference to accordance with the instructions, may cause harmful interference to the control of the control o that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

Reorient or relocate the receiving antenna.

Increase the separation between the equipment and receiver.

- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected. Consult the dealer or an experienced radio/TV technician for help.

Unauthorized changes or modification to this system can void the users authority to operate this equipment. This equipment requires shielded interface cables in order to meet FCC class B Limit.

For Canada

NOTICE


This Class B digital apparatus meets all requirements of the Canadian Interference-Causing Equipment Regulations.

AVIS

Cet appareil numérique de la classe B respecte toutes les exigences du Règlement sur le matériel brouilleur du Canada.

Installing the Music Stand (RS-9 Only)

A music stand is provided with the RS-9. The following describes how to attach and remove the stand.



1 Using the supplied screws, fasten the music stand to the back of the RS-9 as shown at left.

Turn the screws clockwise to tighten them.

- **2**To remove the music stand, support it with one hand while loosening the screws.
 - * When attaching the music stand, support it firmly with one hand to make sure that you do not drop it. Be careful, so you do not get your fingers pinched.
 - * Do not apply excessive force to the front or back of the installed music stand.
 - * Should you remove the screws used for attaching the music stand, make sure to put them in a safe place out of children's reach, so there is no chance of them being swallowed accidentally.