



élite
Passive Series

EM526

Overview

The élite Series EM526 passive floor monitor is engineered to deliver maximum clarity and high SPL in an ultra compact low-profile cabinet design. A custom designed 90°x 60° rotatable horn, dual 6-inch high power woofers, solid perforated all-metal grille and a solid 5/8-inch plywood enclosure ensure maximum long term performance and reliability.

Features

- 520 Watt Ultra Compact Floor Monitor
- Extremely Low Profile Design
- Delivers 124dB Continuous Max SPL
- Dual 6-inch woofer / 1-inch Compression Driver
- 90° x 60° Rotatable ABS Waveguide Horn
- Innovative CTL™ High Frequency Driver Protection
- 2 x Speakon™ and 2 x 1/4-inch Parallel Inputs
- Solid 5/8-inch (15mm) Birch Plywood Construction
- Made in Canada





Specifications

System Type	Monitor
Active or Passive	Passive
Program Power (Watts)	520 Watts Program
Biampable	No
Nominal Impedance (Ohms)	8 ohms
Sensitivity (dB @1Watt/1m)	97dB
Max SPL (dB)	124dB Continuous
Frequency Response (Hz +/- 3dB)	80Hz to 20kHz
Crossover Frequency (Hz)	1600Hz
Driver Configuration	2 x 6-inch woofers / 1-inch Horn
HF Driver(s)	1-inch Mylar Driver
HF Dispersion (°H x °V)	90 x 60 Rotatable
HF Protection	CTL™
LF Driver(s)	2 x 6-inch w/ 1.77-inch Voicecoil
Total Power (Watts)	520 Watts
Inputs - 1/4" Jacks	x 2
Inputs - Speakon 4-pin	x 2
Enclosure Materials	15mm (5/8inch) 11-ply Russian Birch
Baffle Material	15mm (5/8inch) 11-ply Russian Birch
Grille	Perforated Metal
Covering / Finish	Black Ozite
Optional Covering / Finishes	Black Ultrathane Paint (EM526B)
Dimensions (DWH xbackW COM inches)	15 x 15 x 11.5
Dimensions (DWH xbackW COM cm)	38 x 38 x 29.2
Weight (lbs/kg)	24 / 10.8

Specifications subject to change without notice